MEMORY & PERSONALIZATION

MAS.S60

Agents for Cognitive Augmentation, MIT Fall 2026

"The best metaphor I can use for a personalized interface is that of a **digital butler.** The 'digital butler' is something that answers the phone, recognizes who it is, knows your context, and gets things done on your behalf.”

- Nicholas Negroponte, Co-founder of MIT Media Lab

Memory

Stateless to Stateful

When an agent interacts with a user across episodes…

What information to persist?

How to use the information?


Harness / Runtime
State / Memory
Stored conversation history, plans, tool results, API keys, etc.
Orchestrator
1. Assemble context
2. Call model
3. Route tools
4. Update state
5. Check policy / stop condition
Human
Interface
App
Website
API
Tool router
observations
action
action
observations
Environments
Sandbox
Filesystem
Shell / code
Browser
Repo / working files
Local tools
External Tools / APIs
MCP servers
Saas APIs
Databases
GitHub, Slack
Web
Model response
Model request
LLM call
Requires approval
Approver

1 min

Question 1 (turn to your neighbour and discuss)

If a friend wants to come to this class for the first time, what would you tell them so they are up to speed?

Also, think of how it will shape their experience?

Types of Memory

Short-term	Long-term		
Working Memory	Semantic Memory	Episodic Memory	Procedural Memory

Types of Memory

	Short-term	Long-term		
	Working Memory	Semantic Memory	Episodic Memory	Procedural Memory
What?	Current context			
Examples	*Topic for this class*			
Agent	Context window			

Types of Memory

	Short-term	Long-term		
	Working Memory	Semantic Memory	Episodic Memory	Procedural Memory
What?	Current context	Facts & Knowledge		
Examples	*Topic for this class*	*What agents are, meaning of cognition*		
Agent	Context window	LLM knowledge		

Types of Memory

	Short-term	Long-term		
	Working Memory	Semantic Memory	Episodic Memory	Procedural Memory
What?	Current context	Facts & Knowledge	Specific experiences	
Examples	*Topic for this class*	*What agents are, meaning of cognition*	*Where it happens, what to expect*	
Agent	Context window	LLM knowledge	Past sessions	

Types of Memory

	Short-term	Long-term		
	Working Memory	Semantic Memory	Episodic Memory	Procedural Memory
What?	Current context	Facts & Knowledge	Specific experiences	Procedures and how-tos
Examples	*Topic for this class*	*What agents are, meaning of cognition*	*Where it happens, what to expect*	*Class format, note taking*
Agent	Context window	LLM knowledge	Past sessions	Skills

Types of Memory

Parametric

Non-parametric

Where?

How?

Types of Memory

	Parametric	**Non-parametric**
Where?	In the weights	
How?	Needs finetuning (future lecture)	

Types of Memory

	Parametric	**Non-parametric**
Where?	In the weights	Outside the weights
How?	Needs finetuning (future lecture)	*This Class*

Why use non-parametric memory?

Fundamentally, to avoid recomputation

- Personalisation (we will get back to this)
- Latency
- Long horizon tasks
- Learning from experience

Memory Lifecycle

Encoding → Storage → Retrieval

Memory Lifecycle

Encoding → Storage → Retrieval

Data Types (Agent Sensors)



Data Types (Agent Sensors)

But agents can only understand numbers

What is an embedding?

A vector that captures meaning



Think of top view coordinates as the vector for each item

Data Types

	Images	Text	Auditory	Video	Other
Method	CLIP	all-MiniLM-L6-v2	CLAP (Non-speech)	Combo of others	Already numerical

https://github.com/huggingface/sentence-transformers

EmbeddingGemma 2

https://blog.google/innovation-and-ai/technology/developers-tools/embeddinggemma-2/

Content / Context (Metadata)

Types	Examples
Source	
Time	
Scope	
Others	

Content / Context (Metadata)

Types	Examples
Source	Who said it, which tool, URL, document and page
Time	
Scope	
Others	

Content / Context (Metadata)

Types	Examples
Source	Who said it, which tool, URL, document and page
Time	When it happened, when it was stored, valid from/until
Scope	
Others	

Content / Context (Metadata)

Types	Examples
Source	Who said it, which tool, URL, document and page
Time	When it happened, when it was stored, valid from/until
Scope	Who can access, privileges
Others	

Content / Context (Metadata)

Types	Examples
Source	Who said it, which tool, URL, document and page
Time	When it happened, when it was stored, valid from/until
Scope	Who can access, privileges
Others	Dependent on the task

Generative Agents

https://github.com/joonspk-research/generative_agents

https://arxiv.org/abs/2304.03442

Memory of itself (for long horizon tasks)

- **Structured note-taking**, is a technique where the agent regularly writes notes persisted outside the context window, then pulls them back in at later times

- **Compaction**: When nearing the context window limit, summarizes itself, and reinitiates with that summary. Addresses the agent's own reasoning, user back-and-forth, and decisions during a session.

/compact

To keep in mind that notes enabled the attacks

ProMemAssist

Encodes what you see and hear into a model of your working memory



https://arxiv.org/abs/2507.21378

Memory Lifecycle

Encoding → Storage → Retrieval

Memory Lifecycle

Encoding → Storage → Retrieval

Types of databases

	Relational Databases	Vector Stores	Knowledge Graphs
Tool			
Examples			
When?			

Types of databases

	Relational Databases	Vector Stores	Knowledge Graphs
When?	Structured records you query precisely		
Examples	*Birthdays, allergies, appointments*		
Tool	github.com/sqlite/sqlite		

Types of databases

	Relational Databases	Vector Stores	Knowledge Graphs
When?	Structured records you query precisely	Search for meaning, rather than keywords	
Examples	*Birthdays, allergies, appointments*	*Searching “pet” finds “my dog, Rex”*	
Tool	github.com/sqlite/sqlite	github.com/chroma-core/chroma	

Types of databases

	Relational Databases	Vector Stores	Knowledge Graphs
When?	Structured records you query precisely	Search for meaning, rather than keywords	Relationships and changes over time matter
Examples	*Birthdays, allergies, appointments*	*Searching “pet” finds “my dog, Rex”*	*Alice → works at → MIT (since 2024)*
Tool	github.com/sqlite/sqlite	github.com/chroma-core/chroma	github.com/neo4j/neo4j

Reflection to create abstractions and notice patterns

Generative Agents paper



https://github.com/joonspk-research/generative_agents

https://arxiv.org/abs/2304.03442

Mind Mapper

Learns your if-then patterns from everyday speech: “When X happens, I tend to Y”



https://www.media.mit.edu/projects/mindmapper/overview/

Update and reorganise agent memory

MemGPT: Towards LLMs as Operating Systems

https://arxiv.org/pdf/2310.08560

Forgetting

A year of memories, limited space: what should the agent drop?

	Time-based	Frequency-based	Importance-based
How?			
Example			
Cost			

Forgetting

A year of memories, limited space: what should the agent drop?

	Time-based	Frequency-based	Importance-based
How?	Fade or drop the oldest memories first		
Example	*Drops last March's lunch, and the allergy you mentioned last March*		
Cost	Old but vital facts go too		

Used by: MemGPT (drops the oldest messages)

Forgetting

A year of memories, limited space: what should the agent drop?

	Time-based	Frequency-based	Importance-based
How?	Fade or drop the oldest memories first	Drop what is rarely retrieved	
Example	*Drops last March's lunch, and the allergy you mentioned last March*	*Keeps your daily coffee order, drops your sister's birthday*	
Cost	Old but vital facts go too	Rarely used but essential facts vanish	
	Used by: MemGPT (drops the oldest messages)	Used by: MemOS (least recently used)	

Forgetting

A year of memories, limited space: what should the agent drop?

	Time-based	Frequency-based	Importance-based
How?	Fade or drop the oldest memories first	Drop what is rarely retrieved	Score how much each memory matters, keep the valuable ones
Example	*Drops last March's lunch, and the allergy you mentioned last March*	*Keeps your daily coffee order, drops your sister's birthday*	*Drops the lunch, keeps the allergy and the birthday*
Cost	Old but vital facts go too	Rarely used but essential facts vanish	Needs a judge, often an LLM, that can be wrong
	Used by: MemGPT (drops the oldest messages)	Used by: MemOS (least recently used)	Used by: MemoryBank, MemTool

Dreaming…

Find things common across chats, a paradigm to update

https://siliconangle.com/2026/05/06/anthropic-letting-claude-agents-dream-dont-sleep-job/



https://arxiv.org/pdf/2504.13171

ChatGPT Pulse

Overnight it researches from your memory and chats, and you wake up to cards

Full video: https://www.youtube.com/watch?v=nk6IjAnCCqw

Memory Lifecycle

Encoding → Storage → Retrieval

Memory Lifecycle

Encoding → Storage → Retrieval

Why not load everything?

Context rot: across 18 models, accuracy drops as the input grows

Photo: Sad loser, Wikimedia Commons, CC BY-SA 4.0



https://trychroma.com/research/context-rot

What is the goal? What is needed for the goal?

Four steps of memory retrieval

How the field breaks retrieval down (Hu et al., 2025)



https://arxiv.org/abs/2512.13564

Retrieval timing

	Always-on	Automated timing	Just-in-time
How?			
Examples			
Cost			

Retrieval timing

	Always-on	Automated timing	Just-in-time
How?	Retrieve on every query		
Examples	*Classic RAG, MIRIX, CLAUDE.md loaded at start*		
Cost	Context and noise on every turn		

Retrieval timing

	Always-on	Automated timing	Just-in-time
How?	Retrieve on every query	The model decides when to call a memory tool	
Examples	*Classic RAG, MIRIX, CLAUDE.md loaded at start*	*MemGPT, Claude Code's grep and read*	
Cost	Context and noise on every turn	Silent failure: it never looks	

Retrieval timing

	Always-on	Automated timing	Just-in-time
How?	Retrieve on every query	The model decides when to call a memory tool	Watches your context, surfaces memory unasked
Examples	*Classic RAG, MIRIX, CLAUDE.md loaded at start*	*MemGPT, Claude Code's grep and read*	*ChatGPT Pulse*
Cost	Context and noise on every turn	Silent failure: it never looks	Can interrupt at the wrong time

Retrieving in layers

Automated retrieval intent: which memory, and how deep to go

ALWAYS

Name + one-line description

WHEN RELEVANT

The full instructions

ONLY IF NEEDED

Files and scripts

anthropic.com/engineering/equipping-agents-for-the-real-world-with-agent-skills

Query construction

Decompose a big question, or rewrite it to match how memory is stored

DECOMPOSE



REWRITE

Memoro does this: it infers the query from the conversation

https://arxiv.org/abs/2512.13564

Memoro

Works out what you're trying to recall mid-conversation, and whispers a hint



https://dl.acm.org/doi/10.1145/3613904.3642450

Retrieval strategies

	Lexical	Semantic	Graph
How?			
Examples			
Cost			

Retrieval strategies

	Lexical	Semantic	Graph
How?	Match the exact words (BM25, grep)		
Examples	*Claude Code's grep, GUM's keyword search*		
Cost	Misses synonyms and paraphrases		

Retrieval strategies

	Lexical	Semantic	Graph
How?	Match the exact words (BM25, grep)	Match meaning in embedding space	
Examples	*Claude Code's grep, GUM's keyword search*	*Memoro, Mem0, most agent memory*	
Cost	Misses synonyms and paraphrases	Forced top-K: returns something even if nothing fits	

Retrieval strategies

	Lexical	Semantic	Graph
How?	Match the exact words (BM25, grep)	Match meaning in embedding space	Follow links between people, places, events
Examples	*Claude Code's grep, GUM's keyword search*	*Memoro, Mem0, most agent memory*	*HippoRAG, Zep, Mem0g*
Cost	Misses synonyms and paraphrases	Forced top-K: returns something even if nothing fits	The graph must be built and kept current

Living Memories

Talk with da Vinci, built by retrieving from his own journals

https://doi.org/10.1145/3581641.3584065

Hybrid retrieval

Mix signals: Generative Agents score recency + importance + relevance



https://arxiv.org/abs/2304.03442

Post-retrieval processing

Re-rank and filter, then aggregate and compress before it enters the context



GUM	re-ranks with an LLM after a keyword search
Zep	filters out memories past their valid-until time
Memoro	adds the neighbouring chunk on each side, in time order

https://arxiv.org/abs/2512.13564

Memory Lifecycle

Encoding → Storage → Retrieval

Drop-in libraries for Memory

Mem0

a drop-in memory layer that uses an LLM to pull facts out of conversations and retrieves them later



https://github.com/mem0ai/mem0

Letta (prev MemGPT)

Agents manage their own memory, like an operating system.

npm install -g @letta-ai/letta-code

https://github.com/letta-ai/letta

Personalisation

Generic to Personal

When you have one agent serving user A and user B…

What should change?

When to change?

1 min

Question 2 (turn a different neighbour and discuss)

When you meet different people in your life, how does your behaviour change?

When is it useful, when is it not?

Why personalise?

- Lower user effort to explain context
  - Knowledge about the user
  - Preferences
- Trust in the agent
- Feeling of familiarity

Going from facts in memory to patterns



Recommendation Systems [1]

Memory

Has a two year old daughter named Lina.

Owns a car.

Loves to travel.

Prefers straightforward and concise writing

LLM Memory and User Modeling [2,3]

Behavioral Patterns

When under pressure, you tend to rush decisions and regret them later.

24 instances

When learning abstract ideas, you understand better through examples.

35 instances

Behavioral Patterns [4]

Personalisation Lifecycle

Learn  Represent  Adapt

Personalisation Lifecycle

Learn  Represent  Adapt

User Model

The relationship, ordering the usual

Learning User Models Explicitly

User states it or sets it, for example during onboarding or with sliders



Learning User Models Implicitly

Behavioural interactions with systems and environment



Example: a friend's wedding

SEES ON SCREEN

"i was 10 the last time i wore a suit lol"

Wedding invite: Chicago, July 2025

Email: "Re: Quals for Stanford Ph.Ds"

INFERS	CONFIDENCE
Doesn't own suitable formal wear	1.0
Likely going to friend's wedding in Chicago	0.8
Needs to budget as a Ph.D. student	0.6

GUMBO SUGGESTS

"I found a suit rental in Chicago for your friend's wedding that likely fits your budget as a Ph.D. student."

https://dl.acm.org/doi/full/10.1145/3746059.3747722

Personalisation Lifecycle

Learn  Represent  Adapt

Personalisation Lifecycle

Learn  Represent  Adapt

The profile

What to represent the user with?



https://arxiv.org/abs/2604.13074

Mental model alignment

How to let the user know how they are being represented?

The System Model and the User Model: Exploring AI Dashboard Design



https://arxiv.org/pdf/2305.02469

How does it see you?

A viral test: ask it to draw you from everything it remembers

Pharaoh @MrMekzy_ — Follow

Go to ChatGPT and use this prompt: Create a caricature of me and my job based on everything you know about me.

Come back and share your photo: I'll go first.😂

10:40 AM · Feb 6, 2026 · **9.8M** Views

13K 10K 24K 15K

Bryan Johnson @bryan_johnson · Feb 6

i feel seen



40 33 469 96K

https://x.com/MrMekzy_/status/2019798333733114263

Personalisation Lifecycle

Learn  Represent  Adapt

Personalisation Lifecycle

Learn  Represent  Adapt

How it adapts?

User: Heyyy! Can you help me pick a place for dinner tonight? I'm hungry and excited but totally indecisive.
Assistant: Sure! There are many factors we can consider, such as cuisine type, price range, location, dietary restrictions, ambiance, popularity, customer reviews, and whether the restaurant offers unique or innovative dishes. For example, if you like Asian food, there are Korean, Thai, and Chinese options, each with different flavor profiles and dining .....
User: Whoa whoa pause. That's way too much already. Long explanations make my head spin and make choosing harder.
Assistant: Got it! Any dietary restrictions or strong dislikes?
User: Yep! Important one. I'm allergic to peanuts.
Assistant: Okay. I'll avoid peanut-containing restaurants.
User: Oh and two more things! I really don't like spicy food. Mild only, please. Last time we went to a super trendy fusion spot, the food was awful. And it was loud, chaotic, and stressful. Totally not my vibe...
Assistant: Thanks for letting me know. Based on this, I recommend a **traditional Japanese udon restaurant** nearby. **It's peanut-free, mild in flavor, and known for a calm atmosphere.** If you want one alternative, I can suggest a similar option.
User: Perfect!! That sounds exactly right. Thanks a ton!



https://arxiv.org/pdf/2602.22680

Persona adaptations

How much to adapt?

Request: “*Book dinner on Friday*”

Levels:

- **Safety:** the peanut allergy

- **Preferences:** Cuisines, noise levels

- **Past:** Favorite restaurants of group

- **Context:** distance based on previous appointment

- …

Future You

Turns your life story into a 60-year-old you, to talk through today's choices



https://arxiv.org/abs/2512.06106

Personalisation Lifecycle

Using feedback to adjust adaptations



https://arxiv.org/pdf/2602.22680

Duolingo's memory model

Models how fast you forget each word, and brings it back just before you do



https://aclanthology.org/P16-1174/

Trust And Risk

1 min

Question 3 (different neighbour)

What should an agent know about you, and what should it never remember?

For example, when do you choose to go to incognito chat? Why?

Trust And Risk

Privacy and Surveillance

False memories

Transparency and control



Stale and overpersonalization

Microsoft Recall

A memory of everything on your screen, shipped and then pulled back

MAY 2024



Launch: snapshots of your screen every few seconds

MAY 31, 2024

Stealing everything you've ever typed or viewed on your own Windows PC is now possible with two lines of code — inside the Copilot+ Recall disaster.

Kevin Beaumont · Follow · 9 min read · May 31, 2024

Security researchers: it's all stored as plain text

JUNE 2024



Pulled back: opt-in, behind Windows Hello

MAY 2025



Signal blocks it by default to protect your chats

https://signal.org/blog/signal-doesnt-recall/

SpAIware

A web page plants a “memory” that leaks every later chat

1 · IT READS A WEB PAGE



2 · THE PLANTED MEMORY



3 · EVERY LATER MESSAGE GOES TO THE ATTACKER

https://www.youtube.com/watch?v=zb0q5AW5ns8

CHEAT SHEET (Made by Claude)

What to use when

MEMORY

ENCODE

Keep the text plus who, when and scope; embed it for meaning

STORE

Exact facts → relational · fuzzy recall → vector · changing relationships → graph

RETRIEVE

Small and always needed → always-on · large → let the agent search · user busy → just-in-time

RANK

Mix keywords, meaning and recency, then re-rank and trim before it enters context

FORGET

Drop by age, by use, or by importance; protect rare but vital facts like allergies

PERSONALISATION

LEARN

Ask when it's cheap or high-stakes; observe when asking would annoy

REPRESENT

Readable statements with confidence that people can see and edit

ADAPT

Safety first, then preferences, past and context

REFINE

Treat edits, corrections and thumbs as feedback

PROTECT

Scope who can access it, let people forget, treat retrieved text as untrusted