

CS23333-Object Oriented Programming Using Java-2023

Dashboard / My courses / CS23333-OOPJ-2023 / Lab-11-Set, Map / Lab-11-Logic Building

Quiz navigation



Show one page at a time  
Finish review

Status	Finished
Started	Monday, 18 November 2024, 5:14 PM
Completed	Monday, 18 November 2024, 5:34 PM
Duration	20 mins 16 secs

Question 1  
Correct  
Marked out of 1.00  
Flag question

**Java HashSet** class implements the Set interface, backed by a hash table which is actually a [HashMap](#) instance. No guarantee is made as to the iteration order of the hash sets which means that the class does not guarantee the constant order of elements over time. This class permits the null element.

The class also offers constant time performance for the basic operations like add, remove, contains, and size assuming the hash function disperses the elements properly among the buckets.

Java HashSet Features

A few important features of HashSet are mentioned below:

- Implements [Set Interface](#).
- The underlying data structure for HashSet is [Hashtable](#).
- As it implements the Set Interface, duplicate values are not allowed.
- Objects that you insert in HashSet are not guaranteed to be inserted in the same order. Objects are inserted based on their hash code.
- NULL elements are allowed in HashSet.
- HashSet also implements [Serializable](#) and [Cloneable](#) interfaces.
- public class HashSet<E> extends AbstractSet<E> implements Set<E>, Cloneable, Serializable

Sample Input and Output:

```
5
90
56
45
78
25
78
Sample Output:
78 was found in the set.
Sample Input and output:
3
2
7
9
5
Sample Input and output:
5 was not found in the set.
```

Answer: (penalty regime: 0 %)

Reset answer

```
1 import java.util.HashSet;
2 import java.util.Scanner;
3 class prog {
4     public static void main(String[] args) {
5         Scanner sc= new Scanner(System.in);
6         int n = sc.nextInt();
7         // Create a HashSet object called numbers
8         HashSet<Integer> numbers = new HashSet<>();
9
10        // Add values to the set
11        for(int i=0;i<n;i++)
12            numbers.add(sc.nextInt());
13
14        int skey=sc.nextInt();
15
16        // Show which numbers between 1 and 10 are in the set
17
18        if (numbers.contains(skey)) {
19            System.out.println( skey + " was found in the set.");
20        } else {
21            System.out.println(skey + " was not found in the set.");
22        }
23
24    }
25 }
```

	Test	Input	Expected	Got	
✓	1	5 90 56 45 78 25 78	78 was found in the set.	78 was found in the set.	✓
✓	2	3 -1 2 4 5	5 was not found in the set.	5 was not found in the set.	✓

Passed all tests! ✓

Question 2  
Correct  
Marked out of 1.00  
Flag question

Write a Java program to compare two sets and retain elements that are the same.

Sample Input and Output:

5  
Football  
Hockey  
Cricket  
Volleyball  
Basketball  
7 // HashSet 2:  
Golf  
Cricket  
Badminton  
Football  
Hockey  
Volleyball  
Handball

SAMPLE OUTPUT:

Football  
Hockey  
Cricket  
Volleyball  
Basketball

Answer: (penalty regime: 0 %)

```

1 | import java.util.HashSet;
2 | import java.util.Scanner;
3 |
4 | class prog {
5 |     public static void main(String[] args) {
6 |         Scanner sc = new Scanner(System.in);
7 |         int n1 = sc.nextInt();
8 |         sc.nextLine();
9 |         HashSet<String> set1 = new HashSet<>();
10 |         for (int i = 0; i < n1; i++) {
11 |             set1.add(sc.nextLine());
12 |         }
13 |         int n2 = sc.nextInt();
14 |         sc.nextLine();
15 |         HashSet<String> set2 = new HashSet<>();
16 |         for (int i = 0; i < n2; i++) {
17 |             set2.add(sc.nextLine());
18 |         }
19 |         set1.retainAll(set2);
20 |         for (String element : set1) {
21 |             System.out.println(element);
22 |         }
23 |     }
24 | }
25 |

```

	Test	Input	Expected	Got	
✓	1	5 Football Hockey Cricket Volleyball Basketball 7 Golf Cricket Badminton Football Hockey Volleyball Throwball	Cricket Hockey Volleyball Football Football	Cricket Hockey Volleyball Football Football	✓
✓	2	4 Toy Bus Car Auto 3 Car Bus Lorry	Bus Car Car	Bus Car Car	✓

Passed all tests! ✓

Question 3  
Correct  
Marked out of 1.00  
Flag question

#### Java HashMap Methods

**containsKey()** Indicate if an entry with the specified key exists in the map

**containsValue()** Indicate if an entry with the specified value exists in the map

**putIfAbsent()** Write an entry into the map but only if an entry with the same key does not already exist

**remove()** Remove an entry from the map

**replace()** Write to an entry in the map only if it exists

**size()** Return the number of entries in the map

Your task is to fill the incomplete code to get desired output

Answer: (penalty regime: 0 %)

Reset answer

```

1 | import java.util.HashMap;
2 | import java.util.Map.Entry;
3 | import java.util.Set;
4 | import java.util.Scanner;
5 | class prog
6 | {
7 |     public static void main(String[] args)
8 |     {
9 |         //Creating HashMap with default initial capacity and load factor
10 |         HashMap<String, Integer> map = new HashMap<String, Integer>();
11 |
12 |         String name;
13 |         int num;
14 |         Scanner sc = new Scanner(System.in);
15 |         int n = sc.nextInt();
16 |         for (int i = 0; i < n; i++)
17 |         {
18 |             name = sc.next();
19 |             num = sc.nextInt();
20 |             map.put(name, num);
21 |         }
22 |
23 |         //Printing key-value pairs
24 |
25 |         Set<Entry<String, Integer>> entrySet = map.entrySet();
26 |
27 |         for (Entry<String, Integer> entry : entrySet)
28 |         {
29 |             System.out.println(entry.getKey()+" : "+entry.getValue());
30 |         }
31 |         System.out.println("-----");
32 |         //Creating another HashMap
33 |
34 |         HashMap<String, Integer> anotherMap = new HashMap<String, Integer>();
35 |
36 |         //Inserting key-value pairs to anotherMap using put() method
37 |
38 |         anotherMap.put("SIX", 6);
39 |
40 |         anotherMap.put("SEVEN", 7);
41 |
42 |         //Inserting key-value pairs of map to anotherMap using putAll() method
43 |
44 |         anotherMap.putAll(map); // code here
45 |
46 |         //Printing key-value pairs of anotherMap
47 |
48 |         entrySet = anotherMap.entrySet();
49 |
50 |         for (Entry<String, Integer> entry : entrySet)
51 |         {
52 |             System.out.println(entry.getKey()+" : "+entry.getValue());

```

	Test	Input	Expected	Got	
✓	1	3 ONE TWO 1 THREE 2 THREE 3	ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 2 true true 4	ONE : 1 TWO : 2 THREE : 3 ----- SIX : 6 ONE : 1 TWO : 2 SEVEN : 7 THREE : 3 2 true true 4	✓

Passed all tests! ✓

[Finish review](#)

[→ Lab-11-MCQ](#)

Jump to...



[TreeSet example](#) ▶