

T-Pack: Network Security in Real-Time Systems

Network Security & Attacks

- **Security:** Policies to detect and prevent intrusion and malware execution
- Two broad categories: **System Security & Network Security**
- **Network Attacks**
 - **Man-In-the-Middle (MITM)**
 - Eg. Relay and Replay attacks. (Common attacks in real time systems)
 - **Denial of service (DS)**
 - Eg. ping-of-death, syn-flooding etc.
- **Delay Attacks** (Common in real-time systems)
 - Delay in intended execution time of applications
- Network attacks induces delay in packet transmission
 - MITM increases end-to-end travel time by interfering.
 - DS stalls the flow of useful packet through network congestion. (Inc. travel time)



Takeaway, Motivation & Hypothesis

- Takeaway
 - Need to detect network attacks
 - Can cause delays (deadline misses)
- Motivation
 - **Early Detection of Network Delay** with **no cost** and **negligible performance** overhead for a Distributed Real-Time System Using **Simple** Monitoring Techniques
- Hypothesis
 - Monitoring round trip time at packet level in a distributed real-time system (periodic)
 - provides a means to detect network intrusions
 - complements conventional security methods.

Assumption & Attack Model

- Assumption
 - Distributed real-time system with end-to-end real-time guarantees of message transmission
 - Aware of the novel background traffic (Even the worst case)
 - Packet prioritization using TT-Ethernet (time-based traffic shaping) or SDN defined equipments
 - Public key encryption between subsystems
 - An attacker cannot modify novel packets
- Attack: Alter network behaviour
 - Additional, duplicate or dropped packets induces a time delay in the given real-time system


Design



- Expected End-to-End time(ETT) or Round-Trip Time (RTT) (Also T_{exp})
 - $ETT = t_R - t_s + \Delta t_{rs}$ (clock offset) (UDP)
 - $RTT = t_{AS} - t_s$ (TCP)
- T_{exp} includes internal error $T_d + \Delta T_d$
 - $T_{wcet} = T_{exp}$ if internal delay is $T_d + |\Delta T_d|$
- Attacker induces delay $T_c + \Delta T_c$
 - $T_{obs} = T_{exp} + T_c + \Delta T_c$
- $T_{obs} > T_{wcet}$ indicates intrusion
- $T_c + \Delta T_c + T_d + \Delta T_d \leq T_d + |\Delta T_d|$
 - $T_{WCET} \geq T_{obs}$: vulnerability of T-Pack

- **TCP_QUICKACK & TCP_NODELAY (needed for packet level analysis)**
 - TCP Optimizations
 - Cumulative send and ack's (wait time at sender and receiver)
 - Non-deterministic execution in real-time systems
 - Controlled flow of packets in distributed real-time systems
 - TCP optimization provides only a marginal performance difference
 - Socket options: TCP_QUICKACK and TCP_NODELAY
 - to immediately transmit packet and acknowledgement.
 - Percentage of network utilization of transmission and receiver buffer for UAV paparazzi
 - (Observed for 60 sec period on Raspberry Pi 3 with preempt-RT Linux)
 - **With 'QUICKACK' & 'NODELAY' : 0.780% (tx) , 0.354% (rx)**
 - **Without 'QUICKACK' & 'NODELAY' : 0.754% (tx), 0.348% (rx)**
 - Easier for implementation of T-Pack

Comparison to Timeout Techniques




a) TCP

b) UDP


1. T-Pack works with global timeouts but providing early intrusion detection.
2. In time arrival of packet at t_R
 - Cancelling t_E and t_O
3. Long delay before packet sent or a lost packet detected by global timeout
 - Cancel t_E
 - T-Pack needs global timeouts
4. Packet sent early or simply late arrival of packet
 - Early timeout at t_E leaving $t_O - t_E$ to transition into safe mode.
5. For UDP, T-Pack raises an exception at t_R for late arrival of a packet
 - Receiver unaware of the sender
 - $t_R - t_O$ time to transition to safe mode
6. Early intrusion detection for T-Pack

Utilizing Linux Network Stack



- Linux packet data structure (Reading or updating packet data)
 - socket buffers (SKB)
- **Measuring time at lower layers of the network stack (Kernel level)**
 - Avoid transition time from user to kernel space
 - Packet time depends on read and write buffer capacity of sender and receiver
 - Earlier intrusion detection

Implementation




- Linux netfilter hooks execute T-Pack module
- UDP packets between sender and receiver in **red**.
- TCP between sender and receiver in **blue**.

Inside T-Pack: TCP

- Store current time in lookup table with IP address and port as key (monitoring each connection separately)
- Lookup table maintains Queues (For packet sent before ack received)
 - Send and Receive pointers
 - Send points to most recent packet sent (end of queue)
 - Receive points to packet waiting for Ack
 - Queue Nodes
 - Time
 - Expected sequence number
 - Next pointer


Inside T-Pack: UDP




- SKB as parameter to T-Pack callback function (2.1)
- (2.1.1) `skb_pull+skb_push` functions to remove existing headers and create space for custom header
- (2.1.2) `memcpy` custom header and then removed headers
- Recalculate UDP and IP header checksum
- Custom Header
 - offset (clock sync), sender time (t_s), checksum (integrity of custom header)

Experiment 1 Framework

- Client Server Model
 - Periodic messages from client to server
 - Resembling time triggered real time system
 - TCP protocol
 - **demonstrates**
 - **performance overhead of T-Pack**
 - **benefit of recording timestamp information at the lower layer.**



Observed Round-Trip Time(RTT) - Exp 1




- Box plot for RTT
 - 1. Time recorded at network layer (T-Pack),
 - 2. Time recorded at Application layer with T-Pack running,
 - 3. Time recorded at Application layer without T-Pack running
- (2) and (3)
 - demonstrate overhead of introducing T-Pack.
 - Mean RTT increases by a marginal amount of approximately 0.09 msecs.
- (1) and (2)
 - Demonstrate time packet spends between application layer and network layer
 - At sender and receiver
 - Early intrusion detection at network layer (~0.3 msecs)

T-Pack vs Baseline

- **Why not monitor packet at the application layer (Not just delayed intrusion detection)?**
 - Explicit reply packets needed to replicate acknowledgement
 - Twice the number of packets saturates write buffer of receiver (delay)
 - Increase in RTT (T_{exp}) (as increase in internal delay)
 - Higher acceptable RTT because of transitions from lower to upper layers of network stack and vice versa
 - Higher RTT results in more false negatives
- DDOS attack on the setup in experiment 1
 - 1 Attacker sending 100 bytes of ICMP packets with 0.001 sec interval on 10 parallel threads
 - Observed over 300 packet; Baseline (~289 false negatives) & T-Pack (~130 false negatives)

Experiment 2 Framework




- **UAV Paparazzi model**
 - **Unmanned aerial vehicle control software**
 - Models a real-time system based on a traditional shared memory of a real-time control systems.
 - A peer-to-peer network of 3 subsystems,
 - auto pilot (AP), fly by wire (FBW) control and ground station communicator (GSC)
 - **Model maintains the similar communication flow as the actual UAV paparazzi**
 - Replaces processing and calculation by each subsystems with sleep operations
 - Socket operations work as intended
- **Demonstrates ability of T-Pack to detect delay due to different intensities of distributed-denial-of-service attack on the network**

Attack Introduced in Experiment 2 and 3


- Distributed denial of service: ping-of-death
- Attack vector defined as $P(n,t,b,i)$
 - P: ping
 - n: number of attackers on the network
 - t : No. of parallel threads on each attacker executing the attack
 - b: byte size of each icmp packet
 - i: time interval between each packet in seconds
- Attack Vectors
 - Attack 1: $P(0,0,0,0)$ (No Attack)
 - Attack 2: $P(1,10,500,0.5)$
 - Attack 3: $P(1,10,500,0.1)$
 - Attack 4: $P(2,10,500,0.1)$
 - Attack 5: $P(2,30,500,0.05)$
 - Attack 6: $P(2,10,500,0) \sim$ ping flood
 - Attack 7: $P(2,30,1000,0.001) \sim$ ping flood

Observed Round-Trip Time(RTT) Against Different Attack Parameters - Exp2




- Monitoring packets using T-Pack
 - between autopilot and ground station communicator for the UAV Paparazzi model.
- Introducing ddos attack with various attack vectors as show in the Figure.
- Increase in the attack intensity increases RTT
- Worst case RTT without attack is less than all values of RTT with UAV under Attack 7, $P(2,30,1000,0.001)$
 - demonstrates 100% detection of a compromised network by T-Pack

Frequency Distribution of RTT within UAV under No Attack and Attack 7 - Exp2




- Number of times (y-axis) and RTT is observed (x-axis)
- Results indicate **no intersection** between the distributions
 - both cases can be discreetly distinguished
- **Attack with similar time delay effects as Attack 7, $P(2,30,1000,0.001)$ will always be detected by T-Pack.**

Frequency Distribution of RTT within UAV under No Attack and Attack 6 - Exp2




- Number of times (y-axis) and RTT is observed (x-axis)
- Results indicate **~1% intersection** between the distributions.
- <1% of the samples fall into the 0.9-0.95 msec range
 - **>99% of the attacks would be detected by T-Pack**
 - for a compromised network with time delay similar to that caused by Attack 6, $P(2,10,500,0)$

Frequency Distribution of RTT within UAV under No Attack and Attack 2 - Exp2




- Number of times (y-axis) and RTT is observed (x-axis)
- Results indicate significant overlap between distributions (~99%) b/w 0.65-0.85 msec range.
- Illustrates limitations of T-Pack.
 - Any attack with similar delays of
 - Attack 2, $P(1, 10, 500, 0.5)$
 - Will not be detected by T-Pack
- T-Pack can only complement other system security methods,
 - Does not replace them as not a panacea for intrusions.

Compatibility with Encryption Methods - IPSec




- Network layer security protocol
- Encrypts payload (everything after network header) after T-Pack implementation
- Decrypts the packet before extracting information using T-Pack.
- Protects against packet modification
 - Cannot prevent induced delays
 - T-Packs complements IPSec
- Results show T-Packs compatibility with other security protocols
- Similar trend in RTT values
 - Slightly higher due to encryption overhead

T-Pack with UDP



- Demonstrates ability of T-Pack to comply with different communication protocol
- Requires clock offset to calculate ETT (end-to-end trip time)
- Implemented NTP analogy within T-Pack
 - Clock offset calculated is used to estimate ETT
- Periodic re-synchronizations
 - Linear increase in clock-offset due to clock drift
- Results demonstrate similar trend in T-Pack for paparazzi UAV over UDP.

T-Pack for Paparazzi UAV over UDP & IPSec




- Consistency of T-Pack over UDP with IPSec enabled
- Avg. ETT values increase slightly due to encryption compared to T-Pack over UDP without IPSec (prev. slide)

Experiment 3 Framework

- Waters Workshop Challenge 2018
 - **Drone like multisystem demonstrating time triggered distributed real time system**
 - A peer-to-peer network of seven subsystems (TCP):
 - **Mission management system (MMS), Electrical Propulsion System (EPS),** Hydraulic Braking System (HBS), Sensors (communicating also with other sensors in the Waters model), Ground Station and Maintenance System
 - Model functions and communication patterns in each subsystem
 - **The RTT monitored between EPS and MMS**
 - Attack between the two subsystems is induced to analyze the accuracy of T-Pack during the attack
 - **Demonstrates consistency in detecting delay due to distributed denial-of-service attack by T-Pack.**

Observed Round-Trip Time(RTT) Against Different Attack Parameters - Exp3



- Similar to the UAV Paparazzi model
 - T-Pack fully detects Attack 7, $P(2,3,1000,0.001)$
- Consistency in results compared to the UAV Paparazzi model
- Demonstrates Consistency of T-Pack with other distributed real-time systems

Conclusion

- Experimental results indicated that **T-Pack successfully detected malware intrusion with almost 100% accuracy**
 - For attacks with similar intensity as Attack 7: $P(2,30,1000,0.001)$
- **Better compared to baseline**
- **T-Pack can be implemented at no cost with only a small overhead**
- **Implementation and results demonstrated in this work support the hypothesis**
 - Monitoring round trip time at packet level in a real-time distributed system (periodic)
 - provides a means to detect network intrusions complementing conventional security methods.

Thank You!