

RKE CIS v1.20 Benchmark - Self-Assessment Guide - Rancher v2.6

Contents

RKE CIS v1.20 Kubernetes Benchmark – Rancher v2.6 with Kubernetes v1.19 to v1.21	11
--	----

Controls	12
----------	----

1.1 Master Node Configuration Files	13
-------------------------------------	----

1.1.1 Ensure that the API server pod specification file permissions are set to 644 or more restrictive (Automated)	13
1.1.2 Ensure that the API server pod specification file ownership is set to root:root (Automated)	13
1.1.3 Ensure that the controller manager pod specification file permissions are set to 644 or more restrictive (Automated)	13
1.1.4 Ensure that the controller manager pod specification file ownership is set to root:root (Automated)	13
1.1.5 Ensure that the scheduler pod specification file permissions are set to 644 or more restrictive (Automated)	13
1.1.6 Ensure that the scheduler pod specification file ownership is set to root:root (Automated)	14
1.1.7 Ensure that the etcd pod specification file permissions are set to 644 or more restrictive (Automated)	14
1.1.8 Ensure that the etcd pod specification file ownership is set to root:root (Automated)	14
1.1.9 Ensure that the Container Network Interface file permissions are set to 644 or more restrictive (Manual)	14
1.1.10 Ensure that the Container Network Interface file ownership is set to root:root (Manual)	15
1.1.11 Ensure that the etcd data directory permissions are set to 700 or more restrictive (Automated)	15



1.1.12 Ensure that the etcd data directory ownership is set to etcd:etcd (Automated)	16
1.1.13 Ensure that the admin.conf file permissions are set to 644 or more restrictive (Automated)	16
1.1.14 Ensure that the admin.conf file ownership is set to root:root (Automated)	16
1.1.15 Ensure that the scheduler.conf file permissions are set to 644 or more restrictive (Automated)	16
1.1.16 Ensure that the scheduler.conf file ownership is set to root:root (Automated)	16
1.1.17 Ensure that the controller-manager.conf file permissions are set to 644 or more restrictive (Automated)	17
1.1.18 Ensure that the controller-manager.conf file ownership is set to root:root (Automated)	17
1.1.19 Ensure that the Kubernetes PKI directory and file ownership is set to root:root (Automated)	17
1.1.20 Ensure that the Kubernetes PKI certificate file permissions are set to 644 or more restrictive (Automated)	19
1.1.21 Ensure that the Kubernetes PKI key file permissions are set to 600 (Automated)	21

1.2 API Server 24

1.2.1 Ensure that the --anonymous-auth argument is set to false (Automated)	24
1.2.2 Ensure that the --token-auth-file parameter is not set (Automated)	25
1.2.3 Ensure that the --kubelet-https argument is set to true (Automated)	27
1.2.4 Ensure that the --kubelet-client-certificate and --kubelet-client-key arguments are set as appropriate (Automated)	28
1.2.5 Ensure that the --kubelet-certificate-authority argument is set as appropriate (Automated)	30
1.2.6 Ensure that the --authorization-mode argument is not set to AlwaysAllow (Automated)	30
1.2.7 Ensure that the --authorization-mode argument includes Node (Automated)	32



1.2.8 Ensure that the --authorization-mode argument includes RBAC (Automated)	34
1.2.9 Ensure that the admission control plugin EventRateLimit is set (Manual)	35
1.2.10 Ensure that the admission control plugin AlwaysAdmit is not set (Automated)	37
1.2.11 Ensure that the admission control plugin AlwaysPullImages is set (Manual)	38
1.2.12 Ensure that the admission control plugin SecurityContextDeny is set if PodSecurityPolicy is not used (Manual)	39
1.2.13 Ensure that the admission control plugin ServiceAccount is set (Automated)	39
1.2.14 Ensure that the admission control plugin NamespaceLifecycle is set (Automated)	41
1.2.15 Ensure that the admission control plugin PodSecurityPolicy is set (Automated)	42
1.2.16 Ensure that the admission control plugin NodeRestriction is set (Automated)	43
1.2.17 Ensure that the --insecure-bind-address argument is not set (Automated)	44
1.2.18 Ensure that the --insecure-port argument is set to 0 (Automated)	46
1.2.19 Ensure that the --secure-port argument is not set to 0 (Automated)	47
1.2.20 Ensure that the --profiling argument is set to false (Automated)	49
1.2.21 Ensure that the --audit-log-path argument is set (Automated)	51
1.2.22 Ensure that the --audit-log-maxage argument is set to 30 or as appropriate (Automated)	52
1.2.23 Ensure that the --audit-log-maxbackup argument is set to 10 or as appropriate (Automated)	54
1.2.24 Ensure that the --audit-log-maxsize argument is set to 100 or as appropriate (Automated)	55
1.2.25 Ensure that the --request-timeout argument is set as appropriate (Automated)	57



1.2.26 Ensure that the --service-account-lookup argument is set to true (Automated)	59
1.2.27 Ensure that the --service-account-key-file argument is set as appropriate (Automated)	60
1.2.28 Ensure that the --etcd-certfile and --etcd-keyfile arguments are set as appropriate (Automated)	62
1.2.29 Ensure that the --tls-cert-file and --tls-private-key-file arguments are set as appropriate (Automated)	64
1.2.30 Ensure that the --client-ca-file argument is set as appropriate (Automated)	65
1.2.31 Ensure that the --etcd-cafile argument is set as appropriate (Automated)	67
1.2.32 Ensure that the --encryption-provider-config argument is set as appropriate (Manual)	68
1.2.33 Ensure that encryption providers are appropriately configured (Manual)	69
1.2.34 Ensure that the API Server only makes use of Strong Cryptographic Ciphers (Manual)	69

1.3 Controller Manager 70

1.3.1 Ensure that the --terminated-pod-gc-threshold argument is set as appropriate (Automated)	70
1.3.2 Ensure that the --profiling argument is set to false (Automated)	70
1.3.3 Ensure that the --use-service-account-credentials argument is set to true (Automated)	71
1.3.4 Ensure that the --service-account-private-key-file argument is set as appropriate (Automated)	72
1.3.5 Ensure that the --root-ca-file argument is set as appropriate (Automated)	73
1.3.6 Ensure that the RotateKubeletServerCertificate argument is set to true (Automated)	73
1.3.7 Ensure that the --bind-address argument is set to 127.0.0.1 (Automated)	74



1.4 Scheduler 75

1.4.1 Ensure that the --profiling argument is set to false (Automated) 75

1.4.2 Ensure that the --bind-address argument is set to 127.0.0.1 (Automated) 75

2 Etcd Node Configuration Files 77

2.1 Ensure that the --cert-file and --key-file arguments are set as appropriate (Automated) 77

2.2 Ensure that the --client-cert-auth argument is set to true (Automated) 78

2.3 Ensure that the --auto-tls argument is not set to true (Automated) 79

2.4 Ensure that the --peer-cert-file and --peer-key-file arguments are set as appropriate (Automated) 79

2.5 Ensure that the --peer-client-cert-auth argument is set to true (Automated) 80

2.6 Ensure that the --peer-auto-tls argument is not set to true (Automated) 81

2.7 Ensure that a unique Certificate Authority is used for etcd (Automated) 82

3.1 Authentication and Authorization 84

3.1.1 Client certificate authentication should not be used for users (Manual) 84

3.2 Logging 85

3.2.1 Ensure that a minimal audit policy is created (Automated) 85

3.2.2 Ensure that the audit policy covers key security concerns (Manual) 86



4.1 Worker Node Configuration Files

87

- 4.1.1 Ensure that the kubelet service file permissions are set to 644 or more restrictive (Automated) 87
- 4.1.2 Ensure that the kubelet service file ownership is set to root:root (Automated) 87
- 4.1.3 If proxy kubeconfig file exists ensure permissions are set to 644 or more restrictive (Automated) 87
- 4.1.4 If proxy kubeconfig file exists ensure ownership is set to root:root (Automated) 88
- 4.1.5 Ensure that the --kubeconfig kubelet.conf file permissions are set to 644 or more restrictive (Automated) 88
- 4.1.6 Ensure that the --kubeconfig kubelet.conf file ownership is set to root:root (Automated) 89
- 4.1.7 Ensure that the certificate authorities file permissions are set to 644 or more restrictive (Automated) 89
- 4.1.8 Ensure that the client certificate authorities file ownership is set to root:root (Automated) 89
- 4.1.9 Ensure that the kubelet --config configuration file has permissions set to 644 or more restrictive (Automated) 90
- 4.1.10 Ensure that the kubelet --config configuration file ownership is set to root:root (Automated) 90

4.2 Kubelet

91

- 4.2.1 Ensure that the anonymous-auth argument is set to false (Automated) 91
- 4.2.2 Ensure that the --authorization-mode argument is not set to AlwaysAllow (Automated) 93
- 4.2.3 Ensure that the --client-ca-file argument is set as appropriate (Automated) 95
- 4.2.4 Ensure that the --read-only-port argument is set to 0 (Automated) 97
- 4.2.5 Ensure that the --streaming-connection-idle-timeout argument is not set to 0 (Automated) 100



4.2.6 Ensure that the --protect-kernel-defaults argument is set to true (Automated)	102
4.2.7 Ensure that the --make-iptables-util-chains argument is set to true (Automated)	102
4.2.8 Ensure that the --hostname-override argument is not set (Manual)	105
4.2.9 Ensure that the --event-qps argument is set to 0 or a level which ensures appropriate event capture (Automated)	105
4.2.10 Ensure that the --tls-cert-file and --tls-private-key-file arguments are set as appropriate (Manual)	107
4.2.11 Ensure that the --rotate-certificates argument is not set to false (Automated)	108
4.2.12 Verify that the RotateKubeletServerCertificate argument is set to true (Manual)	108
4.2.13 Ensure that the Kubelet only makes use of Strong Cryptographic Ciphers (Automated)	109

5.1 RBAC and Service Accounts 112

5.1.1 Ensure that the cluster-admin role is only used where required (Manual)	112
5.1.2 Minimize access to secrets (Manual)	112
5.1.3 Minimize wildcard use in Roles and ClusterRoles (Manual)	112
5.1.4 Minimize access to create pods (Manual)	112
5.1.5 Ensure that default service accounts are not actively used. (Automated)	112
5.1.6 Ensure that Service Account Tokens are only mounted where necessary (Manual)	113
5.1.7 Avoid use of system:masters group (Manual)	113
5.1.8 Limit use of the Bind, Impersonate and Escalate permissions in the Kubernetes cluster (Manual)	113



5.2 Pod Security Policies 114

- 5.2.1 Minimize the admission of privileged containers (Automated)** 114
- 5.2.2 Minimize the admission of containers wishing to share the host process ID namespace (Automated)** 114
- 5.2.3 Minimize the admission of containers wishing to share the host IPC namespace (Automated)** 114
- 5.2.4 Minimize the admission of containers wishing to share the host network namespace (Automated)** 114
- 5.2.5 Minimize the admission of containers with allowPrivilegeEscalation (Automated)** 114
- 5.2.6 Minimize the admission of root containers (Automated)** 115
- 5.2.7 Minimize the admission of containers with the NET_RAW capability (Automated)** 115
- 5.2.8 Minimize the admission of containers with added capabilities (Automated)** 115
- 5.2.9 Minimize the admission of containers with capabilities assigned (Manual)** 115

5.3 Network Policies and CNI 116

- 5.3.1 Ensure that the CNI in use supports Network Policies (Manual)** 116
- 5.3.2 Ensure that all Namespaces have Network Policies defined (Manual)** 116

5.4 Secrets Management 117

- 5.4.1 Prefer using secrets as files over secrets as environment variables (Manual)** 117
- 5.4.2 Consider external secret storage (Manual)** 117



5.5 Extensible Admission Control 118

5.5.1 Configure Image Provenance using ImagePolicyWebhook admission controller (Manual) 118

5.7 General Policies 119

5.7.1 Create administrative boundaries between resources using namespaces (Manual) 119

5.7.2 Ensure that the seccomp profile is set to docker/default in your pod definitions (Manual) 119

5.7.3 Apply Security Context to Your Pods and Containers (Manual) 119

5.7.4 The default namespace should not be used (Manual) 119



RKE CIS v1.20 Kubernetes Benchmark – Rancher v2.6 with Kubernetes v1.19 to v1.21

[Click here to download a PDF version of this document.](#)

Overview

This document is a companion to the [Rancher v2.6 RKE security hardening guide](#). The hardening guide provides prescriptive guidance for hardening a production installation of Rancher, and this benchmark guide is meant to help you evaluate the level of security of the hardened cluster against each control in the benchmark.

This guide corresponds to specific versions of the hardening guide, Rancher, CIS Benchmark and Kubernetes:

Hardening Guide Version	Rancher Version	CIS Benchmark Version	Kubernetes Version
Hardening Guide CIS v1.20 Benchmark	Rancher v2.6	CIS v1.20	Kubernetes v1.19 up to v1.21

Because Rancher and RKE install Kubernetes services as Docker containers, many of the control verification checks in the CIS Kubernetes Benchmark do not apply and will have a result of `Not Applicable`. This guide will walk through the various controls and provide updated example commands to audit compliance in Rancher created clusters.

This document is to be used by Rancher operators, security teams, auditors and decision makers.

For more detail about each audit, including rationales and remediations for failing tests, you can refer to the corresponding section of the CIS Kubernetes Benchmark v1.6. You can download the benchmark, after creating a free account, in [Center for Internet Security \(CIS\)](#).

Testing controls methodology

Rancher and RKE install Kubernetes services via Docker containers. Configuration is defined by arguments passed to the container at the time of initialization, not via configuration files.



Where control audits differ from the original CIS benchmark, the audit commands specific to Rancher are provided for testing. When performing the tests, you will need access to the command line on the hosts of all RKE nodes. The commands also make use of the [kubect](#)l (with a valid configuration file) and [jq](#) tools, which are required in the testing and evaluation of test results.

NOTE: Only **automated** tests (previously called **scored**) are covered in this guide.

Controls

1.1 Master Node

Configuration Files

1.1.1 Ensure that the API server pod specification file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for kube-apiserver. All configuration is passed in as arguments at container run time.

1.1.2 Ensure that the API server pod specification file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for kube-apiserver. All configuration is passed in as arguments at container run time.

1.1.3 Ensure that the controller manager pod specification file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for controller-manager. All configuration is passed in as arguments at container run time.

1.1.4 Ensure that the controller manager pod specification file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for controller-manager. All configuration is passed in as arguments at container run time.

1.1.5 Ensure that the scheduler pod specification file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable



Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for controller-manager. All configuration is passed in as arguments at container run time.

1.1.6 Ensure that the scheduler pod specification file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.7 Ensure that the etcd pod specification file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.8 Ensure that the etcd pod specification file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.9 Ensure that the Container Network Interface file permissions are set to 644 or more restrictive (Manual)

Result: warn

Remediation: Run the below command (based on the file location on your system) on the master node. For example, `chmod 644`

Audit:

```
ps -ef | grep $kubeletbin | grep -- --cni-conf-dir | sed 's%.*
cni-conf-dir[= ]\([^ ]*\)\.*/%' | xargs -I{} find {} -
mindepth 1 | xargs --no-run-if-empty stat -c permissions=%a
find /var/lib/cni/networks -type f 2> /dev/null | xargs --no-
run-if-empty stat -c permissions=%a
```

Expected Result:



```
'permissions' is present
```

Returned Value:

```
Usage: grep [OPTION]... PATTERN [FILE]... Try 'grep --help'
for more information.
```

1.1.10 Ensure that the Container Network Interface file ownership is set to root:root (Manual)

Result: warn

Remediation: Run the below command (based on the file location on your system) on the master node. For example, chown root:root

Audit:

```
ps -ef | grep $kubeletbin | grep -- --cni-conf-dir | sed 's%.*
cni-conf-dir[= ]\([^ ]*\)\.*/.*\1%' | xargs -I{} find {} -
mindepth 1 | xargs --no-run-if-empty stat -c %U:%G find /var/
lib/cni/networks -type f 2> /dev/null | xargs --no-run-if-
empty stat -c %U:%G
```

Expected Result:

```
'root:root' is present
```

Returned Value:

```
Usage: grep [OPTION]... PATTERN [FILE]... Try 'grep --help'
for more information.
```

1.1.11 Ensure that the etcd data directory permissions are set to 700 or more restrictive (Automated)

Result: pass

Remediation: On the etcd server node, get the etcd data directory, passed as an argument --data-dir, from the below command: ps -ef | grep etcd Run the below command (based on the etcd data directory found above). For example, chmod 700 /var/lib/etcd

Audit:

```
stat -c %a /node/var/lib/etcd
```

Expected Result:



```
'700' is equal to '700'
```

Returned Value:

```
700
```

1.1.12 Ensure that the etcd data directory ownership is set to etcd:etcd (Automated)

Result: Not Applicable

Remediation: On the etcd server node, get the etcd data directory, passed as an argument --data-dir, from the below command: `ps -ef | grep etcd` Run the below command (based on the etcd data directory found above). For example, `chown etcd:etcd /var/lib/etcd`

1.1.13 Ensure that the admin.conf file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE does not store the kubernetes default kubeconfig credentials file on the nodes.

1.1.14 Ensure that the admin.conf file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE does not store the kubernetes default kubeconfig credentials file on the nodes.

1.1.15 Ensure that the scheduler.conf file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.16 Ensure that the scheduler.conf file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.



1.1.17 Ensure that the controller-manager.conf file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.18 Ensure that the controller-manager.conf file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for scheduler. All configuration is passed in as arguments at container run time.

1.1.19 Ensure that the Kubernetes PKI directory and file ownership is set to root:root (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the master node. For example, `chown -R root:root /etc/kubernetes/pki/`

Audit Script: `check_files_owner_in_dir.sh`

```
#!/usr/bin/env bash

# This script is used to ensure the owner is set to root:root
# for
# the given directory and all the files in it
#
# inputs:
#   $1 = /full/path/to/directory
#
# outputs:
#   true/false

INPUT_DIR=$1

if [[ "${INPUT_DIR}" == "" ]]; then
    echo "false"
```



```

        exit
    fi

    if [[ $(stat -c %U:%G ${INPUT_DIR}) != "root:root" ]]; then
        echo "false"
        exit
    fi

    statInfoLines=$(stat -c "%n %U:%G" ${INPUT_DIR}/*)
    while read -r statInfoLine; do
        f=$(echo ${statInfoLine} | cut -d' ' -f1)
        p=$(echo ${statInfoLine} | cut -d' ' -f2)

        if [[ $(basename "$f" .pem) == "kube-etcd-*" ]]; then
            if [[ "$p" != "root:root" && "$p" != "etcd:etcd" ]]; then
                echo "false"
                exit
            fi
        else
            if [[ "$p" != "root:root" ]]; then
                echo "false"
                exit
            fi
        fi
    done <<< "${statInfoLines}"

    echo "true"
    exit

```

Audit Execution:

```
./check_files_owner_in_dir.sh /node/etc/kubernetes/ssl
```

Expected Result:

```
'true' is equal to 'true'
```

Returned Value:

`true`

1.1.20 Ensure that the Kubernetes PKI certificate file permissions are set to 644 or more restrictive (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the master node. For example, `chmod -R 644 /etc/kubernetes/pki/*.crt`

Audit Script: `check_files_permissions.sh`

```
#!/usr/bin/env bash

# This script is used to ensure the file permissions are set
# to 644 or
# more restrictive for all files in a given directory or a
# wildcard
# selection of files
#
# inputs:
#   $1 = /full/path/to/directory or /path/to/fileswithpattern
#                                     ex: !(*key).pem
#
#   $2 (optional) = permission (ex: 600)
#
# outputs:
#   true/false

# Turn on "extended glob" for use of '!' in wildcard
shopt -s extglob

# Turn off history to avoid surprises when using '!'
set -H

USER_INPUT=$1

if [[ "${USER_INPUT}" == "" ]]; then
    echo "false"
    exit
```



```

fi

if [[ -d ${USER_INPUT} ]]; then
    PATTERN="${USER_INPUT}/*"
else
    PATTERN="${USER_INPUT}"
fi

PERMISSION=""
if [[ "$2" != "" ]]; then
    PERMISSION=$2
fi

FILES_PERMISSIONS=$(stat -c %n\ %a ${PATTERN})

while read -r fileInfo; do
    p=$(echo ${fileInfo} | cut -d' ' -f2)

    if [[ "${PERMISSION}" != "" ]]; then
        if [[ "$p" != "${PERMISSION}" ]]; then
            echo "false"
            exit
        fi
    else
        if [[ "$p" != "644" && "$p" != "640" && "$p" != "600" ]];
    then
        echo "false"
        exit
    fi
fi
done <<< "${FILES_PERMISSIONS}"

echo "true"
exit

```

Audit Execution:



```
./check_files_permissions.sh '/node/etc/kubernetes/ssl/!
(*key).pem'
```

Expected Result:

```
'true' is equal to 'true'
```

Returned Value:

```
true
```

1.1.21 Ensure that the Kubernetes PKI key file permissions are set to 600 (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the master node. For example, `chmod -R 600 /etc/kubernetes/ssl/*key.pem`

Audit Script: `check_files_permissions.sh`

```
#!/usr/bin/env bash

# This script is used to ensure the file permissions are set
# to 644 or
# more restrictive for all files in a given directory or a
# wildcard
# selection of files
#
# inputs:
#   $1 = /full/path/to/directory or /path/to/fileswithpattern
#                                     ex: !(*key).pem
#
#   $2 (optional) = permission (ex: 600)
#
# outputs:
#   true/false

# Turn on "extended glob" for use of '!' in wildcard
shopt -s extglob
```



```

# Turn off history to avoid surprises when using '!'
set -H

USER_INPUT=$1

if [[ "${USER_INPUT}" == "" ]]; then
    echo "false"
    exit
fi

if [[ -d ${USER_INPUT} ]]; then
    PATTERN="${USER_INPUT}/*"
else
    PATTERN="${USER_INPUT}"
fi

PERMISSION=""
if [[ "$2" != "" ]]; then
    PERMISSION=$2
fi

FILES_PERMISSIONS=$(stat -c %n\ %a ${PATTERN})

while read -r fileInfo; do
    p=$(echo ${fileInfo} | cut -d' ' -f2)

    if [[ "${PERMISSION}" != "" ]]; then
        if [[ "$p" != "${PERMISSION}" ]]; then
            echo "false"
            exit
        fi
    else
        if [[ "$p" != "644" && "$p" != "640" && "$p" != "600" ]]; then
            echo "false"
            exit
        fi
    fi
done

```



```
    fi
done <<< "${FILES_PERMISSIONS}"

echo "true"
exit
```

Audit Execution:

```
./check_files_permissions.sh '/node/etc/kubernetes/ssl/
*key.pem'
```

Expected Result:

```
'true' is equal to 'true'
```

Returned Value:

```
true
```

1.2 API Server

1.2.1 Ensure that the --anonymous-auth argument is set to false (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the below parameter. `--anonymous-auth=false`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--anonymous-auth' is equal to 'false'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/
```




```

v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-webhook.yaml --audit-policy-file=/etc/kubernetes/audit-policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --authorization-mode=Node,RBAC --enable-admission-plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultStorageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Priority,TaintNodesByCondition,PersistentVolumeClaimResize --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16

```

1.2.2 Ensure that the --token-auth-file parameter is not set (Automated)

Result: pass

Remediation: Follow the documentation and configure alternate mechanisms for authentication. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and remove the `--token-auth-file=` parameter.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:



```
'--token-auth-file' is not present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
```



```

cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.3 Ensure that the --kubelet-https argument is set to true (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and remove the `--kubelet-https` parameter.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--kubelet-https' is present OR '--kubelet-https' is not
present
```

Returned Value:

```

root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-

```



```

apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-webhook.yaml --audit-policy-file=/etc/kubernetes/audit-policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --authorization-mode=Node,RBAC --enable-admission-plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultStorageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Priority,TaintNodesByCondition,PersistentVolumeClaimResize --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16

```

1.2.4 Ensure that the --kubelet-client-certificate and --kubelet-client-key arguments are set as appropriate (Automated)

Result: pass



Remediation: Follow the Kubernetes documentation and set up the TLS connection between the apiserver and kubelets. Then, edit API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the kubelet client certificate and key parameters as below. `--kubelet-client-certificate=` `--kubelet-client-key=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--kubelet-client-certificate' is present AND '--kubelet-client-key' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/
```



```
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.5 Ensure that the --kubelet-certificate-authority argument is set as appropriate (Automated)

Result: Not Applicable

Remediation: Follow the Kubernetes documentation and setup the TLS connection between the apiserver and kubelets. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--kubelet-certificate-authority` parameter to the path to the cert file for the certificate authority. `--kubelet-certificate-authority=` When generating serving certificates, functionality could break in conjunction with hostname overrides which are required for certain cloud providers.

1.2.6 Ensure that the --authorization-mode argument is not set to AlwaysAllow (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--`



authorization-mode parameter to values other than AlwaysAllow. One such example could be as below. --authorization-mode=RBAC

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--authorization-mode' does not have 'AlwaysAllow'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
```



```
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.7 Ensure that the --authorization-mode argument includes Node (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--authorization-mode` parameter to a value that includes Node. `--authorization-mode=Node,RBAC`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--authorization-mode' has 'Node'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
```




```

file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-

```



```
apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16
```

1.2.8 Ensure that the --authorization-mode argument includes RBAC (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--authorization-mode` parameter to a value that includes RBAC, for example: `--authorization-mode=Node,RBAC`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--authorization-mode' has 'RBAC'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-
```



```
headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-webhook.yaml --audit-policy-file=/etc/kubernetes/audit-policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --authorization-mode=Node,RBAC --enable-admission-plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultStorageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Priority,TaintNodesByCondition,PersistentVolumeClaimResize --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16
```

1.2.9 Ensure that the admission control plugin EventRateLimit is set (Manual)

Result: warn

Remediation: Follow the Kubernetes documentation and set the desired limits in a configuration file. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` and set the below parameters. `--enable-admission-plugins=...,EventRateLimit,...` `--admission-control-config-file=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:



```
'--enable-admission-plugins' has 'EventRateLimit'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
```



```

cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.10 Ensure that the admission control plugin AlwaysAdmit is not set (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and either remove the `--enable-admission-plugins` parameter, or set it to a value that does not include AlwaysAdmit.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--enable-admission-plugins' does not have 'AlwaysAdmit' OR
'--enable-admission-plugins' is not present
```

Returned Value:

```

root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-

```



```

client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.11 Ensure that the admission control plugin AlwaysPullImages is set (Manual)

Result: warn



Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--enable-admission-plugins` parameter to include `AlwaysPullImages`. `--enable-admission-plugins=...,AlwaysPullImages,...`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

1.2.12 Ensure that the admission control plugin `SecurityContextDeny` is set if `PodSecurityPolicy` is not used (Manual)

Result: warn

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--enable-admission-plugins` parameter to include `SecurityContextDeny`, unless `PodSecurityPolicy` is already in place. `--enable-admission-plugins=...,SecurityContextDeny,...`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

1.2.13 Ensure that the admission control plugin `ServiceAccount` is set (Automated)

Result: pass

Remediation: Follow the documentation and create `ServiceAccount` objects as per your environment. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and ensure that the `--disable-admission-plugins` parameter is set to a value that does not include `ServiceAccount`.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--disable-admission-plugins' is present OR '--disable-admission-plugins' is not present
```

Returned Value:



```

root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130

```




```
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16
```

1.2.14 Ensure that the admission control plugin NamespaceLifecycle is set (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--disable-admission-plugins` parameter to ensure it does not include `NamespaceLifecycle`.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--disable-admission-plugins' is present OR '--disable-admission-plugins' is not present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
```



```

provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.15 Ensure that the admission control plugin PodSecurityPolicy is set (Automated)

Result: Not Applicable

Remediation: Follow the documentation and create Pod Security Policy objects as per your environment. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--enable-admission-plugins` parameter



to a value that includes PodSecurityPolicy: --enable-admission-plugins=...,PodSecurityPolicy,... Then restart the API Server. Enabling Pod Security Policy can cause applications to unexpectedly fail.

1.2.16 Ensure that the admission control plugin NodeRestriction is set (Automated)

Result: pass

Remediation: Follow the Kubernetes documentation and configure NodeRestriction plug-in on kubelets. Then, edit the API server pod specification file /etc/kubernetes/manifests/kube-apiserver.yaml on the master node and set the --enable-admission-plugins parameter to a value that includes NodeRestriction. --enable-admission-plugins=...,NodeRestriction,...

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--enable-admission-plugins' has 'NodeRestriction'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-
```



```

Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.17 Ensure that the --insecure-bind-address argument is not set (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and remove the `--insecure-bind-address` parameter.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:



```
'--insecure-bind-address' is not present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
```



```

cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.18 Ensure that the --insecure-port argument is set to 0 (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the below parameter. `--insecure-port=0`

Audit:

```
/bin/ps -ef | grep kube-apiserver
```

Expected Result:

```
'--insecure-port' is equal to '0' OR '--insecure-port' is not
present
```

Returned Value:

```

root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-

```



```

apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-webhook.yaml --audit-policy-file=/etc/kubernetes/audit-policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --authorization-mode=Node,RBAC --enable-admission-plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultStorageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Priority,TaintNodesByCondition,PersistentVolumeClaimResize --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16 root 22820 22818 0 10:36 ? 00:00:00 grep kube-apiserver

```

1.2.19 Ensure that the --secure-port argument is not set to 0 (Automated)

Result: pass



Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and either remove the `--secure-port` parameter or set it to a different (non-zero) desired port.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--secure-port' is greater than 0 OR '--secure-port' is not present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-
```




```
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,Defaults
storageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.20 Ensure that the --profiling argument is set to false (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the below parameter. `--profiling=false`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--profiling' is equal to 'false'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
```



```
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
```



```
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.21 Ensure that the --audit-log-path argument is set (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--audit-log-path` parameter to a suitable path and file where you would like audit logs to be written, for example: `--audit-log-path=/var/log/apiserver/audit.log`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--audit-log-path' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:07 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
```



```

Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.22 Ensure that the --audit-log-maxage argument is set to 30 or as appropriate (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the --audit-log-maxage parameter to 30 or as an appropriate number of days: `--audit-log-maxage=30`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```



Expected Result:

```
'--audit-log-maxage' is greater or equal to 30
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
```



```
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.23 Ensure that the --audit-log-maxbackup argument is set to 10 or as appropriate (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--audit-log-maxbackup` parameter to 10 or to an appropriate value. `--audit-log-maxbackup=10`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--audit-log-maxbackup' is greater or equal to 10
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
```



```

client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

1.2.24 Ensure that the --audit-log-maxsize argument is set to 100 or as appropriate (Automated)

Result: pass



Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the `--audit-log-maxsize` parameter to an appropriate size in MB. For example, to set it as 100 MB: `--audit-log-maxsize=100`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--audit-log-maxsize' is greater or equal to 100
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
```




```
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.25 Ensure that the --request-timeout argument is set as appropriate (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` and set the below parameter as appropriate and if needed. For example, `--request-timeout=300s`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--request-timeout' is not present OR '--request-timeout' is
present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
```



```
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
```



```
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.26 Ensure that the --service-account-lookup argument is set to true (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the below parameter. `--service-account-lookup=true` Alternatively, you can delete the `--service-account-lookup` parameter from this file so that the default takes effect.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--service-account-lookup' is not present OR '--service-
account-lookup' is equal to 'true'
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
```



```
secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-log.json --service-account-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --tls-private-key-file=/etc/kubernetes/ssl/kube-apiserver-key.pem --authentication-token-webhook-config-file=/etc/kubernetes/kube-api-authn-webhook.yaml --audit-policy-file=/etc/kubernetes/audit-policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --authorization-mode=Node,RBAC --enable-admission-plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultStorageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Priority,TaintNodesByCondition,PersistentVolumeClaimResize --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16
```

1.2.27 Ensure that the --service-account-key-file argument is set as appropriate (Automated)

Result: pass

Remediation: Edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the --service-account-key-file parameter to the public key file for service accounts: `--service-account-key-file=`

Audit:



```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--service-account-key-file' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,Defaults
```



```
storageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.28 Ensure that the --etcd-certfile and --etcd-keyfile arguments are set as appropriate (Automated)

Result: pass

Remediation: Follow the Kubernetes documentation and set up the TLS connection between the apiserver and etcd. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the etcd certificate and key file parameters. `--etcd-certfile=` `--etcd-keyfile=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--etcd-certfile' is present AND '--etcd-keyfile' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
```



```

kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```



1.2.29 Ensure that the --tls-cert-file and --tls-private-key-file arguments are set as appropriate (Automated)

Result: pass

Remediation: Follow the Kubernetes documentation and set up the TLS connection on the apiserver. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the TLS certificate and private key file parameters. `--tls-cert-file=` `--tls-private-key-file=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--tls-cert-file' is present AND '--tls-private-key-file' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-
```




```
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.30 Ensure that the --client-ca-file argument is set as appropriate (Automated)

Result: pass

Remediation: Follow the Kubernetes documentation and set up the TLS connection on the apiserver. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the client certificate authority file. `--client-ca-file=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--client-ca-file' is present
```



Returned Value:

```

root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-
account-signing-key-file=/etc/kubernetes/ssl/kube-service-
account-token-key.pem --kubelet-preferred-address-
types=InternalIP,ExternalIP,Hostname --allow-privileged=true
--audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-
file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-
issuer=rke --anonymous-auth=false --audit-log-format=json --
audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/
kube-node.pem --authentication-token-webhook-cache-ttl=5s --
service-account-lookup=true --api-audiences=unknown --proxy-
client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-
client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-
apiserver-proxy-client-key.pem --requestheader-username-
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA

```



```
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --insecure-port=0 --requestheader-allowed-names=kube-apiserver-proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --requestheader-client-ca-file=/etc/kubernetes/ssl/kube-apiserver-requestheader-ca.pem --service-cluster-ip-range=10.43.0.0/16
```

1.2.31 Ensure that the --etcd-cafile argument is set as appropriate (Automated)

Result: pass

Remediation: Follow the Kubernetes documentation and set up the TLS connection between the apiserver and etcd. Then, edit the API server pod specification file `/etc/kubernetes/manifests/kube-apiserver.yaml` on the master node and set the etcd certificate authority file parameter. `--etcd-cafile=`

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--etcd-cafile' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-
```



```
headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-
provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-
key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-
client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --
secure-port=6443 --requestheader-extra-headers-prefix=X-
Remote-Extra- --runtime-config=authorization.k8s.io/
v1beta1=true --storage-backend=etcd3 --requestheader-group-
headers=X-Remote-Group --profiling=false --service-node-port-
range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,DefaultS
torageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16
```

1.2.32 Ensure that the --encryption-provider-config argument is set as appropriate (Manual)

Result: Not Applicable

Remediation: Follow the Kubernetes documentation and configure a EncryptionConfig file. Then, edit the API server pod specification file /



etc/kubernetes/manifests/kube-apiserver.yaml on the master node and set the --encryption-provider-config parameter to the path of that file: --encryption-provider-config= Enabling encryption changes how data can be recovered as data is encrypted.

1.2.33 Ensure that encryption providers are appropriately configured (Manual)

Result: Not Applicable

Remediation: Follow the Kubernetes documentation and configure a EncryptionConfig file. In this file, choose aescbc, kms or secretbox as the encryption provider. Enabling encryption changes how data can be recovered as data is encrypted.

1.2.34 Ensure that the API Server only makes use of Strong Cryptographic Ciphers (Manual)

Result: warn

Remediation: Edit the API server pod specification file /etc/kubernetes/manifests/kube-apiserver.yaml on the master node and set the below parameter. --tls-cipher-

suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```



1.3 Controller Manager

1.3.1 Ensure that the --terminated-pod-gc-threshold argument is set as appropriate (Automated)

Result: pass

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and set the `--terminated-pod-gc-threshold` to an appropriate threshold, for example: `--terminated-pod-gc-threshold=10`

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--terminated-pod-gc-threshold' is present
```

Returned Value:

```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```

1.3.2 Ensure that the --profiling argument is set to false (Automated)

Result: pass



Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and set the below parameter. `--profiling=false`

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--profiling' is equal to 'false'
```

Returned Value:

```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```

1.3.3 Ensure that the `--use-service-account-credentials` argument is set to true (Automated)

Result: pass

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node to set the below parameter. `--use-service-account-credentials=true`

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--use-service-account-credentials' is not equal to 'false'
```

Returned Value:



```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```

1.3.4 Ensure that the --service-account-private-key-file argument is set as appropriate (Automated)

Result: pass

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and set the `--service-account-private-key-file` parameter to the private key file for service accounts. `--service-account-private-key-file=`

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--service-account-private-key-file' is present
```

Returned Value:

```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
```




```
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```

1.3.5 Ensure that the --root-ca-file argument is set as appropriate (Automated)

Result: pass

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and set the `--root-ca-file` parameter to the certificate bundle file. `--root-ca-file=`

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--root-ca-file' is present
```

Returned Value:

```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```

1.3.6 Ensure that the RotateKubeletServerCertificate argument is set to true (Automated)

Result: Not Applicable

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and set the `--feature-gates` parameter to include



RotateKubeletServerCertificate=true. --feature-gates=RotateKubeletServerCertificate=true Cluster provisioned by RKE handles certificate rotation directly through RKE.

1.3.7 Ensure that the --bind-address argument is set to 127.0.0.1 (Automated)

Result: pass

Remediation: Edit the Controller Manager pod specification file `/etc/kubernetes/manifests/kube-controller-manager.yaml` on the master node and ensure the correct value for the `--bind-address` parameter

Audit:

```
/bin/ps -ef | grep kube-controller-manager | grep -v grep
```

Expected Result:

```
'--bind-address' is present OR '--bind-address' is not present
```

Returned Value:

```
root 13538 13518 2 10:28 ? 00:00:12 kube-controller-manager --
cluster-cidr=10.42.0.0/16 --root-ca-file=/etc/kubernetes/ssl/
kube-ca.pem --configure-cloud-routes=false --service-account-
private-key-file=/etc/kubernetes/ssl/kube-service-account-
token-key.pem --allocate-node-cidrs=true --kubeconfig=/etc/
kubernetes/ssl/kubecfg-kube-controller-manager.yaml --allow-
untagged-cloud=true --leader-elect=true --profiling=false --
cloud-provider= --service-cluster-ip-range=10.43.0.0/16 --pod-
eviction-timeout=5m0s --v=2 --address=0.0.0.0 --enable-
hostpath-provisioner=false --node-monitor-grace-period=40s --
terminated-pod-gc-threshold=1000 --use-service-account-
credentials=true
```



1.4 Scheduler

1.4.1 Ensure that the --profiling argument is set to false (Automated)

Result: pass

Remediation: Edit the Scheduler pod specification file `/etc/kubernetes/manifests/kube-scheduler.yaml` on the master node and set the below parameter. `--profiling=false`

Audit:

```
/bin/ps -ef | grep kube-scheduler | grep -v grep
```

Expected Result:

```
'--profiling' is equal to 'false'
```

Returned Value:

```
root 13694 13674 0 10:28 ? 00:00:02 kube-scheduler --
kubecfg=/etc/kubernetes/ssl/kubecfg-kube-scheduler.yaml --
address=0.0.0.0 --leader-elect=true --profiling=false --v=2
```

1.4.2 Ensure that the --bind-address argument is set to 127.0.0.1 (Automated)

Result: pass

Remediation: Edit the Scheduler pod specification file `/etc/kubernetes/manifests/kube-scheduler.yaml` on the master node and ensure the correct value for the `--bind-address` parameter

Audit:

```
/bin/ps -ef | grep kube-scheduler | grep -v grep
```

Expected Result:

```
'--bind-address' is present OR '--bind-address' is not present
```

Returned Value:



```
root 13694 13674 0 10:28 ? 00:00:02 kube-scheduler --  
kubecfg=/etc/kubernetes/ssl/kubecfg-kube-scheduler.yaml --  
address=0.0.0.0 --leader-elect=true --profiling=false --v=2
```



2 Etcd Node

Configuration Files

2.1 Ensure that the `--cert-file` and `--key-file` arguments are set as appropriate (Automated)

Result: pass

Remediation: Follow the etcd service documentation and configure TLS encryption. Then, edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and set the below parameters. `--cert-file=` `--key-file=`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:

```
'--cert-file' is present AND '--key-file' is present
```

Returned Value:

```
root 13075 13055 3 10:28 ? 00:00:16 /usr/local/bin/etcd --
peer-key-file=/etc/kubernetes/ssl/kube-etcd-172-31-8-188-
key.pem --advertise-client-urls=https://172.31.8.188:2379 --
client-cert-auth=true --name=etcd-rke1-120-cis-e1 --listen-
peer-urls=https://172.31.8.188:2380 --initial-cluster=etcd-
rke1-120-cis-e1=https://172.31.8.188:2380 --cert-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188.pem --key-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188-key.pem --data-dir=/var/
lib/rancher/etcd/ --initial-advertise-peer-urls=https://
172.31.8.188:2380 --initial-cluster-state=new --heartbeat-
interval=500 --listen-client-urls=https://172.31.8.188:2379 --
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --peer-
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cipher-
suites=TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WIT
H_AES_256_GCM_SHA384 --enable-v2=true --initial-cluster-
token=etcd-cluster-1 --peer-cert-file=/etc/kubernetes/ssl/
kube-etcd-172-31-8-188.pem --peer-client-cert-auth=true --
```



```
election-timeout=5000 root 23666 23640 10 10:36 ? 00:00:00
kube-bench run --targets etcd --scored --nosummary --
noremediations --v=0 --config-dir=/etc/kube-bench/cfg --
benchmark rke-cis-1.20-permissive --json --log_dir /tmp/
sonobuoy/logs --outputfile /tmp/sonobuoy/etcd.json
```

2.2 Ensure that the --client-cert-auth argument is set to true (Automated)

Result: pass

Remediation: Edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and set the below parameter.
`--client-cert-auth="true"`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:

```
'--client-cert-auth' is present OR '--client-cert-auth' is
equal to 'true'
```

Returned Value:

```
root 13075 13055 3 10:28 ? 00:00:16 /usr/local/bin/etcd --
peer-key-file=/etc/kubernetes/ssl/kube-etcd-172-31-8-188-
key.pem --advertise-client-urls=https://172.31.8.188:2379 --
client-cert-auth=true --name=etcd-rke1-120-cis-e1 --listen-
peer-urls=https://172.31.8.188:2380 --initial-cluster=etcd-
rke1-120-cis-e1=https://172.31.8.188:2380 --cert-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188.pem --key-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188-key.pem --data-dir=/var/
lib/rancher/etcd/ --initial-advertise-peer-urls=https://
172.31.8.188:2380 --initial-cluster-state=new --heartbeat-
interval=500 --listen-client-urls=https://172.31.8.188:2379 --
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --peer-
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cipher-
suites=TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WIT
H_AES_256_GCM_SHA384 --enable-v2=true --initial-cluster-
token=etcd-cluster-1 --peer-cert-file=/etc/kubernetes/ssl/
kube-etcd-172-31-8-188.pem --peer-client-cert-auth=true --
```



```
election-timeout=5000 root 23666 23640 7 10:36 ? 00:00:00
kube-bench run --targets etcd --scored --nosummary --
noremediations --v=0 --config-dir=/etc/kube-bench/cfg --
benchmark rke-cis-1.20-permissive --json --log_dir /tmp/
sonobuoy/logs --outputfile /tmp/sonobuoy/etcd.json
```

2.3 Ensure that the --auto-tls argument is not set to true (Automated)

Result: pass

Remediation: Edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and either remove the `--auto-tls` parameter or set it to false. `--auto-tls=false`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:

```
'ETCD_AUTO_TLS' is not present OR 'ETCD_AUTO_TLS' is present
```

Returned Value:

```
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/
bin HOSTNAME=rke1-120-cis-e1 ETCDCTL_API=3 ETCDCTL_CACERT=/
etc/kubernetes/ssl/kube-ca.pem ETCDCTL_CERT=/etc/kubernetes/
ssl/kube-etcd-172-31-8-188.pem ETCDCTL_KEY=/etc/kubernetes/
ssl/kube-etcd-172-31-8-188-key.pem ETCDCTL_ENDPOINTS=https://
172.31.8.188:2379 ETCD_UNSUPPORTED_ARCH=x86_64 HOME=/root
```

2.4 Ensure that the --peer-cert-file and --peer-key-file arguments are set as appropriate (Automated)

Result: pass

Remediation: Follow the etcd service documentation and configure peer TLS encryption as appropriate for your etcd cluster. Then, edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and set the below parameters. `--peer-client-file=` `--peer-key-file=`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```



Expected Result:

```
'--peer-cert-file' is present AND '--peer-key-file' is present
```

Returned Value:

```
root 13075 13055 3 10:28 ? 00:00:17 /usr/local/bin/etcd --
peer-key-file=/etc/kubernetes/ssl/kube-etcd-172-31-8-188-
key.pem --advertise-client-urls=https://172.31.8.188:2379 --
client-cert-auth=true --name=etcd-rke1-120-cis-e1 --listen-
peer-urls=https://172.31.8.188:2380 --initial-cluster=etcd-
rke1-120-cis-e1=https://172.31.8.188:2380 --cert-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188.pem --key-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188-key.pem --data-dir=/var/
lib/rancher/etcd/ --initial-advertise-peer-urls=https://
172.31.8.188:2380 --initial-cluster-state=new --heartbeat-
interval=500 --listen-client-urls=https://172.31.8.188:2379 --
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --peer-
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cipher-
suites=TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WIT
H_AES_256_GCM_SHA384 --enable-v2=true --initial-cluster-
token=etcd-cluster-1 --peer-cert-file=/etc/kubernetes/ssl/
kube-etcd-172-31-8-188.pem --peer-client-cert-auth=true --
election-timeout=5000 root 23666 23640 4 10:36 ? 00:00:00
kube-bench run --targets etcd --scored --nosummary --
noremediations --v=0 --config-dir=/etc/kube-bench/cfg --
benchmark rke-cis-1.20-permissive --json --log_dir /tmp/
sonobuoy/logs --outputfile /tmp/sonobuoy/etcd.json
```

2.5 Ensure that the `--peer-client-cert-auth` argument is set to true (Automated)

Result: pass

Remediation: Edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and set the below parameter.
`--peer-client-cert-auth=true`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:




```
'--peer-client-cert-auth' is present OR '--peer-client-cert-auth' is equal to 'true'
```

Returned Value:

```
root 13075 13055 3 10:28 ? 00:00:17 /usr/local/bin/etcd --
peer-key-file=/etc/kubernetes/ssl/kube-etcd-172-31-8-188-
key.pem --advertise-client-urls=https://172.31.8.188:2379 --
client-cert-auth=true --name=etcd-rke1-120-cis-e1 --listen-
peer-urls=https://172.31.8.188:2380 --initial-cluster=etcd-
rke1-120-cis-e1=https://172.31.8.188:2380 --cert-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188.pem --key-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188-key.pem --data-dir=/var/
lib/rancher/etcd/ --initial-advertise-peer-urls=https://
172.31.8.188:2380 --initial-cluster-state=new --heartbeat-
interval=500 --listen-client-urls=https://172.31.8.188:2379 --
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --peer-
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cipher-
suites=TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WIT
H_AES_256_GCM_SHA384 --enable-v2=true --initial-cluster-
token=etcd-cluster-1 --peer-cert-file=/etc/kubernetes/ssl/
kube-etcd-172-31-8-188.pem --peer-client-cert-auth=true --
election-timeout=5000 root 23666 23640 3 10:36 ? 00:00:00
kube-bench run --targets etcd --scored --nosummary --
noremediations --v=0 --config-dir=/etc/kube-bench/cfg --
benchmark rke-cis-1.20-permissive --json --log_dir /tmp/
sonobuoy/logs --outputfile /tmp/sonobuoy/etcd.json
```

2.6 Ensure that the --peer-auto-tls argument is not set to true (Automated)

Result: pass

Remediation: Edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and either remove the `--peer-auto-tls` parameter or set it to false. `--peer-auto-tls=false`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:



```
'ETCD_PEER_AUTO_TLS' is not present OR 'ETCD_PEER_AUTO_TLS'
is not present
```

Returned Value:

```
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/
bin HOSTNAME=rke1-120-cis-e1 ETCDCTL_API=3 ETCDCTL_CACERT=/
etc/kubernetes/ssl/kube-ca.pem ETCDCTL_CERT=/etc/kubernetes/
ssl/kube-etcd-172-31-8-188.pem ETCDCTL_KEY=/etc/kubernetes/
ssl/kube-etcd-172-31-8-188-key.pem ETCDCTL_ENDPOINTS=https://
172.31.8.188:2379 ETCD_UNSUPPORTED_ARCH=x86_64 HOME=/root
```

2.7 Ensure that a unique Certificate Authority is used for etcd (Automated)

Result: pass

Remediation: [Manual test] Follow the etcd documentation and create a dedicated certificate authority setup for the etcd service. Then, edit the etcd pod specification file `/etc/kubernetes/manifests/etcd.yaml` on the master node and set the below parameter. `--trusted-ca-file=`

Audit:

```
/bin/ps -ef | /bin/grep etcd | /bin/grep -v grep
```

Expected Result:

```
'--trusted-ca-file' is present
```

Returned Value:

```
root 13075 13055 3 10:28 ? 00:00:17 /usr/local/bin/etcd --
peer-key-file=/etc/kubernetes/ssl/kube-etcd-172-31-8-188-
key.pem --advertise-client-urls=https://172.31.8.188:2379 --
client-cert-auth=true --name=etcd-rke1-120-cis-e1 --listen-
peer-urls=https://172.31.8.188:2380 --initial-cluster=etcd-
rke1-120-cis-e1=https://172.31.8.188:2380 --cert-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188.pem --key-file=/etc/
kubernetes/ssl/kube-etcd-172-31-8-188-key.pem --data-dir=/var/
lib/rancher/etcd/ --initial-advertise-peer-urls=https://
172.31.8.188:2380 --initial-cluster-state=new --heartbeat-
interval=500 --listen-client-urls=https://172.31.8.188:2379 --
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --peer-
```



```
trusted-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cipher-  
suites=TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WIT  
H_AES_256_GCM_SHA384 --enable-v2=true --initial-cluster-  
token=etcd-cluster-1 --peer-cert-file=/etc/kubernetes/ssl/  
kube-etcd-172-31-8-188.pem --peer-client-cert-auth=true --  
election-timeout=5000 root 23666 23640 3 10:36 ? 00:00:00  
kube-bench run --targets etcd --scored --nosummary --  
noremediations --v=0 --config-dir=/etc/kube-bench/cfg --  
benchmark rke-cis-1.20-permissive --json --log_dir /tmp/  
sonobuoy/logs --outputfile /tmp/sonobuoy/etcd.json
```

3.1 Authentication and Authorization

3.1.1 Client certificate authentication should not be used for users (Manual)

Result: warn

Remediation: Alternative mechanisms provided by Kubernetes such as the use of OIDC should be implemented in place of client certificates.

3.2 Logging

3.2.1 Ensure that a minimal audit policy is created (Automated)

Result: pass

Remediation: Create an audit policy file for your cluster.

Audit:

```
/bin/ps -ef | grep kube-apiserver | grep -v grep
```

Expected Result:

```
'--audit-policy-file' is present
```

Returned Value:

```
root 13371 13350 13 10:28 ? 00:01:08 kube-apiserver --service-account-signing-key-file=/etc/kubernetes/ssl/kube-service-account-token-key.pem --kubelet-preferred-address-types=InternalIP,ExternalIP,Hostname --allow-privileged=true --audit-log-maxbackup=10 --etcd-prefix=/registry --tls-cert-file=/etc/kubernetes/ssl/kube-apiserver.pem --service-account-issuer=rke --anonymous-auth=false --audit-log-format=json --audit-log-maxsize=100 --etcd-certfile=/etc/kubernetes/ssl/kube-node.pem --authentication-token-webhook-cache-ttl=5s --service-account-lookup=true --api-audiences=unknown --proxy-client-cert-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client.pem --proxy-client-key-file=/etc/kubernetes/ssl/kube-apiserver-proxy-client-key.pem --requestheader-username-headers=X-Remote-User --advertise-address=172.31.2.76 --cloud-provider= --etcd-keyfile=/etc/kubernetes/ssl/kube-node-key.pem --etcd-servers=https://172.31.8.188:2379 --kubelet-client-key=/etc/kubernetes/ssl/kube-apiserver-key.pem --secure-port=6443 --requestheader-extra-headers-prefix=X-Remote-Extra- --runtime-config=authorization.k8s.io/v1beta1=true --storage-backend=etcd3 --requestheader-group-headers=X-Remote-Group --profiling=false --service-node-port-
```



```

range=30000-32767 --audit-log-path=/var/log/kube-audit/audit-
log.json --service-account-key-file=/etc/kubernetes/ssl/kube-
service-account-token-key.pem --tls-private-key-file=/etc/
kubernetes/ssl/kube-apiserver-key.pem --authentication-token-
webhook-config-file=/etc/kubernetes/kube-api-authn-
webhook.yaml --audit-policy-file=/etc/kubernetes/audit-
policy.yaml --audit-log-maxage=30 --client-ca-file=/etc/
kubernetes/ssl/kube-ca.pem --kubelet-client-certificate=/etc/
kubernetes/ssl/kube-apiserver.pem --bind-address=0.0.0.0 --
authorization-mode=Node,RBAC --enable-admission-
plugins=NamespaceLifecycle,LimitRanger,ServiceAccount,Defaults
storageClass,DefaultTolerationSeconds,MutatingAdmissionWebhook,
ValidatingAdmissionWebhook,ResourceQuota,NodeRestriction,Prior
ity,TaintNodesByCondition,PersistentVolumeClaimResize --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
insecure-port=0 --requestheader-allowed-names=kube-apiserver-
proxy-client --etcd-cafile=/etc/kubernetes/ssl/kube-ca.pem --
requestheader-client-ca-file=/etc/kubernetes/ssl/kube-
apiserver-requestheader-ca.pem --service-cluster-ip-
range=10.43.0.0/16

```

3.2.2 Ensure that the audit policy covers key security concerns (Manual)

Result: warn

Remediation: Consider modification of the audit policy in use on the cluster to include these items, at a minimum.



4.1 Worker Node

Configuration Files

4.1.1 Ensure that the kubelet service file permissions are set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for the kubelet service. All configuration is passed in as arguments at container run time.

4.1.2 Ensure that the kubelet service file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Cluster provisioned by RKE doesn't require or maintain a configuration file for the kubelet service. All configuration is passed in as arguments at container run time.

4.1.3 If proxy kubeconfig file exists ensure permissions are set to 644 or more restrictive (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the each worker node. For example, `chmod 644 /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml`

Audit:

```
/bin/sh -c 'if test -e /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml; then stat -c permissions=%a /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml; fi'
```

Expected Result:

```
'permissions' is present OR '/etc/kubernetes/ssl/kubecfg-kube-proxy.yaml' is not present
```



4.1.4 If proxy kubeconfig file exists ensure ownership is set to root:root (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the each worker node. For example, chown root:root /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml

Audit:

```
/bin/sh -c 'if test -e /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml; then stat -c %U:%G /etc/kubernetes/ssl/kubecfg-kube-proxy.yaml; fi'
```

Expected Result:

```
'root:root' is present OR '/etc/kubernetes/ssl/kubecfg-kube-proxy.yaml' is not present
```

4.1.5 Ensure that the --kubeconfig kubelet.conf file permissions are set to 644 or more restrictive (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the each worker node. For example, chmod 644 /etc/kubernetes/ssl/kubecfg-kube-node.yaml

Audit:

```
/bin/sh -c 'if test -e /node/etc/kubernetes/ssl/kubecfg-kube-node.yaml; then stat -c permissions=%a node/etc/kubernetes/ssl/kubecfg-kube-node.yaml; fi'
```

Expected Result:

```
permissions has permissions 600, expected 644 or more restrictive
```

Returned Value:

```
permissions=600 permissions=600 permissions=600
```



4.1.6 Ensure that the --kubeconfig kubelet.conf file ownership is set to root:root (Automated)

Result: pass

Remediation: Run the below command (based on the file location on your system) on the each worker node. For example, chown root:root /etc/kubernetes/ssl/kubecfg-kube-node.yaml

Audit:

```
/bin/sh -c 'if test -e /node/etc/kubernetes/ssl/kubecfg-kube-node.yaml; then stat -c %U:%G /node/etc/kubernetes/ssl/kubecfg-kube-node.yaml; fi'
```

Expected Result:

```
'root:root' is present
```

Returned Value:

```
root:root root:root root:root
```

4.1.7 Ensure that the certificate authorities file permissions are set to 644 or more restrictive (Automated)

Result: pass

Remediation: Run the following command to modify the file permissions of the --client-ca-file chmod 644

Audit:

```
stat -c permissions=%a /node/etc/kubernetes/ssl/kube-ca.pem
```

Expected Result:

```
permissions has permissions 600, expected 644 or more restrictive
```

Returned Value:

```
permissions=600 permissions=600 permissions=600
```

4.1.8 Ensure that the client certificate authorities file ownership is set to root:root (Automated)

Result: pass



Remediation: Run the following command to modify the ownership of the `--client-ca-file`. `chown root:root`

Audit:

```
stat -c %U:%G /node/etc/kubernetes/ssl/kube-ca.pem
```

Expected Result:

```
'root:root' is equal to 'root:root'
```

Returned Value:

```
root:root root:root root:root
```

4.1.9 Ensure that the kubelet `--config` configuration file has permissions set to 644 or more restrictive (Automated)

Result: Not Applicable

Remediation: Clusters provisioned by RKE doesn't require or maintain a configuration file for the kubelet. All configuration is passed in as arguments at container run time.

4.1.10 Ensure that the kubelet `--config` configuration file ownership is set to root:root (Automated)

Result: Not Applicable

Remediation: Clusters provisioned by RKE doesn't require or maintain a configuration file for the kubelet. All configuration is passed in as arguments at container run time.



4.2 Kubelet

4.2.1 Ensure that the anonymous-auth argument is set to false (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set authentication: anonymous: enabled to false. If using executable arguments, edit the kubelet service file `/etc/systemd/system/kubelet.service.d/10-kubeadm.conf` on each worker node and set the below parameter in `KUBELET_SYSTEM_PODS_ARGS` variable. `--anonymous-auth=false` Based on your system, restart the kubelet service. For example: `systemctl daemon-reload systemctl restart kubelet.service`

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--anonymous-auth' is equal to 'false'
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
```



```

ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --

```



```
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf
```

4.2.2 Ensure that the --authorization-mode argument is not set to AlwaysAllow (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set authorization: mode to Webhook. If using executable arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in KUBELET_AUTHZ_ARGS variable. --authorization-mode=Webhook
Based on your system, restart the kubelet service. For example:
systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--authorization-mode' does not have 'AlwaysAllow'
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
```



```

cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-

```



```
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf
```

4.2.3 Ensure that the --client-ca-file argument is set as appropriate (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set authentication: x509: clientCAFile to the location of the client CA file. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in KUBELET_AUTHZ_ARGS variable. --client-ca-file= Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:



```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--client-ca-file' is present
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
```




```

kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf

```

4.2.4 Ensure that the --read-only-port argument is set to 0 (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set readOnlyPort to 0. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in



KUBELET_SYSTEM_PODS_ARGS variable. --read-only-port=0 Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--read-only-port' is equal to '0' OR '--read-only-port' is not present
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
```



```

root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/

```



```
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf
```

4.2.5 Ensure that the --streaming-connection-idle-timeout argument is not set to 0 (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set streamingConnectionIdleTimeout to a value other than 0. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in KUBELET_SYSTEM_PODS_ARGS variable. --streaming-connection-idle-timeout=5m Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--streaming-connection-idle-timeout' is not equal to '0' OR
'--streaming-connection-idle-timeout' is not present
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
```



```

ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --

```



```
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf
```

4.2.6 Ensure that the --protect-kernel-defaults argument is set to true (Automated)

Result: Not Applicable

Remediation: If using a Kubelet config file, edit the file to set protectKernelDefaults: true. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in KUBELET_SYSTEM_PODS_ARGS variable. --protect-kernel-defaults=true Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service System level configurations are required prior to provisioning the cluster in order for this argument to be set to true.

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

4.2.7 Ensure that the --make-iptables-util-chains argument is set to true (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set makeIPTablesUtilChains: true. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and remove the --make-iptables-util-chains argument from the KUBELET_SYSTEM_PODS_ARGS



variable. Based on your system, restart the kubelet service. For example: `systemctl daemon-reload systemctl restart kubelet.service`

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--make-iptables-util-chains' is equal to 'true' OR '--make-
iptables-util-chains' is not present
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
```



```

ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/

```




```
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf
```

4.2.8 Ensure that the --hostname-override argument is not set (Manual)

Result: Not Applicable

Remediation: Edit the kubelet service file `/etc/systemd/system/kubelet.service.d/10-kubeadm.conf` on each worker node and remove the `--hostname-override` argument from the `KUBELET_SYSTEM_PODS_ARGS` variable. Based on your system, restart the kubelet service. For example: `systemctl daemon-reload systemctl restart kubelet.service` Clusters provisioned by RKE set the `--hostname-override` to avoid any hostname configuration errors

4.2.9 Ensure that the --event-qps argument is set to 0 or a level which ensures appropriate event capture (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set `eventRecordQPS` to an appropriate level. If using command line arguments, edit the kubelet service file `/etc/systemd/system/kubelet.service.d/10-kubeadm.conf` on each worker node and set the below parameter in `KUBELET_SYSTEM_PODS_ARGS` variable. Based on your system, restart the kubelet service. For example: `systemctl daemon-reload systemctl restart kubelet.service`

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--event-qps' is equal to '0'
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
```



```

cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-

```



```

image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-
auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf

```

4.2.10 Ensure that the --tls-cert-file and --tls-private-key-file arguments are set as appropriate (Manual)

Result: Not Applicable

Remediation: If using a Kubelet config file, edit the file to set `tlsCertFile` to the location of the certificate file to use to identify this Kubelet, and `tlsPrivateKeyFile` to the location of the corresponding private key file. If using command line arguments, edit the kubelet service file `/etc/systemd/system/kubelet.service.d/10-kubeadm.conf` on each worker node and set the below parameters in `KUBELET_CERTIFICATE_ARGS` variable. `--tls-cert-file=` `--tls-private-key-file=` Based on your system, restart the kubelet service. For example: `systemctl daemon-reload` `systemctl restart kubelet.service` When generating serving certificates, functionality could break in conjunction with hostname overrides which are required for certain cloud providers.

Audit Config:



```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

4.2.11 Ensure that the --rotate-certificates argument is not set to false (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to add the line rotateCertificates: true or remove it altogether to use the default value. If using command line arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and remove --rotate-certificates=false argument from the KUBELET_CERTIFICATE_ARGS variable. Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fC kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'{.rotateCertificates}' is present OR '{.rotateCertificates}'
is not present
```

4.2.12 Verify that the RotateKubeletServerCertificate argument is set to true (Manual)

Result: Not Applicable

Remediation: Edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the below parameter in KUBELET_CERTIFICATE_ARGS variable. --feature-gates=RotateKubeletServerCertificate=true Based on your system, restart the kubelet service. For example: systemctl daemon-reload systemctl restart kubelet.service Clusters provisioned by RKE handles certificate rotation directly through RKE.

Audit Config:



```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

4.2.13 Ensure that the Kubelet only makes use of Strong Cryptographic Ciphers (Automated)

Result: pass

Remediation: If using a Kubelet config file, edit the file to set TLSCipherSuites to

TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 or to a subset of these values. If using executable arguments, edit the kubelet service file /etc/systemd/system/kubelet.service.d/10-kubeadm.conf on each worker node and set the --tls-cipher-suites parameter as follows, or to a subset of these values. --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 Based on your system, restart the kubelet service. For example:
systemctl daemon-reload systemctl restart kubelet.service

Audit:

```
/bin/ps -fc kubelet
```

Audit Config:

```
/bin/sh -c 'if test -e /var/lib/kubelet/config.yaml; then /
bin/cat /var/lib/kubelet/config.yaml; fi'
```

Expected Result:

```
'--tls-cipher-suites' contains valid elements from
'TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_AES_128_GCM_SHA256'
```

Returned Value:

```
UID PID PPID C STIME TTY TIME CMD root 13858 13835 4 10:28 ?
00:00:22 kubelet --hostname-override=rke1-120-cis-c1 --tls-
cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
```



```

_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --anonymous-auth=false --authorization-
mode=Webhook --cloud-provider= --cluster-dns=10.43.0.10 --pod-
infra-container-image=rancher/mirrored-pause:3.6 --resolv-
conf=/etc/resolv.conf --cni-conf-dir=/etc/cni/net.d --client-
ca-file=/etc/kubernetes/ssl/kube-ca.pem --node-ip=172.31.2.76
--cgroups-per-qos=True --make-iptables-util-chains=true --
cluster-domain=cluster.local --fail-swap-on=false --cni-bin-
dir=/opt/cni/bin --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --register-with-taints=node-role.kubernetes.io/
controlplane=true:NoSchedule --network-plugin=cni --event-
qps=0 --read-only-port=0 --root-dir=/var/lib/kubelet --v=2 --
volume-plugin-dir=/var/lib/kubelet/volumeplugins --streaming-
connection-idle-timeout=30m --authentication-token-
webhook=true --cgroup-driver=cgroupfs --resolv-conf=/run/
systemd/resolve/resolv.conf UID PID PPID C STIME TTY TIME CMD
root 13405 13385 2 10:28 ? 00:00:13 kubelet --node-
ip=172.31.8.188 --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --event-
qps=0 --streaming-connection-idle-timeout=30m --cgroups-per-
qos=True --cluster-dns=10.43.0.10 --cluster-
domain=cluster.local --kubeconfig=/etc/kubernetes/ssl/kubecfg-
kube-node.yaml --read-only-port=0 --cni-conf-dir=/etc/cni/
net.d --volume-plugin-dir=/var/lib/kubelet/volumeplugins --
cni-bin-dir=/opt/cni/bin --make-iptables-util-chains=true --
client-ca-file=/etc/kubernetes/ssl/kube-ca.pem --cloud-
provider= --network-plugin=cni --hostname-override=rke1-120-
cis-e1 --anonymous-auth=false --root-dir=/var/lib/kubelet --
address=0.0.0.0 --authorization-mode=Webhook --v=2 --
authentication-token-webhook=true --resolv-conf=/etc/
resolv.conf --fail-swap-on=false --pod-infra-container-
image=rancher/mirrored-pause:3.6 --cgroup-driver=cgroupfs --
resolv-conf=/run/systemd/resolve/resolv.conf UID PID PPID C
STIME TTY TIME CMD root 12665 12646 3 10:30 ? 00:00:15
kubelet --make-iptables-util-chains=true --anonymous-

```



```

auth=false --cluster-domain=cluster.local --fail-swap-
on=false --kubeconfig=/etc/kubernetes/ssl/kubecfg-kube-
node.yaml --pod-infra-container-image=rancher/mirrored-pause:
3.6 --authentication-token-webhook=true --network-plugin=cni
--v=2 --cloud-provider= --event-qps=0 --read-only-port=0 --
hostname-override=rke1-120-cis-w1 --resolv-conf=/etc/
resolv.conf --streaming-connection-idle-timeout=30m --
authorization-mode=Webhook --volume-plugin-dir=/var/lib/
kubelet/volumeplugins --tls-cipher-
suites=TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA
_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY130
5,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES
_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305 --
address=0.0.0.0 --client-ca-file=/etc/kubernetes/ssl/kube-
ca.pem --cluster-dns=10.43.0.10 --root-dir=/var/lib/kubelet --
node-ip=172.31.14.164 --cgroups-per-qos=True --cni-bin-dir=/
opt/cni/bin --cni-conf-dir=/etc/cni/net.d --cgroup-
driver=cgroupfs --resolv-conf=/run/systemd/resolve/resolv.conf

```



5.1 RBAC and Service Accounts

5.1.1 Ensure that the cluster-admin role is only used where required (Manual)

Result: warn

Remediation: Identify all clusterrolebindings to the cluster-admin role. Check if they are used and if they need this role or if they could use a role with fewer privileges. Where possible, first bind users to a lower privileged role and then remove the clusterrolebinding to the cluster-admin role : `kubectl delete clusterrolebinding [name]`

5.1.2 Minimize access to secrets (Manual)

Result: warn

Remediation: Where possible, remove get, list and watch access to secret objects in the cluster.

5.1.3 Minimize wildcard use in Roles and ClusterRoles (Manual)

Result: warn

Remediation: Where possible replace any use of wildcards in clusterroles and roles with specific objects or actions.

5.1.4 Minimize access to create pods (Manual)

Result: warn

Remediation: Where possible, remove create access to pod objects in the cluster.

5.1.5 Ensure that default service accounts are not actively used. (Automated)

Result: Not Applicable

Remediation: Create explicit service accounts wherever a Kubernetes workload requires specific access to the Kubernetes API server. Modify the configuration of each default service account to include this value `automountServiceAccountToken: false`



5.1.6 Ensure that Service Account Tokens are only mounted where necessary (Manual)

Result: warn

Remediation: Modify the definition of pods and service accounts which do not need to mount service account tokens to disable it.

5.1.7 Avoid use of system:masters group (Manual)

Result: warn

Remediation: Remove the system:masters group from all users in the cluster.

5.1.8 Limit use of the Bind, Impersonate and Escalate permissions in the Kubernetes cluster (Manual)

Result: warn

Remediation: Where possible, remove the impersonate, bind and escalate rights from subjects.



5.2 Pod Security Policies

5.2.1 Minimize the admission of privileged containers (Automated)

Result: warn

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.privileged` field is omitted or set to false.

5.2.2 Minimize the admission of containers wishing to share the host process ID namespace (Automated)

Result: Not Applicable

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.hostPID` field is omitted or set to false.

5.2.3 Minimize the admission of containers wishing to share the host IPC namespace (Automated)

Result: Not Applicable

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.hostIPC` field is omitted or set to false.

5.2.4 Minimize the admission of containers wishing to share the host network namespace (Automated)

Result: Not Applicable

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.hostNetwork` field is omitted or set to false.

5.2.5 Minimize the admission of containers with allowPrivilegeEscalation (Automated)

Result: Not Applicable

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.allowPrivilegeEscalation` field is omitted or set to false.



5.2.6 Minimize the admission of root containers (Automated)

Result: warn

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.runAsUser.rule` is set to either `MustRunAsNonRoot` or `MustRunAs` with the range of UIDs not including 0.

5.2.7 Minimize the admission of containers with the NET_RAW capability (Automated)

Result: warn

Remediation: Create a PSP as described in the Kubernetes documentation, ensuring that the `.spec.requiredDropCapabilities` is set to include either `NET_RAW` or `ALL`.

5.2.8 Minimize the admission of containers with added capabilities (Automated)

Result: warn

Remediation: Ensure that `allowedCapabilities` is not present in PSPs for the cluster unless it is set to an empty array.

5.2.9 Minimize the admission of containers with capabilities assigned (Manual)

Result: warn

Remediation: Review the use of capabilities in applications running on your cluster. Where a namespace contains applications which do not require any Linux capabilities to operate consider adding a PSP which forbids the admission of containers which do not drop all capabilities.



5.3 Network Policies and CNI

5.3.1 Ensure that the CNI in use supports Network Policies (Manual)

Result: warn

Remediation: If the CNI plugin in use does not support network policies, consideration should be given to making use of a different plugin, or finding an alternate mechanism for restricting traffic in the Kubernetes cluster.

5.3.2 Ensure that all Namespaces have Network Policies defined (Manual)

Result: Not Applicable

Remediation: Follow the documentation and create NetworkPolicy objects as you need them.

5.4 Secrets Management

5.4.1 Prefer using secrets as files over secrets as environment variables (Manual)

Result: warn

Remediation: if possible, rewrite application code to read secrets from mounted secret files, rather than from environment variables.

5.4.2 Consider external secret storage (Manual)

Result: warn

Remediation: Refer to the secrets management options offered by your cloud provider or a third-party secrets management solution.

5.5 Extensible

Admission Control

5.5.1 Configure Image Provenance using ImagePolicyWebhook admission controller (Manual)

Result: warn

Remediation: Follow the Kubernetes documentation and setup image provenance.

5.7 General Policies

5.7.1 Create administrative boundaries between resources using namespaces (Manual)

Result: warn

Remediation: Follow the documentation and create namespaces for objects in your deployment as you need them.

5.7.2 Ensure that the seccomp profile is set to docker/default in your pod definitions (Manual)

Result: warn

Remediation: Use security context to enable the docker/default seccomp profile in your pod definitions. An example is as below:
securityContext: seccompProfile: type: RuntimeDefault

5.7.3 Apply Security Context to Your Pods and Containers (Manual)

Result: warn

Remediation: Follow the Kubernetes documentation and apply security contexts to your pods. For a suggested list of security contexts, you may refer to the CIS Security Benchmark for Docker Containers.

5.7.4 The default namespace should not be used (Manual)

Result: Not Applicable

Remediation: Ensure that namespaces are created to allow for appropriate segregation of Kubernetes resources and that all new resources are created in a specific namespace.

