



```
In[*]:= Quit[]
```

```
In[*]:= With[{pts = {{0, 0, 0}, {1, 0, 0}, {0, 1, 0}, {1, 0, 1}, {0, 1, 1}, {1, 1, 1}}, fcs =
  {{1, 2, 3}, {4, 5, 6}, {1, 2, 4}, {1, 3, 5}, {2, 3, 6}, {1, 4, 5}, {3, 5, 6}, {2, 4, 6}}},
  Graphics3D[{Opacity[0.9], Texture[, Polyhedron[pts[[Sequence@#]] & /@ fcs,
    VertexTextureCoordinates -> (pts[[Sequence@#]] & /@ fcs) ]}]]
```

```
Out[*]=
```



```
In[*]:= With[{pts = {{0, 0, 0}, {1, 0, 0}, {0, 1, 0}, {1, 0, 1}, {0, 1, 1}, {1, 1, 1}},
  fcs = {{1, 2, 3}, {4, 5, 6}, {1, 2, 4}, {1, 3, 5}, {2, 3, 6},
    {1, 4, 5}, {3, 5, 6}, {2, 4, 6}}}, pts[[Sequence@#]] & /@ fcs]
```

```
Out[*]=
```

```
{{{0, 0, 0}, {1, 0, 0}, {0, 1, 0}}, {{1, 0, 1}, {0, 1, 1}, {1, 1, 1}},
  {{0, 0, 0}, {1, 0, 0}, {1, 0, 1}}, {{0, 0, 0}, {0, 1, 0}, {0, 1, 1}},
  {{1, 0, 0}, {0, 1, 0}, {1, 1, 1}}, {{0, 0, 0}, {1, 0, 1}, {0, 1, 1}},
  {{0, 1, 0}, {0, 1, 1}, {1, 1, 1}}, {{1, 0, 0}, {1, 0, 1}, {1, 1, 1}}}
```


```
In[*]:= Inverse[{{1, 0, 1}, {0, 1, 1}, {1, 1, 1}}^T]
```

```
Out[*]=
```

```
{{0, -1, 1}, {-1, 0, 1}, {1, 1, -1}}
```

```
In[*]:= Graphics3D[Arrow[{{0, 0, 0}, #}] & /@ (Tuples[{0, 1}, 3].%32)]
```

```
Out[*]=
```



Are there any arrangement acheiving maximum product except for cube-with-basis? achNumber counts number of such arrangements given a non-degenerate 0-1 matrix -- basis of the second set in the coordinates dual to some basis of the second set. If maximum is only acheived with cube+ba-sis, the function will return 2

```
In[*]:= $HistoryLength = 1
```

```
Out[*]=
```

```
1
```

```

In[*]:= achNumber[B01_List] := With[{Cpl = Complement, Len = Length,
  d = Length@B01, cube = Tuples[{0, 1}, Length@B01], inv = Inverse[B01]},
  With[{acan = Select[Subsets[Cpl[cube, B01]], Divisible[2d (d + 1), (Len@# + d)] &]},
    bcan = Select[Subsets[Cpl[cube, B01T]], Divisible[2d (d + 1), (Len@# + d)] &]},
    Total@Flatten@Table[Boole[Cpl[Flatten[Join[B01, a].inv.(Join[B01T, b]T)],
      {0, 1}] == {}], {a, acan}, {b, Select[bcan, Len@# ==  $\frac{2^d (d + 1)}{d + \text{Len@a}} - d$  &]}]]]

```

Test on all invertible 2 x2 matrices :

```

In[*]:= Tally[achNumber /@ Select[Tuples[{0, 1}, {2, 2}], MatrixRank@# == 2 &]] // AbsoluteTiming
Out[*]= {0.0036872, {{2, 6}}}

```

Test on all invertible 3x3 matrices:

```

In[*]:= Tally[achNumber /@ Select[Tuples[{0, 1}, {3, 3}], MatrixRank@# == 3 &]] // AbsoluteTiming
Out[*]= {0.140387, {{2, 174}}}

```

Number of 4x4 bases ignoring order:

```

In[*]:= Select[DeleteDuplicates[Sort /@ Tuples[{0, 1}, {4, 4}]], MatrixRank@# == 4 &]] // Length
Out[*]= 940

```

```

In[*]:= achNumber[IdentityMatrix[4]] // AbsoluteTiming
Out[*]= {15.8582, 2}

```

```

In[*]:= 35 *  $\frac{940}{3600}$ .
Out[*]= 9.13889

```

```

In[*]:= SeedRandom[42];
fourByFourSample = Transpose /@ RandomSample[
  Select[DeleteDuplicates[Sort /@ Tuples[{0, 1}, {4, 4}]], MatrixRank@# == 4 &], 4]
Out[*]=
{{ {0, 0, 1, 1}, {0, 1, 0, 0}, {1, 0, 0, 1}, {1, 0, 1, 0} },
  { {0, 0, 0, 1}, {0, 1, 1, 0}, {0, 0, 1, 1}, {1, 1, 0, 0} },
  { {0, 0, 0, 1}, {0, 0, 1, 1}, {0, 1, 0, 0}, {1, 1, 1, 0} },
  { {0, 0, 1, 1}, {0, 1, 0, 1}, {0, 1, 1, 0}, {1, 1, 1, 0} }}

```

```

In[*]:= (achNumber /@ fourByFourSample) // AbsoluteTiming
Out[*]= {565.683, {2, 2, 2, 2}}

```

```


In[ ]:= matrixPicture[B01_] :=
Module[{d = Length@B01, cube, final, pos1, pos2}, cube = Tuples[{0, 1}, d];
pos1 = Flatten[Position[cube, #] & /@ (B01^T)];
pos2 = Flatten[Position[cube, #] & /@ B01];
final = cube.Inverse@B01.(cube^T);
Style[{ArrayPlot[final, ColorRules -> {0 -> Black, 1 -> White},
ColorFunction -> {ColorData["Rainbow",  $\frac{\# + 1}{2}$ ] &},
Epilog -> {Black, MapIndexed[Text[#1, Reverse[#2 - 0.5]] &, Reverse[final], {2}],
■, Arrow[{ $\{\# - 0.5, 2^d\}$ ,  $\{\# - 0.5, 2^d - \frac{1}{2}\}$ ]}] & /@ pos1,
Arrow[{ $\{0, 2^d - \# + 0.5\}$ ,  $\{0.5, 2^d - \# + 0.5\}$ ]}] & /@ pos2},
ImageSize -> 300, Frame -> None, Background -> White, PlotRangePadding -> 0.1],
Style[B01 // MatrixForm, White]}, White, Background -> Black]]

```


```

In[ ]:= matrixPicture[{{1, 0, 1}, {0, 1, 1}, {0, 0, 1}}] // Rasterize
Out[ ]:=

```



```
In[*]:= matrixPicture[IdentityMatrix@3] // Rasterize
Out[*]=
```




```
In[*]:= matrixPicture@First[
  RandomChoice[Select[Tuples[{0, 1}, {3, 3}], MatrixRank@# == 3 &], 1]] // Rasterize
imlist = Rasterize /@ matrixPicture /@ Select[Tuples[{0, 1}, {3, 3}], MatrixRank@# == 3 &];
```

```
In[*]:= matrixPicture@IdentityMatrix[4] // Rasterize
```

```
In[*]:= NestWhile[RandomChoice[{0, 1}, {4, 4}] &, {{0}}, MatrixRank[#] != 4 &]
Out[*]=
{{0, 1, 1, 1}, {1, 0, 0, 1}, {0, 1, 1, 0}, {0, 1, 0, 1}}
```


```
In[*]:= matrixPicture@% // Rasterize
Out[*]=
```



```
In[*]:= Inverse@{{0, 1, 1, 1}, {1, 0, 0, 1}, {0, 1, 1, 0}, {0, 1, 0, 1}}
Out[*]=
{{-1, 1, 1, 0}, {-1, 0, 1, 1}, {1, 0, 0, -1}, {1, 0, -1, 0}}
```


```
In[ ]:= Graph[graphPicture@{{0, 1, 1, 1}, {1, 0, 0, 1}, {0, 1, 1, 0}, {0, 1, 0, 1}},
  Background → Black, VertexStyle → Yellow, EdgeStyle → White]
```

```
Out[ ]:=
```



```
Graph[graphFullSym@IdentityMatrix[3]]
```

```
Out[ ]:=
```



Check whether sets of “skewed dot products” coincide with all nonbinary inputs treated as same and no distinction between 0 and 1:

```
In[ ]:= coincidingSets[B01_] := Module[{d = Length@B01, cube, final}, cube = Tuples[{0, 1}, d];
  final = cube.Inverse@B01.(cube^T) /. {1 → 0, x_ /; x ≠ 0 → 2};
  Map[Sort, final, {0, -2}] == Map[Sort, final^T, {0, -2}]]
```

Check on invertible $d \times d$ matrices for d from 2 to 4:

```
In[ ]:= Table[
  And @@ coincidingSets /@ Select[Tuples[{0, 1}, {d, d}], MatrixRank@# == d &], {d, 2, 4}]
```

```
Out[ ]:=
```

```
{True, True, True}
```

```
In[ ]:= randomInvertible[d_] :=
  NestWhile[RandomChoice[{0, 1}, {d, d}] &, {{0}}, MatrixRank[#] ≠ d &]
```

```
In[ ]:= randomInvertible[5]
```

```
Out[ ]:=
```

```
{{1, 1, 1, 0, 1}, {1, 0, 0, 1, 0}, {0, 1, 0, 0, 0}, {1, 0, 0, 1, 1}, {1, 0, 0, 0, 1}}
```

```
In[ ]:= NotebookDelete[temp]
```

```
Out[ ]:=
```

```
NotebookDelete[temp]
```

```

In[*]:= cnt = 0;
SeedRandom[42];
NestWhile[If[Mod[cnt, 1] == 0, NotebookDelete[temp];
temp = PrintTemporary[cnt]];
cnt++;
randomInvertible[4] &, {{1}}, coincidingSets[#] &]

Out[*]:=
$Aborted

In[*]:= counterexample5 =
{{0, 0, 1, 1, 1}, {0, 1, 0, 0, 0}, {1, 0, 0, 1, 1}, {1, 1, 0, 1, 0}, {1, 0, 0, 0, 0}}


Out[*]:=
{{0, 0, 1, 1, 1}, {0, 1, 0, 0, 0}, {1, 0, 0, 1, 1}, {1, 1, 0, 1, 0}, {1, 0, 0, 0, 0}}

In[*]:= coincidingSets@counterexample5

Out[*]:=
False

In[*]:= matrixPicture@counterexample5 // Rasterize
Out[*]:=

```



```

In[*]:= cube01[d_] := Tuples[{0, 1}, d]


```

```

In[ ]:= Style[With[{cube = Tuples[{0, 1}, 5]},
  ArrayPlot[Map[Sort, (cube.Inverse[#].(cubeT)) /. {1 → 0, x_ /; x ≠ 0 → 2}, {0, -2}],
  Frame → True, FrameStyle → White, Background → Black, PlotRangePadding → None,
  Mesh → True, MeshStyle → Directive[■, Thickness[10-4]],
  ColorRules → {0 → Black, 2 → Orange}]] & /@
  {counterexample5, counterexample5T}, White, Background → Black] // Rasterize

```

Out[]:=



```

In[ ]:= Inverse@counterexample5

```

Out[]:=

```

{{0, 0, 0, 0, 1}, {0, 1, 0, 0, 0}, {1, 0, -1, 0, 1}, {0, -1, 0, 1, -1}, {0, 1, 1, -1, 0}}

```

Function to produce graph of allowable relations given symmetric invertible 01 matrix:

```

In[ ]:= graphFullSym[B01_] := Module[{d = Length@B01, cube, matr}, cube = Tuples[{0, 1}, d];
  matr = (cube.Inverse@B01.(cubeT)) /. {1 → 0, x_ /; x ≠ 0 → 2};
  Flatten@Table[If[i ≠ j && And@@ NonNegative[matr[[i]] - matr[[j]]],
    cube[[i]] ↔ cube[[j]], Nothing], {i, 2d}, {j, 2d}]

```

```


In[ ]:= allSymInvertible[d_] :=
  DeleteDuplicatesBy[Select[(# + LowerTriangularize[#T, -1]) & /@
    PadLeft /@ (Internal`PartitionRagged[#, Range[d, 1, -1]] &) /@
    Tuples[{0, 1},  $\frac{d(d+1)}{2}$ ], MatrixRank@# == d &], Sort]

```

```

In[ ]:= Style[
  Grid@DeleteDuplicates[{Graph[graphFullSym@#, Background → Black, VertexStyle → White,
    EdgeStyle → Yellow], matrixPicture@#} & /@ allSymInvertible[3],
  IsomorphicGraphQ[#1[[1]], #2[[1]] &], Background → Black, White]

```

$Out[*]=$




```
In[*]:= Inverse@
$$\begin{pmatrix} 0 & 0 & 1 \\ 0 & 1 & 0 \\ 1 & 0 & 1 \end{pmatrix}$$



```

```
Out[*]= {{-1, 0, 1}, {0, 1, 0}, {1, 0, 0}}
```



```
In[*]:= Style[
  Grid@DeleteDuplicates[{Graph[graphFullSym@#, Background → Black, VertexStyle → White,
    EdgeStyle → Yellow], matrixPicture@#} & /@ allSymInvertible[4],
  IsomorphicGraphQ[#1[[1]], #2[[1]] &], Background → Black, White]
```

```
Out[*]=
```









$$\begin{pmatrix} 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 1 \end{pmatrix}$$



$$\begin{pmatrix} 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 1 & 1 \\ 1 & 0 & 1 & 1 \end{pmatrix}$$



$$\begin{pmatrix} 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 1 & 0 \end{pmatrix}$$




$$\begin{pmatrix} 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 1 & 1 & 1 & 0 \end{pmatrix}$$

```

In[ ]:= {Graph[graphFullSym[counterexample5]], Graph[graphFullSym[counterexample5T]]}
Out[ ]:=

```




```

In[ ]:= graphSymNoSinks[B01_] := Module[{d = Length@B01, filtcube, matr, pos},
  filtcube = Rest@DeleteCases[Tuples[{0, 1}, d], Alternatives@@B01];
  matr = (filtcube.Inverse@B01.(filtcubeT)) /. {1 → 0, x_ /; x ≠ 0 → 2};
  Flatten@Table[If[i ≠ j && And @@ NonNegative[matr[[i]] - matr[[j]]],
    filtcube[[i]] ↔ filtcube[[j]], Nothing], {i, 2d - d - 1}, {j, 2d - d - 1}]

In[ ]:= Graph[graphSymNoSinks@IdentityMatrix@5, GraphLayout → "LayeredEmbedding"]
Out[ ]:=

```



```

In[ ]:= graphSymFactorizedAndSzs[B01_] :=
  Module[{d = Length@B01, cube, grps, filt = (# /. {1 → 0, x_ /; x ≠ 0 → 2} &)},
    cube = Tuples[{0, 1}, d];
    grps = {#, filt[#[[1]]]} & /@ GatherBy[cube.Inverse@B01.(cubeT), filt];
    {Flatten@Table[If[i ≠ j && And @@ NonNegative[grps[[i, 2]] - grps[[j, 2]]],
      grps[[i, 1]] ↔ grps[[j, 1]], Nothing], {i, Length@grps}, {j, Length@grps}},
    Normal@AssociationMap[Length, grps[[All, 1]]]}


```

```

In[ ]:= With[{gsf = graphSymFactorizedAndSzs[IdentityMatrix[3]]},
  Graph[First@gsf, VertexLabels → MapAt[Placed[#, Center] &, gsf[[2]], {All, 2}],
  VertexSize → MapAt[{ "Scaled",  $\frac{\text{Sqrt}[\#]}{20}$  } &, gsf[[2]], {All, 2}]]]

```


Out[]:=



```

In[ ]:= Get["https://raw.githubusercontent.com/szhorvat/IGraphM/master/IGInstaller.m"]
The currently installed versions of IGraph/M are: {}

```

Installing IGraph/M is complete: PacletObject[ Name: IGraphM
Version: 0.6.5].

It can now be loaded using the command << IGraphM`

```

In[ ]:= << IGraphM`

```

Out[]:=

IGraph/M 0.6.5 (December 21, 2022)
Evaluate IGDocumentation[] to get started.

```

graphSymFactorizedRaw[B01_] :=
Module[{d = Length@B01, cube, grps, filt = (# /. {1 → 0, x_ /; x ≠ 0 → 2} &)},
  cube = Tuples[{0, 1}, d];
  grps = {#, filt[#[[1]]]} & /@ GatherBy[cube.Inverse@B01.(cube^T), filt];
  Flatten@Table[If[i ≠ j && And @@ NonNegative[grps[[i, 2]] - grps[[j, 2]],
    grps[[i, 1]] → grps[[j, 1]], Nothing], {i, Length@grps}, {j, Length@grps}]]
hasseDiagram[gr_] := With[{f = EdgeQ[gr, #1 → #2] &, s = VertexList[gr]},
  ResourceFunction["HasseDiagram"][f, s, PerformanceGoal → "Quality"]]


In[ ]:= addGraphProps[gr_] := Module[{filt = (# /. {1 → 0, x_ /; x ≠ 0 → 2} &)},
  gr // IGVertexMap[Sqrt@*Length, "SqLength" → VertexList] /*
    IGVertexMap[Length, "Length" → VertexList] /* IGVertexMap[filt[#[[1]]] &,
      "Filter" → VertexList] /* IGVertexMap[MatrixForm[#^T] &, Tooltip → VertexList]]
grSymFact[B01_] :=
  addGraphProps[Graph[graphSymFactorizedRaw[B01], PerformanceGoal → "Quality"]]
hasseSymFact[B01_] := addGraphProps[
  hasseDiagram@Graph[graphSymFactorizedRaw[B01], PerformanceGoal → "Speed"]]


In[ ]:= dispFact[gr_] :=
  gr // IGVertexMap[0.1 # &, VertexSize → IGVertexProp["SqLength"]] /* IGVertexMap[
    Placed[If[# == 1, "", #], Center] &, VertexLabels → IGVertexProp["Length"]]


In[ ]:= dispFact[grSymFact[#]] & /@ allSymInvertible[3]

```

Out[]:=








```
In[ ]:= matrixPicture@IdentityMatrix[4]
```

```
Out[ ]:=
```




```
In[ ]:= dispFact[grSymFact[IdentityMatrix[4]]]
```

```
Out[ ]:=
```





```
In[ ]:= dispFact[hasseSymFact[IdentityMatrix@4]]
```

```
Out[ ]:=
```




```
In[*]:= (dispFact@*hasseSymFact) /@ RandomSample[allSymInvertible[4], 30]
Out[*]=
```






```
In[*]:= deepSort[expr_] := Map[Sort, expr, {0, -2}]
```

```
In[*]:= allSymInvertibleDiffGraph[d_] :=  
  First /@ DeleteDuplicates[{#, Graph@graphFullSym@#} & /@ allSymInvertible[d],  
    IsomorphicGraphQ[#1[[2]], #2[[2]]] &]
```


```
In[*]:= allThreeHasse = dispFact /@ hasseSymFact /@ allSymInvertibleDiffGraph[3]
```

```
Out[*]:=
```




```
In[*]:= allFourHasse = dispFact /@ hasseSymFact /@ allSymInvertibleDiffGraph[4]
```

```
Out[*]:=
```



```
In[*]:= setGraphStyle[graph_Graph] := Graph[graph, EdgeStyle → Yellow,  
  VertexStyle → White, Background → Black, PerformanceGoal → "Quality"]
```

```
Grid[ArrayReshape[setGraphStyle /@ (allFourHasse ~ Join ~ allThreeHasse), {5, 2}],
      Background → Black]
```



```
In[*]:= Export[FileNameJoin[{NotebookDirectory[], "All-Hasse-3-4-diagrams.jpg"}],
```

```
In[*]:= allHasse5withDup = ParallelMap[hasseSymFact, allSymInvertible[5]];
```

```
In[*]:= allFiveHasse = DeleteDuplicates[allHasse5withDup, IsomorphicGraphQ];
```

```
Grid[ArrayReshape[setGraphStyle /@ (allFourHasse ~ Join ~ allThreeHasse), {5, 2}],
      Background → Black]
```

```
In[ ]:= DumpSave[FileNameJoin[{NotebookDirectory[], "all-sym-hasce-3.mx"}], allThreeHasce];
DumpSave[FileNameJoin[{NotebookDirectory[], "all-sym-hasce-4.mx"}], allFourHasce];
DumpSave[FileNameJoin[{NotebookDirectory[], "all-sym-hasce-5.mx"}], allFiveHasce];
```

```
In[ ]:= MapIndexed[Export[FileNameJoin[{NotebookDirectory[],
    "all-sym-hasce-5-pictures", ToString[#2[[1]]] <> ".jpg"}], #1] &,
    setGraphStyle[Graph[disFact@#, ImageSize -> 800]] & /@ allFiveHasce];
```


There is an example that is not even a semilattice among 4 by 4 matrices

```
In[ ]:= nonSemilatticeCounter = allSymInvertibleDiffGraph[4][4]
```

```
Out[ ]:= {{0, 0, 0, 1}, {0, 0, 1, 0}, {0, 1, 0, 1}, {1, 0, 1, 1}}
```

```
In[ ]:= Style[{matrixPicture[nonSemilatticeCounter],
    Style[MatrixForm@Inverse@nonSemilatticeCounter, White],
    Graph[setGraphStyle@disFact@hasceSymFact@nonSemilatticeCounter,
        ImageSize -> 400]}, Background -> Black]
```

```
Out[ ]:=
```



```
In[ ]:= Export[FileNameJoin[{NotebookDirectory[], "non-semilattice-4.jpg"}], %];
```

```
In[ ]:= With[{c = cube01[4], ctr = Inverse@nonSemilatticeCounter},
    {MatrixForm[c.ctr.(c^T)], MatrixForm@c, MatrixForm@ctr, MatrixForm@(c^T)}]
```

Unlike the simple cube case there might be more than $d+1$ vectors that can lie in intersection (meet) of A and B; the following function counts the number of such vectors.

```
In[*]:= selfCompatibleCount[B01_] :=  
  With[{c = Tuples[{0, 1}, Length@B01]}, Count[Diagonal[c.Inverse[B01].(cT)], 0 | 1]]
```

```
In[*]:= Union[selfCompatibleCount /@ allSymInvertible[3]]  
Out[*]= {4, 6}
```

```
In[*]:= Union[selfCompatibleCount /@ allSymInvertible[4]]  
Out[*]= {5, 6, 8, 9, 10}
```

```
In[*]:= Union[selfCompatibleCount /@ allSymInvertible[5]]  
Out[*]= {6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 24}
```

In case of 4 by 4 matrices numbers of possible self-compatible vectors reduces when only considering matrices that produce non-isomorphic graphs. So there are matrices producing isomorphic graphs but having different-sized self-compatible sets.

A matrix with many self-compatible vectors:

```
In[*]:= manySelfCompatibleExample =  
  Select[allSymInvertible[5], selfCompatibleCount@# == 24 &, 1] // First  
Out[*]= {{0, 0, 0, 1, 1}, {0, 1, 1, 0, 1}, {0, 1, 1, 1, 0}, {1, 0, 1, 0, 0}, {1, 1, 0, 0, 1}}
```


```

In[ ]:= Labeled[Style[{matrixPicture[manySelfCompatibleExample], Graph[
    setGraphStyle@dispFact@hasseSymFact@manySelfCompatibleExample, ImageSize → 550]],
    Background → Black], Style["5×5 matrix producing 24 self-compatible vectors",
    White, Background → Black], Top]

```

```
Out[ ]:=
```

5×5 matrix producing 24 self-compatible vectors



```

In[ ]:= Export[FileNameJoin[{NotebookDirectory[], "many-self-compatible-example.jpg"}],
    %345, Background → Black];

```