

TCP的厄运，网络协议侧信道分析 析及利用

- Zhiyun Qian, University of California, Riverside

Research Interest

- Vulnerability discovery and exploitation techniques
 - CVE-2016-5696, CVE-2015-8950, CVE-2016-8756, CVE-2016-8757, CVE-2015-8950, CVE-2016-8758, CVE-2016-3360, CVE-2016-3683, ...
- Side channels analysis (system/network)
 - Live demo competition @ GeekPwn 2016 and 2017

Research Interest

- Vulnerability discovery and exploitation techniques
 - CVE-2016-5696, CVE-2015-8950, CVE-2016-8756, CVE-2016-8757, CVE-2015-8950, CVE-2016-8758, CVE-2016-3360, CVE-2016-3683, ...
- Side channels analysis (system/network)
 - Live demo competition @ GeekPwn 2016 and 2017

Research Interest

- Vulnerability discovery and exploitation techniques
 - CVE-2016-5696, CVE-2015-8950, CVE-2016-8756, CVE-2016-8757, CVE-2015-8950, CVE-2016-8758, CVE-2016-3360, CVE-2016-3683, ...
- Side channels analysis (system/network)
 - Live demo competition @ GeekPwn 2016 and 2017
- Measurement/characterization
 - Internet-wide scan
 - One-click root app

Real world side channel attacks – mafia game



Another example

Anyone at home?




???



Why TCP?

- Extremely widely used, any security issues could have huge impact
- But decades old
- Yet still under heavy development
 - TCP fast open
 - Security improvements
 - Maintenance



Outline


- Background on Off-Path TCP Exploits
- Off-Path TCP Exploits
 - Malware-assisted [Oakland 12, CCS 12]
 - Pure Off-Path [USENIX Security 16]
 - Unfixable WiFi timing [USENIX Security 18]

Outline

- Background on Off-Path TCP Exploits
- Off-Path TCP Exploits
 - Malware-assisted
 - Pure Off-Path
 - Unfixable WiFi timing

Man-in-the-middle vs. Off-path attacks


- Man-in-the-middle attacks
 - On the communication path
 - Harder but possible: open wifi, route hijack, etc.
 - Prevention with crypto: PKI, complexity, overhead
 - **Caching (HTTP-only)** in mobile networks
 - Why bother, <45% of Alexa top 1M traffic encrypted in 2016 [\[wikipedia\]](#)



B

Man-in-the-middle vs. Off-path attacks

- Off-path attacks
 - Off the communication path
 - Cannot intercept/modify/block traffic
 - Prevention with challenge-response (e.g., cookie)
 - Subject to prediction or side channel attacks!



Initial TCP sequence number as challenge/response


□ Three-way handshake



Remembers X



Checks Ack=X+1
Remembers Y



Checks Ack=Y+1

TCP sequence number war timeline






Research contributions

- Uncover a new class of side channel attacks against TCP
- Real-world security vulnerabilities caused by
 - Firewall middleboxes
 - OS implementation
 - TCP specifications
- Develop program analysis tools to automatically identify such class of vulnerabilities

Outline


- Background on Off-Path TCP Exploits
- Off-Path TCP Exploits
 - Malware-assisted [Oakland 12, CCS 12]
 - Pure Off-Path
 - Unfixable WiFi timing

Threat model and problem formulation



- Unprivileged malware + off-path attackers
- Attack goal
 - Write into a target connection owned by a different app (e.g., facebook connection)

TCP sequence number inference attack



- Required information
 - Target four tuples: (source/dest IP, source/dest port)
 - Sequence number
 - How? Unprivileged malware is isolated from other apps

Req 1 – Obtaining target four tuples


- On-site unprivileged malware
 - netstat (no root required)

```
netstat -nn
```

```
Active Internet connections
```

| Proto | Recv-Q | Send-Q | Local Address | Foreign Address | (state) |
|-------|--------|--------|---------------------|--------------------|-------------|
| tcp4 | 37 | 0 | 192.168.1.102.50469 | 199.47.219.159.443 | CLOSE_WAIT |
| tcp4 | 37 | 0 | 192.168.1.102.50468 | 174.129.195.86.443 | CLOSE_WAIT |
| tcp4 | 37 | 0 | 192.168.1.102.50467 | 199.47.219.159.443 | CLOSE_WAIT |
| tcp4 | 0 | 0 | 192.168.1.102.50460 | 199.47.219.159.443 | LAST_ACK |
| tcp4 | 0 | 0 | 192.168.1.102.50457 | 199.47.219.159.443 | LAST_ACK |
| tcp4 | 0 | 0 | 192.168.1.102.50445 | 199.47.219.159.443 | LAST_ACK |
| tcp4 | 0 | 0 | 192.168.1.102.50441 | 199.47.219.159.443 | LAST_ACK |
| tcp4 | 0 | 0 | 127.0.0.1.26164 | 127.0.0.1.50422 | ESTABLISHED |

Req 2 – Feedback through side channels




Expecting seq Y

- Intuition: actively guess sequence numbers and observe feedbacks through side channels


Firewall-enabled side channels

- Sequence-number-checking firewalls
 - Drop out-of-window (likely random or malicious packets)
 - Cut down resource waste and “**supposedly**” improve security
- However, we turn it into a side channel attack!



Popularity of sequence-number-checking firewalls

- 33% of the 179 tested carriers deploy such firewalls
 - Vendors: Checkpoint, Cisco, Juniper
 - Could be used in other networks as well



The screenshot shows the Check Point Support Center interface. At the top, there's a navigation bar with links for Home, Products & Services, Buy, Support, and About Us. Below this, the breadcrumb trail reads: Support Center > Search Results > SecureKnowledge Details. The main heading is "Support Center" with a search bar and a magnifying glass icon. To the right of the search bar are links for Print and Email. The title of the document is "Check Point response to 'Off-Path TCP Sequence Number Inference Attack'". Below the title, the document details are listed: Solution ID: sk74640, Severity: Low, Product: Security Gateway, Version: All, Date Created: 24-May-2012, and Last Modified: 14-Mar-2013. To the right of these details is a "Rate this document" section with five stars and a rating of [1=Worst,5=Best]. The "SYMPTOMS" section follows, containing three bullet points: 1. Researchers at the University of Michigan have published a paper "Off-Path TCP Sequence Number Inference Attack How Firewall Middleboxes Reduce Security". 2. This attack identifies the current sequence range of a TCP connection, by exploiting the fact that firewalls drop out-of-window TCP packets. After the sequence range is identified, an off-path attacker may inject data or hijack the TCP connection. 3. Client applications that use cleartext connections (e.g., HTTP and not HTTPS) are potential targets for these attacks.

Check Point
SOFTWARE TECHNOLOGIES LTD.

Global Sites | My Account

Home Products & Services Buy Support About Us

Support Center > Search Results > SecureKnowledge Details

Support Center

Search

Print Email

Check Point response to "Off-Path TCP Sequence Number Inference Attack"

Solution ID: sk74640
Severity: Low
Product: Security Gateway
Version: All
Date Created: 24-May-2012
Last Modified: 14-Mar-2013

Rate this document
☆☆☆☆☆ [1=Worst,5=Best]

SYMPTOMS

- Researchers at the University of Michigan have published a paper "[Off-Path TCP Sequence Number Inference Attack How Firewall Middleboxes Reduce Security](#)".
- This attack identifies the current sequence range of a TCP connection, by exploiting the fact that firewalls drop out-of-window TCP packets. After the sequence range is identified, an off-path attacker may inject data or hijack the TCP connection.
- Client applications that use cleartext connections (e.g., HTTP and not HTTPS) are potential targets for these attacks.

Host packet counter side channels

- What if no firewall is deployed?

Tcp:

157921111 segments received

125446192 segments send out

39673 segments retransmitted

489 bad segments received


679561 resets sent

TcpExt:


25508 ICMP packets dropped because they were out-of-window

9491 TCP sockets finished time wait in fast timer

Quick ack mode was activated 160830 times



Results



- Total inference time: ~1s
- Success rate: 62.5 – 97.5%

Impact

- Contacted security team in Linux, FreeBSD, Apple
 - Vulnerability partially patched in Linux
 - FreeBSD acknowledged this issue but cannot easily patch
- Backward compatibility is a challenge
- Side channels not always easy to patch



Outline

- Background on Off-Path TCP Exploits
- Off-Path TCP Exploits
 - Malware-assisted
 - Pure Off-Path [USENIX Security 16]
 - Unfixable WiFi timing

Even worse problems?

- Malware assisted
 - With and w/o firewall
- What now? Is there still a vulnerability even without help of malware?



Off-Path TCP Exploits: Global Rate Limit Considered Dangerous


- GeekPwn 2016 most creative idea award
- Facebook Internet Defense Prize Finalist

Yet another side channel

- Discovered a subtle TCP side channel vulnerability in Linux 3.6+
 - **CVE-2016-5696**
- Can be used towards:
 - Privacy breach (which service you are visiting)
 - TCP connection termination attack
 - Malicious data injection attack

Global rate limit (from RFC 5961)

- `sysctl_tcp_challenge_ack_limit`: implemented in Linux 3.6+
 - *Global* limit of all challenge ACK per sec, ***shared across all connections***
 - Default value: 100 (reset per second)



Exploit the vulnerability

- Example: to guess correct client-port number
 - If it's a correct guess:



Client

1 challenge ACK

Spoofed SYN packets with client's IP
and a guessed src port

100 RST

99 challenge ACK



Attacker



Server

Exploit the vulnerability

- Example: to guess correct client-port number
 - If it's a wrong guess:



Client

no challenge ACK



Attacker

Spoofed SYN packets with client's IP
and a guessed src port

100 RST


100 challenge ACK



Server

Evaluation

- Existence of connection: <10 seconds
- Sequence number: 30 seconds
- ACK number: <10 seconds



Defense

- Our proposed defenses:
 - Add random noise to the channel (global challenge ACK rate limit)

Adopted in Linux kernel 4.7 in July 2016 (within days)

- Eliminate the side channel

Adopted in Linux kernel subsequently

TCP specification (RFC 5961) amended

<https://tools.ietf.org/html/draft-lvelvindron-ack-throttling-02>

What now?

- So far ...
- All side channels are software vulnerabilities
 - Relatively simple fixes
- Anything more fundamental?

Outline

- Background on Off-Path TCP Exploits
- Off-Path TCP Exploits
 - Malware-assisted
 - Pure Off-Path [USENIX Security 16]
 - Unfixable WiFi timing [USENIX Security 18]

Off-Path TCP Exploit: How Wireless Routers Can Jeopardize Your Secret

GeekPwn 2017 award-winning pwn
USENIX Security 2018

General research interest



TCP packet receiving basics




Spoofed packets with server's IP and a guessed src port



TCP packet receiving basics

Has connection

No connection




How can the attacker see the difference?


Timing channel

- Leaks information about whether the client has replied or not
 - Challenge: tiny amount of delay (on the order of us)
- **But it becomes visible in wireless!**
 - Root cause: Half-duplex
 - In all generations of WiFi and 802.11 technology


Timing difference – not trigger reply




Timing difference – trigger reply



Timing difference – evaluation




(a) Local experiment



(b) Remote experiment (RTT = ~ 20ms)

Web cache poisoning



Web cache poisoning

- Works against all major OSes + browsers:
 - Windows, macOS, Linux
 - Chrome, Firefox
- Success rate: 90%
- Time-to-succeed: 25s – 600s

Conclusion

- TCP side channel problems are real!
 - Huge impact on network security
 - Variety of side channels
 - Variety of exploitation scenarios and techniques
 - Difficult to fix at times

Thank you!
Q & A

Zhiyun Qian
zhiyunq@cs.ucr.edu

