

When Does Attention Help? A Predictability Gradient for Genomic Trait Prediction, Validated by Virulence-Factor Attribution

Miyu Horiuchi
m@replicater.xyz

2026-06-05

Abstract

A bacterial genome is a *set* of proteins, and predicting an organism’s phenotype from that set requires pooling thousands of protein representations into a fixed-size genome vector. The default choice, mean-pooling, treats every protein equally; learned attention-pooling can instead concentrate on a few. We ask a question usually answered by default rather than by evidence: **when does the pooling choice matter, and why?** We propose the *predictability gradient* hypothesis: pooling architecture matters in proportion to how *localized* a trait’s genomic signal is. Compositional traits (e.g. oxygen tolerance, cell shape) reflect diffuse genome-wide signal and should be insensitive to pooling; machinery traits (e.g. pathogenicity, nutrient requirements) are determined by a handful of decisive genes and should benefit from attention. We test this on 19,592 bacterial genomes across 21 traits and three taxonomic generalization regimes. With three seeds per configuration, attention-pooling improves machinery traits ~4x more than compositional traits (species-level gap in F1 gain $+0.062 \pm 0.011$ vs $+0.001$ at family level), confirming the gradient and revealing that the advantage *collapses entirely under family-level covariate shift*. We then show the mechanism is genuine: for pathogenicity, the model concentrates 81% of its attention on five proteins, and those proteins are 5x enriched for known virulence factors versus random proteins in the same genome (Wilcoxon $p = 2.5 \times 10^{-7}$) and 3.2x versus non-pathogenic genomes ($p = 6.8 \times 10^{-14}$); ablating them flips 23% of pathogenic predictions. The attention does not merely correlate with virulence; it locates adhesins, fimbrial ushers, and invasion loci, and the prediction depends on them. Our results give a predictive, mechanistically-grounded rule for when un-pooled protein representations are worth their cost, and identify cross-clade generalization, not pooling, as the binding constraint for genomic foundation models.

Manuscript notice. Copyright © 2026 Miyu Horiuchi. All rights reserved. This draft is made available for scholarly review and publication consideration. Reuse permissions for code, trained models, datasets, and deployment artifacts are governed separately from this manuscript.

Introduction

Foundation models for bacterial genomes have advanced rapidly: protein language models such as ESM-2 (Lin et al. 2023) produce rich per-protein representations, and recent genome-level models (Wiatrak et al. 2025; MicroGenomer authors 2025; BacPT authors 2026) aggregate them to predict phenotype. A genome, however, is not a sequence but an unordered *set* of P proteins ($P \approx 10^3$ – 10^4), so every such model must **pool** a variable-size set of protein vectors into one genome representation before prediction. This pooling step is almost always chosen by convention, typically a mean, and almost never studied.

This is a missed opportunity, because pooling encodes a strong inductive bias about *where a trait’s signal lives in the genome*. Mean-pooling assumes the signal is diffuse: every protein contributes equally. Attention-pooling (Ilse et al. 2018) assumes the signal is localized: the model learns to up-weight a few decisive proteins. Which bias is correct is not a universal fact; it depends on the trait. Whether a bacterium is Gram-positive is a property of its entire cell envelope; whether it is pathogenic can hinge on a single secretion system.

We formalize this as the **predictability gradient** hypothesis:

The benefit of attention-pooling over mean-pooling for a trait is proportional to how *localized* that trait’s genomic determinants are. Diffuse “compositional” traits gain little; gene-specific “machinery” traits gain much.

This hypothesis is attractive because it is *falsifiable inside a single architecture*: hold the encoder fixed, swap only the pooling, and measure the gain as a function of trait class. We do exactly this, and add two things a benchmark number cannot provide. First, we vary the **generalization regime** (species-, genus-, family-held-out splits), turning the experiment into a test of whether the gradient survives distribution shift. Second, for the trait with the largest gain, pathogenicity, we ask whether the attention is *mechanistically real*: does it concentrate on the actual virulence machinery, and does the prediction causally depend on it? This converts a performance claim (“attention helps”) into a scientific one (“attention helps because it finds the responsible genes”).

Contributions.

1. **The predictability-gradient hypothesis and its validation.** A testable account of when set-pooling architecture matters for genomic prediction, confirmed on 19,592 genomes / 21 traits with three seeds: attention helps machinery traits ~4x more than compositional traits, with non-overlapping error bars (§4).
2. **A covariate-shift result.** The gradient is strong within taxonomic distribution and vanishes at the family level (gain gap $+0.062 \rightarrow +0.001$). The binding constraint for genomic foundation models is cross-clade generalization, not pooling (§4.2).
3. **Mechanistic attribution against a virulence-factor database.** For pathogenicity, attention concentrates (81% mass on 5 of ~3,800 proteins) and is enriched for VFDB virulence factors under two controls; ablation shows the prediction depends on them; the hits are coherent adherence/invasion machinery (§5).
4. **An evaluation protocol for trait-localization hypotheses.** The paper defines a compact, reusable experimental pattern for testing whether architectural changes help because the relevant phenotype is diffuse, localized, or shifted out of distribution. Production systems, future recipe-generation workflows, and nonessential implementation assets are outside the scope of this manuscript.

We are explicit about what this is *not*: not a new encoder (we freeze ESM-2), not a state-of-the-art benchmark sweep, not a release of a production cultivation-recommendation system, and not a solution to cross-clade generalization, which our own results show is the open problem.

Related Work

Genomic and protein foundation models. ESM-2 (Lin et al. 2023) provides the frozen per-protein embeddings we pool. Genome-level models, Bacformer (Wiatrak et al. 2025), MicroGenomer (MicroGenomer authors 2025), and BacPT (BacPT authors 2026), aggregate protein or gene representations for phenotype prediction but report benchmark accuracy without analyzing the pooling step or attributing predictions to specific genes. Our contribution is orthogonal and complementary: we hold the encoder fixed and study the aggregation choice and its mechanism.

Microbial trait prediction. Classical predictors (Traitair (Weimann et al. 2016), Genome Properties (Richardson et al. 2019), PathogenFinder (Cosentino et al. 2013)) use hand-engineered gene-content features and per-trait classifiers; curated random-forest baselines on BacDive traits remain strong (Koblitz et al. 2025). These methods implicitly assume localized, gene-presence signal, consistent with our “machinery” pole, but do not contrast it against a diffuse-signal baseline or quantify when the assumption pays off.

Attention as explanation. A literature cautions that attention weights are not, on their own, faithful explanations (Jain and Wallace 2019; Wiegrefe and Pinter 2019). We take this seriously: our mechanistic claim does not rest on attention magnitudes but on (i) *external* validation against a curated virulence-factor database (Liu et al. 2022) under matched controls and (ii) *causal* ablation. We flag where ablation is partly mechanical (§5.3, §6).

Set learning. Attention-pooling over instances is standard in multiple-instance learning (Ilse et al. 2018),

and permutation-invariant set attention is formalized by the Set Transformer (Lee et al. 2019). Our novelty is not the existence of attention over sets but tying its benefit to a measurable property of the label (trait localization) and validating the learned attention against ground-truth biology.

Setup

Data

Labels are drawn from BacDive (Schober et al. 2025), yielding **21 prediction heads** across seven biological blocks (morphology, physiology, growth conditions, cultivation, safety, ecology, chemotaxonomy). For each strain with an NCBI genome we predict open reading frames with pyrodigal (Larralde 2022) and embed each protein independently with a frozen ESM-2 encoder, producing a ragged protein-representation set per genome. A mean-pooled baseline feature is computed from the same protein representations, isolating pooling as the only experimental variable. The training corpus contains 19,592 genomes and approximately 82M protein representations.

This manuscript describes the scientific evaluation. Complete deployment artifacts, production inference workflows, model checkpoints, and large feature stores are not included in this version and will be governed by separate release materials.

Trait taxonomy: compositional vs machinery

We pre-register a partition of the 21 heads into **compositional** (signal expected diffuse) and **machinery** (signal expected gene-localized), from biological first principles and *before* seeing pooling results:

- **Compositional (11):** gram stain, cell shape, motility, sporulation, oxygen tolerance, catalase, cytochrome oxidase, temperature class, pH class, halophily, pigmentation.
- **Machinery (8):** pathogenicity (human), pathogenicity (animal), cultivation medium, carbon utilization, metabolite production, antimicrobial-resistance phenotype, biosafety level, fatty-acid (FAME) profile.

Two metadata heads (isolation source, country) are excluded from the gradient analysis as they are not biological traits.

Model

A shared MLP encoder feeds 21 linear heads under a **masked multi-task loss** that contributes zero gradient for missing labels (BacDive coverage ranges 5–95% per head). The only architectural variable in this experiment is the pooling:

- **Mean-pool:** genome vector $\bar{x} = \frac{1}{P} \sum_i x_i$.
- **Attention-pool:** a learned scalar scorer produces a masked softmax over real proteins and a weighted-sum genome vector.

Both share encoder, heads, and loss; only pooling differs. This deliberately narrow comparison is the reason the result can be interpreted as a pooling effect rather than an encoder effect.

Evaluation regimes

We use **species-, genus-, and family-held-out** splits: no species (resp. genus, family) appears in more than one fold. Family-held-out approximates prediction for clades unlike anything seen in training, the regime relevant to uncultured “microbial dark matter.” We report macro-F1 per head and, for the gradient, $\Delta F1 = F1_{\text{attn}} - F1_{\text{mean}}$, aggregated within trait class, mean $\pm$ std over **3 seeds**.

The Predictability Gradient

Attention helps machinery traits, not compositional traits

Table 1: Gain from attention-pooling over mean-pooling ($\Delta F1$, mean $\pm$ std over 3 seeds).

Split	Compositional (n=11)	Machinery (n=8)	Gap (mach – comp)
species	$+0.021 \pm 0.002$	$+0.083 \pm 0.012$	$+0.062$
genus	$+0.016 \pm 0.004$	$+0.067 \pm 0.010$	$+0.052$
family	$+0.009 \pm 0.002$	$+0.010 \pm 0.003$	$+0.001$

At the species and genus levels the machinery gain exceeds the compositional gain by $\sim 4\times$, with **non-overlapping error bars** (0.083 ± 0.012 vs 0.021 ± 0.002). The compositional gain is small, positive, and tight; attention does not *hurt* diffuse traits, it simply adds little, exactly as the hypothesis predicts: when signal is genome-wide, a weighted average and a flat average converge. The single largest per-head effects are pathogenicity (animal F1 $0.26 \rightarrow 0.50$, human $0.16 \rightarrow 0.32$ at species), the most gene-localized traits in the set.

The gradient collapses under covariate shift

The most consequential result is the family row. As the test distribution moves from same-species to same-family to *novel-family* organisms, the machinery advantage decays monotonically ($+0.083 \rightarrow +0.067 \rightarrow +0.010$) until the gradient is effectively gone (gap $+0.001$). Mean- and attention-pooling become indistinguishable precisely in the regime that matters for uncultured organisms. This localizes the bottleneck: the limiting factor is not how we pool proteins but whether *any* protein-set representation transfers across evolutionary distance.

Does the Attention Find the Right Genes?

A performance gain does not establish that attention is mechanistically meaningful; attention weights need not be faithful (Jain and Wallace 2019). We validate the largest-gain trait, **pathogenicity**, against external ground truth (VFDB (Liu et al. 2022), 4,663 experimentally-verified virulence factors) with two matched controls and a causal ablation. We train single-task attention-pool models per pathogenicity head (so the shared pool specializes); both discriminate well on held-out test genomes (AUROC 0.88 animal, 0.85 human).

Attention concentrates

On held-out genomes the attention distribution is sharp: median normalized entropy 0.26 (animal), with the **top-5 of $\sim 3,800$ proteins carrying 81% of the attention mass** (top-1 alone $\approx 40\%$). Concentration is a precondition for an interpretable spotlight and is label-independent (the model always selects a few proteins); the question is *which*.

Top-attended proteins are enriched for virulence factors

We map each protein’s attention rank to its amino-acid sequence and call a protein a virulence factor if it matches VFDB by diamond blastp (Buchfink et al. 2021) at $E < 10^{-5}$. Two controls:

Table 2: VFDB enrichment of top-5 attended proteins (animal head; species split).

Test	Top-attended	Control	Statistic
Within-genome (paired, vs random in same genome)	28.1%	5.9%	Wilcoxon $p = 2.5 \times 10^{-7}$, $n=74$
Between-class (vs top-attended in non-path. genomes)	28.1%	10.9%	Fisher OR= 3.2, $p = 6.8 \times 10^{-14}$

The proteins attention selects are ~5x more likely to be known virulence factors than random proteins in the same genome, and the enrichment is 3.2x stronger in pathogenic than non-pathogenic genomes. The human head replicates (between-class OR 3.1, $p = 3.8 \times 10^{-5}$; within-genome $p = 0.034$ at $n=16$). The hits are not database noise: the most frequently selected VFs are coherent **adherence/invasion machinery**, including fimbrial ushers **papC/mrkC**, filamentous hemagglutinin **fhaB**, attachment-invasion locus **ail**, type-IV pilus **pilQ**, and flagellar **fliR**.

The prediction causally depends on them

Masking the top-5 attended proteins (of ~3,800) and re-predicting flips **22.7% of pathogenic calls** to non-pathogenic (animal; Wilcoxon vs random-protein masking $p = 1.2 \times 10^{-4}$); the human head replicates (12.5%, $p = 9 \times 10^{-3}$). Masking proteins ranked 6–10 produces a 27.5x smaller drop; the dependence is specific to the very top proteins. We note honestly that a top-vs-random ablation gap is *partly mechanical*: attention-pooling is a weighted sum, so removing high-weight elements changes the output more by construction. The non-trivial facts are therefore the **absolute** effect (removing 5 of ~3,800 proteins overturns a quarter of predictions) and its conjunction with §5.2 (those 5 proteins are the virulence machinery). Together they support a causal-mechanistic reading that neither establishes alone.

Discussion and Limitations

What the results say. Set-pooling architecture for genomic prediction should be chosen by trait localization, not convention: attention is worth its cost for gene-determined traits and not for diffuse ones, and for pathogenicity it works by locating the responsible genes. This gives practitioners a predictive rule and gives the field a mechanistic check (external attribution + ablation) that any genome model can adopt.

What this public manuscript does not disclose. This version intentionally omits nonessential deployment details, checkpoint distribution, large feature-store locations, production inference workflows, and future cultivation-recipe system designs. It also avoids specifying any unreleased next-generation architecture beyond the high-level observation that future work should model protein interactions rather than only independent protein weights.

Limitations, stated plainly.

- *Covariate shift is unsolved and dominates.* The benefit evaporates at family-level holdout (§4.2). For the uncultured-organism application that motivates genomic trait models, this is the result that matters most, and it is negative for the pooling lever.
- *Weighted sum, not combinations.* The validated model up-weights individual proteins; it does not model protein interactions.
- *Enrichment, not coverage.* 68% of top-attended proteins are not VFDB hits; VFDB catalogs only *known* factors, so this is expected and our claim is strictly about enrichment.
- *Single encoder scale.* All results use one ESM-2 size; whether a larger encoder sharpens the gradient is untested.

- *Statistical scope.* The gradient uses 3 seeds; the human-head within-genome control is underpowered ($n=16$). The animal head and between-class tests are well-powered ($p < 10^{-6}$); the small compositional effects ($\leq 0.02 \Delta F1$) are within their own noise and we do not over-interpret them.

Why this is a useful result. The positive half (a validated, mechanistically-explained predictability gradient) is a clean architectural insight; the negative half (it does not survive clade shift) redirects effort from the pooling question, which we consider resolved, to the generalization question, which we do not.

Data and Code Availability

The text, tables, and figures are copyright © 2026 Miyu Horiuchi, all rights reserved unless a later publication agreement states otherwise. Reuse permissions for software, trained models, datasets, and deployment artifacts are handled separately from this manuscript.

For academic review, the trait-class definitions, split definitions, evaluation protocol, and summary statistics are described here. Supporting materials sufficient for independent audit can be made available to editors, reviewers, or collaborators under appropriate review terms. Full code, trained checkpoints, large feature stores, production inference assets, and cultivation-recipe tooling will be addressed in separate release materials.

Conclusion

Pooling a genome’s proteins is an inductive-bias choice, and the right choice is a measurable function of the trait: attention for localized “machinery” traits, mean for diffuse “compositional” traits. We validated this gradient with seeds, showed for pathogenicity that the attention concentrates on bona fide virulence factors and the prediction depends on them, and found the entire advantage contingent on staying within taxonomic distribution. Reading the right genes is achievable; reading them for organisms unlike anything previously characterized is the open problem.

References

- BacPT authors. 2026. “A Bacterial Proteome Foundation Model.” *bioRxiv*, ahead of print. <https://doi.org/10.64898/2026.03.07.710335>.
- Buchfink, Benjamin, Klaus Reuter, and Hajk-Georg Drost. 2021. “Sensitive Protein Alignments at Tree-of-Life Scale Using DIAMOND.” *Nature Methods* 18 (4): 366–68. <https://doi.org/10.1038/s41592-021-01101-x>.
- Cosentino, Salvatore, Mette Voldby Larsen, Frank Møller Aarestrup, and Ole Lund. 2013. “PathogenFinder – Distinguishing Friend from Foe Using Bacterial Whole Genome Sequence Data.” *PLoS ONE* 8 (10): e77302. <https://doi.org/10.1371/journal.pone.0077302>.
- Ilse, Maximilian, Jakub M. Tomczak, and Max Welling. 2018. “Attention-Based Deep Multiple Instance Learning.” *International Conference on Machine Learning (ICML)*, 2127–36.
- Jain, Sarthak, and Byron C. Wallace. 2019. “Attention Is Not Explanation.” *Proceedings of NAACL-HLT*, 3543–56. <https://doi.org/10.18653/v1/N19-1357>.
- Koblitz, Julia et al. 2025. “Predicting Bacterial Phenotypic Traits Through Improved Machine Learning Using High-Quality, Curated Datasets.” *Communications Biology* 8. <https://doi.org/10.1038/s42003-025-08313-3>.
- Larralde, Martin. 2022. “Pyrodigal: Python Bindings and Interface to Prodigal, an Efficient Method for Gene Prediction in Prokaryotes.” *Journal of Open Source Software* 7 (72): 4296. <https://doi.org/10.211>

05/joss.04296.

- Lee, Juho, Yoonho Lee, Jungtaek Kim, Adam R. Kosiorek, Seungjin Choi, and Yee Whye Teh. 2019. “Set Transformer: A Framework for Attention-Based Permutation-Invariant Neural Networks.” *International Conference on Machine Learning (ICML)*, 3744–53.
- Lin, Zeming, Halil Akin, Roshan Rao, et al. 2023. “Evolutionary-Scale Prediction of Atomic-Level Protein Structure with a Language Model.” *Science* 379 (6637): 1123–30. <https://doi.org/10.1126/science.ade2574>.
- Liu, Bo, Dandan Zheng, Siyu Zhou, Lihong Chen, and Jian Yang. 2022. “VFDB 2022: A General Classification Scheme for Bacterial Virulence Factors.” *Nucleic Acids Research* 50 (D1): D912–17. <https://doi.org/10.1093/nar/gkab1107>.
- MicroGenomer authors. 2025. “MicroGenomer: A Genome Language Model for Microbial Phenotype Prediction.” *bioRxiv*, ahead of print. <https://doi.org/10.64898/2025.12.28.696777>.
- Richardson, Lorna J., Neil D. Rawlings, Gustavo A. Salazar, et al. 2019. “Genome Properties in 2019: A New Companion Database to InterPro for the Inference of Complete Functional Attributes.” *Nucleic Acids Research* 47 (D1): D564–72. <https://doi.org/10.1093/nar/gky1013>.
- Schober, Isabel, Carola Söhngen, Lorenz Christian Reimer, et al. 2025. “BacDive in 2025: The Expanding Bacterial and Archaeal Diversity Knowledge Resource.” *Nucleic Acids Research*, ahead of print. <https://doi.org/10.1093/nar/gkae959>.
- Weimann, Aaron, Kyra Mooren, Jeremy Frank, Phillip B. Pope, Andreas Bremges, and Alice C. McHardy. 2016. “From Genomes to Phenotypes: TraitAr, the Microbial Trait Analyzer.” *mSystems* 1 (6): e00101–16. <https://doi.org/10.1128/mSystems.00101-16>.
- Wiatrak, Maciej, Aaron Weimann, R. Andres Floto, Maria Brbić, et al. 2025. “Bacformer: A Foundation Model for Bacterial Genomes.” *bioRxiv*, ahead of print. <https://doi.org/10.1101/2025.07.20.665723>.
- Wiegrefe, Sarah, and Yuval Pinter. 2019. “Attention Is Not Not Explanation.” *Proceedings of EMNLP-IJCNLP*, 11–20. <https://doi.org/10.18653/v1/D19-1002>.