DL Doorlink

Setup guide: keys, services and Replit

Everything to connect before real customers use Doorlink: which accounts to open, which keys to copy, where each one goes on Replit, which addresses to register with each provider, and how to check each one works.

> **Keep keys secret.** Paste keys only into Replit's **Secrets**. Never put them in code, chat, screenshots or email. Doorlink keeps every private key on the server and never shows its value, not even on the admin pages.

The order that works

1. Bring the Repl up to date with GitHub (section 1).
2. Database and core settings (sections 2 and 3). The app will not start properly without these.
3. Sign-in and uploads with Supabase (section 4).
4. Payments, email, texts and AI (sections 5 to 8). Each is optional: a missing one switches off only its own feature.
5. Deploy, then register the webhook addresses and the schedule (sections 9 and 10).
6. Open **Admin → Integrations** and press **Check connection** on every service (section 11).

Where secrets go on Replit

1. Open the Repl, then **Tools → Secrets** (the padlock).
2. Add each one with **New secret**: the **key** is the exact name in this guide (capital letters, underscores), the **value** is what you copied.
3. Open **Deployments** and check the same names appear under the deployment's secrets. Add any that are missing there too.
4. **Redeploy** after any change: a running deployment does not pick up new secrets until it is redeployed.

Names starting with `NEXT_PUBLIC_` are read when the app is built, so they always need a redeploy. They are safe to be public; everything else is private.

---

1 Bring the Repl up to date

All the latest work is on GitHub (`mizlaa/doorlink`), on both `main` and the Replit branch `replit-ui-improvements`. In the Repl's **Shell**:

```
git fetch origin
git checkout replit-ui-improvements
git pull --ff-only origin replit-ui-improvements
npm install
```

Use a Blank Repl attached with git, as described in `WORKFLOW.md`. Never use Replit's "Import from GitHub", which starts an unwanted conversion.

2 Database (Replit PostgreSQL)

Secret	Value
`DATABASE_URL` REQUIRED	Added automatically when you add **PostgreSQL** to the Repl (Tools → Database). If it is missing, copy the connection string from the Database tool.
`DIRECT_URL` REQUIRED	The **same** connection string as `DATABASE_URL`.

Production data. Back up first and apply schema changes deliberately; nothing is dropped. The exact commands and the backup check are in `docs/OPERATIONS.md`, section 1. On a fresh, empty database, `npm run db:push` then `npm run db:seed` is enough.

3 Core settings

Secret	What to put	Why
`NEXT_PUBLIC_SITE_URL` REQUIRED	Your live address, e.g. `https://doorlink.com.au` (https, no slash at the end).	Links in emails, payment return pages, password reset, and every webhook address below.
`AUTH_SECRET` REQUIRED	A long random value: in the Shell run `openssl rand -hex 32` and copy the output.	Signs sign-in cookies, share links and recovery codes. Never change it once live.
`MFA_ENCRYPTION_KEY` RECOMMENDED	Another `openssl rand -hex 32`.	Encrypts two-step sign-in secrets. Never change it once set: everyone would have to set up two-step sign-in again.
`CRON_SECRET` REQUIRED	Another `openssl rand -hex 32`.	Lets the scheduler run reminders and job housekeeping (section 10).
`DOORLINK_DEMO_MODE` OPTIONAL	`false` once the catalogue is real.	Hides the "Demo mode" banner.
`TRUSTED_PROXY_HOPS` RECOMMENDED	Usually `1` on Replit (check as described in `docs/OPERATIONS.md` §5).	Rate limits count the real visitor, not Replit's proxy.
`NEXT_PUBLIC_FEATURE_3D_V2` OPTIONAL	`1` to turn on the 3D homepage intro.	The designer works either way.

4 Supabase: sign-in and uploads

Account: supabase.com → New project (choose the Sydney region). Doorlink uses Supabase for sign-in and file storage; the data itself stays in Replit's database.

Secret	Where to find it
`NEXT_PUBLIC_SUPABASE_URL` REQUIRED	Project Settings → API → **Project URL**
`NEXT_PUBLIC_SUPABASE_ANON_KEY` REQUIRED	Project Settings → API → **anon / public** key
`SUPABASE_SERVICE_ROLE_KEY` REQUIRED	Project Settings → API → **service_role** key (private: Secrets only)

`SUPABASE_STORAGE_BUCKET` FOR UPLOADS	Storage → New bucket → name it `doorlink-documents`, leave **Public** off. Put the bucket name here.

In the Supabase dashboard

- **Authentication → URL Configuration:** set Site URL to your live address and add `https://<your-site>/auth/confirm` to **Redirect URLs**.
- **Authentication → Email Templates → Reset password:** make the link `{{ .SiteURL }}/auth/confirm?token_hash={{ .TokenHash }}&type=recovery&next=/reset-password`

Check it: Admin → Integrations → Supabase Auth and Supabase Storage → Check connection. Then sign out and use "Forgot your password?"; the email link should open the reset page.

5 Stripe: card payments

Account: stripe.com. Start in **test mode** (the toggle at the top of the dashboard); switch to live keys only when you are ready to take real money. Turn on **Connect** (Connect → Get started) so each business is paid into its own account.

Secret	Where to find it
`STRIPE_SECRET_KEY` FOR PAYMENTS	Developers → API keys → **Secret key** (`sk_test_…` in test mode)
`STRIPE_WEBHOOK_SECRET` FOR PAYMENTS	The signing secret (`whsec_…`) of webhook 1 below
`STRIPE_CONNECT_WEBHOOK_SECRET` FOR INVOICE PAYMENTS	The signing secret of webhook 2 below

Create both webhooks under **Developers → Webhooks → Add endpoint** after the first deploy (section 9 lists the addresses and events).

Check it: Check connection shows "test mode". Issue an invoice to yourself, pay it with card `4242 4242 4242 4242` (any future date, any CVC), and it turns **Paid** once Stripe confirms.

6 Resend: email

Account: resend.com. Add your domain under **Domains** and add the DNS records it shows at your domain registrar; wait until it says **Verified**.

Secret	Where to find it
`RESEND_API_KEY` FOR EMAIL	API Keys → Create API key (sending access)
`EMAIL_FROM` FOR EMAIL	You choose it, on the verified domain: `Doorlink <alerts@yourdomain.com.au>`
`RESEND_WEBHOOK_SECRET` FOR "DELIVERED"	Webhooks → Add endpoint (section 9) → its signing secret

Check it: Check connection confirms the key and that the sender's domain is verified. Email an invoice to yourself: it shows **Sent**, then **Delivered**.

7 Twilio: appointment reminder texts

Account: twilio.com. Buy a number that can send SMS to Australian mobiles (Phone Numbers → Buy a number). Australian numbers may ask for a regulatory bundle (your business details); Twilio walks you through it. A trial account can only text numbers you have verified with Twilio.

Secret	Where to find it
`TWILIO_ACCOUNT_SID` FOR TEXTS	Console home → Account Info → **Account SID** (`AC…`)
`TWILIO_AUTH_TOKEN` FOR TEXTS	Console home → Account Info → **Auth Token**
`TWILIO_FROM` FOR TEXTS	Your Twilio number in `+61…` form, or a Messaging Service SID (`MG…`)

No webhook to set up: each text tells Twilio where to report delivery.

Check it: Check connection. Then book a visit for tomorrow for a customer with your own mobile; the hourly reminder texts you, and the visit history shows "SMS sent" then "delivered".

8 AI services

Secret	Feature	Where to find it
`ANTHROPIC_API_KEY` OPTIONAL	Automatic review of manuals people submit	console.anthropic.com → API Keys (add billing credit first)
`OPENAI_API_KEY` OPTIONAL	"Photo preview" of a design in the designer	platform.openai.com → API keys (add billing; if images are refused, check whether your organisation needs verifying)

Check it: Check connection on each confirms the key and that the model is available to your account.

9 Webhook addresses to register (after deploying)

Replace `<site>` with your live address. Admin → Integrations shows these filled in.

Where	Address	Events to tick
Stripe, webhook 1 "Your account"	`https://<site>/api/webhooks/stripe`	checkout.session.completed, customer.subscription.updated, customer.subscription.deleted, payment_intent.succeeded, payment_intent.payment_failed, charge.refunded, payout.paid, payout.failed, transfer.paid, transfer.failed
Stripe, webhook 2 "Connected accounts"	`https://<site>/api/webhooks/stripe-connect`	account.updated, checkout.session.completed, checkout.session.async_payment_succeeded, checkout.session.async_payment_failed, checkout.session.expired, payment_intent.payment_failed, charge.refunded, charge.dispute.created
Resend	`https://<site>/api/webhooks/resend`	email.delivered, email.bounced, email.complained
Supabase	`https://<site>/auth/confirm`	Redirect URL (section 4)
Twilio	Nothing to add.	

Copy each new webhook's signing secret into the matching Secret, then **redeploy**.

10 Schedule: reminders and housekeeping

Two addresses must be called on a timer, each with the header `Authorization: Bearer <your CRON_SECRET>`:

Address	How often	What it does
`https://<site>/api/cron/reminders`	Every hour	Appointment reminder emails and texts; clears old rate-limit rows
`https://<site>/api/cron/jobs`	Once a day	Completes finished jobs automatically

A Repl runs one deployment, so set the timer up in one of these ways:

Option A: external scheduler (simplest). A service such as cron-job.org: create two jobs with the addresses above, method GET, and a request header `Authorization` with value `Bearer` , a space, then your `CRON_SECRET` .

Option B: a second small Repl. Add `CRON_SECRET` and `NEXT_PUBLIC_SITE_URL` as its Secrets and create a **Scheduled** deployment (hourly) that runs: `curl -fsS -H "Authorization: Bearer $CRON_SECRET" "$NEXT_PUBLIC_SITE_URL/api/cron/reminders"` and a daily one for `/api/cron/jobs` .

Running either twice is harmless: each reminder is claimed before it is sent.

Check it: Check connection on "Scheduler" shows when the last reminder went out.

11 Final check

- ☐ Deployed after the last secret was added.
- ☐ Admin → Integrations: every service you use says **Configured**, and **Check connection** is green.
- ☐ The yellow banner about the site address is gone (it needs `https://`).
- ☐ Sign up, sign out, reset the password by email.
- ☐ Upload a business logo; issue a test invoice; email it to yourself; pay it with the 4242 test card.
- ☐ Book a visit for tomorrow on your own mobile; get the reminder text.
- ☐ Admin accounts: turn on two-step sign-in (Account → Sign-in security). It is required for admins in production.
- ☐ Switch Stripe to live keys only after the test payment works, then repeat section 9 for live mode.

Not needed yet

`NEXT_PUBLIC_VAPID_PUBLIC_KEY` and `VAPID_PRIVATE_KEY` (phone push notifications) have no effect: sending push notifications is not built yet. Leave them out.

Full list of names

`DATABASE_URL` · `DIRECT_URL` · `NEXT_PUBLIC_SITE_URL` · `AUTH_SECRET` · `MFA_ENCRYPTION_KEY` · `CRON_SECRET` · `DOORLINK_DEMO_MODE` · `TRUSTED_PROXY_HOPS` · `NEXT_PUBLIC_FEATURE_3D_V2` · `NEXT_PUBLIC_SUPABASE_URL` · `NEXT_PUBLIC_SUPABASE_ANON_KEY` · `SUPABASE_SERVICE_ROLE_KEY` · `SUPABASE_STORAGE_BUCKET` · `STRIPE_SECRET_KEY` · `STRIPE_WEBHOOK_SECRET` · `STRIPE_CONNECT_WEBHOOK_SECRET` · `RESEND_API_KEY` · `EMAIL_FROM` · `RESEND_WEBHOOK_SECRET` · `TWILIO_ACCOUNT_SID` · `TWILIO_AUTH_TOKEN` · `TWILIO_FROM` · `ANTHROPIC_API_KEY` · `OPENAI_API_KEY`

The same names, with placeholders, are in `.env.example` in the project.