Exercise 3

```
● mj@JsM-Macbook-Pro exercise-3 % terraform init
  Initializing the backend...
  Initializing provider plugins...
  - Finding hashicorp/google versions matching "6.8.0"...
  - Installing hashicorp/google v6.8.0...
  - Installed hashicorp/google v6.8.0 (signed by HashiCorp)
  Terraform has created a lock file .terraform.lock.hcl to record the provider
  selections it made above. Include this file in your version control repository
  so that Terraform can guarantee to make the same selections by default when
  you run "terraform init" in the future.

  Terraform has been successfully initialized!

  You may now begin working with Terraform. Try running "terraform plan" to see
  any changes that are required for your infrastructure. All Terraform commands
  should now work.

  If you ever set or change modules or backend configuration for Terraform,
  rerun this command to reinitialize your working directory. If you forget, other
  commands will detect it and remind you to do so if necessary.
○ mj@JsM-Macbook-Pro exercise-3 %
```

```
● mj@JsM-Macbook-Pro exercise-3 % terraform plan

  Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
    + create

  Terraform will perform the following actions:

    # google_compute_instance.instance-mockexam-1 will be created
    + resource "google_compute_instance" "instance-mockexam-1" {
        + can_ip_forward       = false
        + cpu_platform         = (known after apply)
        + current_status       = (known after apply)
        + deletion_protection  = false
        + effective_labels     = {
            + "goog-ec-src"                = "vm_add-tf"
            + "goog-terraform-provisioned" = "true"
          }
        + enable_display       = false
        + id                   = (known after apply)
        + instance_id          = (known after apply)
        + label_fingerprint    = (known after apply)
        + labels               = {
            + "goog-ec-src" = "vm_add-tf"
          }
        + machine_type         = "e2-medium"
        + metadata_fingerprint = (known after apply)
        + min_cpu_platform     = (known after apply)
        + name                 = "instance-mockexam-1"
        + project              = "s5terraform"
        + self_link            = (known after apply)
        + tags                 = [
            + "http-server",
          ]
        + tags_fingerprint     = (known after apply)
        + terraform_labels     = {
            + "goog-ec-src"                = "vm_add-tf"
            + "goog-terraform-provisioned" = "true"
          }
        + zone                 = "europe-north1-c"

        + boot_disk {
            + auto_delete                = true
            + device_name                = "instance-mockexam-1"
            + disk_encryption_key_sha256 = (known after apply)
            + kms_key_self_link          = (known after apply)
            + mode                       = "READ_WRITE"
            + source                     = (known after apply)

            + initialize_params {
                + image                  = "projects/debian-cloud/global/images/debian-12-bookworm-v20241009"
                + labels                 = (known after apply)
                + provisioned_iops       = (known after apply)
                + provisioned_throughput = (known after apply)
                + resource_policies      = (known after apply)
```

```
mj@JsM-Macbook-Pro exercise-3 % terraform apply

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
  + create

Terraform will perform the following actions:

  # google_compute_instance.instance-mockexam-1 will be created
  + resource "google_compute_instance" "instance-mockexam-1" {
      + can_ip_forward       = false
      + cpu_platform         = (known after apply)
      + current_status       = (known after apply)
      + deletion_protection  = false
      + effective_labels     = {
          + "goog-ec-src"               = "vm_add-tf"
          + "goog-terraform-provisioned" = "true"
        }
      + enable_display       = false
      + id                   = (known after apply)
      + instance_id          = (known after apply)
      + label_fingerprint    = (known after apply)
      + labels               = {
          + "goog-ec-src" = "vm_add-tf"
        }
      + machine_type         = "e2-medium"
      + metadata_fingerprint = (known after apply)
      + min_cpu_platform     = (known after apply)
      + name                 = "instance-mockexam-1"
      + project              = "s5terraform"
      + self_link            = (known after apply)
      + tags                 = [
          + "http-server",
        ]
      + tags_fingerprint     = (known after apply)
      + terraform_labels     = {
          + "goog-ec-src"               = "vm_add-tf"
          + "goog-terraform-provisioned" = "true"
        }
      + zone                 = "europe-north1-c"

      + boot_disk {
          + auto_delete                = true
          + device_name                = "instance-mockexam-1"
          + disk_encryption_key_sha256 = (known after apply)
          + kms_key_self_link          = (known after apply)
          + mode                       = "READ_WRITE"
          + source                     = (known after apply)

          + initialize_params {
              + image                  = "projects/debian-cloud/global/images/debian-12-bookworm-v20241009"
              + labels                 = (known after apply)
              + provisioned_iops       = (known after apply)
              + provisioned_throughput = (known after apply)
              + resource_policies      = (known after apply)
```

```
      + self_link                                = (known after apply)
    }

Plan: 2 to add, 0 to change, 0 to destroy.

Do you want to perform these actions?
  Terraform will perform the actions described above.
  Only 'yes' will be accepted to approve.

  Enter a value: yes
```

Status	Name	Zone	Recommendations	In use by	Internal IP	External IP	Connect
✓	instance-mockexam-1	europe-north1-c			10.166.0.5 (nic0)	34.88.179.153 (nic0)	SSH

HIDE

onitor VMs
tlier VMs across metrics like CPU
work

tch management
e patch updates and view patch
nce on VM instances

mj — ping 34.88.179.153 — 80×24

```
Last login: Sat Nov  9 18:23:30 on ttys002
mj@JsM-Macbook-Pro ~ % ping 34.88.179.153
PING 34.88.179.153 (34.88.179.153): 56 data bytes
64 bytes from 34.88.179.153: icmp_seq=0 ttl=54 time=31.541 ms
64 bytes from 34.88.179.153: icmp_seq=1 ttl=54 time=29.081 ms
64 bytes from 34.88.179.153: icmp_seq=2 ttl=54 time=27.285 ms
64 bytes from 34.88.179.153: icmp_seq=3 ttl=54 time=28.253 ms
64 bytes from 34.88.179.153: icmp_seq=4 ttl=54 time=27.918 ms
64 bytes from 34.88.179.153: icmp_seq=5 ttl=54 time=26.101 ms
64 bytes from 34.88.179.153: icmp_seq=6 ttl=54 time=28.055 ms
64 bytes from 34.88.179.153: icmp_seq=7 ttl=54 time=29.185 ms
64 bytes from 34.88.179.153: icmp_seq=8 ttl=54 time=26.311 ms
```

```
mj@JsM-Macbook-Pro exercise-3 % terraform destroy
google_compute_network.vpc_network: Refreshing state... [id=projects/s5terraform/global/networks/exam-network]
google_compute_instance.instance-mockexam-1: Refreshing state... [id=projects/s5terraform/zones/europe-north1-c/instances/instance-mockexam-1]

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
  - destroy

Terraform will perform the following actions:

  # google_compute_instance.instance-mockexam-1 will be destroyed
  - resource "google_compute_instance" "instance-mockexam-1" {
      - can_ip_forward       = false -> null
      - cpu_platform         = "Intel Broadwell" -> null
      - current_status       = "RUNNING" -> null
      - deletion_protection  = false -> null
      - effective_labels     = {
          - "goog-ec-src"               = "vm_add-tf"
          - "goog-terraform-provisioned" = "true"
        } -> null
      - enable_display       = false -> null
      - id                   = "projects/s5terraform/zones/europe-north1-c/instances/instance-mockexam-1" -> null
      - instance_id          = "6646125529015166052" -> null
      - label_fingerprint    = "4si_kQkSihg=" -> null
      - labels               = {
          - "goog-ec-src" = "vm_add-tf"
        } -> null
      - machine_type         = "e2-medium" -> null
      - metadata             = {} -> null
      - metadata_fingerprint = "DFqQtECjtL0=" -> null
      - name                 = "instance-mockexam-1" -> null
      - project              = "s5terraform" -> null
      - resource_policies    = [] -> null
      - self_link            = "https://www.googleapis.com/compute/v1/projects/s5terraform/zones/europe-north1-c/instances/instance-mockexam-1" -> nu
      - tags                 = [
          - "http-server",
        ] -> null
      - tags_fingerprint     = "FYLDgkTKlA4=" -> null
      - terraform_labels     = {
          - "goog-ec-src"               = "vm_add-tf"
          - "goog-terraform-provisioned" = "true"
        } -> null
      - zone                 = "europe-north1-c" -> null
        # (3 unchanged attributes hidden)

      - boot_disk {
          - auto_delete                = true -> null
          - device_name                = "instance-mockexam-1" -> null
```

```
      - routing_mode                   = "REGIONAL" -> null
      - self_link                      = "https://www.googleapis.com/compute/v1/projects/s5terraform/global/networks/exam-network" -> null
        # (3 unchanged attributes hidden)
    }

Plan: 0 to add, 0 to change, 2 to destroy.

Do you really want to destroy all resources?
  Terraform will destroy all your managed infrastructure, as shown above.
  There is no undo. Only 'yes' will be accepted to confirm.

  Enter a value: yes
```

Filter Enter property name or value

Status	Name	Zone	Recommendations	In use by	Internal IP	External IP	Connect

mj — ping 34.88.179.153 — 80×24

```
mj@JsM-Macbook-Pro ~ % ping 34.88.179.153
PING 34.88.179.153 (34.88.179.153): 56 data bytes
Request timeout for icmp_seq 0
Request timeout for icmp_seq 1
Request timeout for icmp_seq 2
Request timeout for icmp_seq 3
Request timeout for icmp_seq 4
Request timeout for icmp_seq 5
Request timeout for icmp_seq 6
```