


Computer Security Principles

Lecture 2: Information Security
Concepts



Confidentiality

- Preserving authorized restrictions on information access and disclosure, including means for protecting personal privacy and proprietary information

Integrity

- Guarding against improper information modification or destruction, including ensuring information nonrepudiation and authenticity

Availability

- Ensuring timely and reliable access to and use of information



Low

The loss could be expected to have a limited adverse effect on organizational operations, organizational assets, or individuals

Moderate

The loss could be expected to have a serious adverse effect on organizational operations, organizational assets, or individuals

High

The loss could be expected to have a severe or catastrophic adverse effect on organizational operations, organizational assets, or individuals

Computer Security Challenges

- Computer security is not as simple as it might first appear to the novice
- Potential attacks on the security features must be considered
- Procedures used to provide particular services are often counterintuitive
- Physical and logical placement needs to be determined
- Additional algorithms or protocols may be involved
- Attackers only need to find a single weakness, the developer needs to find all weaknesses
- Users and system managers tend to not see the benefits of security until a failure occurs
- Security requires regular and constant monitoring
- Is often an afterthought to be incorporated into a system after the design is complete
- Thought of as an impediment to efficient and user-friendly operation






Figure 1.1 Security Concepts and Relationships



- Categories of vulnerabilities
 - Corrupted (loss of integrity)
 - Leaky (loss of confidentiality)
 - Unavailable or very slow (loss of availability)
- Threats
 - Capable of exploiting vulnerabilities
 - Represent potential security harm to an asset
- Attacks (threats carried out)
 - Passive – attempt to learn or make use of information from the system that does not affect system resources
 - Active – attempt to alter system resources or affect their operation
 - Insider – initiated by an entity inside the security parameter
 - Outsider – initiated from outside the perimeter



Threat Consequence	Threat Action (Attack)
Unauthorized Disclosure A circumstance or event whereby an entity gains access to data for which the entity is not authorized.	Exposure: Sensitive data are directly released to an unauthorized entity. Interception: An unauthorized entity directly accesses sensitive data traveling between authorized sources and destinations. Inference: A threat action whereby an unauthorized entity indirectly accesses sensitive data (but not necessarily the data contained in the communication) by reasoning from characteristics or byproducts of communications. Intrusion: An unauthorized entity gains access to sensitive data by circumventing a system's security protections.
Deception A circumstance or event that may result in an authorized entity receiving false data and believing it to be true.	Masquerade: An unauthorized entity gains access to a system or performs a malicious act by posing as an authorized entity. Falsification: False data deceive an authorized entity. Repudiation: An entity deceives another by falsely denying responsibility for an act.
Disruption A circumstance or event that interrupts or prevents the correct operation of system services and functions.	Incapacitation: Prevents or interrupts system operation by disabling a system component. Corruption: Undesirably alters system operation by adversely modifying system functions or data. Obstruction: A threat action that interrupts delivery of system services by hindering system operation.
Usurpation A circumstance or event that results in control of system services or functions by an unauthorized entity.	Misappropriation: An entity assumes unauthorized logical or physical control of a system resource. Misuse: Causes a system component to perform a function or service that is detrimental to system security.

Computer and Network Assets: Threats

	Availability	Confidentiality	Integrity
Hardware	Equipment is stolen or disabled, thus denying service.	An unencrypted CD-ROM or DVD is stolen.	
Software	Programs are deleted, denying access to users.	An unauthorized copy of software is made.	A working program is modified, either to cause it to fail during execution or to cause it to do some unintended task.
Data	Files are deleted, denying access to users.	An unauthorized read of data is performed. An analysis of statistical data reveals underlying data.	Existing files are modified or new files are fabricated.
Communication Lines and Networks	Messages are destroyed or deleted. Communication lines or networks are rendered unavailable.	Messages are read. The traffic pattern of messages is observed.	Messages are modified, delayed, reordered, or duplicated. False messages are fabricated.

Passive Attack

- Attempts to learn or make use of information from the system but does not affect system resources
- Eavesdropping on, or monitoring of, transmissions
- Goal of attacker is to obtain information that is being transmitted
- Two types:
 - Release of message contents
 - Traffic analysis

Active Attack

- Attempts to alter system resources or affect their operation
- Involve some modification of the data stream or the creation of a false stream
- Four categories:
 - Replay
 - Masquerade
 - Modification of messages
 - Denial of service

Fundamental Security Design Principles

Economy of
mechanism

Fail-safe
defaults

Complete
mediation

Open design

Separation of
privilege

Least
privilege

Least
common
mechanism

Psychological
acceptability

Isolation

Encapsulation

Modularity

Layering

Least
astonishment

Consist of the reachable and exploitable vulnerabilities in a system

Examples:

Open ports on outward facing Web and other servers, and code listening on those ports

Services available on the inside of a firewall

Code that processes incoming data, email, XML, office documents, & industry-specific custom data exchange formats

Interfaces, SQL, and Web forms

An employee with access to sensitive information vulnerable to a social engineering attack

Attack Surface Categories

Network Attack Surface

Vulnerabilities over an enterprise network, wide-area network, or the Internet

Network protocol vulnerabilities, such as those used for a denial-of-service attack, disruption of communications links, & various forms of intruder attacks

Software Attack Surface


Vulnerabilities in application, utility, or operating system code

Particular focus is Web server software


Human Attack Surface

Vulnerabilities created by personnel or outsiders, such as social engineering, human error, and trusted insiders

Defense in Depth and Attack Surfaces



Internet Banking Authentication Attack Tree



Security Policy

- Formal statement of rules and practices that specify or regulate how a system or organization provides security services to protect sensitive and critical system resources

Security Implementation

- Involves four complementary courses of action:
 - Prevention
 - Detection
 - Response
 - Recovery

Assurance

- The degree of confidence one has that the security measures, both technical and operational, work as intended to protect the system and the information it processes

Evaluation

- Process of examining a computer product or system with respect to certain criteria

