

AHD Camera 1.0 Megapixel



DOME CAMERA
Model No. I224D
key features:
1/4" HD-CMOS
IR Dome Camera
HD@720P
3.6mm MP HD Lens
3-IR Array LED /.10-20Mtr..



BULLET CAMERA
Model No. I224B
key features:
1/4" HD-CMOS
IR Dome Camera
HD@720P
3.6mm 2MP HD Lens
3-IR Array LED /.20-25Mtr..



BULLET CAMERA
Model No. I224B6
key features:
1/4" HD-CMOS
IR Dome Camera
HD@720P
6mm 2MP HD Lens
3-IR Array LED /.30-40Mtr..

Key Features:	
Image Sensor	1/4" HD CMOS
Resolution	PAL/NTSC : 1280 x 720
Minimum Illumination	0.1 Lux (Color/Day) 0Lux(B/W)
Shutter Type	1/50(1/60)s~1/100,000s
Camera Pixels	720P
White Balance	Auto Tracking White Balance
Back light Compensation	Auto
Lens Furnished	3.6mm 3MP HD Lens
Lens Type	HD Lens / IR Cut Filter
Gain Control	Auto
3D-DNR (3D Digital Noise Reduction)	Auto
IR LED / IR Distance	6-IR Array LED / 20-30 Mtr.
Video Output	AHD - BNC
Power Source	12 V DC \pm 10%
Current Drawn	500mA (Max.)
Operating Temperature	-10°C to +55°C

SONY CCD/DIS With High Performance Taiwanese IR LED

SAFEVIEW EXIM
WWW.SAFEVIEWEXIM.COM



MAKE IN INDIA

AHD Camera 2.4 Megapixel



DOME CAMERA
Model No. 2024D
key features:
1/2.9" HD-CMOS
IR Dome Camera
Full HD@1080P
3.6mm 3MP HD Lens
3-IR Array LED /.10-20Mtr..



BULLET CAMERA
Model No. 2024B
key features:
1/2.9" HD-CMOS
IR Bullet Camera
Full HD@1080P
3.6mm 3MP HD Lens
6-IR Array LED /.15-20Mtr..



BULLET CAMERA
Model No. 2024B6
key features:
1/2.9" HD-CMOS
IR Bullet Camera
Full HD@1080P
6/8mm 3MP HD Lens
6-IR Array LED /.30-40Mtr..

Key Features:	
Image Sensor	1/2.9" HD CMOS
Resolution	PAL/NTSC : 1920x1080
Minimum Illumination	0.1 Lux (Color/Day) 0Lux(B/W)
Shutter Type	1/50(1/60)s~1/100,000s
Camera Pixels	1080P
White Balance	Auto Tracking White Balance
Back light Compensation	Auto
Lens Furnished	3.6mm MP HD Lens
Lens Type	HD Lens / IR Cut Filter
Gain Control	Auto
3D-DNR (3D Digital Noise Reduction)	Auto
IR LED / IR Distance	6-IR Array LED / 20-30 Mtr.
Video Output	AHD - BNC
Power Source	12 V DC \pm 10%
Current Drawn	500mA (Max.)
Operating Temperature	-10°C to +55°C

SONY CCD/DIS With High Performance Taiwanese IR LED

SAFEVIEW EXIM
WWW.SAFEVIEWEXIM.COM



MAKE IN INDIA

AHD Camera 3.0 Megapixel



DOME CAMERA
Model No. 3024D
key features:
1/2.7" HD-CMOS
IR Dome Camera
3MP Resolution (2048x1536)
3.6mm 3MP HD Lens
3-IR Array LED /.10-20Mtr..



BULLET CAMERA
Model No. 3024B
key features:
1/2.7" HD-CMOS
IR Bullet Camera
3MP Resolution (2048x1536)
3.6mm 3MP HD Lens
6-IR Array LED /.15-20Mtr..



BULLET CAMERA
Model No. 3024B6
key features:
1/2.7" HD-CMOS
IR Bullet Camera
3MP Resolution (2048x1536)
6/8mm 3MP HD Lens
6-IR Array LED /.30-40Mtr..

Key Features:	
Image Sensor	1/2.7" HD CMOS
Resolution	PAL/NTSC : 2048x1536
Minimum Illumination	0.1 Lux (Color/Day) 0Lux(B/W)
Shutter Type	1/50(1/60)s~1/100,000s
Camera Pixels	3MP (2048P)
White Balance	Auto Tracking White Balance
Back light Compensation	Auto
Lens Furnished	3.6mm MP HD Lens
Lens Type	HD Lens / IR Cut Filter
Gain Control	Auto
3D-DNR (3D Digital Noise Reduction)	Auto
IR LED / IR Distance	6-IR Array LED / 20-30 Mtr.
Video Output	AHD - BNC
Power Source	12 V DC \pm 10%
Current Drawn	500mA (Max.)
Operating Temperature	-10°C to +55°C

SONY CCD/DIS With High Performance Taiwanese IR LED

SAFEVIEW EXIM
WWW.SAFEVIEWEXIM.COM



MAKE IN INDIA

AHD Camera 4.0 Megapixel



DOME CAMERA

Model No. 4024D

key features:

1/3" HD-CMOS

IR Dome Camera

4MP Resolution (2688x1520)

3.6mm HD Lens

3-IR Array LED /.10-20Mtr..



BULLET CAMERA

Model No. 4024B

key features:

1/3" HD-CMOS

IR Bullet Camera

4MP Resolution (2688x1520)

3.6mm HD Lens

6-IR Array LED /.15-20Mtr..



BULLET CAMERA

Model No. 4024B6

key features:

1/3" HD-CMOS

IR Bullet Camera

4MP Resolution (2688x1520)

6/8mm HD Lens

6-IR Array LED /.30-40Mtr..

Key Features:	
Image Sensor	1/3" HD CMOS
Resolution	PAL/NTSC : 2688x1520
Minimum Illumination	0.1 Lux (Color/Day) 0Lux(B/W)
Shutter Type	1/50(1/60)s~1/100,000s
Camera Pixels	4MP (2688P)
White Balance	Auto Tracking White Balance
Back light Compensation	Auto
Lens Furnished	3.6mm MP HD Lens
Lens Type	HD Lens / IR Cut Filter
Gain Control	Auto
3D-DNR (3D Digital Noise Reduction)	Auto
IR LED / IR Distance	6-IR Array LED / 20-30 Mtr.
Video Output	AHD - BNC
Power Source	12 V DC \pm 10%
Current Drawn	500mA (Max.)
Operating Temperature	-10°C to +55°C

SONY CCD/DIS With High Performance Taiwanese IR LED

SAFEVIEW EXIM
WWW.SAFEVIEWEXIM.COM



MAKE IN INDIA