

Sept 4 2025

IMClean Gen4 product Hardware capabilities

Feature	DAD 4
CAN1 (6&14)	J1979-1, J1979-2
FT-CAN2 (6&14)	x
CAN 2 (3&11)	x
CAN 2 (2&10)	x
CAN 2 (1&9)	x
CAN 2 (3&8)	x
CAN 2 (12&13)	x
CAN 2 (13&12)	x
FT-CAN 2 (3&11)	x
SW-CAN 2 (1)	x
FT-CAN 2 (1&9)	x
J1850 (VPW) (2)	J1979-1
J1850 (PWM) (2&10)	J1979-1
ISO Serial K (Pin 1)	x
ISO Serial K (Pin 2)	x
ISO Serial K (Pin 3)	x
ISO Serial K (Pin 6)	x
ISO Serial K (Pin 7)	J1979-1
ISO Serial K (Pin 8)	x
ISO Serial K (Pin 9)	x
ISO Serial K (Pin 10)	x
ISO Serial K (Pin 11)	x
ISO Serial K (Pin 12)	x
ISO Serial K (Pin 13)	x
ISO Serial K (Pin 14)	x
ISO Serial K (Pin 15)	x
ISO Serial L (Pin 15)	J1979-1
Chrysler SCI	x
DiagH(Pin 1)	x
DiagH(Pin 14)	x
GM UART (Pin 1)	x
GM UART (Pin 9)	x
UART Echo Byte (7)	x
KW82 (7)	x
STG(Pin 1)	x
STG(Pin 9)	x
STG(Pin 12)	x
STG(Pin 15)	x
TP 1.6 / 2.0	x
J1939	x
Battery powered	x
Vehicle connector pin count	26
Max Vehicle Voltage	28