



Fundamental Concepts in Data Insight:

Demo: Unsupervised Learning & Network Science

Fundamentals for a General Audience





QA Ltd. owns the copyright and other intellectual property rights of this material and asserts its moral rights as the author. All rights reserved.





The following code sets up the datasets needed for the demo.

Data

We obtain,

- a dataset of messages between possible criminal (gang) suspects
- statistical metrics which describe this messaging behaviour
- a predictive model which connects these metrics to gang rank hierarchies

NB

This derives from a simulation of messaging behaviour. This simulation is available in a separate notebook. The simulation generates messages; and everything else is statistically derived.

```
data      = pickle.load(open('data/suspectgraph.pkl', 'rb'))
metrics   = pd.read_csv('data/gmetrics.csv')
model     = pickle.load(open('data/gmodel.pkl', 'rb'))
```





The message log shows communication events between suspects,

```
sample(data['log'], 3)
```

```
[{'subject': '+44 77133 00082',  
  'verb': 'SEND',  
  'object': '+44 77133 00034',  
  'context': {'body': 'where are you?', 'created': 1621839523.4468455},  
  'event': {'created': 1621839523.4468455, 'inserted': None}},  
 {'subject': '+44 77133 00086',  
  'verb': 'SEND',  
  'object': '+44 77133 00057',  
  'context': {'body': 'do that!', 'created': 1621839523.4468455},  
  'event': {'created': 1621839523.4468455, 'inserted': None}},  
 {'subject': '+44 77133 00064',  
  'verb': 'SEND',  
  'object': '+44 77133 00034',  
  'context': {'body': 'do it NOW!', 'created': 1621839523.4468455},  
  'event': {'created': 1621839523.4468455, 'inserted': None}}]
```





From this we can generate a graph whose *nodes* are the suspect IDs (mobile numbers), and whose *edges* are the communication activity,

```
sample(data['graph'], 3)
```

```
[('+44 77133 00094', '+44 77133 00086', {'freq': 2}),  
 ('+44 77133 00092', '+44 77133 00064', {'freq': 2}),  
 ('+44 77133 00064', '+44 77133 00057', {'freq': 2})]
```


We can visualize this graph,





```
G = nx.from_edgelist(data['graph'], nx.DiGraph)

nx.draw(G, pos := nx.spring_layout(G), with_labels=True)
nx.draw_networkx_edge_labels(G, pos,
    edge_labels=nx.get_edge_attributes(G, 'freq'));
```





The inferential challenge is to assign each node a *rank* within a possible gang hierachy. To do this we compute *metrics* on this graph,

metrics

node				degree_in	degree_out	freq_in	freq_out
0	+44	77133	00092	0.142857	0.107143	0.103448	0.086207
1	+44	77133	00094	0.214286	0.250000	0.155172	0.224138
2	+44	77133	00086	0.071429	0.250000	0.051724	0.241379
3	+44	77133	00064	0.214286	0.250000	0.155172	0.189655
4	+44	77133	00057	0.142857	0.107143	0.120690	0.068966
5	+44	77133	00082	0.178571	0.107143	0.137931	0.051724
6	+44	77133	00022	0.142857	0.142857	0.120690	0.086207
7	+44	77133	00034	0.214286	0.107143	0.155172	0.051724





Here these metrics represent, for each suspect,

- **degree in**
 - number of people *sent* messages **to** / total possible
- **degree out**
 - number of people *received* messages **from** / total possible
- **freq in**
 - number of messages received / total sent in network
- **freq out**
 - number of messages sent / total sent in network

These metrics are computed in an "unsupervised manner": they merely summarise patterns in data we can already observe.





We can use these metrics in a supervised machine learning model to *predict* ranks,

```
features = metrics.copy()
nodes = features.pop('node')
predictions = model.predict(features)
```

```
predictions
```

```
array(['Commander', 'Senior', 'Senior', 'Relay', 'Frontline', 'Frontline',
      'Frontline', 'Frontline'], dtype=object)
```





For the sake of clarity, we can put these in a table alongside the original suspect IDs,

```

ranks = ['Commander', 'Senior', 'Relay', 'Frontline']
result = pd.DataFrame([ {"node": n, "rank": ranks.index(p), "role":
p}
    for n, p in zip(nodes, predictions)
])

result
```

	node	rank	role
0	+44 77133 00092	0	Commander
1	+44 77133 00094	1	Senior
2	+44 77133 00086	1	Senior
3	+44 77133 00064	2	Relay
4	+44 77133 00057	3	Frontline
5	+44 77133 00082	3	Frontline
6	+44 77133 00022	3	Frontline
7	+44 77133 00034	3	Frontline





Aside: Visualizing the Hierachy

With some extra steps we can visualize the table above as a hierachical graph ("tree"),





```
nx.draw(H:=nx.from_edgelist(tree, nx.DiGraph), graphviz_layout(H, prog='dot'), with_labels=True)
```

