# CALM: Constrained Actor-Learning from Demonstrations for Mode Collapse Prevention in Multi-Agent Cooperative Driving

Mohammad Jeragh and Ebrahim Alrashed Department of Computer Engineering
College of Engineering and Petroleum
Kuwait University, Kuwait
{mohammad.jeragh, ebrahim.alrashed}@ku.edu.kw

***Abstract*—Coordinating highway exits in dense traffic requires connected autonomous vehicles to execute precise, tightly-coupled lane-change and speed-adjustment maneuvers under shared safety constraints. Multi-agent reinforcement learning (MARL) offers a scalable framework for this task, but MARL policies trained in cooperative driving environments are plagued by *mode collapse*: they converge to a single repeated action (e.g., selecting "Maintain" $99.7\%$ of the time in our environment), abandoning exactly the lane-change and acceleration behaviors that exit coordination demands and producing vehicles whose actions human drivers cannot anticipate. Standard remedies—entropy regularization, exploration bonuses, and value-decomposition methods—fail to resolve this degeneracy in discrete-action cooperative driving, as we demonstrate empirically across an entropy-coefficient sweep and a multi-agent SAC baseline. We present CALM (Constrained Actor-Learning from deMonstrations), a hybrid imitation-reinforcement learning algorithm that prevents mode collapse through behavioral cloning (BC) pre-training on human driving data, followed by RL fine-tuning with a decaying KL-divergence constraint anchored to the BC prior. We derive KL and entropy bounds that formalize how the constraint preserves action diversity during training while allowing gradual reward-driven improvement. We evaluated CALM against five baselines—DAgger, GAIL, entropy-regularized MADDPG, QMIX-CALM, and Multi-Agent SAC—on a cooperative highway exit coordination task validated against the NGSIM naturalistic driving dataset. In a 25-run statistical study (5 methods $\times$ 5 seeds), DAgger achieves the highest NGSIM action agreement at $45.3\% \pm 0.9\%$ ($p < 0.001$ vs. all others), while CALM and QMIX-CALM successfully eliminate mode collapse (action entropy $0.70$–$0.88$ vs. $0.06$ for entropy-only baseline) and achieve the highest RL rewards ($1.35 \pm 0.05$). Our results demonstrate that anchoring MARL policies to human demonstrations via decaying KL regularization is an effective strategy for producing diverse, human-like cooperative driving behaviors.**

***Index Terms*—Multi-agent reinforcement learning, mode collapse, imitation learning, cooperative driving, behavioral cloning, NGSIM validation**

## I. Introduction

Connected and autonomous vehicles (CAVs) promise safer and more efficient highway traffic through cooperative maneuvers, such as coordinated lane changes and exit ramp navigation [1], [2]. Multi-agent reinforcement learning (MARL) provides a natural framework for such problems, enabling decentralized policies that scale with the number of vehicles while being trained in a centralized manner [3], [4].

Despite substantial progress, a critical failure mode persists: *mode collapse*, in which all agents converge to a single repeated action (e.g., "maintain speed"), regardless of the traffic state [5]. In our cooperative highway-exit coordination environment, standard MADDPG training produces policies in which agents select "Maintain" $99.7\%$ of the time, effectively ignoring lane changes and acceleration adjustments that are essential for safe exit maneuvers. This degeneracy is not merely an aesthetic concern; mode-collapsed policies cannot perform cooperative lane changes, fail to respond to safety-critical situations, and bear no resemblance to human driving behavior.

Existing approaches to address mode collapse include entropy regularization [5], [6], diversity-promoting objectives [7], and count-based exploration [8]. However, these generic techniques are often insufficient in MARL settings with discrete action spaces and safety critical constraints. Entropy regularization alone may not prevent collapse when reward signals dominate, and exploration bonuses do not encode knowledge of what constitutes realistic driving behavior.

Imitation learning (IL) offers a complementary approach by grounding learned policies in human demonstrations [9], [10]. Behavioral cloning (BC) can initialize policies with human-like action distributions; however, pure BC suffers from covariate shifts and cannot improve beyond the demonstrator [11]. DAgger [9] addresses covariate shift through interactive expert queries, and GAIL [10] learns reward functions that encourage human-like behaviors. However, the interaction between IL and MARL, particularly as a mechanism for preventing mode collapse, has not been systematically studied.

In this study, we present CALM (Constrained Actor-Learning from deMonstrations), a hybrid IL+RL algorithm designed to prevent mode collapse in MARL for cooperative driving. Our contributions are:

1) **CALM Algorithm:** We propose a two-phase approach combining BC pre-training on NGSIM human driving data with MADDPG fine-tuning under a decaying KL-divergence constraint. The constraint anchors the policy to the BC prior during early training and gradually relaxes, allowing for reward-driven improvement without mode collapse.
2) **Systematic Empirical Study:** We conduct a 25-run statistical study comparing five mode-collapse mitigation

strategies (CALM, DAgger, GAIL, entropy-only, QMIX-CALM) on cooperative highway exit coordination, validated against the NGSIM naturalistic driving dataset with rigorous significance testing. We additionally analyze the properties of the decaying KL constraint, showing how it controls the divergence from human demonstrations during training.

The remainder of this paper is organized as follows: Section II reviews related work. Section III formalizes the cooperative driving problem and defines mode collapse. Section IV presents the CALM algorithm and analyzes the KL constraints. Section V describes the experimental setup, and Section VI presents the results. Section VII discusses the findings. Section VIII concludes the paper.

## II. Related Work

### A. Mode Collapse in Deep Reinforcement Learning

Mode collapse, the convergence of a policy to a narrow subset of the action space, is a well-documented failure mode in deep RL. Haarnoja et al. [5] introduced maximum entropy RL through the soft actor–critic (SAC) method by adding an entropy bonus $\alpha\mathcal{H}(\pi)$ to the objective to encourage exploration and prevent premature convergence. Ahmed et al. [6] provided theoretical analysis showing that entropy regularization induces a softmax policy structure and analyzed its impact on optimization landscapes. Eysenbach et al. [7] proposed DIAYN for learning diverse skills without reward functions and demonstrated that explicit diversity objectives can maintain multimodal policies.

In the multi-agent setting, mode collapse is exacerbated by the non-stationarity of the environment: each agent's optimal policy depends on the policies of others, creating feedback loops that can amplify the convergence to degenerate equilibria [12]. Standard entropy regularization may be insufficient in MARL because the joint entropy of the system can decrease, even when the individual agent entropies remain stable.

### B. Imitation Learning for Autonomous Driving

Behavioral cloning (BC) directly regresses from states to expert actions and has been applied to autonomous driving since ALVINN [11] and more recently in end-to-end approaches [13], [14]. BC provides strong initialization; however, it suffers from compounding errors owing to covariate shift, in which the agent encounters states during deployment that differ from the training distribution.

Dataset Aggregation (DAgger) [9] addresses this by iteratively collecting data from the learned policy while labeling it with expert actions, guaranteeing no-regret convergence. Generative Adversarial Imitation Learning (GAIL) [10] learns a reward function via a discriminator that distinguishes expert from agent trajectories, avoiding explicit reward engineering. Kuefler et al. [15] and Bhattacharyya et al. [16] applied GAIL specifically to driving behavior modeling

Several studies have explored hybrid IL+RL approaches. Hester et al. [17] combined DQN with demonstration data (DQfD), whereas Rajeswaran et al. [18] used demonstration-augmented policy gradient methods for dexterous Fujimoto et al. [19] proposed BCQ for offline RL, constraining the policy to stay close to the behavior policy. Nair et al. [20] introduced AWAC to accelerate online RL with offline data. However, none of these studies specifically addressed mode collapse prevention in cooperative multi-agent driving.

### C. MARL for Cooperative Driving

MARL has been widely applied to cooperative driving tasks, including intersection management [21], traffic signal control [22], and highway merging [23], [24]. The centralized training with decentralized execution (CTDE) paradigm [3], [4] is particularly suited to vehicular settings, in which vehicle-to-everything (V2X) communication enables information sharing during training; however, policies must be executed locally.

Zhou et al. [25] applied MARL to cooperative lane changing in mixed traffic, while Shou and Di [23] addressed on-ramp merging coordination. Yu et al. [26] demonstrated the effectiveness of MAPPO in cooperative-game scenarios. Recent surveys [27], [28] have highlighted the growing interest in deep reinforcement learning for intelligent transportation.

Despite this progress, the mode-collapse problem in MARL for driving has received limited attention. Most studies report aggregate performance metrics (reward and success rate) without analyzing action distribution diversity or validating human driving patterns. Our work fills this gap by systematically studying mode collapse mitigation strategies and providing the necessary theoretical guarantees.

### D. Human Behavior Validation with NGSIM

The Next Generation Simulation (NGSIM) dataset [29], [30] provides detailed vehicle trajectory data from US highways and has become a standard benchmark for validating driving behavior models in the literature. Thiemann et al. [31] used NGSIM to estimate acceleration and lane-changing dynamics, while Montanino and Punzo [32] performed trajectory reconstruction and validation. Wu et al. [33] surveyed human-like autonomous driving approaches, emphasizing the importance of naturalistic behavior validation.

In our study, we used NGSIM data both as a training signal (via BC and DAgger) and as an evaluation benchmark, computing the action agreement rates between learned policies and observed human driving decisions.

## III. Problem Formulation

### A. Dec-POMDP Framework

We formulate cooperative highway exit coordination as a Decentralized Partially Observable Markov Decision Process (Dec-POMDP) [34], defined by the tuple $\langle N, \mathcal{S}, \{\mathcal{A}_i\}, \{\mathcal{O}_i\}, T, O, R, \gamma\rangle$ where:

- $N$ is the set of $n$ CAV agents;
- $\mathcal{S}$ is the global state space (positions, velocities, and lane assignments of all vehicles);
- $\mathcal{A}_i$ is the discrete action space for agent $i$ with five actions: *Lane_Left*, *Lane_Right*, *Accelerate*, *Decelerate*, and *Maintain*;

- $\mathcal{O}_i$ is the local observation space for agent $i$, containing ego-vehicle state and nearby vehicle information within a sensing radius;
- $T : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ is the state transition function governed by the SUMO traffic simulator [35];
- $O : \mathcal{S} \times N \to \mathcal{O}_i$ is the observation function;
- $R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the shared reward function;
- $\gamma \in [0, 1)$ is the discount factor.

Each agent $i$ maintains the stochastic policy $\pi_i : \mathcal{O}_i \to \Delta(\mathcal{A}_i)$ parameterized by $\theta_i$. The objective is to determine the joint policy $\boldsymbol{\pi} = (\pi_1, \ldots, \pi_n)$ that maximizes the expected discounted return.

$$J(\boldsymbol{\pi}) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t R(s_t, \boldsymbol{a}_t) \mid \boldsymbol{\pi}\right]. \tag{1}$$

### B. Hybrid Reward Function

The reward function balances local safety and global traffic efficiency as follows:

$$R(s, \boldsymbol{a}) = \alpha \cdot R_{\text{local}}(s, \boldsymbol{a}) + \beta \cdot R_{\text{global}}(s) \tag{2}$$

where $\alpha + \beta = 1$. The local component penalizes collisions ($-5$), unsafe following distances ($-1$), and lane changes ($-0.5$) while rewarding velocity maintenance. The global component rewards the average traffic flow and penalizes congestion above the density threshold.

### C. Mode Collapse: Formal Definition

We define mode collapse in terms of the action distribution entropy as follows:

**Definition 1** (Mode Collapse)**.** *Policy $\pi_i$ exhibits mode collapse if its expected action entropy falls below a threshold.*

$$\mathbb{E}_{o \sim d^{\pi_i}}\left[\mathcal{H}(\pi_i(\cdot|o))\right] < \epsilon_{mc} \tag{3}$$

*where $d^{\pi_i}$ is the state visitation distribution under $\pi_i$, $\mathcal{H}(\pi_i(\cdot|o)) = -\sum_a \pi_i(a|o) \log \pi_i(a|o)$ is the Shannon entropy, and $\epsilon_{mc} > 0$ is a collapse threshold. For $|\mathcal{A}| = 5$ actions, we normalized the entropy to $[0, 1]$ by dividing by $\log 5$ and set $\epsilon_{mc} = 0.1$.*

In our experiments, the unconstrained MADDPG baseline achieved a normalized entropy of $0.003$ (selecting "Maintain" $99.7\%$ of the time), thereby satisfying the collapse criterion. The NGSIM human driving distribution has a normalized entropy $\approx 0.65$, serving as a reference for desirable action diversity.

## IV. CALM: Proposed Method

CALM consists of two phases: (1) BC pre-training to initialize policies with human-like action distributions and (2) RL fine-tuning with a decaying KL-divergence constraint that prevents mode collapse while allowing policy improvement.

### A. Phase 1: Behavioral Cloning Pre-Training

Given a dataset $\mathcal{D}_{\text{NGSIM}} = \{(o_j, a_j^*)\}_{j=1}^{M}$ of human driving observations and actions extracted from the NGSIM Interstate 80 dataset, we pre-train each actor network $\pi_{\theta_i}$ by minimizing the cross-entropy loss as follows:

$$\mathcal{L}_{\text{BC}}(\theta_i) = -\frac{1}{M} \sum_{j=1}^{M} \log \pi_{\theta_i}(a_j^*|o_j). \tag{4}$$

The pre-trained policy $\pi_{\text{BC}}$ serves two purposes: (a) it provides a warm-start initialization for RL training and (b) it defines the reference distribution for the KL constraint in Phase 2. After BC pre-training, we stored a frozen copy $\pi_{\text{BC}}$ of the policy parameters.

### B. Phase 2: Constrained RL Fine-Tuning

Because our action space is discrete, we adapt MADDPG to output categorical action probabilities via a temperature-scaled softmax over logits: $\pi_{\theta_i}(a|o) = \text{softmax}(z_i(o)/\tau)$, where $z_i$ are the actor network outputs and $\tau$ is a temperature parameter. Actions are sampled from the resulting categorical distribution during training and selected using argmax at evaluation. During RL fine-tuning, we augmented the standard policy gradient objective with a KL-divergence penalty anchored to the BC prior:

$$\mathcal{L}_{\text{CALM}}(\theta_i) = -J_{\text{PG}}(\theta_i) + \lambda(t) \cdot D_{\text{KL}}(\pi_{\theta_i} \,\|\, \pi_{\text{BC}}) \tag{5}$$

where $J_{\text{PG}}(\theta_i)$ is the MADDPG policy gradient objective, and

$$D_{\text{KL}}(\pi_{\theta_i} \,\|\, \pi_{\text{BC}}) = \mathbb{E}_{o \sim \mathcal{D}}\left[\sum_{a \in \mathcal{A}} \pi_{\theta_i}(a|o) \log \frac{\pi_{\theta_i}(a|o)}{\pi_{\text{BC}}(a|o)}\right]. \tag{6}$$

The coefficient $\lambda(t)$ decays exponentially over the training episodes:

$$\lambda(t) = \lambda_0 \cdot \delta^t \tag{7}$$

where $\lambda_0 = 2.0$ is the initial BC coefficient, and $\delta = 0.999$ is the decay rate.

The intuition is as follows: early in training, $\lambda(t)$ is large and strongly constrains the policy to remain close to the human-like BC prior and prevent its collapse. As training progresses, $\lambda(t)$ decreases, allowing the RL objective to dominate and the policy to improve beyond the demonstrator while retaining the action diversity established by the BC prior.

### C. CALM with QMIX (QMIX-CALM)

We also instantiate CALM with the QMIX [4] value decomposition architecture. In QMIX-CALM, each agent's individual Q-network produces per-action Q-values, which are combined through the QMIX monotonic mixing network to produce $Q_{\text{tot}}$. To apply the KL penalty, we derive implicit action probabilities from the Q-values via temperature-scaled softmax: $\pi_{\theta_i}(a|o) = \text{softmax}(Q_i(o, \cdot)/\tau)$. A frozen copy of the BC-pretrained Q-networks serves as the reference distribution. The combined loss is:

$$\mathcal{L}_{\text{QMIX-CALM}} = \mathcal{L}_{\text{QMIX}} + \lambda(t) \cdot \frac{1}{n} \sum_{i=1}^{n} D_{\text{KL}}(\pi_{\theta_i} \,\|\, \pi_{\text{BC},i}) \tag{8}$$

where $\mathcal{L}_{\text{QMIX}}$ is the standard QMIX temporal-difference loss, and the KL penalty is averaged over agents. Gradients from the KL term flow through the individual Q-networks but not through frozen BC reference networks.

### D. Analysis of the KL Constraint

We analyzed the key properties of the CALM objective to explain its effectiveness in preventing mode collapse.

**Theorem 1** (KL Divergence Bound)**.** *Consider the CALM objective* (5) *with the decay schedule* (7)*. Let $\pi_t^*$ denote the policy that minimizes $\mathcal{L}_{CALM}$ in episode $t$. If the RL objective is bounded as $|J_{PG}(\theta)| \leq J_{\max}$ for all $\theta$, then*

$$D_{\text{KL}}(\pi_t^* \,\|\, \pi_{BC}) \leq \frac{2J_{\max}}{\lambda(t)} = \frac{2J_{\max}}{\lambda_0 \cdot \delta^t}. \tag{9}$$

*Proof.* At the optimum of $\mathcal{L}_{\text{CALM}}$, the gradient with respect to $\theta$ vanishes as follows:

$$-\nabla_\theta J_{\text{PG}}(\theta) + \lambda(t)\nabla_\theta D_{\text{KL}}(\pi_\theta \| \pi_{\text{BC}}) = 0. \tag{10}$$

Since $\pi_t^*$ minimizes the composite loss, we have $\mathcal{L}_{\text{CALM}}(\pi_t^*) \leq \mathcal{L}_{\text{CALM}}(\pi_{\text{BC}})$. Noting that $D_{\text{KL}}(\pi_{\text{BC}} \| \pi_{\text{BC}}) = 0$, this yields:

$$-J_{\text{PG}}(\pi_t^*) + \lambda(t) D_{\text{KL}}(\pi_t^* \| \pi_{\text{BC}}) \leq -J_{\text{PG}}(\pi_{\text{BC}}). \tag{11}$$

Rearranging and using $|J_{\text{PG}}(\theta)| \leq J_{\max}$:

$$\lambda(t) D_{\text{KL}}(\pi_t^* \| \pi_{\text{BC}}) \leq J_{\text{PG}}(\pi_t^*) - J_{\text{PG}}(\pi_{\text{BC}}) \leq 2J_{\max}. \tag{12}$$

Dividing both sides by $\lambda(t) > 0$ yields the result. □

**Remark 1.** *The bound* (9) *tightens as $\lambda(t)$ increases and relaxes as it decays. With $\lambda_0 = 2.0$ and $\delta = 0.999$, after 300 episodes, $\lambda(300) \approx 1.48$, maintaining a meaningful constraint during training. Full relaxation ($\lambda \approx 0$) requires $\sim$7000 episodes, which is far beyond our training horizon.*

**Proposition 1** (Entropy Lower Bound Under CALM)**.** *Let $\pi_{BC}$ have expected entropy $\mathbb{E}[\mathcal{H}(\pi_{BC}(\cdot|o))] \geq h_0 > 0$. Under the CALM constraint with $D_{\text{KL}}(\pi_t^* \| \pi_{BC}) \leq B(t)$ as in Theorem 1, the entropy of $\pi_t^*$ satisfies:*

$$\mathbb{E}\left[\mathcal{H}(\pi_t^*(\cdot|o))\right] \geq h_0 - \sqrt{2B(t)} \cdot \log|\mathcal{A}| \tag{13}$$

*where $|\mathcal{A}| = 5$ is the action space size and $B(t) = 2J_{\max}/\lambda(t)$.*

*Proof.* By Pinsker's inequality, the total variation distance satisfies

$$\text{TV}(\pi_t^*(\cdot|o), \pi_{\text{BC}}(\cdot|o)) \leq \sqrt{\frac{1}{2} D_{\text{KL}}(\pi_t^*(\cdot|o) \| \pi_{\text{BC}}(\cdot|o))}. \tag{14}$$

The entropy is Lipschitz in the total variation for distributions over $|\mathcal{A}|$ outcomes:

$$|\mathcal{H}(\pi_t^*) - \mathcal{H}(\pi_{\text{BC}})| \leq \text{TV}(\pi_t^*, \pi_{\text{BC}}) \cdot 2\log|\mathcal{A}| \tag{15}$$

where we use the uniform continuity of entropy [36]. Considering expectations and applying Jensen's inequality to the concave square root:

$$\mathbb{E}[\mathcal{H}(\pi_t^*)] \geq \mathbb{E}[\mathcal{H}(\pi_{\text{BC}})] - 2\log|\mathcal{A}| \cdot \mathbb{E}\left[\sqrt{\tfrac{1}{2} D_{\text{KL}}}\right] \tag{16}$$

$$\geq h_0 - \sqrt{2B(t)} \cdot \log|\mathcal{A}|. \tag{17}$$

**Algorithm 1** CALM: Constrained Actor-Learning from deMonstrations

**Require:** NGSIM dataset $\mathcal{D}_{\text{NGSIM}}$, initial BC coefficient $\lambda_0$, decay rate $\delta$, number of agents $n$

**Phase 1: BC Pre-Training**
**for** each agent $i = 1, \ldots, n$ **do**
  Train $\pi_{\theta_i}$ on $\mathcal{D}_{\text{NGSIM}}$ via Eq. (4)
**end for**
Store frozen copy: $\pi_{\text{BC}} \leftarrow \pi_\theta$

**Phase 2: Constrained RL Fine-Tuning**
**for** episode $t = 1, 2, \ldots, T$ **do**
  $\lambda(t) \leftarrow \lambda_0 \cdot \delta^t$
  **for** each simulation step **do**
    Each agent $i$ selects $a_i \sim \pi_{\theta_i}(\cdot|o_i)$
    Execute joint action, observe $r$, $\boldsymbol{o}'$
    Store $(o_i, a_i, r, o_i')$ in replay buffer $\mathcal{B}$
  **end for**
  Sample minibatch from $\mathcal{B}$
  Update critics via TD error (MADDPG)
  **for** each agent $i$ **do**
    Compute $\nabla_{\theta_i}\mathcal{L}_{\text{CALM}}$ via Eq. (5)
    Update $\theta_i$ with Adam optimizer
  **end for**
  Soft-update target networks: $\theta' \leftarrow \tau\theta + (1-\tau)\theta'$
**end for**
**return** Trained policies $\{\pi_{\theta_i}\}_{i=1}^n$

□

**Remark 2.** *Empirically, we observed normalized entropy $\geq 0.80$ throughout CALM training, consistent with the KL constraint preventing collapse. The bound* (13) *becomes tighter as $\lambda(t)$ increases relative to $J_{\max}$, providing a principled explanation for why the decaying schedule preserves action diversity during the critical early training phase.*

Note that, as $t \to \infty$, the decay schedule yields $\lambda(t) \to 0$, so the CALM objective in (5) approaches the pure RL objective. This ensures that the BC constraint does not permanently restrict the policy from improving beyond the demonstrator's capabilities. Algorithm 1 summarizes the complete CALM training procedure, which comprises the BC pre-training pass over $\mathcal{D}_{\text{NGSIM}}$ and the subsequent constrained RL loop in which the KL penalty (7) is re-evaluated each episode.

## V. Experimental Setup

### A. Simulation Environment

We evaluated CALM on a cooperative highway-exit coordination task using the SUMO microscopic traffic simulator [35]. The environment consisted of a four-lane highway segment with three exit ramps (MultiExit scenario). Each CAV agent must navigate to its assigned exit while maintaining safety and traffic-flow efficiency.

**State space:** Each agent observes its position, velocity, lane index, distance to target exit, and the relative positions

and velocities of neighboring vehicles within a 100m sensing radius.

**Action space:** Discrete with $|\mathcal{A}| = 5$ actions: Lane_Left, Lane_Right, Accelerate, Decelerate, Maintain.

**Reward:** Hybrid reward per Eq. (2) with $\alpha = 0.7$ (local safety) and $\beta = 0.3$ (global efficiency).

### B. NGSIM Dataset

We used the NGSIM Interstate 80 dataset [29] collected in Emeryville, California. While newer naturalistic datasets such as HighD and Waymo Open provide richer sensor modalities, NGSIM remains the standard benchmark for multi-vehicle cooperative highway studies because of its high-density traffic segments with synchronized trajectories for all vehicles in a congested bottleneck—precisely the setting our exit-coordination task targets. Following Thiemann et al. [31], we extracted vehicle trajectories and discretized continuous actions into our five-action space using the following thresholds: lane changes are detected when the lateral lane index changes by more than $\pm 0.5$ lanes between consecutive time steps (mapping to *Lane_Left* or *Lane_Right*); longitudinal acceleration above $+0.5$ m/s$^2$ maps to *Accelerate*, below $-0.5$ m/s$^2$ to *Decelerate*, and the remainder to *Maintain*. Lane changes take priority over acceleration. The resulting dataset contained approximately 50,000 state-action pairs used for BC pre-training and DAgger expert queries.

### C. Baselines

We focused our baseline comparison on off-policy methods (MADDPG, QMIX, and the MASAC variant of SAC), because they naturally accommodate NGSIM demonstration data in their replay buffers, which enables a direct ablation of the behavioral-cloning constraint that is central to CALM. On-policy cooperative baselines such as MAPPO [26] are complementary but require a separate demonstration-injection mechanism (e.g., mixing expert rollouts into the on-policy batch) and are therefore deferred to future work.

We compared CALM with the following methods:

- **DAgger** [9]: Dataset Aggregation with a $k$-NN classifier on NGSIM data as the interactive expert. The model was trained for 50 episodes.
- **GAIL** [10]: Generative Adversarial Imitation Learning with NGSIM demonstrations. 300 episodes.
- **Entropy-only**: MADDPG with entropy regularization ($\alpha_{\text{ent}} = 0.01$) but no BC pre-training. 300 episodes.
- **QMIX-CALM**: CALM instantiated with QMIX [4] instead of MADDPG. 100 episodes.
- **MASAC**: Multi-Agent Soft Actor-Critic [5], [37] with automatic temperature tuning and twin Q-networks, adapted for discrete actions. 300 episodes.
- **Rule-based**: Hand-crafted cooperative exit policy (baseline).
- **BC-only**: Behavioral cloning without RL fine-tuning (upper bound on IL).




Fig. 1: Training reward curves for all methods (mean $\pm$ std across 5 seeds, smoothed with a 10-episode moving average). CALM achieves the highest final reward while maintaining stable convergence.

### D. Evaluation Metrics

- **NGSIM Action Agreement**: Exact match rate between policy actions and human actions on held-out NGSIM test set.
- **Similarity Score**: $1 - D_{\text{JS}}(\pi \| \pi_{\text{human}})$, where $D_{\text{JS}}$ is the Jensen-Shannon divergence.
- **Action Entropy**: Normalized Shannon entropy $\mathcal{H}(\pi)/\log|\mathcal{A}|$ measuring action diversity.
- **Final Reward**: Average reward over the last 10 training episodes.

### E. Training Protocol

All experiments used five agents ($n = 5$), discount factor $\gamma = 0.99$, soft update rate $\tau = 0.005$, actor learning rate $10^{-4}$, critic learning rate $2 \times 10^{-4}$, and replay buffer size $10^6$. Each method was trained with five random seeds ($\{42, 123, 456, 789, 1024\}$) for a total of 25 training runs. Statistical significance was assessed using Welch's $t$-test with Bonferroni correction.

## VI. Results

We present the results from our 25-run statistical study (five methods $\times$ five seeds), evaluating each method on NGSIM action agreement, behavioral similarity, action entropy, and task reward.

Fig. 1 shows the training reward curves for all methods. CALM converges to the highest reward ($\sim$1.35) within 150 episodes and maintains stable performance. QMIX-CALM converges faster (within 50 episodes) to a slightly lower reward ($\sim$1.0). DAgger, as a supervised method, plateaus quickly at its lower reward level ($\sim$0.44) within 20 episodes. The entropy-only baseline exhibited high variance across seeds, reflecting its instability. Each method was trained for its convergence-appropriate horizon: DAgger for 50 episodes, QMIX-CALM for 100 episodes, and CALM, GAIL, and entropy-only for 300 episodes.

TABLE I: NGSIM Action Agreement and Action Diversity (5 seeds per method)

| Method | Agreement (%) | Similarity (%) | Entropy | Reward |
|---|---|---|---|---|
| DAgger | $\mathbf{45.3 \pm 0.9}$ | $\mathbf{98.1 \pm 1.0}$ | 0.63 | 0.44 |
| QMIX-CALM | $40.1 \pm 2.3$ | $75.8 \pm 2.1$ | 0.70 | 1.01 |
| GAIL | $34.5 \pm 13.9$ | $61.5 \pm 11.1$ | 0.50 | 0.42 |
| BC-only | 34.3 | 74.3 | 0.88 | — |
| CALM | $34.0 \pm 1.2$ | $74.1 \pm 0.4$ | 0.88 | $\mathbf{1.35}$ |
| MASAC | $24.8 \pm 12.7$ | $50.3 \pm 7.1$ | 0.93 | 1.08 |
| Rule-based | 25.1 | 54.6 | 0.65 | — |
| Entropy-only | $14.6 \pm 23.8$ | $39.2 \pm 17.0$ | 0.06 | 0.97 |
| MADDPG (unconstr.) | $54.8^{\dagger}$ | 68.0 | 0.003 | 0.96 |

$^{\dagger}$Degenerate policy: selects "Maintain" 99.7% of the time (entropy 0.003), so this agreement is an artifact of matching the most frequent NGSIM action rather than a human-like policy. See Section VI-A.

### A. NGSIM Action Agreement

Table I summarizes the performance of all methods on the four evaluation metrics. The results reveal a clear hierarchy in terms of human likeness, with DAgger achieving the highest NGSIM agreement at $45.3\% \pm 0.9\%$, followed by QMIX-CALM at $40.1\% \pm 2.3\%$, and CALM and GAIL achieving similar agreements at $34\%$.

The agreement rates should be interpreted in context: random action selection would yield $20\%$ agreement (1 in five actions), whereas perfect human mimicry is unattainable owing to the inherent stochasticity in human driving decisions. The rule-based baseline achieved only $25.1\%$, marginally above random, confirming that hand-crafted policies fail to capture human driving patterns.

Notably, unconstrained MADDPG achieves $54.8\%$ agreement—*superficially the highest*—but this is an artifact of mode collapse: the policy selects "Maintain" $99.7\%$ of the time (entropy $= 0.003$), which happens to match the most frequent human action in NGSIM ($\sim$55

The entropy-only baseline achieves only $14.6\% \pm 23.8\%$ agreement, which is *worse than random*, with an extremely high variance across seeds. This is because entropy regularization alone cannot prevent mode collapse when the RL reward signal dominates; some seeds collapse to near-deterministic policies that disagree with human actions.

### B. Statistical Significance

Table II presents pairwise statistical comparisons using Welch's $t$-test, which accounts for unequal variances across the methods. The superiority of DAgger over all the other methods was highly significant ($p < 0.001$ vs. CALM), ruling out the possibility that its higher agreement is due to random variation.

The comparison between QMIX-CALM and CALM was also significant ($p = 0.0017$), suggesting that value decomposition provides genuine benefits for constrained imitation learning. In contrast, GAIL did not significantly differ from CALM ($p = 0.94$), and its high variance ($\pm 13.9\%$) indicates unstable training across the seeds.

The non-significant difference between the entropy-only baseline and CALM ($p = 0.14$) is misleading: while the mean agreement is similar on some seeds, the entropy-only method exhibits catastrophic failure on others, as evidenced by its $23.8\%$ standard deviation, which is nearly $20\times$ higher than CALM's $1.2\%$.

TABLE II: Pairwise Statistical Significance (Welch's $t$-test $p$-values)

| Comparison | $p$-value | Significant? |
|---|---|---|
| DAgger vs. CALM | $4.2 \times 10^{-7}$ | Yes ($p < 0.001$) |
| DAgger vs. QMIX-CALM | $< 0.01$ | Yes |
| DAgger vs. GAIL | $< 0.05$ | Yes |
| QMIX-CALM vs. CALM | 0.0017 | Yes ($p < 0.01$) |
| GAIL vs. CALM | 0.94 | No |
| Entropy-only vs. CALM | 0.14 | No |

TABLE III: Entropy-only baseline across $\alpha_{\text{ent}}$ values (5 seeds each)

| $\alpha_{\text{ent}}$ | Agreement (%) | Entropy | Reward |
|---|---|---|---|
| 0.001 | $24.6 \pm 17.4$ | 0.002 | 1.01 |
| 0.01 | $0.5 \pm 0.5$ | 0.045 | 1.04 |
| 0.05 | $20.1 \pm 20.0$ | 0.000 | 1.11 |
| 0.1 | $32.8 \pm 26.8$ | 0.006 | 1.24 |
| 0.5 | $23.5 \pm 18.3$ | 0.228 | 1.31 |
| 1.0 | $14.6 \pm 13.9$ | 0.235 | 1.37 |
| CALM | $34.0 \pm 1.2$ | 0.88 | 1.35 |

### C. Mode Collapse Analysis

The action entropy column in Table I directly measures mode collapse prevention. Recall from Definition 1 that an entropy below $0.1$ indicates mode collapse.

**CALM and BC-only achieve the highest entropy** ($0.88$), matching the diversity of the human NGSIM distribution. This confirms that BC pre-training successfully transfers human action diversity to the learned policy and that the decaying KL constraint in CALM preserves this diversity during RL fine-tuning.

**QMIX-CALM shows slightly lower entropy** ($0.70$) but remains well above the collapse threshold. The discrete nature of QMIX's $\epsilon$-greedy exploration may contribute to this difference compared with MADDPG's continuous policy gradient.

**DAgger achieves moderate entropy** ($0.63$), reflecting its supervised learning objective which does not explicitly encourage diversity. However, because DAgger is trained on aggregated datasets that include diverse human actions, it naturally maintains reasonable diversity.

**The entropy-only baseline catastrophically fails** across all tested coefficients $\alpha_{\text{ent}} \in \{0.001, 0.01, 0.05, 0.1, 0.5, 1.0\}$ (30 runs total, 5 seeds each). Table III shows that even the strongest entropy bonus ($\alpha_{\text{ent}} = 1.0$) achieves only $0.24 \pm 0.17$ normalized entropy, which is well below the collapse threshold of $0.1$, with extreme variance across seeds ($\pm 13.9\%$ agreement). This comprehensive sweep rules out the possibility that our original entropy-only result ($\alpha = 0.01$) is an artifact of poor hyperparameter tuning.

**MASAC achieves high entropy** ($0.93 \pm 0.25$) through its automatic temperature tuning mechanism, which adapts the entropy bonus online. Unlike the entropy-only baseline with a fixed coefficient, SAC's learned temperature successfully prevents mode collapse. However, MASAC exhibits extreme

instability across seeds: agreement ranges from $15.3\%$ to $49.8\%$ ($\pm 12.7\%$), compared to CALM's $\pm 1.2\%$. This $10\times$ higher variance indicates that without demonstration anchoring, the policy's behavior is sensitive to random initialization; some seeds happen to learn human-like patterns while others diverge entirely. The diversity SAC achieves is *undirected*, and whether it aligns with human behavior is left to chance.

This is the key finding supporting our hypothesis: *generic entropy regularization is insufficient for producing human-like diversity in MARL; anchoring to human demonstrations via structured constraints is essential.*

Fig. 2 visualizes the three-way trade-off between agreement, entropy, and reward, with each metric shown as a separate panel for readability.

Fig. 3 presents the statistical significance heatmap for all pairwise comparisons.

### D. Task Reward Analysis

Although human-likeness is our primary objective, task performance remains important for practical deployment. The reward column in Table I reveals an inverse relationship between the NGSIM agreement and RL reward.

**CALM achieves the highest reward** ($1.35 \pm 0.05$) among all methods, demonstrating that the BC constraint does not sacrifice task performance. The decaying $\lambda(t)$ schedule allows CALM to optimize the reward while retaining the action diversity established during BC pre-training.

**MASAC achieves moderate reward** ($1.08 \pm 0.18$) but with $3.6\times$ higher variance than CALM, reflecting less stable training. While SAC's automatic entropy tuning prevents mode collapse, the lack of demonstration anchoring leads to undirected exploration that is less sample-efficient than CALM's constrained approach.

**QMIX-CALM achieves good reward** ($1.01 \pm 0.06$) while also ranking second in NGSIM agreement, making it a strong candidate for applications requiring both human-likeness and task performance.

**DAgger achieves the lowest reward** ($0.44 \pm 0.02$) among trained methods, reflecting its pure imitation objective. DAgger optimizes action matching rather than the task reward, and human drivers in the NGSIM dataset did not optimize for our specific reward function.

This trade-off is fundamental: methods that closely match human behavior inherit human sub-optimality with respect to the engineered reward, whereas methods that optimize rewards may deviate from human-like behavior. CALM and QMIX-CALM achieve a favorable balance using human demonstrations as constraints rather than objectives.

### E. Driving Safety Evaluation

In addition to policy-level metrics, we evaluated each trained policy on transportation-relevant safety metrics by running 20 evaluation episodes per checkpoint (100 in total per method) in the MultiExit scenario. Table IV lists the collision rate, exit success rate, average speed, and proximity events.

Table IV shows that CALM achieved the best driving performance across all safety metrics. CALM's exit success rate ($33.3\%$) was significantly higher than those of DAgger ($7.7\%$) and GAIL ($6.7\%$), demonstrating that reward optimization enables task completion, whereas the BC constraint preserves behavioral diversity. CALM also maintained the highest average speed (25.8 m/s, close to the highway speed limit of 33.3 m/s) with the lowest variance ($\pm 1.2$ m/s), indicating consistent and efficient driving.

The proximity event metric reveals a stark contrast: DAgger and GAIL policies produce over 2500 close-proximity steps per episode, compared with only 42.5 for CALM. These imitation-focused methods learn cautious and slow behavior from human demonstrations (avg. speed 8–11 m/s), which paradoxically increases time spent near other vehicles. CALM's higher speed and more decisive lane-changing behavior reduce exposure to proximity risks.

All methods achieved a zero collision rate because the SUMO safety model prevented physical collisions via forced braking. Therefore, the proximity and speed metrics are more informative discriminators of driving quality in this simulation environment.

TABLE IV: Safety Metrics (20 eval episodes $\times$ 5 seeds per method)

| Method | Collision Rate (%) | Exit Success Rate (%) | Avg. Speed (m/s) | Proximity Events/ep |
|---|---|---|---|---|
| CALM | **0.0** | **33.3** | $\mathbf{25.8 \pm 1.2}$ | **42.5** |
| QMIX-CALM | 0.0 | 26.7 | $19.7 \pm 6.9$ | 220.9 |
| Entropy-only | 0.0 | 20.0 | $16.3 \pm 6.1$ | 685.4 |
| DAgger | 0.0 | 7.7 | $11.0 \pm 3.6$ | 3150.5 |
| GAIL | 0.0 | 6.7 | $8.1 \pm 2.2$ | 2563.8 |

Collision rate: fraction of episodes with $\geq 1$ vehicle teleportation. Exit success: Fraction of exit-assigned agents reaching an exit ramp. Proximity events: simulation steps with $< 5$ m inter-vehicle distance.

TABLE V: Hyperparameter sensitivity: last-50-episode average reward across $\lambda_0$ (initial KL weight) and $\delta$ (decay rate). Each cell reports mean $\pm$ std over five seeds. Bold denotes the best configuration; the default is marked with †.

| | Decay rate $\delta$ | | | |
|---|---|---|---|---|
| $\lambda_0$ | 0.99 | 0.995 | 0.999 | 1.0 |
| 0.5 | $\mathbf{1.39 \pm 0.07}$ | $1.34 \pm 0.06$ | $1.32 \pm 0.04$ | $1.35 \pm 0.03$ |
| 1.0 | $1.32 \pm 0.06$ | $1.30 \pm 0.08$ | $1.35 \pm 0.05$ | $1.34 \pm 0.03$ |
| 2.0 | $1.34 \pm 0.03$ | $1.31 \pm 0.03$ | $1.36 \pm 0.04^{\dagger}$ | $1.34 \pm 0.03$ |
| 5.0 | $1.33 \pm 0.03$ | $1.32 \pm 0.04$ | $1.33 \pm 0.03$ | $1.33 \pm 0.04$ |

### F. Hyperparameter Sensitivity

CALM introduces two key hyperparameters: the initial KL penalty weight $\lambda_0$ and its exponential decay rate $\delta$, where $\lambda(t) = \lambda_0 \cdot \delta^t$. To assess the sensitivity, we swept $\lambda_0 \in \{0.5, 1.0, 2.0, 5.0\}$ and $\delta \in \{0.99, 0.995, 0.999, 1.0\}$, training each of the 16 configurations with five seeds (80 runs total, 300 episodes each). Table V reports the last-50-episode average reward.

The results demonstrate that CALM is robust to hyperparameter selection: all 16 configurations achieved rewards between 1.30 and 1.39, a variation of less than $7\%$. The default configuration ($\lambda_0 = 2.0$, $\delta = 0.999$) achieved $1.36 \pm 0.04$,




(a) NGSIM action agreement (%). (b) Normalized action entropy. (c) Final training reward.

Fig. 2: Comparison of mode collapse mitigation methods across three metrics. Error bars show $\pm 1$ standard deviation across 5 seeds.




Fig. 3: Statistical significance heatmap ($-\log_{10} p$) for pairwise Welch's $t$-tests on NGSIM agreement. Darker cells indicate stronger statistical differences.

ranking second among all configurations. Notably, the best-performing configuration ($\lambda_0 = 0.5$, $\delta = 0.99$) used a weaker initial constraint with a faster decay, suggesting that even light demonstration anchoring suffices to prevent mode collapse. At the other extreme, $\delta = 1.0$ (no decay) maintained a constant KL penalty throughout training and still achieved competitive performance (1.33–1.35), indicating that the decay schedule is beneficial but not critical.

Stronger initial constraints ($\lambda_0 = 5.0$) slightly compress the reward range across decay rates (1.32–1.33) because the dominant KL term leaves less room for reward optimization early in training. This confirms the design intuition behind CALM: a moderate $\lambda_0$ with gradual decay provides the best balance between behavioral anchoring and reward maximization.

## VII. Discussion

### A. Key Findings: Human-Anchored Diversity, Not Human Mimicry

The central finding of this study is that *human-anchored* diversity and *human-mimicking* diversity are not the same, and the difference is measurable at the transportation level. DAgger attains the highest NGSIM action agreement (45.3%) and an entropy (0.63) that matches the NGSIM empirical distribution ($\approx 0.65$) almost exactly; on these two policy-level metrics, it is the most "human-like" method in our study. Yet Table IV tells a different story: DAgger produces 3150.5 close-proximity events per episode, compared with only 42.5 for CALM—a nearly two-order-of-magnitude gap. The mechanism is direct: NGSIM drivers in the Interstate 80 segment are cautious and slow (avg. speed $\sim$11 m/s in a congested bottleneck), and blind mimicry inherits that caution along with the elevated exposure it implies. CALM's higher entropy ($0.88 > 0.65$) is therefore not "over-exploration" but task-conditioned redistribution of mass: the BC prior anchors the action marginals so that the policy never collapses, while the decaying KL schedule allows the reward to lift mass onto decisive lane changes and confident speed selection (25.8 m/s avg., 33.3% exit success). In short, CALM reproduces the *structure* of human action diversity without importing the sub-optimality of a specific congested dataset.

Against that reframe, the rest of the comparison falls into place. QMIX-CALM sits between DAgger and CALM (40.1% agreement, 1.01 reward, entropy 0.70), and the monotonic mixer appears well suited to constrained IL+RL because it admits per-agent KL penalties without disturbing centralized credit assignment. The baselines that omit demonstration anchoring tell a complementary story: the entropy-only baseline collapses to near-zero entropy (0.06), despite an explicit diversity bonus and a six-value coefficient sweep (Table III), confirming that generic entropy regularization is insufficient when the reward signal dominates. MASAC's automatic temperature tuning sustains high entropy (0.93), but fails on a different axis entirely: its NGSIM agreement (24.8%$\pm$12.7%) has roughly 10$\times$ CALM's seed-to-seed variance ($\pm$1.2%). The distinction between *undirected diversity* (SAC) and *structured diversity* (CALM) is therefore not rhetorical; it is visible in the variance of the learned policies. Preventing collapse is necessary but not sufficient; the diversity that remains must be anchored to human demonstrations to be both reliable and safe.

### B. Implications for Cooperative Driving

These findings have several practical implications for deploying MARL-based cooperative driving systems. First, the correct safety argument is not that autonomous vehicles should mimic human actions, but that they should inherit the *shape* of the human action distribution so that their behavior remains predictable to surrounding drivers while still being improvable under an engineered reward. The mode collapse observed in

unconstrained MADDPG ($99.7\%$ "Maintain") would manifest in practice as vehicles that refuse to change lanes or adjust speed, thereby creating disruptions exactly at the exit ramps where coordination matters most; and the catastrophic failure of the entropy-only baseline and the high seed-to-seed variance of MASAC show that neither generic entropy nor learned temperatures are substitutes for a demonstration prior. Therefore, BC pre-training on a modest human dataset, such as NGSIM, is not an optional enhancement but a crucial inductive bias.

Second, the choice between DAgger and CALM is context-dependent, but the conventional framing of that trade-off is misleading: it is not "human-likeness vs. task reward" but "human-mimicking vs. human-anchored." In mixed-autonomy traffic, where matching the action distribution of the surrounding human drivers is the explicit objective (e.g., a human-study evaluation), DAgger's $45.3\%$ agreement is the right operating point. In any deployment where safety and task completion matter—that is, in every real deployment—CALM's combination of preserved diversity, highest reward ($1.35$), and the lowest proximity-event rate in our study is the more defensible choice. QMIX-CALM offers a practical middle ground with strong agreement ($40.1\%$) and reward ($1.01$), and its value-decomposition architecture offers better scalability to larger agent populations.

### C. Relation to Prior Work

This study extends our prior work on cooperative highway exit coordination [38], which introduced the Dec-POMDP formulation, hybrid reward function, and first comparison of MADDPG and QMIX for multi-exit scenarios. The previous study reported $54.83\%$ NGSIM action agreement for unconstrained MADDPG, which is consistent with the $54.8\%$ reported herein; however, it did not analyze action distributions in depth. The present work reveals that this seemingly high agreement is an artifact of mode collapse (Table I), thus motivating the CALM algorithm as a principled solution to this problem. The two studies shared the same simulation environment and NGSIM validation pipeline, ensuring consistency across the results.

## VIII. Conclusion

Mode collapse is a critical barrier to the deployment of MARL in cooperative autonomous driving. This study presented CALM, a hybrid imitation-reinforcement learning algorithm that prevents this degeneracy through behavioral-cloning pre-training followed by RL fine-tuning under a decaying KL-divergence constraint anchored to the BC prior, for which we derived KL and entropy bounds that formalize how the constraint preserves action diversity during training. Our 25-run statistical study on cooperative highway exit coordination, validated against the NGSIM naturalistic driving dataset, yielded three key findings.

1) **DAgger achieves the highest human-likeness** with $45.3\% \pm 0.9\%$ NGSIM action agreement ($p < 0.001$), making it the preferred choice when matching human behavior is paramount.
2) **CALM achieves the highest task reward** ($1.35 \pm 0.05$) while maintaining high action diversity (entropy $= 0.88$) and the best safety profile ($33.3\%$ exit success, lowest proximity events), demonstrating that the BC constraint prevents mode collapse while simultaneously improving both task performance and driving safety.
3) **Entropy regularization alone is insufficient**: the entropy-only baseline collapsed to near-zero entropy ($0.06$) despite explicit diversity incentives, and MASAC's automatic temperature tuning sustained high entropy ($0.93$) only at the cost of wildly unstable agreement ($\pm 12.7\%$ vs. CALM's $\pm 1.2\%$), confirming that the resulting diversity must be structured by human demonstrations rather than merely enforced by an entropy bonus. Together these results establish that incorporating human behavioral priors through constrained learning is essential for MARL policies that are simultaneously diverse, human-like, and safe.

Future work will address several open challenges: (1)scaling CALM to larger agent populations ($> 100$ vehicles) using hierarchical or mean-field approximations, (2)transferring learned policies from simulation to real vehicles via domain randomization and sim-to-real techniques, (3)extending the theoretical analysis to heterogeneous agent populations with varying objectives, and (4)investigating online adaptation mechanisms that allow policies to adjust to regional driving norms.

The code and trained models are available at https://github.com/mjeragh/VANET.

## Acknowledgments

This study was supported by Kuwait University.

## References

[1] J. Guanetti, Y. Kim, and F. Borrelli, "Control of connected and automated vehicles: State of the art and future challenges," *Annual Reviews in Control*, vol. 45, pp. 18–40, 2018.

[2] Z. Wang, G. Wu, and M. J. Barth, "Cooperative autonomous driving for traffic congestion avoidance through vehicle-to-vehicle communications," *IEEE Vehicular Technology Magazine*, vol. 17, no. 1, pp. 60–67, 2021.

[3] R. Lowe, Y. Wu, A. Tamar, J. Harb, O. P. Abbeel, and I. Mordatch, "Multi-agent actor-critic for mixed cooperative-competitive environments," *Advances in Neural Information Processing Systems*, vol. 30, 2017.

[4] T. Rashid, M. Samvelyan, C. Schroeder, G. Farquhar, J. Foerster, and S. Whiteson, "QMIX: Monotonic value function factorisation for decentralised multi-agent reinforcement learning," in *International Conference on Machine Learning*. PMLR, 2018, pp. 4295–4304.

[5] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine, "Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor," in *International Conference on Machine Learning*. PMLR, 2018, pp. 1861–1870.

[6] Z. Ahmed, N. Le Roux, M. Norouzi, and D. Schuurmans, "Understanding the impact of entropy on policy optimization," in *International Conference on Machine Learning*. PMLR, 2019, pp. 151–160.

[7] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine, "Diversity is all you need: Learning skills without a reward function," in *International Conference on Learning Representations*, 2019.

[8] H. Tang, R. Houthooft, D. Foote, A. Stooke, X. Chen, Y. Duan, J. Schulman, F. De Turck, and P. Abbeel, "#exploration: A study of count-based exploration for deep reinforcement learning," *Advances in Neural Information Processing Systems*, vol. 30, 2017.

[9] S. Ross, G. Gordon, and D. Bagnell, "A reduction of imitation learning and structured prediction to no-regret online learning," in *Proceedings of the fourteenth international conference on artificial intelligence and statistics*. JMLR Workshop and Conference Proceedings, 2011, pp. 627–635.

[10] J. Ho and S. Ermon, "Generative adversarial imitation learning," *Advances in Neural Information Processing Systems*, vol. 29, 2016.

[11] D. A. Pomerleau, "Efficient training of artificial neural networks for autonomous navigation," *Neural Computation*, vol. 3, no. 1, pp. 88–97, 1991.

[12] K. Zhang, Z. Yang, and T. Basar, "Multi-agent reinforcement learning: A selective overview of theories and algorithms," *Handbook of Reinforcement Learning and Control*, pp. 321–384, 2021.

[13] M. Bojarski, D. Del Testa, D. Dworakowski, B. Firner, B. Flepp, P. Goyal, L. D. Jackel, M. Monfort, U. Muller, J. Zhang *et al.*, "End to end learning for self-driving cars," *arXiv preprint arXiv:1604.07316*, 2016.

[14] F. Codevilla, M. Müller, A. López, V. Koltun, and A. Dosovitskiy, "End-to-end driving via conditional imitation learning," in *IEEE International Conference on Robotics and Automation*, 2018, pp. 4693–4700.

[15] A. Kuefler, J. Morton, T. Wheeler, and M. Kochenderfer, "Imitating driver behavior with generative adversarial networks," in *IEEE Intelligent Vehicles Symposium*, 2017, pp. 204–211.

[16] R. P. Bhattacharyya, D. J. Phillips, B. Wulfe, J. Morton, A. Kuefler, and M. J. Kochenderfer, "Modeling human driving behavior through generative adversarial imitation learning," *IEEE Transactions on Intelligent Transportation Systems*, vol. 24, no. 3, pp. 2874–2887, 2022.

[17] T. Hester, M. Vecerik, O. Pietquin, M. Lanctot, T. Schaul, B. Piot, D. Horgan, J. Quan, A. Sendonaris, I. Osband *et al.*, "Deep Q-learning from demonstrations," in *AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, 2018.

[18] A. Rajeswaran, V. Kumar, A. Gupta, G. Vezzani, J. Schulman, E. Todorov, and S. Levine, "Learning complex dexterous manipulation with deep reinforcement learning and demonstrations," in *Robotics: Science and Systems*, 2018.

[19] S. Fujimoto, D. Meger, and D. Precup, "Off-policy deep reinforcement learning without exploration," in *International Conference on Machine Learning*. PMLR, 2019, pp. 2052–2062.

[20] A. Nair, M. Dalal, A. Gupta, and S. Levine, "Accelerating online reinforcement learning with offline datasets," *arXiv preprint arXiv:2006.09359*, 2020.

[21] J. Chen, Z. Xu, and M. Tomizuka, "Cooperative driving at unsignalized intersections using tree search," *IEEE Transactions on Intelligent Transportation Systems*, vol. 21, no. 11, pp. 4563–4571, 2020.

[22] T. Chu, J. Wang, L. Codecà, and Z. Li, "Multi-agent deep reinforcement learning for large-scale traffic signal control," *IEEE Transactions on Intelligent Transportation Systems*, vol. 21, no. 3, pp. 1086–1095, 2019.

[23] Z. Shou and X. Di, "Multi-agent coordination for on-ramp merging with deep reinforcement learning," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 9, pp. 14 711–14 721, 2022.

[24] C. Letter and L. Elefteriadou, "Efficient control of fully automated connected vehicles at freeway merge segments," *Transportation Research Part C: Emerging Technologies*, vol. 80, pp. 190–205, 2017.

[25] M. Zhou, Y. Yu, and X. Qu, "Multi-agent reinforcement learning for cooperative lane changing of connected and autonomous vehicles in mixed traffic," *Autonomous Intelligent Systems*, vol. 2, no. 1, pp. 1–14, 2022.

[26] C. Yu, A. Velu, E. Vinitsky, J. Gao, Y. Wang, A. Bayen, and Y. Wu, "The surprising effectiveness of ppo in cooperative multi-agent games," *Advances in Neural Information Processing Systems*, vol. 35, pp. 24 611–24 624, 2022.

[27] A. Haydari and Y. Yilmaz, "Deep reinforcement learning for intelligent transportation systems: A survey," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 1, pp. 11–32, 2020.

[28] L. Li, Y. Lv, and F.-Y. Wang, "Reinforcement learning for autonomous driving: A survey," *IEEE Transactions on Intelligent Transportation Systems*, vol. 24, no. 6, pp. 5921–5940, 2023.

[29] Federal Highway Administration, "NGSIM – next generation simulation," U.S. Department of Transportation, Tech. Rep., 2006, dataset: Interstate 80 Freeway, Emeryville, CA.

[30] J. Colyar and J. Halkias, "US highway 101 dataset," in *Federal Highway Administration (FHWA), Tech. Rep. FHWA-HRT-07-030*, 2007.

[31] C. Thiemann, M. Treiber, and A. Kesting, "Estimating acceleration and lane-changing dynamics from next generation simulation trajectory data," *Transportation Research Record*, vol. 2088, no. 1, pp. 90–101, 2008.

[32] M. Montanino and V. Punzo, "Trajectory data reconstruction and simulation-based validation against macroscopic traffic patterns," *Transportation Research Part B: Methodological*, vol. 80, pp. 82–106, 2015.

[33] Z. Wu, Z. Sun, K. Zhang, and L. Chen, "Human-like autonomous driving: A survey," *IEEE Transactions on Intelligent Vehicles*, vol. 8, no. 6, pp. 3538–3557, 2023.

[34] F. A. Oliehoek and C. Amato, "A concise introduction to decentralized pomdps," *Springer Briefs in Intelligent Systems*, 2016.

[35] P. A. Lopez, M. Behrisch, L. Bieker-Walz, J. Erdmann, Y.-P. Flötteröd, R. Hilbrich, L. Lücken, J. Rummel, P. Wagner, and E. Wießner, "Microscopic traffic simulation using SUMO," in *21st International Conference on Intelligent Transportation Systems (ITSC)*. IEEE, 2018, pp. 2575–2582.

[36] T. M. Cover and J. A. Thomas, *Elements of Information Theory*, 2nd ed. John Wiley & Sons, 2006.

[37] P. Christodoulou, "Soft actor-critic for discrete action settings," *arXiv preprint arXiv:1910.07207*, 2019.

[38] M. Jeragh and E. Alrashed, "Multi-agent reinforcement learning for highway exit coordination in connected vehicles," *Journal of Intelligent Transportation Systems*, 2026, under review, Manuscript #269158218.