

Introduction to Web Applications

A browser interface for the pet database

Gregory S. DeLozier, PhD

The Pet Application

- Requests select Python functions.
- Templates produce browser pages.
- Forms supply values for database operations.
- Saved records survive the server stopping.

Running Flask

From a working copy of `chapter-03-intro-to-web-apps/code`:

```
flask run
```

```
http://127.0.0.1:5000/pets
```

The supplied `pets.db` holds the existing records.

Reading a URL

Uniform Resource Locator (URL)

```
http://127.0.0.1:5000/pets
```

Part	Meaning
http	Protocol scheme
127.0.0.1	This computer’s loopback address
5000	Port
/pets	Requested path

A Request Calls a Function

```
@app.route("/bye", methods=["GET"])  
def get_bye():  
    return "Bye!"
```

GET /bye receives Bye!

A Value in the Path

```
@app.route("/hello/<name>", methods=["GET"])  
def get_hello(name="world"):  
    return render_template("hello.html", name=name)
```

```
<body>Hello, {{ name }}! (from the template)</body>
```

/hello/Ada displays **Hello, Ada! (from the template)**

Loading the Pet List

```
cursor = connection.execute("select * from pet")  
rows = cursor.fetchall()  
return render_template("pets.html", pets=rows)
```

```
(id, name, kind, age, food)
```

Each returned tuple becomes one displayed row.

A Template Builds the Table

```
{% for pet in pets %}  
<tr>  
    {% for item in pet %}  
    <td>{{ item }}</td>  
    {% endfor %}  
</tr>  
{% endfor %}
```

{% ... %} controls the loop. {{ ... }} inserts a value.

Opening and Submitting a Form

Request	Function	Result
GET /create	get_create	Blank form
POST /create	post_create	Saved pet, then redirect

Same path. Different methods and work.

Named Inputs Become Form Values

```
<form action="/create" method="post">  
  <input name="name"/>  
  <input name="age"/>  
  <button type="submit">Create</button>  
</form>
```

```
data = dict(request.form)
```


`data["age"]` arrives as a string.

Saving the New Pet

```
connection.execute(  
    "INSERT INTO pet(name, kind, age, food) "  
    "VALUES (?, ?, ?, ?)",  
    (data["name"], data["kind"],  
     data["age"], data["food"])  
)  
connection.commit()
```

SQLite supplies the identifier.

After the Save



Editing Pet 3


```
GET /update/3
```

```
cursor.execute("SELECT * FROM pet WHERE id = ?", (id,))
```

```
<form action="/update/{{data['id']}}" method="post">  
  <input name="name" value="{{data['name']}}"/>
```

The loaded value becomes the form's starting value.

The Persistence Cycle in an Edit



Deleting a Pet

```
GET /delete/3
```

```
connection.execute("DELETE FROM pet WHERE id = ?", (id,))  
connection.commit()  
return redirect(url_for("get_pets"))
```

The refreshed list shows the remaining pets.

Tracing an Application Operation

Request: Which path and method?

Route: Which values and database operation?

Response: A page, a redirect, or an error?

The database preserves state between requests.