

**References:** Chapter 17 of Geron's book. For 1-Dim plots, Keras tutorial :

<https://www.tensorflow.org/tutorials/generative/autoencoder>

This file trains a VAE with the instances of the normal digits in the training data.

Then, it measures the reconstruction loss for the digits in the test data.

The reconstruction loss for the instances of the abnormal digits in the test data is higher.

A threshold is determined based on the distribution of the reconstruction losses of the normal training data (threshold = mean + 2.5\*std of this distribution).

Then, if the reconstruction loss of a digit in the test data is higher than this threshold, it is classified as abnormal.

By comparing with the known labels of test data (with T for normal digit(s) and F for abnormal digit(s)), the confusion matrix and the accuracy is calculated.

```
import sklearn
import tensorflow as tf
from tensorflow import keras
import numpy as np

import matplotlib as mpl
import matplotlib.pyplot as plt
mpl.rc('axes', labelsize=14)
mpl.rc('xtick', labelsize=12)
mpl.rc('ytick', labelsize=12)

from sklearn.metrics import accuracy_score, precision_score, recall_score, confusion_matrix
from sklearn.model_selection import train_test_split
```

- Loading the MNIST data and forming arrays of the normal training data, the validation data (normal and abnormal) and the test data (normal and abnormal)**
- ▼

```
#Labels
# 0 T-shirt/top
# 1 Trouser
# 2 Pullover
# 3 Dress
# 4 Coat
# 5 Sandal
# 6 Shirt
# 7 Sneaker
```

```
# 8 Bag
# 9 Ankle boot
```

```
nl1 = 9
nl2 = 9
abn1 = 3
abn2 = 3
```

```
(x_train_0, y_train_0), (x_test, y_test) = keras.datasets.fashion_mnist.load_data()
x_train_0 = x_train_0.astype(np.float32) / 255
x_test = x_test.astype(np.float32) / 255

train_size = x_train_0.shape[0] * 9 // 10

x_train, x_valid, y_train, y_valid = train_test_split(x_train_0, y_train_0, train_size = train_size)

normal_data = x_train[(y_train == nl1) | (y_train == nl2)]           # Normal training data (Normal)
normal_labels = y_train[(y_train == nl1) | (y_train == nl2)]

valid_data = x_valid[(y_valid == abn1) | (y_valid == abn2) | (y_valid == nl1) | (y_valid == nl2)]
valid_labels = y_valid[(y_valid == abn1) | (y_valid == abn2) | (y_valid == nl1) | (y_valid == nl2)]

test_data = x_test[(y_test == abn1) | (y_test == abn2) | (y_test == nl1) | (y_test == nl2)]
test_labels = y_test[(y_test == abn1) | (y_test == abn2) | (y_test == nl1) | (y_test == nl2)]

test_labels_T_F = np.where((test_labels == nl1) | (test_labels == nl2), True, False)
# Array of T and F, T where test digits are normal and F where test digits are abnormal

valid_labels_T_F = np.where((valid_labels == nl1) | (valid_labels == nl2), True, False)
# Array of T and F, T where test digits are normal and F where test digits are abnormal
```

```
Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/train-32768/29515 [=====] - 0s 0us/step
40960/29515 [=====] - 0s 0us/step
Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/train-26427392/26421880 [=====] - 0s 0us/step
26435584/26421880 [=====] - 0s 0us/step
Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/t10k-16384/5148 [=====]
Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/t10k-4423680/4422102 [=====] - 0s 0us/step
4431872/4422102 [=====] - 0s 0us/step
```



```
normal_data.shape, normal_labels.shape, valid_data.shape, valid_labels.shape, test_data.shape

((5388, 28, 28), (5388,), (1188, 28, 28), (1188,), (2000, 28, 28), (2000,))
```

```
normal_test_data = test_data[(test_labels == nl1) | (test_labels == nl2)]           # The normal
abnormal_test_data = test_data[(test_labels == abn1) | (test_labels == abn2)]           # The abnormal
```

```

normal_test_labels = test_labels[(test_labels == nl1) | (test_labels == nl2)]      # Their
abnormal test labels = test labels[(test labels == abn1) | (test labels == abn2)]  # Their
normal_test_data.shape, abnormal_test_data.shape

((1000, 28, 28), (1000, 28, 28))

normal_valid_data = valid_data[(valid_labels == nl1) | (valid_labels == nl2)]      # Th
abnormal_valid_data = valid_data[(valid_labels == abn1) | (valid_labels == abn2)]  # Th
normal_valid_labels = valid_labels[(valid_labels == nl1) | (valid_labels == nl2)]  # Th
abnormal_valid_labels = valid_labels[(valid_labels == abn1) | (valid_labels == abn1)] # Th

normal_valid_data.shape, abnormal_valid_data.shape

((612, 28, 28), (576, 28, 28))

```

## ▼ Building and training the network

```

K = keras.backend
# def rounded_accuracy(y_true, y_pred):
#   return keras.metrics.binary_accuracy(tf.round(y_true), tf.round(y_pred))

# For details please see Geron's book. Uses the reparametrization trick to do stochastic
# sampling from the MVN distribution, while allowing the 2 parallel layers containing the
# means and stds of the MVN distribution for each dimension to be trained via
# backpropogation of the error signal.
class Sampling(keras.layers.Layer):
    def call(self, inputs):
        mean, log_var = inputs
        return K.random_normal(tf.shape(log_var)) * K.exp(log_var / 2) + mean

# For details please see Geron's book.
codings_size = 16    # The number of dimensions of the MVN distribution in the sampling layer

inputs = keras.layers.Input(shape=[28, 28])
z = keras.layers.Flatten()(inputs)
z = keras.layers.Dense(256, activation="selu")(z)
z = keras.layers.Dense(128, activation="selu")(z)
z = keras.layers.Dense(64, activation="selu")(z)

# Parallel layers at the end of the encoder for means
# and standard deviations of the Multivariate Normal (MVN) distribution
# in the dimensions of the coding size (here 32).
codings_mean = keras.layers.Dense(codings_size)(z)
codings_log_var = keras.layers.Dense(codings_size)(z)

# Sampling layer at the end of the encoder

```

```

codings = Sampling()([codings_mean, codings_log_var])
variational_encoder = keras.models.Model(
    inputs=[inputs], outputs=[codings_mean, codings_log_var, codings])

decoder_inputs = keras.layers.Input(shape=[codings_size])
x = keras.layers.Dense(64, activation="selu")(decoder_inputs)
x = keras.layers.Dense(128, activation="selu")(x)
x = keras.layers.Dense(256, activation="selu")(x)
x = keras.layers.Dense(28 * 28, activation="sigmoid")(x)
outputs = keras.layers.Reshape([28, 28])(x)
variational_decoder = keras.models.Model(inputs=[decoder_inputs], outputs=[outputs])

_, _, codings = variational_encoder(inputs)
reconstructions = variational_decoder(codings)
variational_ae = keras.models.Model(inputs=[inputs], outputs=[reconstructions])

# The latent loss function
latent_loss = -0.5 * K.sum(
    1 + codings_log_var - K.exp(codings_log_var) - K.square(codings_mean),
    axis=-1)

# Add the latent loss to the reconstruction loss
variational_ae.add_loss(K.mean(latent_loss) / 784.)

# For the reconstruction loss binary cross-entropy loss is used.
# For details please see Chapter 17 of Geron's book (Stacked AE and VAE sections)
variational_ae.compile(loss="binary_crossentropy", optimizer="rmsprop")

checkpoint_cb = keras.callbacks.ModelCheckpoint("VAE_model", monitor="val_loss", save_best_on

history = variational_ae.fit(normal_data, normal_data, epochs=100, batch_size=128, callbacks=
    validation_data=(normal_valid_data, normal_valid_data), shuffle=

```

```

Epoch 74/100
43/43 [=====] - 0s 9ms/step - loss: 0.2864 - val_loss: 0.294
Epoch 75/100
43/43 [=====] - 0s 9ms/step - loss: 0.2860 - val_loss: 0.290
Epoch 76/100
39/43 [=====>...] - ETA: 0s - loss: 0.2857INFO:tensorflow:Assets
43/43 [=====] - 3s 75ms/step - loss: 0.2858 - val_loss: 0.28
Epoch 77/100
43/43 [=====] - 0s 9ms/step - loss: 0.2859 - val_loss: 0.290
Epoch 78/100
43/43 [=====] - 0s 9ms/step - loss: 0.2860 - val_loss: 0.291
Epoch 79/100
43/43 [=====] - 0s 9ms/step - loss: 0.2857 - val_loss: 0.297
Epoch 80/100
43/43 [=====] - 0s 9ms/step - loss: 0.2856 - val_loss: 0.290
Epoch 81/100
43/43 [=====] - 0s 10ms/step - loss: 0.2855 - val_loss: 0.290
Epoch 82/100
43/43 [=====] - 0s 9ms/step - loss: 0.2854 - val_loss: 0.289
Epoch 83/100

```

```
43/43 [=====] - 0s 9ms/step - loss: 0.2853 - val_loss: 0.288
Epoch 84/100
43/43 [=====] - 0s 9ms/step - loss: 0.2854 - val_loss: 0.288
Epoch 85/100
43/43 [=====] - 0s 9ms/step - loss: 0.2853 - val_loss: 0.288
Epoch 86/100
43/43 [=====] - 0s 9ms/step - loss: 0.2851 - val_loss: 0.292
Epoch 87/100
43/43 [=====] - 0s 9ms/step - loss: 0.2849 - val_loss: 0.291
Epoch 88/100
43/43 [=====] - 0s 9ms/step - loss: 0.2852 - val_loss: 0.292
Epoch 89/100
39/43 [=====>...] - ETA: 0s - loss: 0.2850INFO:tensorflow:Assets
43/43 [=====] - 3s 67ms/step - loss: 0.2849 - val_loss: 0.28
Epoch 90/100
38/43 [=====>....] - ETA: 0s - loss: 0.2854INFO:tensorflow:Assets
43/43 [=====] - 3s 74ms/step - loss: 0.2850 - val_loss: 0.28
Epoch 91/100
43/43 [=====] - 0s 9ms/step - loss: 0.2847 - val_loss: 0.290
Epoch 92/100
43/43 [=====] - 0s 9ms/step - loss: 0.2846 - val_loss: 0.295
Epoch 93/100
43/43 [=====] - 0s 9ms/step - loss: 0.2847 - val_loss: 0.296
Epoch 94/100
43/43 [=====] - 0s 9ms/step - loss: 0.2847 - val_loss: 0.288
Epoch 95/100
43/43 [=====] - 0s 9ms/step - loss: 0.2845 - val_loss: 0.290
Epoch 96/100
43/43 [=====] - 0s 9ms/step - loss: 0.2843 - val_loss: 0.289
Epoch 97/100
43/43 [=====] - 0s 9ms/step - loss: 0.2844 - val_loss: 0.287
Epoch 98/100
43/43 [=====] - 0s 9ms/step - loss: 0.2843 - val_loss: 0.290
Epoch 99/100
41/43 [=====>..] - ETA: 0s - loss: 0.2840INFO:tensorflow:Assets
43/43 [=====] - 3s 78ms/step - loss: 0.2839 - val_loss: 0.28
Epoch 100/100
```

```
plt.plot(history.history["loss"], label="Training Loss")
plt.plot(history.history["val_loss"], label="Validation Loss")
plt.legend()
```

<matplotlib.legend.Legend at 0x7fec963e050>



```
model = variational_ae
model.summary(expand_nested=True, show_trainable=True)
```

model_1 (Functional)	(None, 28, 28)	243920	[ 'model[0][2]' ]	
input_2 (InputLayer)	[(None, 16)]	0	[ ]	
dense_5 (Dense)	(None, 64)	1088	[ ]	
dense_6 (Dense)	(None, 128)	8320	[ ]	
dense_7 (Dense)	(None, 256)	33024	[ ]	
dense_8 (Dense)	(None, 784)	201488	[ ]	
reshape (Reshape)	(None, 28, 28)	0	[ ]	
flatten (Flatten)	(None, 784)	0	[ 'input_1[0][0]' ]	
dense (Dense)	(None, 256)	200960	[ 'flatten[0][0]' ]	
dense_1 (Dense)	(None, 128)	32896	[ 'dense[0][0]' ]	
dense_2 (Dense)	(None, 64)	8256	[ 'dense_1[0][0]' ]	
dense_4 (Dense)	(None, 16)	1040	[ 'dense_2[0][0]' ]	
tf.__operators__.add (TFOpLambda	(None, 16)	0	[ 'dense_4[0][0]' ]	da)
tf.math.exp (TFOpLambda)	(None, 16)	0	[ 'dense_4[0][0]' ]	
dense_3 (Dense)	(None, 16)	1040	[ 'dense_2[0][0]' ]	
tf.math.subtract (TFOpLambda)	(None, 16)	0	[ 'tf.__operators__.a'	'tf.math.exp[0][0]' ]
tf.math.square (TFOpLambda)	(None, 16)	0	[ 'dense_3[0][0]' ]	
tf.math.subtract_1 (TFOpLambda	(None, 16)	0	[ 'tf.math.subtract[0'	)
tf.math.reduce_sum (TFOpLambda	(None, )	0	[ 'tf.math.subtract_1'	)
tf.math.multiply (TFOpLambda)	(None, )	0	[ 'tf.math.reduce_sum'	
tf.math.reduce_mean (TFOpLambd	(None, )	0	[ 'tf.math.multiply[0'	a)

```

tf.math.truediv (TFOpLambda)      ()           0           ['tf.math.reduce_mean'
add_loss (AddLoss)              ()           0           ['tf.math.truediv[0]']

=====
Total params: 488,112
Trainable params: 488,112
Non-trainable params: 0

```



```

model_encoder = variational_encoder
# model_encoder.summary(expand_nested=True, show_trainable=True)

model_decoder = variational_decoder
# model_decoder.summary(expand_nested=True, show_trainable=True)

model_layers = np.array(model.layers)
n_layers = model_layers.shape[0]
# np.concatenate((np.arange(n_layers).reshape(n_layers,1), model_layers.reshape(n_layers,1)),

```

## The original and reconstructed images for the first 30 instances of the normal training data, validation data, normal validation data, abnormal validation data, test data, normal test data, and abnormal test data

```

def plot_image(image):
    plt.imshow(image, cmap="binary")
    plt.axis("off")

def show_reconstructions(model, images, n_images=5):
    reconstructions = model.predict(images[:n_images])
    fig = plt.figure(figsize=(n_images * 1.5, 3))
    for image_index in range(n_images):
        plt.subplot(2, n_images, 1 + image_index)
        plot_image(images[image_index])
        plt.subplot(2, n_images, 1 + n_images + image_index)
        plot_image(reconstructions[image_index])

show_reconstructions(variational_ae, normal_data, 30)
plt.show()

```



```
show_reconstructions(variational_ae, valid_data, 30)  
plt.show()
```



```
show_reconstructions(variational_ae, normal_valid_data, 30)  
plt.show()
```



```
show_reconstructions(variational_ae, abnormal_valid_data, 30)  
plt.show()
```



```
show_reconstructions(variational_ae, test_data, 30)  
plt.show()
```



```
show_reconstructions(variational_ae, normal_test_data, 30)  
plt.show()
```




```
show_reconstructions(variational_ae, abnormal_test_data, 30)  
plt.show()
```



## 1-Dim plot of pixels of the first normal test data

```
reconstructions_nl_test = variational_ae.predict(normal_test_data)
```


```
plt.figure(figsize=(25,7))
plt.plot(normal_test_data[0].ravel(), 'r')
plt.plot(reconstructions_nl_test[0].ravel(), 'g')
plt.fill_between(np.arange(28*28), reconstructions_nl_test[0].ravel(), normal_test_data[0].ravel(), 'b')
plt.legend(labels=["Input", "Reconstruction", "Error"])
plt.show()
```



### 1-D plot of pixels of the first abnormal test data

```
reconstructions_abn_test = variational_ae.predict(abnormal_test_data)
```


```
plt.figure(figsize=(25,7))
plt.plot(abnormal_test_data[0].ravel(), 'r')
plt.plot(reconstructions_abn_test[0].ravel(), 'g')
plt.fill_between(np.arange(28*28), reconstructions_abn_test[0].ravel(), normal_test_data[0].ravel(), 'b')
plt.legend(labels=["Input", "Reconstruction", "Error"])
plt.show()
```



## ▼ Distributions of the reconstruction losses and the calculation of the threshold.

## Distribution of the reconstruction losses of the normal training data

```
reconstructions = variational_ae.predict(normal_data)
train_loss = tf.keras.losses.mae(reconstructions.reshape(-1, 784), normal_data.reshape(-1, 784))
plt.figure(figsize=(10,5))
plt.hist(train_loss[None,:], bins=100)
threshold1 = np.mean(train_loss) + 2.5*np.std(train_loss)
plt.axvline(threshold1,c='g')
plt.xlabel("MAE reconstruction loss of the normal training data")
plt.ylabel("No of examples")
plt.show()
```



```
print("Mean: ", np.mean(train_loss))
print("Std: ", np.std(train_loss))
```

```
Mean:  0.06513636
Std:  0.016570596
```

```
threshold_train_mean_2_5_std = np.mean(train_loss) + 2.5*np.std(train_loss)
print("Threshold based on the mean of the training data MAE reconstruction losses + 2.5 std: ")
```

```
Threshold based on the mean of the training data MAE reconstruction losses + 2.5 std:  0.115
```


```
threshold1 = threshold_train_mean_2_5_std
```

## Distribution of the reconstruction losses of the abnormal validation data

```

reconstructions = variational_ae.predict(abnormal_valid_data)
abn_valid_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), abnormal_valid_data.reshape(-1,784))
plt.figure(figsize=(10,5))
plt.hist(abn_valid_loss[None, :], bins=100)
threshold2 = np.mean(abn_valid_loss) - np.std(abn_valid_loss)
plt.axvline(threshold2,c='cyan')
plt.axvline(threshold1,c='g')
plt.xlabel("MAE reconstruction loss of the abnormal validation data")
plt.ylabel("No of examples")
plt.show()

```



```
abnormal_valid_mean_loss = np.mean(abn_valid_loss)
```

```
abnormal_valid_mean_loss , np.std(abn_valid_loss)
```

```
(0.17413285, 0.030357046)
```

```
threshold2 = abnormal_valid_mean_loss - np.std(abn_valid_loss)
print("Threshold2: ", threshold2)
```

```
Threshold2:  0.1437758
```


## Distribution of the reconstruction losses of the normal validation data

```

reconstructions = variational_ae.predict(normal_valid_data)
nl_valid_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), normal_valid_data.reshape(-1,784))
plt.figure(figsize=(10,5))
plt.hist(nl_valid_loss[None, :], bins=100)
threshold3 = np.mean(nl_valid_loss) + np.std(nl_valid_loss)

```

```
plt.axvline(threshold3, c='magenta')
plt.axvline(threshold2, c='cyan')
plt.axvline(threshold1, c='g')
plt.xlabel("MAE reconstruction loss of the normal validation data")
plt.ylabel("No of examples")
plt.show()
```



```
normal_valid_mean_loss = np.mean(nl_valid_loss)
```

```
normal_valid_mean_loss , np.std(nl_valid_loss)
```

```
(0.06584041, 0.017228957)
```

```
threshold3 = normal_valid_mean_loss + np.std(nl_valid_loss)
print("Threshold3: ", threshold3)
```

```
Threshold3: 0.08306937
```

**Calculation of a preliminary threshold based on  $(\text{threshold2} + \text{threshold3}) / 2 = \text{Average of (mean} + \text{std of the distribution of the reconstruction losses of the normal validation data) and (mean} - \text{std of the distribution of the reconstruction losses of the abnormal validation data)}$**

```
Avg_of_threshold_2_3 = (threshold2 + threshold3)/2
print("Average of threshold 2 and 3: ", Avg_of_threshold_2_3)
```

```
Average of threshold 2 and 3: 0.11342258751392365
```

```
threshold4 = Avg_of_threshold_2_3
```

## Calculation of the threshold that gives the best accuracy on the validation data and set this as the threshold.

```

def predict(model, data, threshold):
    reconstructions = model.predict(data)
    loss = tf.keras.losses.mae(reconstructions.reshape(-1, 784), data.reshape(-1, 784))
    return tf.math.less(loss, threshold)

increment = (abnormal_valid_mean_loss - normal_valid_mean_loss)/100
thresholds = np.arange(normal_valid_mean_loss, abnormal_valid_mean_loss, increment)
thrs_size = thresholds.shape[0]
accuracies = np.zeros(thrs_size)
for i in range(thrs_size):
    preds = predict(variational_ae, valid_data, thresholds[i])
    accuracies[i] = accuracy_score(preds, valid_labels_T_F)
argmax = np.argmax(accuracies)
valid_data_best_threshold = thresholds[argmax]
print("The best threshold based on validation data: ", valid_data_best_threshold)

    The best threshold based on validation data:  0.11024031087756161

thr_acc = np.zeros((thrs_size, 2))
thr_acc[:, 0] = thresholds
thr_acc[:, 1] = accuracies
thr_acc[argmax-2:argmax+3]

array([[0.10807446, 0.97474747],
       [0.10915739, 0.97727273],
       [0.11024031, 0.98232323],
       [0.11132324, 0.97306397],
       [0.11240616, 0.97979798]])

```

threshold5 = valid\_data\_best\_threshold

threshold = threshold5

## Distribution of the reconstruction losses of all the validation data (normal and abnormal)


The blue line is threshold4 (= the average of threshold3 [magenta] and threshold2 [cyan]).

The red line is the threshold that gives the best accuracy for the validation data.

```

reconstructions = variational_ae.predict(valid_data)
valid_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), valid_data.reshape(-1,784))
plt.figure(figsize=(20,5))
plt.hist(valid_loss[None, :], bins=100)
plt.axvline(threshold, c='r')
plt.axvline(threshold4, c='b')
plt.axvline(threshold2, c='cyan')
plt.axvline(threshold3, c='magenta')
plt.xlabel("MAE reconstruction loss of the validation data")
plt.ylabel("No of examples")
plt.show()

```



## ▼ Distribution of the reconstruction losses of the test data (normal and abnormal)


The blue line is threshold4 (= the average of threshold3 [magenta] and threshold2 [cyan]).

The red line is the threshold that gives the best accuracy for the validation data.

```

reconstructions = variational_ae.predict(test_data)
test_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), test_data.reshape(-1,784))
plt.figure(figsize=(20,5))
plt.hist(test_loss[None, :], bins=100)
plt.axvline(threshold, c='r')
plt.axvline(threshold4, c='b')
plt.axvline(threshold2, c='cyan')
plt.axvline(threshold3, c='magenta')
plt.xlabel("MAE reconstruction loss of the test data")
plt.ylabel("No of examples")
plt.show()

```



## Mean and standard deviation of reconstruction losses for normal and abnormal test data

```

reconstructions = variational_ae.predict(normal_test_data)
nl_test_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), normal_test_data.reshape(
np.mean(nl_test_loss) , np.std(nl_test_loss))

(0.06630774, 0.018920897)

```

```

reconstructions = variational_ae.predict(abnormal_test_data)
abn_test_loss = tf.keras.losses.mae(reconstructions.reshape(-1,784), abnormal_test_data.reshape(
np.mean(abn_test_loss) , np.std(abn_test_loss))

(0.17501564, 0.030621752)

```

## Calculation of the accuracy and the confusion matrix on the test data with threshold set based on the best threshold from the validation data

```

# def predict(model, data, threshold):
#   reconstructions = model.predict(data)
#   loss = tf.keras.losses.mae(reconstructions.reshape(-1, 784), data.reshape(-1, 784))
#   return tf.math.less(loss, threshold)

def print_stats(predictions, labels):
    cf = confusion_matrix(labels, predictions)
    print("Confusion Matrix: \n prediction: F      T ")
    print("          {}  {}".format(preds[preds == False].shape[0], preds[preds == True].sh
    print(" label: F  [[{}  {}]  {}].format(cf[0,0], cf[0,1], test_labels_T_F[test_labels_T_
    print("          T  [{}  {}]]  {}].format(cf[1,0], cf[1,1], test_labels_T_F[test_labels_T_
    print("Accuracy = {}".format(accuracy_score(labels, predictions)))
    print("Normal Test Data Mean = {}".format(np.mean(nl_test_loss)))
    print("Normal Test Data Standard Deviation = {}".format(np.std(nl_test_loss)))
    print("Abnormal Test Data Mean = {}".format(np.mean(abn_test_loss)))
    print("Abnormal Test Data Standard Deviation = {}".format(np.std(abn_test_loss)))
    print("Precision = {}".format(precision_score(labels, predictions)))
    print("Recall = {}".format(recall_score(labels, predictions)))

```

```

print(accuracy_score(labels, predictions))
print(np.mean(nl_test_loss))
print(np.std(nl_test_loss))
print(np.mean(abn_test_loss))
print(np.std(abn_test_loss))
print(precision_score(labels, predictions))
print(recall_score(labels, predictions))
print(accuracy_score(labels, predictions), np.mean(nl_test_loss), np.std(nl_test_loss), np.
      precision_score(labels, predictions), recall_score(labels, predictions))

```

```

preds = predict(variational_ae, test_data, threshold)
print_stats(preds, test_labels_T_F)

```

↳ Confusion Matrix:

		F	T
		999	1001
label:	F	[[977 23]	1000
	T	[22 978]]	1000

Accuracy = 0.9775

Normal Test Data Mean = 0.06630773842334747

Normal Test Data Standard Deviation = 0.01892089657485485

Abnormal Test Data Mean = 0.1750156432390213

Abnormal Test Data Standard Deviation = 0.03062175214290619

Precision = 0.977022977022977

Recall = 0.978

0.9775

0.06630774

0.018920897

0.17501564

0.030621752

0.977022977022977

0.978

0.9775 0.06630774 0.018920897 0.17501564 0.030621752 0.977022977022977 0.978

```

print("Threshold =", valid_data_best_threshold)

```

Threshold = 0.11024031087756161

```

print(confusion_matrix(test_labels_T_F, preds))

```

```

[[977 23]
 [ 22 978]]

```

## Extra accuracy info

**Just informative. Please record the above accuracy.**

Accuracy on the test data with threshold set based on (threshold2 + threshold3) / 2 = Average of (mean + std of the distribution of the reconstruction losses of the normal validation data) and (mean - std of the distribution of the reconstruction losses of the abnormal validation data)

```
preds = predict(variational_ae, test_data, Avg_of_threshold_2_3)
print_stats(preds, test_labels_T_F)
```

Confusion Matrix:

		F	T
prediction:	F	984	1016
	T	[966 34]	1000
label:	F	[18 982]	1000
	T		

Accuracy = 0.974

Normal Test Data Mean = 0.06630773842334747

Normal Test Data Standard Deviation = 0.01892089657485485

Abnormal Test Data Mean = 0.1750156432390213

Abnormal Test Data Standard Deviation = 0.03062175214290619

Precision = 0.9665354330708661

Recall = 0.982

0.974

0.06630774

0.018920897

0.17501564

0.030621752

0.9665354330708661

0.982

0.974 0.06630774 0.018920897 0.17501564 0.030621752 0.9665354330708661 0.982

Accuracy on the test data with threshold set based on the mean of the training data MAE reconstruction losses + 2.5 std

```
preds = predict(variational_ae, test_data, threshold_train_mean_2_5_std)
print_stats(preds, test_labels_T_F)
```

Confusion Matrix:

		F	T
prediction:	F	1013	987
	T	[984 16]	1000
label:	F	[29 971]	1000
	T		

Accuracy = 0.9775

Normal Test Data Mean = 0.06630773842334747

Normal Test Data Standard Deviation = 0.01892089657485485

Abnormal Test Data Mean = 0.1750156432390213

Abnormal Test Data Standard Deviation = 0.03062175214290619

Precision = 0.983789260385005

Recall = 0.971

0.9775

0.06630774

0.018920897

0.17501564

```
0.030621752
0.983789260385005
0.971
0.9775 0.06630774 0.018920897 0.17501564 0.030621752 0.983789260385005 0.971
```

## Extra Info

Giving the VAE codings (please see book) (Just informative, not the goal here)

```
def plot_multiple_images(images, n_cols=None):
    n_cols = n_cols or len(images)
    n_rows = (len(images) - 1) // n_cols + 1
    if images.shape[-1] == 1:
        images = np.squeeze(images, axis=-1)
    plt.figure(figsize=(n_cols, n_rows))
    for index, image in enumerate(images):
        plt.subplot(n_rows, n_cols, index + 1)
        plt.imshow(image, cmap="binary")
        plt.axis("off")

codings = tf.random.normal(shape=[12, codings_size])
images = variational_decoder(codings).numpy()
plot_multiple_images(images, 4)
# save_fig("vae_generated_images_plot", tight_layout=False)
```



```
codings_grid = tf.reshape(codings, [1, 3, 4, codings_size])
larger_grid = tf.image.resize(codings_grid, size=[5, 7])
interpolated_codings = tf.reshape(larger_grid, [-1, codings_size])
images = variational_decoder(interpolated_codings).numpy()

plt.figure(figsize=(7, 5))
for index, image in enumerate(images):
    plt.subplot(5, 7, index + 1)
    if index%7%2==0 and index//7%2==0:
        plt.gca().get_xaxis().set_visible(False)
        plt.gca().get_yaxis().set_visible(False)
    else:
        plt.axis("off")
```

```
plt.imshow(image, cmap="binary")
# save_fig("semantic_interpolation_plot", tight_layout=False)
```



---

✓ 1s completed at 3:49 PM

● ✕