

Chapter 9.

Advanced Classification: SVM


Meng Jiang

CSE 40647/60647 Data Science Fall 2017

Introduction to Data Mining

Classification: A Mathematical Mapping

- **Classification:** predicts categorical class labels
 - E.g., Personal homepage classification
 - $x_i = (x_1, x_2, x_3, \dots)$, $y_i = +1$ or -1
 - x_1 : # of word "homepage"
 - x_2 : # of word "welcome"
- Mathematically, $x \in X = \mathfrak{R}^n$, $y \in Y = \{+1, -1\}$,
 - We want to derive a function $f: X \rightarrow Y$
- Linear Classification
 - Binary Classification problem
 - Data above the red line belongs to class 'x'
 - Data below red line belongs to class 'o'
 - Examples: SVM, Perceptron, Probabilistic Classifiers



Discriminative Classifiers

- Advantages
 - Prediction accuracy is generally high
 - As compared to Bayesian methods
 - Robust, works when training examples contain errors
 - Fast evaluation of the learned target function
 - Bayesian networks are normally slow
- Criticism
 - Long training time
 - Difficult to understand the learned function (weights)
 - Bayesian networks can be used easily for pattern discovery
 - Not easy to incorporate domain knowledge
 - Easy in the form of priors on the data or distributions


SVM: Support Vector Machines

- A relatively new classification method for both linear and nonlinear data
- With the new dimension, it searches for the linear optimal separating **hyperplane** (i.e., “decision boundary”)
- With an appropriate nonlinear mapping to a sufficiently high dimension, data from two classes can always be separated by a hyperplane
- SVM finds this hyperplane using **support vectors** (“essential” training tuples) and **margins** (defined by the support vectors)

SVM: History and Applications

- Vapnik and colleagues (1992)—groundwork from Vapnik & Chervonenkis' statistical learning theory in 1960s
- Features: training can be slow but accuracy is high owing to their ability to model complex nonlinear decision boundaries (margin maximization)
- Used for: classification and numeric prediction
- Applications:
 - handwritten digit recognition, object recognition, speaker identification, benchmarking time-series prediction tests

SVM: General Philosophy





Support Vectors

SVM: When Data Is Linearly Separable

Let data D be $(\mathbf{X}_1, y_1), \dots, (\mathbf{X}_{|D|}, y_{|D|})$, where \mathbf{X}_i is the set of training tuples associated with the class labels y_i

There are infinite lines (hyperplanes) separating the two classes but we want to find the best one (the one that minimizes classification error on unseen data)

*SVM searches for the hyperplane with the largest margin, i.e., **maximum marginal hyperplane** (MMH)*



SVM: Linearly Separable

- A separating hyperplane can be written as

$$\mathbf{W} \bullet \mathbf{X} + b = 0$$

where $\mathbf{W} = \{w_1, w_2, \dots, w_n\}$ is a weight vector and b a scalar (bias)


- For 2-D it can be written as: $w_0 + w_1 x_1 + w_2 x_2 = 0$
- The hyperplane defining the sides of the margin:

$$H_1: w_0 + w_1 x_1 + w_2 x_2 \geq 1 \quad \text{for } y_i = +1, \text{ and}$$

$$H_2: w_0 + w_1 x_1 + w_2 x_2 \leq -1 \quad \text{for } y_i = -1$$

- Any training tuples that fall on hyperplanes H_1 or H_2 (i.e., the sides defining the margin) are **support vectors**
- This becomes a **constrained (convex) quadratic optimization** problem:
 - Quadratic objective function and linear constraints \rightarrow *Quadratic Programming (QP)* \rightarrow Lagrangian multipliers

Optimization: Maximize Margin Width



M =Margin Width

$$H_1: w\mathbf{x}_i + b \geq 1 \quad \text{for } y_i = +1$$

$$H_2: w\mathbf{x}_i + b \leq -1 \quad \text{for } y_i = -1$$

$$\rightarrow y_i (w\mathbf{x}_i + b) \geq 1 \quad \text{for all } i$$

$$\max M = \frac{(\mathbf{x}^+ - \mathbf{x}^-) \cdot \mathbf{w}}{|\mathbf{w}|} = \frac{2}{|\mathbf{w}|}$$

$$\text{same as } \min \frac{1}{2} \mathbf{w}^t \mathbf{w}$$

What we know:

- $\mathbf{w} \cdot \mathbf{x}^+ + b = +1$
- $\mathbf{w} \cdot \mathbf{x}^- + b = -1$
- $\mathbf{w} \cdot (\mathbf{x}^+ - \mathbf{x}^-) = 2$

Quadratic optimization problem:

$$\min \Phi(\mathbf{w}) = \frac{1}{2} \mathbf{w}^t \mathbf{w}$$

$$\text{s.t. } y_i (w\mathbf{x}_i + b) \geq 1 \quad \text{for all } i$$

Solving the Optimization Problem

- Need to optimize a quadratic function subject to linear constraints.
- Quadratic optimization problems are a well-known class of mathematical programming problems, and many (rather intricate) algorithms exist for solving them.
- The solution involves constructing a dual problem where a **Lagrange multiplier** α_i is associated with every constraint in the primary problem:

Find \mathbf{w} and b such that
 $\Phi(\mathbf{w}) = \frac{1}{2} \mathbf{w}^T \mathbf{w}$ is minimized;
and for all $\{(\mathbf{x}_i, y_i)\}$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

Find $\alpha_1 \dots \alpha_N$ such that
 $Q(\boldsymbol{\alpha}) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$
is maximized and
(1) $\sum \alpha_i y_i = 0$
(2) $\alpha_i \geq 0$ for all α_i

LinearSVMs

- The classifier is a separating hyperplane.
- Most “important” training points are support vectors; they define the hyperplane.
- Quadratic optimization algorithms can identify which training points x_i are support vectors with non-zero Lagrangian multipliers α_i .
- Both in the dual formulation of the problem and in the solution training points appear only inside dot products:

Find $\alpha_1 \dots \alpha_N$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j x_i^T x_j$ is maximized and

(1) $\sum \alpha_i y_i = 0$


(2) $0 \leq \alpha_i \leq C$ for all α_i

Why is SVM Effective on High Dimensional Data?

- The complexity of trained classifier is characterized by the # of support vectors rather than the dimensionality of the data
- The support vectors are the essential or critical training examples — they lie closest to the decision boundary
- If all other training examples are removed and the training is repeated, the same separating hyperplane would be found

Non-linear SVMs: Feature Spaces

- General idea: The original input space can always be mapped to some higher-dimensional feature space where the training set is separable:



The “Kernel Trick”

- The classifier relies on dot product between vectors $K(x_i, x_j) = x_i^T x_j$
- If every data point is mapped into high-dimensional space via some transformation $\Phi: x \rightarrow \phi(x)$, the dot product becomes:

$$K(x_i, x_j) = \phi(x_i)^T \phi(x_j)$$

- A *kernel function* is some function that corresponds to an inner product in some expanded feature space.
- Example:

2-dimensional vectors $x = [x_1 \ x_2]$; let $K(x_i, x_j) = (1 + x_i^T x_j)^2$,

Need to show that $K(x_i, x_j) = \phi(x_i)^T \phi(x_j)$:

$$K(x_i, x_j) = (1 + x_i^T x_j)^2,$$

$$\begin{aligned} &= 1 + x_{i1}^2 x_{j1}^2 + 2 x_{i1} x_{j1} x_{i2} x_{j2} + x_{i2}^2 x_{j2}^2 + 2 x_{i1} x_{j1} + 2 x_{i2} x_{j2} \\ &= [1 \ x_{i1}^2 \ \sqrt{2} x_{i1} x_{i2} \ x_{i2}^2 \ \sqrt{2} x_{i1} \ \sqrt{2} x_{i2}]^T [1 \ x_{j1}^2 \ \sqrt{2} x_{j1} x_{j2} \ x_{j2}^2 \ \sqrt{2} x_{j1} \ \sqrt{2} x_{j2}] \\ &= \phi(x_i)^T \phi(x_j), \quad \text{where } \phi(x) = [1 \ x_1^2 \ \sqrt{2} x_1 x_2 \ x_2^2 \ \sqrt{2} x_1 \ \sqrt{2} x_2] \end{aligned}$$

What Functions are Kernels?

- For some functions $K(x_i, x_j)$ checking that $K(x_i, x_j) = \phi(x_i)^\top \phi(x_j)$ can be cumbersome.
- Mercer's theorem:
Every semi-positive definite symmetric function is a kernel
- Semi-positive definite symmetric functions correspond to a semi-positive definite symmetric Gram matrix:

K=

$K(\mathbf{x}_1, \mathbf{x}_1)$	$K(\mathbf{x}_1, \mathbf{x}_2)$	$K(\mathbf{x}_1, \mathbf{x}_3)$...	$K(\mathbf{x}_1, \mathbf{x}_N)$
$K(\mathbf{x}_2, \mathbf{x}_1)$	$K(\mathbf{x}_2, \mathbf{x}_2)$	$K(\mathbf{x}_2, \mathbf{x}_3)$		$K(\mathbf{x}_2, \mathbf{x}_N)$
...
$K(\mathbf{x}_N, \mathbf{x}_1)$	$K(\mathbf{x}_N, \mathbf{x}_2)$	$K(\mathbf{x}_N, \mathbf{x}_3)$...	$K(\mathbf{x}_N, \mathbf{x}_N)$

Kernel Functions for Nonlinear Classification

- Instead of computing the dot product on the transformed data, it is mathematically equivalent to applying a kernel function $K(\mathbf{X}_i, \mathbf{X}_j)$ to the original data, i.e.,

$$K(\mathbf{X}_i, \mathbf{X}_j) = \Phi(\mathbf{X}_i) \cdot \Phi(\mathbf{X}_j)$$

- Typical Kernel Functions

Polynomial kernel of degree h : $K(\mathbf{X}_i, \mathbf{X}_j) = (\mathbf{X}_i \cdot \mathbf{X}_j + 1)^h$

Gaussian radial basis function kernel : $K(\mathbf{X}_i, \mathbf{X}_j) = e^{-\|\mathbf{X}_i - \mathbf{X}_j\|^2 / 2\sigma^2}$

Sigmoid kernel : $K(\mathbf{X}_i, \mathbf{X}_j) = \tanh(\kappa \mathbf{X}_i \cdot \mathbf{X}_j - \delta)$

Non-linear SVMs: Optimization

- Dual problem formulation:

Find $\alpha_1 \dots \alpha_N$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j K(x_i, x_j)$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $\alpha_i \geq 0$ for all α_i

- The solution is:

$$f(x) = \sum \alpha_i y_i K(x_i, x_j) + b$$

- Optimization techniques for finding α_i 's remain the same!

SVM Applications

- SVM has been used successfully in many real-world problems
 - Text (and hypertext) categorization
 - Image classification
 - Bioinformatics (Protein classification, Cancer classification)
 - Hand-written character recognition

SVM Related Links

- SVM Website: <http://www.kernel-machines.org/>
- Representative implementations
 - **LIBSVM**: an efficient implementation of SVM, multi-class classifications, nu-SVM, one-class SVM, including also various interfaces with java, python, etc.
 - **SVM-light**: simpler but performance is not better than LIBSVM, support only binary classification and only in C
 - **SVM-torch**: another recent implementation also written in C

References

- C. M. Bishop, Neural Networks for Pattern Recognition. Oxford University Press, 1995
- L. Breiman, J. Friedman, R. Olshen, and C. Stone. Classification and Regression Trees. Wadsworth International Group, 1984
- C. J. C. Burges. A Tutorial on Support Vector Machines for Pattern Recognition. Data Mining and Knowledge Discovery, 2(2): 121-168, 1998
- N. Cristianini and J. Shawe-Taylor, Introduction to Support Vector Machines and Other Kernel-Based Learning Methods, Cambridge University Press, 2000
- H. Yu, J. Yang, and J. Han. Classifying large data sets using SVM with hierarchical clusters. KDD'03
- A. J. Dobson. An Introduction to Generalized Linear Models. Chapman & Hall, 1990
- R. O. Duda, P. E. Hart, and D. G. Stork. Pattern Classification, 2ed. John Wiley, 2001
- T. Hastie, R. Tibshirani, and J. Friedman. The Elements of Statistical Learning: Data Mining, Inference, and Prediction. Springer-Verlag, 2001
- S. Haykin, Neural Networks and Learning Machines, Prentice Hall, 2008
- D. Heckerman, D. Geiger, and D. M. Chickering. Learning Bayesian networks: The combination of knowledge and statistical data. Machine Learning, 1995
- H. Cheng, X. Yan, J. Han & C.-W. Hsu, Discriminative Frequent Pattern Analysis for Effective Classification, ICDE'07
- W. Cohen. Fast effective rule induction. ICML'95

References (cont.)

- H. Cheng, X. Yan, J. Han & P. S. Yu, Direct Discriminative Pattern Mining for Effective Classification, ICDE'08
- G. Cong, K. Tan, A. Tung & X. Xu. Mining Top-k Covering Rule Groups for Gene Expression Data, SIGMOD'05
- M. Deshpande, M. Kuramochi, N. Wale & G. Karypis. Frequent Substructure-based Approaches for Classifying Chemical Compounds, TKDE'05
- G. Dong & J. Li. Efficient Mining of Emerging Patterns: Discovering Trends and Differences, KDD'99
- W. Fan, K. Zhang, H. Cheng, J. Gao, X. Yan, J. Han, P. S. Yu & O. Verscheure. Direct Mining of Discriminative and Essential Graphical and Itemset Features via Model-based Search Tree, KDD'08
- W. Li, J. Han & J. Pei. CMAR: Accurate and Efficient Classification based on Multiple Class-association Rules, ICDM'01
- B. Liu, W. Hsu & Y. Ma. Integrating Classification and Association Rule Mining, KDD'98
- J. R. Quinlan and R. M. Cameron-Jones. FOIL: A midterm report. ECML'93
- Jingbo Shang, Wenzhu Tong, Jian Peng, and Jiawei Han, "[DPClass: An Effective but Concise Discriminative Patterns-Based Classification Framework](#)", SDM'16
- J. Wang and G. Karypis. HARMONY: Efficiently Mining the Best Rules for Classification, SDM'05
- X. Yin & J. Han. CPAR: Classification Based on Predictive Association Rules, SDM'03