









921 971 898

Show Favorites Only

 Derek 968	 Drew 465	 Olivia 850	 Heidi 589
 James 600	 Meghann 590	 Rebecca 450	 Robyn 500



Chapter 8.

Classification: Basic Concepts

Meng Jiang

CS412 Summer 2017:

Introduction to Data Mining

Classification: Basic Concepts

- **Classification: Basic Concepts**
- Decision Tree Induction
- Bayes Classification Methods
- Model Evaluation and Selection
- Techniques to Improve Classification Accuracy: Ensemble Methods

Supervised vs. Unsupervised Learning

- Supervised learning (classification)
 - Supervision: The training data (observations, measurements, etc.) are accompanied by **labels** indicating the class of the observations
 - New data is classified based on the training set
- Unsupervised learning (clustering)
 - The class labels of training data is unknown
 - Given a set of measurements, observations, etc. with the aim of establishing the existence of classes or clusters in the data


Prediction Problems: Classification vs. Numeric Prediction

- Classification
 - Predicts categorical class labels (discrete or nominal)
 - Classifies data (constructs a model) based on the training set (tuples/samples/objects and their attributes/features; attributes: measurements, observations, etc.) and the class labels
- Numeric Prediction
 - Models continuous-valued functions, i.e., predicts unknown or missing values
- Typical applications
 - Credit/loan approval
 - Medical diagnosis: if a tumor is cancerous or benign
 - Fraud detection: if a transaction is fraudulent
 - Web page categorization: which category it is


Classification: A Two-Step Process

- **Model construction:** describing a set of predetermined classes
 - Each tuple/sample is assumed to belong to a predefined class, as determined by the **class label** attributes
 - The set of tuples used for model construction is **training set**
 - Model: represented as classification rules, decision trees, or mathematical formulae
- **Model usage:** for classifying future or unknown objects
 - Estimate accuracy of the model
 - The known label of test sample is compared with the classified result from the model
 - **Accuracy:** % of test set samples that are correctly classified by the model
 - Test set is independent of training set (otherwise **overfitting**)
 - If the accuracy is acceptable, use the model to classify new data
- Note: If *the test set* is used to select/refine models, it is called **validation (test) set** or development test set

(1) Model Construction



(2) Using the Model in Prediction




Classification: Basic Concepts

- Classification: Basic Concepts
- **Decision Tree Induction**
- Bayes Classification Methods
- Model Evaluation and Selection
- Techniques to Improve Classification Accuracy: Ensemble Methods

Decision Tree Induction: An Example


- Training data set: Buys_computer
- The data set follows an example of **Quinlan's ID₃** (Playing Tennis)
- Resulting tree:



age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

Quinlan's Example – Playing Tennis?

Outlook	Temperature	Humidity	Windy	Class
sunny	hot	high	false	N
sunny	hot	high	true	N
overcast	hot	high	false	P
rain	mild	high	false	P
rain	cool	normal	false	P
rain	cool	normal	true	N
overcast	cool	normal	true	P
sunny	mild	high	false	N
sunny	cool	normal	false	P
rain	mild	normal	false	P
sunny	mild	normal	true	P
overcast	mild	high	true	P
overcast	hot	normal	false	P
rain	mild	high	true	N



Algorithm for Decision Tree Induction

- Basic algorithm (a greedy algorithm)
 - Tree is constructed in a **top-down recursive divide-and-conquer manner**
 - At start, all the training examples are at the root
 - Attributes are categorical (if continuous-valued, they are discretized in advance)
 - Examples are partitioned recursively based on **selected attributes**
 - **Test attributes are selected on the basis of a heuristic or statistical measure (e.g., information gain)**
- Conditions for stopping partitioning
 - All samples for a given node belong to the same class
 - There are no remaining attributes for further partitioning—**majority voting** is employed for classifying the leaf
 - There are no samples left


Brief Review of Entropy

- Entropy (Information Theory)
 - A measure of uncertainty associated with a random number
 - Calculation: For a discrete random variable Y taking m distinct values $\{y_1, y_2, \dots, y_m\}$

$$H(Y) = - \sum_{i=1}^m p_i \log(p_i) \quad \text{where } p_i = P(Y = y_i)$$

- Interpretation
 - Higher entropy \rightarrow higher uncertainty
 - Lower entropy \rightarrow lower uncertainty
- Conditional entropy

$$H(Y|X) = \sum_x p(x) H(Y|X = x)$$



Attribute Selection Measure: Information Gain (ID3/C4.5)

- Select the attribute with the highest information gain
- Let p_i be the probability that an arbitrary tuple in D belongs to class C_i , estimated by $|C_{i,D}|/|D|$
- Expected information (entropy) needed to classify a tuple in D :

$$Info(D) = - \sum_{i=1}^m p_i \log_2(p_i)$$

- Information needed (after using A to split D into v partitions) to classify D :


$$Info_A(D) = \sum_{j=1}^v \frac{|D_j|}{|D|} \times Info(D_j)$$

- Information gained by branching on attribute A

$$Gain(A) = Info(D) - Info_A(D)$$

Attribute Selection: Information Gain

#total (#positive, #negative)



Attribute Selection: Information Gain

- Class P: buys_computer = "yes"
- Class N: buys_computer = "no"

$$Info(D) = I(9,5) = -\frac{9}{14} \log_2\left(\frac{9}{14}\right) - \frac{5}{14} \log_2\left(\frac{5}{14}\right) = 0.940$$

$$Info_{age}(D) = \frac{5}{14} I(2,3) + \frac{4}{14} I(4,0) + \frac{5}{14} I(3,2) = 0.694$$

age	p _i	n _i	I(p _i , n _i)
<=30	2	3	0.971
31...40	4	0	0
>40	3	2	0.971

$\frac{5}{14} I(2,3)$ means "age <=30" has 5 out of 14 samples, with 2 yes'es and 3 no's.

Hence

$$Gain(age) = Info(D) - Info_{age}(D) = 0.246$$

Similarly,

$$Gain(income) = 0.029$$

$$Gain(student) = 0.151$$

$$Gain(credit_rating) = 0.048$$

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

Computing Information-Gain for Continuous-Valued Attributes

- Let attribute A be a continuous-valued attribute
- Must determine the **best split point** for A
 - Sort the value A in increasing order
 - Typically, the **midpoint** between each pair of adjacent values is considered as a possible *split point*
 - $(a_i + a_{i+1})/2$ is the midpoint between the values of a_i and a_{i+1}
 - The point with the **minimum expected information requirement** for A is selected as the split-point for A **$\min_{point} Info_{point}(A)$**
- Split:
 - D1 is the set of tuples in D satisfying $A \leq$ split-point, and D2 is the set of tuples in D satisfying $A >$ split-point

Gain Ratio for Attribute Selection (C4.5)

- Information gain measure is **biased** towards attributes with **a large number of values**
- C4.5 (a successor of ID3) uses **gain ratio** to overcome the problem (normalization to information gain)

$$SplitInfo_A(D) = - \sum_{j=1}^v \frac{|D_j|}{|D|} \times \log_2 \left(\frac{|D_j|}{|D|} \right)$$

$$- \text{GainRatio}(A) = \text{Gain}(A) / \text{SplitInfo}(A)$$

$$Info_{age}(D) = \frac{5}{14} I(2,3) + \frac{4}{14} I(4,0) + \frac{5}{14} I(3,2) = 0.694$$

$$\text{Gain}(age) = \text{Info}(D) - \text{Info}_{age}(D) = 0.246$$

$$\text{Gain}(income) = 0.029 \quad \leftarrow$$

$$\begin{aligned} \text{Gain}(income) &= \text{Info}(\text{root}) - \text{Info}_{income}(\text{root}) \\ &= I(9,5) - \{ 4/14 I(2,2) + 6/14 I(4,2) + 4/14 I(3,1) \} \\ &= 0.940 - 0.911 = 0.029 \end{aligned}$$

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

Gain Ratio for Attribute Selection (C4.5)

- Information gain measure is **biased** towards attributes with **a large number of values**
- C4.5 (a successor of ID3) uses **gain ratio** to overcome the problem (normalization to information gain)

$$SplitInfo_A(D) = - \sum_{j=1}^v \frac{|D_j|}{|D|} \times \log_2 \left(\frac{|D_j|}{|D|} \right)$$

$$- \text{GainRatio}(A) = \text{Gain}(A) / \text{SplitInfo}(A)$$

$$Info_{age}(D) = \frac{5}{14} I(2,3) + \frac{4}{14} I(4,0) + \frac{5}{14} I(3,2) = 0.694$$

$$Gain(age) = Info(D) - Info_{age}(D) = 0.246$$

$$Gain(income) = 0.029$$

$$Gain(student) = 0.151$$

$$Gain(credit_rating) = 0.048$$

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

If we have many income values:

1000-2000, 2000-3000, ... 9000-10000, ...?

Gain Ratio for Attribute Selection (C4.5)

- Information gain measure is **biased** towards attributes with **a large number of values**
- C4.5 (a successor of ID3) uses **gain ratio** to overcome the problem (normalization to information gain)

$$SplitInfo_A(D) = - \sum_{j=1}^v \frac{|D_j|}{|D|} \times \log_2 \left(\frac{|D_j|}{|D|} \right)$$

– $GainRatio(A) = Gain(A) / SplitInfo(A)$

- Ex. $SplitInfo_{income}(D) = -\frac{4}{14} \times \log_2 \left(\frac{4}{14} \right) - \frac{6}{14} \times \log_2 \left(\frac{6}{14} \right) - \frac{4}{14} \times \log_2 \left(\frac{4}{14} \right) = 1.557$
 - $gain_ratio(income) = 0.029 / 1.557 = 0.019$
- The attribute with the maximum gain ratio is selected as the splitting attribute

Gini Index (CART, IBM IntelligentMiner)

- If a data set D contains examples from n classes, gini index, $gini(D)$ is defined as
$$gini(D) = 1 - \sum_{j=1}^n p_j^2$$

where p_j is the relative frequency of class j in D

- If a data set D is split on A into two subsets D_1 and D_2 , the *gini* index $gini(D)$ is defined as

$$gini_A(D) = \frac{|D_1|}{|D|} gini(D_1) + \frac{|D_2|}{|D|} gini(D_2)$$

- Reduction in Impurity:

$$\Delta gini(A) = gini(D) - gini_A(D)$$

- The attribute provides the smallest $gini_{split}(D)$ (or the largest reduction in impurity) is chosen to split the node (*need to enumerate all the possible splitting points for each attribute*)

IG vs Gini

$$Info(D) = - \sum_{i=1}^m p_i \log_2(p_i)$$

$$gini(D) = 1 - \sum_{j=1}^n p_j^2$$

$$Info_A(D) = \sum_{j=1}^v \frac{|D_j|}{|D|} \times Info(D_j)$$

$$gini_A(D) = \frac{|D_1|}{|D|} gini(D_1) + \frac{|D_2|}{|D|} gini(D_2)$$

$$Gain(A) = Info(D) - Info_A(D)$$

$$\Delta gini(A) = gini(D) - gini_A(D)$$

Computation of Gini Index

- Ex. D has 9 tuples in buys_computer = "yes" and 5 in "no"

$$gini(D) = 1 - \left(\frac{9}{14}\right)^2 - \left(\frac{5}{14}\right)^2 = 0.459$$

- Suppose the attribute income partitions D into 10 in D_1 : {low, medium} and 4 in D_2 : {high}

$$\begin{aligned} gini_{income \in \{low, medium\}}(D) &= \left(\frac{10}{14}\right)Gini(D_1) + \left(\frac{4}{14}\right)Gini(D_2) = \frac{10}{14} \left(1 - \left(\frac{7}{10}\right)^2 - \left(\frac{3}{10}\right)^2\right) + \frac{4}{14} \left(1 - \left(\frac{2}{4}\right)^2 - \left(\frac{2}{4}\right)^2\right) \\ &= 0.443 \\ &= Gini_{income \in \{high\}}(D). \end{aligned}$$

$Gini_{\{low, high\}}$ is 0.458; $Gini_{\{medium, high\}}$ is 0.450. Thus, split on the {low, medium} (and {high}) since it has the lowest Gini index

- All attributes are assumed continuous-valued
- May need other tools, e.g., clustering, to get the possible split values
- Can be modified for categorical attributes

Comparing Attribute Selection Measures

- The three measures, in general, return good results but
 - **Information gain:**
 - biased towards multivalued attributes
 - **Gain ratio:**
 - tends to prefer unbalanced splits in which one partition is much smaller than the others
 - **Gini index:**
 - biased to multivalued attributes
 - has difficulty when # of classes is large
 - tends to favor tests that result in equal-sized partitions and purity in both partitions

Other Attribute Selection Measures

- CHAID: a popular decision tree algorithm, measure based on χ^2 test for independence
- C-SEP: performs better than info. gain and gini index in certain cases
- G-statistic: has a close approximation to χ^2 distribution
- MDL (Minimal Description Length) principle (i.e., the simplest solution is preferred):
 - The best tree as the one that requires the fewest # of bits to both (1) encode the tree, and (2) encode the exceptions to the tree
- Multivariate splits (partition based on multiple variable combinations)
 - CART: finds multivariate splits based on a linear comb. of attrs.
- Which attribute selection measure is the best?
 - Most give good results, none is significantly superior than others

Overfitting and Tree Pruning

- Overfitting: An induced tree may overfit the training data
 - Too many branches, some may reflect anomalies due to noise or outliers
 - Poor accuracy for unseen samples
- Two approaches to avoid overfitting
 - Prepruning: *Halt tree construction early*-do not split a node if this would result in the goodness measure falling below a threshold
 - Difficult to choose an appropriate threshold
 - Postpruning: *Remove branches* from a “fully grown” tree—get a sequence of progressively pruned trees
 - Use a set of data different from the training data to decide which is the “best pruned tree”

Classification in Large Databases

- Classification—a classical problem extensively studied by statisticians and machine learning researchers
- Scalability: Classifying data sets with millions of examples and hundreds of attributes with reasonable speed
- Why is decision tree induction popular?
 - relatively faster learning speed (than other classification methods)
 - convertible to simple and easy to understand classification rules
 - can use SQL queries for accessing databases
 - comparable classification accuracy with other methods
- **RainForest** (VLDB'98 — Gehrke, Ramakrishnan & Ganti)
 - Builds an AVC-list (attribute, value, class label)

RainForest: A Scalable Classification Framework

- The criteria that determine the quality of the tree can be computed separately
 - Builds an AVC-list: **AVC (Attribute, Value, Class_label)**
- AVC-set** (of an attribute X)
 - Projection of training dataset onto the attribute X and class label where counts of individual class label are aggregated
- AVC-group** (of a node n)
 - Set of AVC-sets of all predictor attributes at the node n

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

The Training Data

AVC-set on Age

Age	Buy_Computer	
	yes	no
<=30	2	3
31..40	4	0
>40	3	2

AVC-set on Student

student	Buy_Computer	
	yes	no
yes	6	1
no	3	4

AVC-set on Income

income	Buy_Computer	
	yes	no
high	2	2
medium	4	2
low	3	1

AVC-set on Credit_Rating

Credit rating	Buy_Computer	
	yes	no
fair	6	2
excellent	3	3

Its AVC Sets

Classification: Basic Concepts

- Classification: Basic Concepts
- Decision Tree Induction
- **Bayes Classification Methods**
- Model Evaluation and Selection
- Techniques to Improve Classification Accuracy: Ensemble Methods

Bayesian Classification: Why?

- A statistical classifier: performs *probabilistic prediction*, i.e., predicts class membership probabilities
- Foundation: Based on Bayes' Theorem.
- Performance: A simple Bayesian classifier, *naïve Bayesian classifier*, has comparable performance with decision tree and selected neural network classifiers
- Incremental: Each training example can incrementally increase/decrease the probability that a hypothesis is correct — prior knowledge can be combined with observed data
- Standard: Even when Bayesian methods are computationally intractable, they can provide a standard of optimal decision making against which other methods can be measured

Bayes' Theorem: Basics

PROOF OF BAYES THEOREM

The probability of two events A and B happening, $P(A \cap B)$, is the probability of A, $P(A)$, times the probability of B given that A has occurred, $P(B|A)$.

$$P(A \cap B) = P(A)P(B|A) \quad (1)$$

On the other hand, the probability of A and B is also equal to the probability of B times the probability of A given B.

$$P(A \cap B) = P(B)P(A|B) \quad (2)$$

Equating the two yields:

$$P(B)P(A|B) = P(A)P(B|A) \quad (3)$$

and thus

$$P(A|B) = P(A) \frac{P(B|A)}{P(B)} \quad (4)$$

This equation, known as Bayes Theorem is the basis of statistical inference.

Bayes' Theorem: Basics

- Bayes' Theorem:
$$P(H | \mathbf{X}) = \frac{P(\mathbf{X} | H)P(H)}{P(\mathbf{X})} = P(\mathbf{X} | H) \times P(H) / P(\mathbf{X})$$
 - Let \mathbf{X} be a data sample (“evidence”): class label is unknown
 - Let H be a *hypothesis* that \mathbf{X} belongs to class C
 - Classification is to determine $P(H|\mathbf{X})$, (i.e., *posteriori probability*): the probability that the hypothesis holds given the observed data sample \mathbf{X}
 - $P(H)$ (*prior probability*): the initial probability
 - E.g., \mathbf{X} will buy computer, regardless of age, income, ...
 - $P(\mathbf{X})$: probability that sample data is observed
 - $P(\mathbf{X}|H)$ (likelihood): the probability of observing the sample \mathbf{X} , given that the hypothesis holds
 - E.g., Given that \mathbf{X} will buy computer, the prob. that \mathbf{X} is 31..40, medium income

Prediction Based on Bayes' Theorem

- Given training data \mathbf{X} , *posteriori probability of a hypothesis* H , $P(H|\mathbf{X})$, follows the Bayes' theorem

$$P(H|\mathbf{X}) = \frac{P(\mathbf{X}|H)P(H)}{P(\mathbf{X})} = P(\mathbf{X}|H) \times P(H) / P(\mathbf{X})$$

- Informally, this can be viewed as

posteriori = likelihood x prior/evidence

- Predicts \mathbf{X} belongs to C_i iff the probability $P(C_i|\mathbf{X})$ is the highest among all the $P(C_k|\mathbf{X})$ for all the k classes
- Practical difficulty: It requires initial knowledge of many probabilities, involving significant computational cost

Classification is to Derive the Maximum Posteriori

- Let D be a training set of tuples and their associated class labels, and each tuple is represented by an n -D attribute vector $\mathbf{X} = (x_1, x_2, \dots, x_n)$
- Suppose there are m classes C_1, C_2, \dots, C_m .
- Classification is to derive the maximum posteriori, i.e., the maximal $P(C_i|\mathbf{X})$
- This can be derived from Bayes' theorem

$$P(C_i|\mathbf{X}) = \frac{P(\mathbf{X}|C_i)P(C_i)}{P(\mathbf{X})}$$

- Since $P(\mathbf{X})$ is constant for all classes, only

$$P(C_i|\mathbf{X}) = P(\mathbf{X}|C_i)P(C_i)$$

needs to be maximized

Naïve Bayes Classifier

- A simplified assumption: attributes are conditionally independent (i.e., no dependence relation between attributes):

$$P(\mathbf{X} | C_i) = \prod_{k=1}^n P(x_k | C_i) = P(x_1 | C_i) \times P(x_2 | C_i) \times \dots \times P(x_n | C_i)$$

- This greatly reduces the computation cost: Only counts the class distribution
- If A_k is categorical, $P(x_k | C_i)$ is the # of tuples in C_i having value x_k for A_k divided by $|C_{i,D}|$ (# of tuples of C_i in D)
- If A_k is continuous-valued, $P(x_k | C_i)$ is usually computed based on Gaussian distribution with a mean μ and standard deviation σ

$$g(x, \mu, \sigma) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

and $P(x_k | C_i)$ is $P(\mathbf{X} | C_i) = g(x_k, \mu_{C_i}, \sigma_{C_i})$

Naïve Bayes Classifier: Training Dataset

- Class:
 - C1: buys_computer = 'yes'
 - C2: buys_computer = 'no'
- Data to be classified:
 - X = (age <=30, Income = medium, Student = yes, Credit_rating = Fair)

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

Naïve Bayes Classifier: An Example

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
<=30	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

- $P(C_i): P(\text{buys_computer} = \text{"yes"}) = 9/14 = 0.643$

$$P(\text{buys_computer} = \text{"no"}) = 5/14 = 0.357$$

- Compute $P(X|C_i)$ for each class

$$P(\text{age} = \text{"<=30"} | \text{buys_computer} = \text{"yes"}) = 2/9 = 0.222$$

$$P(\text{age} = \text{"<= 30"} | \text{buys_computer} = \text{"no"}) = 3/5 = 0.6$$

$$P(\text{income} = \text{"medium"} | \text{buys_computer} = \text{"yes"}) = 4/9 = 0.444$$

$$P(\text{income} = \text{"medium"} | \text{buys_computer} = \text{"no"}) = 2/5 = 0.4$$

$$P(\text{student} = \text{"yes"} | \text{buys_computer} = \text{"yes"}) = 6/9 = 0.667$$

$$P(\text{student} = \text{"yes"} | \text{buys_computer} = \text{"no"}) = 1/5 = 0.2$$

$$P(\text{credit_rating} = \text{"fair"} | \text{buys_computer} = \text{"yes"}) = 6/9 = 0.667$$

$$P(\text{credit_rating} = \text{"fair"} | \text{buys_computer} = \text{"no"}) = 2/5 = 0.4$$

- **$X = (\text{age} \leq 30, \text{income} = \text{medium}, \text{student} = \text{yes}, \text{credit_rating} = \text{fair})$**

$$P(X|C_i): P(X | \text{buys_computer} = \text{"yes"}) = 0.222 \times 0.444 \times 0.667 \times 0.667 = 0.044$$

$$P(X | \text{buys_computer} = \text{"no"}) = 0.6 \times 0.4 \times 0.2 \times 0.4 = 0.019$$

$$P(X|C_i) * P(C_i): P(X | \text{buys_computer} = \text{"yes"}) * P(\text{buys_computer} = \text{"yes"}) = 0.028$$

$$P(X | \text{buys_computer} = \text{"no"}) * P(\text{buys_computer} = \text{"no"}) = 0.007$$

Therefore, X belongs to class ("buys_computer = yes")

Avoiding the Zero-Probability Problem

- Naïve Bayesian prediction requires each conditional prob. be **non-zero**. Otherwise, the predicted prob. will be zero

$$P(X | C_i) = \prod_{k=1}^n P(x_k | C_i)$$

- Ex. Suppose a dataset with 1000 tuples, income=low (0), income= medium (990), and income = high (10)
- Use **Laplacian correction** (or Laplacian estimator)
 - *Adding 1 to each case*
 - Prob(income = low) = 1/1003
 - Prob(income = medium) = 991/1003
 - Prob(income = high) = 11/1003
 - The “corrected” prob. estimates are close to their “uncorrected” counterparts

Naïve Bayes Classifier: Comments

- Advantages
 - Easy to implement
 - Good results obtained in most of the cases
- Disadvantages
 - Assumption: class conditional independence, therefore loss of accuracy
 - Practically, dependencies exist among variables
 - E.g., hospitals: patients: Profile: age, family history, etc.
Symptoms: fever, cough etc., Disease: lung cancer, diabetes, etc.
 - Dependencies among these cannot be modeled by Naïve Bayes Classifier
- How to deal with these dependencies? Bayesian Belief Networks (Chapter 9)

Classification: Basic Concepts

- Classification: Basic Concepts
- Decision Tree Induction
- Bayes Classification Methods
- **Model Evaluation and Selection**
- Techniques to Improve Classification Accuracy: Ensemble Methods

Model Evaluation and Selection

- Evaluation metrics: How can we measure accuracy? Other metrics to consider?
- Use **validation test set** of class-labeled tuples instead of training set when assessing accuracy
- Methods for estimating a classifier's accuracy:
 - Holdout method, random subsampling
 - Cross-validation
 - Bootstrap
- Comparing classifiers:
 - Confidence intervals
 - Cost-benefit analysis and ROC Curves

Classifier Evaluation Metrics:

Confusion Matrix

Confusion Matrix:

Actual class\Predicted class	C_1	$\neg C_1$
C_1	True Positives (TP)	False Negatives (FN)
$\neg C_1$	False Positives (FP)	True Negatives (TN)

Example of Confusion Matrix:

Actual class\Predicted class	buy_computer = yes	buy_computer = no	Total
buy_computer = yes	6954	46	7000
buy_computer = no	412	2588	3000
Total	7366	2634	10000

- Given m classes, an entry, $CM_{i,j}$ in a **confusion matrix** indicates # of tuples in class i that were labeled by the classifier as class j
 - May have extra rows/columns to provide totals

Classifier Evaluation Metrics: Accuracy, Error Rate, Sensitivity and Specificity

A\P	C	$\neg C$	
C	TP	FN	P
$\neg C$	FP	TN	N
	P'	N'	All

- **Classifier Accuracy**, or recognition rate: percentage of test set tuples that are correctly classified

$$\text{Accuracy} = (TP + TN) / \text{All}$$

- **Error rate**: $1 - \text{accuracy}$, or
 $\text{Error rate} = (FP + FN) / \text{All}$

- **Class Imbalance Problem**:
 - One class may be *rare*, e.g. fraud, or HIV-positive
 - Significant *majority of the negative class* and minority of the positive class
 - **Sensitivity**: True Positive recognition rate
 - **Sensitivity** = TP / P
 - **Specificity**: True Negative recognition rate
 - **Specificity** = TN / N

Classifier Evaluation Metrics: Precision and Recall, and F-measures

- **Precision:** exactness: what % of tuples that the classifier labeled as positive are actually positive

$$precision = \frac{TP}{TP + FP}$$

- **Recall:** completeness – what % of positive tuples did the classifier label as positive?

$$recall = \frac{TP}{TP + FN}$$

- Comment:
 - Perfect score is 1.0
 - Inverse relationship between precision & recall
- **F measure (or F-score):** harmonic mean of precision and recall
 - In general, it is the weighted measure of precision & recall

$$F = \frac{1}{\alpha \cdot \frac{1}{P} + (1 - \alpha) \cdot \frac{1}{R}} = \frac{(\beta^2 + 1)PR}{\beta^2 P + R}$$

Assigning β times as much weight to recall as to precision)

- **F1-measure (balanced F-measure)**

» That is, when $\beta = 1$,
$$F_1 = \frac{2PR}{P + R}$$

Classifier Evaluation Metrics: Example

Actual Class\Predicted class	cancer = yes	cancer = no	Total	Recognition(%)
cancer = yes	90	210	300	30.00 (<i>sensitivity</i>)
cancer = no	140	9560	9700	98.56 (<i>specificity</i>)
Total	230	9770	10000	96.40 (<i>accuracy</i>)

$$\textit{Precision} = 90/230 = 39.13\%$$

$$\textit{Recall} = 90/300 = 30.00\%$$

Evaluating Classifier Accuracy: Holdout & Cross-Validation Methods

- **Holdout method**
 - Given data is randomly partitioned into two independent sets
 - Training set (e.g., $2/3$) for model construction
 - Test set (e.g., $1/3$) for accuracy estimation
 - Random sampling: a variation of holdout
 - Repeat holdout k times, accuracy = avg. of the accuracies obtained
- **Cross-validation** (k -fold, where $k = 10$ is most popular)
 - Randomly partition the data into k *mutually exclusive* subsets, each approximately equal size
 - At i -th iteration, use D_i as test set and others as training set
 - Leave-one-out: k folds where $k = \#$ of tuples, for small sized data
 - *Stratified cross-validation*: folds are stratified so that class dist. in each fold is approx. the same as that in the initial data


Evaluating Classifier Accuracy: Bootstrap

- **Bootstrap**
 - Works well with small data sets
 - Samples the given training tuples uniformly *with replacement*
 - Each time a tuple is selected, it is equally likely to be selected again and re-added to the training set
- Several bootstrap methods, and a common one is **.632 bootstrap**
 - A data set with d tuples is sampled d times, with replacement, resulting in a training set of d samples. The data tuples that did not make it into the training set end up forming the test set. About 63.2% of the original data end up in the bootstrap, and the remaining 36.8% form the test set (since $(1 - 1/d)^d \approx e^{-1} = 0.368$)
 - Repeat the sampling procedure k times, overall accuracy of the model:

$$Acc(M) = \frac{1}{k} \sum_{i=1}^k (0.632 \times Acc(M_i)_{test_set} + 0.368 \times Acc(M_i)_{train_set})$$

Model Selection: ROC Curves

- ROC (Receiver Operating Characteristics) curves: for visual comparison of classification models
- Originated from signal detection theory
- Shows the **trade-off between the true positive rate and the false positive rate**
- The area under the ROC curve is a measure of the accuracy of the model
- Rank the test tuples in decreasing order: the one that is most likely to belong to the positive class appears at the top of the list
- **The closer to the diagonal line (i.e., the closer the area is to 0.5), the less accurate is the model**
- **Vertical axis represents the true positive rate**
- **Horizontal axis rep. the false positive rate**
- The plot also shows a diagonal line
- **A model with perfect accuracy will have an area of 1.0**



Issues Affecting Model Selection


- **Accuracy**
 - classifier accuracy: predicting class label
- **Speed**
 - time to construct the model (training time)
 - time to use the model (classification/prediction time)
- **Robustness**: handling noise and missing values
- **Scalability**: efficiency in disk-resident databases
- **Interpretability**
 - understanding and insight provided by the model
- Other measures, e.g., goodness of rules, such as decision tree size or compactness of classification rules

Classification: Basic Concepts

- Classification: Basic Concepts
- Decision Tree Induction
- Bayes Classification Methods
- Model Evaluation and Selection
- **Techniques to Improve Classification Accuracy: Ensemble Methods**

Ensemble Methods: Increasing the Accuracy

- Ensemble methods
 - Use a **combination of models** to increase accuracy
 - Combine a series of k learned models, M_1, M_2, \dots, M_k , with the aim of creating an improved model M^*
- Popular **ensemble methods**
 - Bagging: averaging the prediction over a collection of classifiers
 - Boosting: weighted vote with a collection of classifiers
 - **Ensemble: combining a set of heterogeneous classifiers**



Bagging: Bootstrap Aggregation

- Analogy: Diagnosis based on multiple doctors' majority vote
- Training
 - Given a set D of d tuples, at each iteration i , a training set D_i of d tuples is sampled with replacement from D (i.e., bootstrap)
 - A classifier model M_i is learned for each training set D_i
- Classification: classify an unknown sample \mathbf{X}
 - Each classifier M_i returns its class prediction
 - The bagged classifier M^* counts the votes and assigns the class with the most votes to \mathbf{X}
- Prediction: can be applied to the prediction of continuous values by taking the average value of each prediction for a given test tuple
- Accuracy: Proved improved accuracy in prediction
 - Often significantly better than a single classifier derived from D
 - For noise data: not considerably worse, more robust

Boosting

- Analogy: Consult several doctors, based on a combination of weighted diagnoses—weight assigned based on the previous diagnosis accuracy
- How boosting works?
 - **Weights** are assigned to each training tuple
 - A series of k classifiers is iteratively learned
 - After a classifier M_i is learned, the weights are updated to allow the subsequent classifier, M_{i+1} , to **pay more attention to the training tuples that were misclassified** by M_i
 - The final **M^* combines the votes** of each individual classifier, where the weight of each classifier's vote is a function of its accuracy
- Boosting algorithm can be extended for numeric prediction
- Comparing with **bagging**: **Boosting** tends to have **greater accuracy**, but it also risks **overfitting** the model to misclassified data

Adaboost (Freund and Schapire, 1997)


- Given a set of d class-labeled tuples, $(\mathbf{X}_1, y_1), \dots, (\mathbf{X}_d, y_d)$
- Initially, all the weights of tuples are set the same ($1/d$)
- Generate k classifiers in k rounds. At round i ,
 - Tuples from D are sampled (with replacement) to form a training set D_i of the same size
 - Each tuple's chance of being selected is based on its weight
 - A classification model M_i is derived from D_i
 - Its error rate is calculated using D_i as a test set
 - If a tuple is misclassified, its weight is increased, o.w. it is decreased
- Error rate: $err(\mathbf{X}_j)$ is the misclassification error of tuple \mathbf{X}_j . Classifier M_i error rate is the sum of the weights of the misclassified tuples:
$$error(M_i) = \sum_j w_j \times err(\mathbf{X}_j)$$
- The weight of classifier M_i 's vote is $\log \frac{1 - error(M_i)}{error(M_i)}$

Random Forest (Breiman 2001)

- Random Forest:
 - Each classifier in the **ensemble** is a ***decision tree classifier*** and is generated using a **random selection of attributes** at each node to determine the split
 - During classification, each tree votes and the most popular class is returned
- Two Methods to construct Random Forest:
 - Forest-RI (*random input selection*): Randomly select, at each node, F attributes as candidates for the split at the node. The CART methodology is used to grow the trees to maximum size
 - Forest-RC (*random linear combinations*): Creates new attributes (or features) that are a linear combination of the existing attributes (reduces the correlation between individual classifiers)
- Comparable in accuracy to Adaboost, but more robust to errors and outliers
- Insensitive to the number of attributes selected for consideration at each split, and faster than bagging or boosting

Classification of Class-Imbalanced Data Sets

- Class-imbalance problem: Rare positive example but numerous negative ones, e.g., medical diagnosis, fraud, oil-spill, fault, etc.
- Traditional methods assume a balanced distribution of classes and equal error costs: not suitable for class-imbalanced data
- Typical methods in two-class classification:
 - **Oversampling**: re-sampling of data from positive class
 - **Under-sampling**: randomly eliminate tuples from negative class
 - **Threshold-moving**: move the decision threshold, t , so that the rare class tuples are easier to classify, and hence, less chance of costly false negative errors
 - **Ensemble techniques**: Ensemble multiple classifiers introduced above
- Still difficult for class imbalance problem on multiclass tasks



Summary

- Classification: Extracting models describing important data classes
- Effective and scalable methods
 - Decision tree induction, Naive Bayesian classification, rule-based classification, and many other classification methods
- Evaluation metrics:
 - Accuracy, sensitivity, specificity, precision, recall, F measure, and F_β measure
 - Stratified k-fold cross-validation is recommended for accuracy estimation
- Ensemble: Bagging and boosting can be used to increase overall accuracy by learning and combining a series of individual models
 - Adaboost
- **No single method has been found to be superior over all others for all data sets**

References

- C. Apte and S. Weiss. Data mining with decision trees and decision rules. *Future Generation Computer Systems*, 13, 1997
- P. K. Chan and S. J. Stolfo. Learning arbiter and combiner trees from partitioned data for scaling machine learning. *KDD'95*
- A. J. Dobson. *An Introduction to Generalized Linear Models*. Chapman & Hall, 1990.
- R. O. Duda, P. E. Hart, and D. G. Stork. *Pattern Classification*, 2ed. John Wiley, 2001
- U. M. Fayyad. Branching on attribute values in decision tree generation. *AAAI'94*.
- Y. Freund and R. E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *J. Computer and System Sciences*, 1997.
- J. Gehrke, R. Ramakrishnan, and V. Ganti. Rainforest: A framework for fast decision tree construction of large datasets. *VLDB'98*.
- J. Gehrke, V. Gant, R. Ramakrishnan, and W.-Y. Loh, BOAT -- Optimistic Decision Tree Construction. *SIGMOD'99*.
- T. Hastie, R. Tibshirani, and J. Friedman. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. Springer-Verlag, 2001.
- T.-S. Lim, W.-Y. Loh, and Y.-S. Shih. A comparison of prediction accuracy, complexity, and training time of thirty-three old and new classification algorithms. *Machine Learning*, 2000

References (cont.)

- J. Magidson. The Chaid approach to segmentation modeling: Chi-squared automatic interaction detection. In R. P. Bagozzi, editor, *Advanced Methods of Marketing Research*, Blackwell Business, 1994
- M. Mehta, R. Agrawal, and J. Rissanen. SLIQ : A fast scalable classifier for data mining. EDBT'96
- T. M. Mitchell. *Machine Learning*. McGraw Hill, 1997
- S. K. Murthy, Automatic Construction of Decision Trees from Data: A Multi-Disciplinary Survey, *Data Mining and Knowledge Discovery* 2(4): 345-389, 1998
- J. R. Quinlan. Induction of decision trees. *Machine Learning*, 1:81-106, 1986.
- J. R. Quinlan. *C4.5: Programs for Machine Learning*. Morgan Kaufmann, 1993.
- J. R. Quinlan. Bagging, boosting, and c4.5. AAAI'96.
- R. Rastogi and K. Shim. **Public: A decision tree classifier that integrates building and pruning.** VLDB'98
- J. Shafer, R. Agrawal, and M. Mehta. **SPRINT : A scalable parallel classifier for data mining.** VLDB'96
- J. W. Shavlik and T. G. Dietterich. **Readings in Machine Learning**. Morgan Kaufmann, 1990
- P. Tan, M. Steinbach, and V. Kumar. **Introduction to Data Mining**. Addison Wesley, 2005
- S. M. Weiss and C. A. Kulikowski. **Computer Systems that Learn: Classification and Prediction Methods from Statistics, Neural Nets, Machine Learning, and Expert Systems**. Morgan Kaufman, 1991
- S. M. Weiss and N. Indurkha. **Predictive Data Mining**. Morgan Kaufmann, 1997
- I. H. Witten and E. Frank. **Data Mining: Practical Machine Learning Tools and Techniques**, 2ed. Morgan Kaufmann, 2005