

3D shape analysis for early diagnosis of malignant lung nodules

Authors: [Ayman El-Baz](#) [Bioimaging Laboratory, Bioengineering Department, University of Louisville, Louisville, KY](#)
[Matthew Nitzken](#) [Bioimaging Laboratory, Bioengineering Department, University of Louisville, Louisville, KY](#)
[Fahmi Khalifa](#) [Bioimaging Laboratory, Bioengineering Department, University of Louisville, Louisville, KY](#)
[Ahmed Elnakib](#) [Bioimaging Laboratory, Bioengineering Department, University of Louisville, Louisville, KY](#)
[Georgy Gimel'farb](#) [Department of Computer Science, University of Auckland, Auckland, New Zealand](#)
[Robert Falk](#) [Department of Radiology, Jewish Hospital, Louisville, KY](#)
[Mohammed Abo El-Ghar](#) [Urology and Nephrology Department, University of Mansoura, Mansoura, Egypt](#)



2011 Article

**Bibliometrics**

- Downloads (6 Weeks): 0
- Downloads (12 Months): 0
- Citation Count: 0

Tools and Resources[Save to Binder](#)

Export Formats:

[BibTeX](#) [EndNote](#) [ACM Ref](#)[Publisher Site](#)

Share:

|

Tags: [diagnosis](#) [lung nodules](#)
[shape](#) [spherical harmonics](#)

Published in:

· Proceeding

IPMI'11 Proceedings of the 22nd international conference on Information processing in medical imaging

Springer-Verlag Berlin, Heidelberg ©2011

[table of contents](#) ISBN: 978-3-642-22091-3[Feedback](#)| Switch to [single page view](#) (no tabs)
[Abstract](#) [Authors](#) [References](#) [Cited By](#) [Index Terms](#) [Publication](#) [Reviews](#) [Comments](#) [Table of Contents](#)

An alternative method for diagnosing malignant lung nodules by their shape rather than conventional growth rate is proposed. The 3D surfaces of the detected lung nodules are delineated by spherical harmonic analysis, which represents a 3D surface of the lung nodule supported by the unit sphere with a linear combination of special basis functions, called spherical harmonics (SHs). The proposed 3D shape analysis is carried out in five steps: (i) 3D lung nodule segmentation with a deformable 3D boundary controlled by two probabilistic visual appearance models (the learned prior and the estimated current appearance one); (ii) 3D Delaunay triangulation to construct a 3D mesh model of the segmented lung nodule surface; (iii) mapping this model to the unit sphere; (iv) computing the SHs for the surface, and (v) determining the number of the SHs to delineate the lung nodule. We describe the lung nodule shape complexity with a new shape index, the estimated number of the SHs, and use it for the K -nearest classification to distinguish malignant and benign lung nodules. Preliminary experiments on 327 lung nodules (153 malignant and 174 benign) resulted in the 93.6% correct classification (for the 95% confidence interval), showing that the proposed method is a promising supplement to current technologies for the early diagnosis of lung cancer.

Powered by **THE ACM GUIDE TO COMPUTING LITERATURE**

The ACM Digital Library is published by the Association for Computing Machinery. Copyright © 2012 ACM, Inc.

[Terms of Usage](#) [Privacy Policy](#) [Code of Ethics](#) [Contact Us](#)Useful downloads: [Adobe Acrobat](#) [QuickTime](#) [Windows Media Player](#) [Real Player](#)

