

How to use YZ-HPC

Department of Physics
Shahjalal University of Science and Technology
Sylhet - 3114, Bangladesh

Support : | `yz-hpc@sust.edu`

1 Getting started with the HPC

1.1 How do I get access to the HPC

Fill out the appropriate tab of the HPC Access Request Form. Access is typically granted within few business days.

1.2 How do I login in the system

Only SSH access is available to login in the system. Any SSH client from various Operating System can be used. Additionally a web browser can be used to get login (firefox, google-chrome, Internet Explorer and Microsoft edges were tested).

1.2.1 From web browser

url `https://10.100.11.71:443`

Permission Accept the secure access

localhost `10.100.11.71`

Port `22`

username `USERNAME`

password `PASSWORD`

1.3 How do I run my jobs on the HPC

See the documents below sections for basic examples of several types of jobs on the HPC system.

- HPC Sample Job: OpenMPI
- HPC Sample Job: LAMMPS
- HPC Sample Job: Gaussian

1.4 How many jobs can I run?

1.5 Why are some of my jobs stuck in the queue?

2 HPC Sample Job: OpenMPI

2.1 Overview

This document shows a very simple "Hello, World!" type program using OpenMPI libraries, adapted from MPI Tutorial: MPI Hello World.

`mpi_hw.c`

```
#include <mpi.h>
#include <stdio.h>

int main(int argc, char** argv) {
    MPI_Init(NULL, NULL);
    int world_size;
    MPI_Comm_size(MPI_COMM_WORLD, &world_size);
    int world_rank;
    MPI_Comm_rank(MPI_COMM_WORLD, &world_rank);
    char processor_name[MPI_MAX_PROCESSOR_NAME];
    int name_len;
    MPI_Get_processor_name(processor_name, &name_len);
    printf("Hello world from processor %s, rank %d"
           " out of %d processors\n",
           processor_name, world_rank, world_size);
    MPI_Finalize();
}
```

2.2 Loading OpenMPI

There are two different version of openMPI available for computing. They are version 2.1.3 and 3.0.0. Use module tools to load the appropriate version of the MPI.

```
$ module load openMPI
```

2.3 Compiling

On the login node or a compute node, the source can be compiled after the module loaded as:

```
$ mpicc -o mpi_hw mpi_hw.c
```

2.4 Running the compiled code

No one should run an MPI code directly in the HPC. Use batch script to submit as a job on the system.

2.5 Running MPI in batch

Make a Slurm job script named mpi_hw.sh with the following contents.

mpi_hw.sh

```
#!/bin/bash
$SBATCH --node=2
$SBATCH --job-name=mpi_hw
$SBATCH --output=mpi_hw

module load openMPI

mpicc -o mpi_hw mpi_hw.c

mpirun ./mpi_hw
```

2.6 Submitting job in Queue

```
$ sbatch mpi_hw.sh
```