

How to use YZ-HPC

Department of Physics
Shahjalal University of Science and Technology
Sylhet - 3114, Bangladesh

Support : | yz-hpc@sust.edu

Contents

| | | |
|----------|--|----------|
| 1 | Getting started with the HPC | 1 |
| 1.1 | How do I get access to the HPC | 1 |
| 1.2 | YZ-HPC Documentation | 2 |
| 1.3 | How do I login in the system | 2 |
| 1.3.1 | From web browser | 2 |
| 1.4 | How do I run my jobs on the HPC | 2 |
| 1.5 | How many jobs can I run? | 2 |
| 1.6 | Why are some of my jobs stuck in the queue? | 2 |
| 2 | How do I use TextEditor | 2 |
| 2.1 | Documentation on TextEditor | 2 |
| 3 | How do I transfer file into/from YZ-HPC | 2 |
| 3.1 | Documentation on File Transfer | 3 |
| 4 | HPC Sample Job: OpenMPI | 3 |
| 4.1 | Overview | 3 |
| 4.2 | Loading OpenMPI | 3 |
| 4.3 | Compiling | 3 |
| 4.4 | Running the compiled code | 3 |
| 4.5 | Running MPI in batch | 3 |
| 4.6 | Submitting job in Queue | 4 |
| 4.7 | Useful Links for openMPI | 4 |

1 Getting started with the HPC

The configuration of YZ-HPC is described below:

- Hardware
 - Compute Node: 05
 - * CPU: Intel Xeon 4-core 2.1 GHz
 - * RAM: 8 GB 800 MHz
 - Compute Node: 16
 - * CPU: Intel Core 2 Duo 2.6 GHz
 - * RAM: 4 GB 800 MHz
 - Total Core: 52 Compute Core
 - Total RAM: 104 GB
- Software

- OS: **Telisc OS**
- Module Environment: **lmod**
- Task/Job Management and Scheduler: **SLURM**
- Computation Software: OpenMPI (Version 2.1.3 and 3.0.0)
- Molecular Dynamics: LAMMPS
- Computational Chemistry: Gaussian (g09)

1.1 How do I get access to the HPC

Fill out the appropriate tab of the HPC Access Request Form. Access is typically granted within few business days. Before requesting access, a minimum experience with the followings are expected:

- How to work on Linux Terminal
- How to write within Linux Terminal (with vim/nano)
- Basics of OpenMPI
- File transfer tools (rsync, FileZilla, WinSCP etc.)

1.2 YZ-HPC Documentation

All the documentation are described briefly at <http://yz-hpc.phy.edu>. An HPC Access Request Form or Registration form is available for registering into YZ-HPC. A username with password will be sent to the user after the registration completion. Those username and password is very important for login.

NOTE: DO NOT CHANGE THE PASSWORD.

1.3 How do I login in the system

Only SSH access is available to login in the system. Any SSH client from various Operating System can be used. Additionally a web browser can be used to get login (firefox, google-chrome, Internet Explorer and Microsoft edges were tested).

1.3.1 From web browser

url <http://yz-hpc.phy.edu>

CLI Click **Go to Command Line Interface**

Permission Accept the secure access

localhost 10.100.11.71

Port 22

username USERNAME

password PASSWORD

A login shell will be available if everything goes fine.

1.4 How do I run my jobs on the HPC

See the documents below sections for basic examples of several types of jobs on the HPC system.

- HPC Sample Job: OpenMPI
- HPC Sample Job: LAMMPS
- HPC Sample Job: Gaussian

1.5 How many jobs can I run?

1.6 Why are some of my jobs stuck in the queue?

2 How do I use TextEditor

By default vim and nano text editor is provided in the YZ-HPC because of their simplicity.

2.1 Documentation on TextEditor

- Vim (An online tutorial is available at [here](#))
- Nano (A simple tutorial is available at [here](#))

3 How do I transfer file into/from YZ-HPC

Any standard SSH tool can be used to transfer files between HPC and client computer. The rsync, WinSCP are Filezilla very useful tools.

3.1 Documentation on File Transfer

4 HPC Sample Job: OpenMPI

4.1 Overview

This document shows a very simple "Hello, World!" type program using OpenMPI libraries, adapted from MPI Tutorial: MPI Hello World.

mpi_hw.c

```
#include <mpi.h>
#include <stdio.h>

int main(int argc, char** argv) {
    MPI_Init(NULL, NULL);
    int world_size;
    MPI_Comm_size(MPI_COMM_WORLD, &world_size);
    int world_rank;
    MPI_Comm_rank(MPI_COMM_WORLD, &world_rank);
    char processor_name[MPI_MAX_PROCESSOR_NAME];
    int name_len;
    MPI_Get_processor_name(processor_name, &name_len);
    printf("Hello world from processor %s, rank %d"
           " out of %d processors\n",
           processor_name, world_rank, world_size);
    MPI_Finalize();
}
```

4.2 Loading OpenMPI

There are two different version of openMPI available for computing. They are version 2.1.3 and 3.0.0. Use module tools to load the appropriate version of the MPI.

```
$ module load openMPI
```

4.3 Compiling

On the login node or a compute node, the source can be compiled after the module loaded as:

```
$ mpicc -o mpi_hw mpi_hw.c
```

4.4 Running the compiled code

No one should run an MPI code directly in the HPC. Use batch script to submit as a job on the system.

4.5 Running MPI in batch

Make a Slurm job script named mpi_hw.sh with the following contents.

mpi_hw.sh

```
#!/bin/bash
#SBATCH --node=2
#SBATCH --job-name=mpi_hw
#SBATCH --output=mpi_hw

module load openMPI

mpicc -o mpi_hw mpi_hw.c

mpirun ./mpi_hw
```

4.6 Submitting job in Queue

```
$ sbatch mpi_hw.sh
```

4.7 Useful Links for openMPI

- [MPI tutorial](#)
- [MPI tutorial](#)