



UPPSALA  
UNIVERSITET

# Reinforcement Learning

## Lecture 2 - Markov Decision Processes

---


Per Mattsson


2022

Department of Information Technology

# Repetition


---





- **Markov property:** State contains all information that is useful to predict future:


$$p(S_{t+1}|S_t, A_t, S_{t-1}, A_{t-1}, \dots, S_0, A_0) = p(S_{t+1}|S_t, A_t).$$



- **Markov property:** State contains all information that is useful to predict future:

$$p(S_{t+1}|S_t, A_t, S_{t-1}, A_{t-1}, \dots, S_0, A_0) = p(S_{t+1}|S_t, A_t).$$


- **Policy:**  $\pi(a|s)$  (probability of choosing  $a$  when we are in state  $s$ ).



- **Markov property:** State contains all information that is useful to predict future:

$$p(S_{t+1}|S_t, A_t, S_{t-1}, A_{t-1}, \dots, S_0, A_0) = p(S_{t+1}|S_t, A_t).$$

- **Policy:**  $\pi(a|s)$  (probability of choosing  $a$  when we are in state  $s$ ).
- **Prediction:** Following a policy, what will the future cumulative reward be?



- **Markov property:** State contains all information that is useful to predict future:

$$p(S_{t+1}|S_t, A_t, S_{t-1}, A_{t-1}, \dots, S_0, A_0) = p(S_{t+1}|S_t, A_t).$$

- **Policy:**  $\pi(a|s)$  (probability of choosing  $a$  when we are in state  $s$ ).
- **Prediction:** Following a policy, what will the future cumulative reward be?
- **Control:** Find the policy that maximize the cumulative future reward.

# Markov Decision Process (MDP)

---



- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.

- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.
- **Transition probabilities:**

$$p(s', r | s, a) = \Pr\{S_{t+1} = s', R_{t+1} = r | S_t = s, A_t = a\}$$

- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.
- **Transition probabilities:**

$$p(s', r | s, a) = \Pr\{S_{t+1} = s', R_{t+1} = r | S_t = s, A_t = a\}$$

- **Markov property:** Completely determines the *dynamics* of the environment.

- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.
- **Transition probabilities:**

$$p(s', r | s, a) = \Pr\{S_{t+1} = s', R_{t+1} = r | S_t = s, A_t = a\}$$

- **Markov property:** Completely determines the *dynamics* of the environment.
- **The expected reward:**

$$r(s, a) = \mathbb{E}[R_{t+1} | S_t = s, A_t = a]$$

- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.
- **Transition probabilities:**

$$p(s', r | s, a) = \Pr\{S_{t+1} = s', R_{t+1} = r | S_t = s, A_t = a\}$$

- **Markov property:** Completely determines the *dynamics* of the environment.
- **The expected reward:**


$$r(s, a) = \mathbb{E}[R_{t+1} | S_t = s, A_t = a] = \sum_{r \in \mathcal{R}} \sum_{s' \in \mathcal{S}} r p(s', r | s, a)$$

- Assume that  $\mathcal{S}$ ,  $\mathcal{A}$  and  $\mathcal{R}$  all have a finite number of elements.
- **Transition probabilities:**


$$p(s', r | s, a) = \Pr\{S_{t+1} = s', R_{t+1} = r | S_t = s, A_t = a\}$$

- **Markov property:** Completely determines the *dynamics* of the environment.
- **The expected reward:**

$$r(s, a) = \mathbb{E}[R_{t+1} | S_t = s, A_t = a] = \sum_{r \in \mathcal{R}} \sum_{s' \in \mathcal{S}} r p(s', r | s, a) = \sum_{r, s'} r p(s', r | s, a).$$




## Example: Study or Facebook?



- **States:** Knowledge 0, Knowledge 1, Knowledge 2, Pass exam (terminating).
- **Actions:** Study or Facebook.




## Example: Study or Facebook?




- **States:** Knowledge 0, Knowledge 1, Knowledge 2, Pass exam (terminating).
- **Actions:** Study or Facebook.

## Example: Study or Facebook?



- **States:** Knowledge 0, Knowledge 1, Knowledge 2, Pass exam (terminating).
- **Actions:** Study or Facebook.

## Example: Study or Facebook?



- **States:** Knowledge 0, Knowledge 1, Knowledge 2, Pass exam (terminating).
- **Actions:** Study or Facebook.

## Episodic tasks:

- Has terminating states, and the task ends in finite time.

## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.

## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.
- **Example:** Taxi environment or “Study or Facebook”-MDP.

## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.
- **Example:** Taxi environment or “Study or Facebook”-MDP.
- “If you reach a terminating state, you will stay there forever and receive no future reward.”

## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.
- **Example:** Taxi environment or “Study or Facebook”-MDP.
- “If you reach a terminating state, you will stay there forever and receive no future reward.”

## Continuing tasks:

- Often not a clear way to divide up the task into independent episodes.



## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.
- **Example:** Taxi environment or “Study or Facebook”-MDP.
- “If you reach a terminating state, you will stay there forever and receive no future reward.”

## Continuing tasks:

- Often not a clear way to divide up the task into independent episodes.
- **Example:** Keep balancing the pendulum. No state where the task is done.

## Episodic tasks:

- Has terminating states, and the task ends in finite time.
- If you reach a terminating state the episode stops.
- **Example:** Taxi environment or “Study or Facebook”-MDP.
- “If you reach a terminating state, you will stay there forever and receive no future reward.”

## Continuing tasks:

- Often not a clear way to divide up the task into independent episodes.
- **Example:** Keep balancing the pendulum. No state where the task is done.
- We have to take into account infinitely many future rewards.

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

The return

$$G_t = R_{t+1} + R_{t+2} + R_{t+3} + \dots = \sum_{k=0}^{\infty} R_{t+k+1}$$

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

## The discounted return

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1}, \text{ where } 0 < \gamma \leq 1.$$

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

## The discounted return

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1}, \text{ where } 0 < \gamma \leq 1.$$

## The discount rate $\gamma$ :

- If  $\gamma < 1$ , we put less value on future rewards.

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

## The discounted return

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1}, \text{ where } 0 < \gamma \leq 1.$$

## The discount rate $\gamma$ :

- If  $\gamma < 1$ , we put less value on future rewards.
- If  $\gamma < 1$ ,  $G_t$  will be finite as long as  $R_k$  are bounded!

- In a given state we want to maximize future rewards  $R_{t+1}, R_{t+2}, \dots$

## The discounted return

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1}, \text{ where } 0 < \gamma \leq 1.$$

## The discount rate $\gamma$ :

- If  $\gamma < 1$ , we put less value on future rewards.
- If  $\gamma < 1$ ,  $G_t$  will be finite as long as  $R_k$  are bounded!
- It is sometimes possible to use undiscounted returns ( $\gamma = 1$ ), e.g., if the task always ends after a finite number of steps.



# Value Functions

---

- Note that  $S_t$  and  $R_t$  etc are random variables.

- Note that  $S_t$  and  $R_t$  etc are random variables.
- Hence the return is also a random variable:

$$G_t = R_{t+1} + \gamma R_{t+2} + \dots$$

- Note that  $S_t$  and  $R_t$  etc are random variables.
- Hence the return is also a random variable:

$$G_t = R_{t+1} + \gamma R_{t+2} + \dots$$

- We thus consider the *expected* return.

- Note that  $S_t$  and  $R_t$  etc are random variables.
- Hence the return is also a random variable:

$$G_t = R_{t+1} + \gamma R_{t+2} + \dots$$

- We thus consider the *expected* return.

## The state-value function

The *state-value function*  $v_\pi(s)$  of an MDP is the expected return starting from state  $s$ , and then following policy  $\pi$ :

$$v_\pi(s) = \mathbb{E}_\pi[G_t | S_t = s].$$

- Note that  $S_t$  and  $R_t$  etc are random variables.
- Hence the return is also a random variable:

$$G_t = R_{t+1} + \gamma R_{t+2} + \dots$$

- We thus consider the *expected* return.

## The state-value function

The *state-value function*  $v_\pi(s)$  of an MDP is the expected return starting from state  $s$ , and then following policy  $\pi$ :


$$v_\pi(s) = \mathbb{E}_\pi[G_t | S_t = s].$$

- **Prediction:** Compute  $v_\pi(s)$ .

# Example

**Discount:**  $\gamma = 0.9$ .


**Policy:**  $\pi(a|s) = 0.5$  for all  $a$  and  $s$ .



# Example

**Discount:**  $\gamma = 0.9$ .


**Policy:**  $\pi(a|s) = 0.5$  for all  $a$  and  $s$ .





**Discount:**  $\gamma = 0.9$ .

**Policy:** Always choose **study**.



- Another important value function is the *action-value function*.

## The action-value function

The *action-value function*  $q_\pi(s, a)$  is the expected return starting from  $s$ , taking action  $a$ , and then following a policy  $\pi$

$$q_\pi(s, a) = \mathbb{E}_\pi[G_t | S_t = s, A_t = a].$$


- Often called the  $Q$ -function.

# Example

**Discount:**  $\gamma = 0.9$ .

**Policy:** Always choose **study**.


**Action-values,  $q$ .**



**Discount:**  $\gamma = 0.9$ .

**Policy:** Always choose **study**.

**Action-values,  $q$ .**



“If I just this one time choose **Facebook**, and after that follow the policy (always **Study**), what will my expected discounted **return** be?”

## Bellman equations

---

- Return: Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots =$$

- Return: Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \cdots = R_{t+1} + \gamma G_{t+1}.$$

- **Return:** Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = R_{t+1} + \gamma G_{t+1}.$$

- Hence, the value function satisfies to following equation:

$$v_\pi(s) = \mathbb{E}_\pi[G_t | S_t = s]$$



- **Return:** Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \cdots = R_{t+1} + \gamma G_{t+1}.$$

- Hence, the value function satisfies to following equation:

$$\begin{aligned} v_\pi(s) &= \mathbb{E}_\pi[G_t | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma G_{t+1} | S_t = s] \end{aligned}$$

- **Return:** Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = R_{t+1} + \gamma G_{t+1}.$$

- Hence, the value function satisfies to following equation:

$$\begin{aligned} v_\pi(s) &= \mathbb{E}_\pi[G_t | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma G_{t+1} | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma v_\pi(S_{t+1}) | S_t = s] \end{aligned}$$

- **Return:** Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = R_{t+1} + \gamma G_{t+1}.$$

- Hence, the value function satisfies to following equation:

$$\begin{aligned} v_\pi(s) &= \mathbb{E}_\pi[G_t | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma G_{t+1} | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma v_\pi(S_{t+1}) | S_t = s] \end{aligned}$$

- “The value of  $s$  is the expected immediate **reward** plus the discounted expected value of the next **state**”.

- **Return:** Note that

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots = R_{t+1} + \gamma G_{t+1}.$$


- Hence, the value function satisfies to following equation:


$$\begin{aligned} v_\pi(s) &= \mathbb{E}_\pi[G_t | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma G_{t+1} | S_t = s] \\ &= \mathbb{E}_\pi[R_{t+1} + \gamma v_\pi(S_{t+1}) | S_t = s] \end{aligned}$$

- “The value of  $s$  is the expected immediate **reward** plus the discounted expected value of the next **state**”.
- In the same way

$$q_\pi(s, a) = \mathbb{E}_\pi[R_{t+1} + \gamma q_\pi(S_{t+1}, A_{t+1}) | S_t = s, A_t = a].$$


$$v_{\pi}(s) = \mathbb{E}_{\pi}[R_{t+1} + \gamma v_{\pi}(S_{t+1}) | S_t = s]$$





- The state-value of  $s$  is the expected action-value:


$$v_\pi(s) = \sum_a \pi(a|s) q_\pi(s, a).$$



- The state-value of  $s$  is the expected action-value:

$$v_\pi(s) = \sum_a \pi(a|s) q_\pi(s, a).$$


- For a deterministic policy  $a = \pi(s)$  we get  $v_\pi(s) = q_\pi(s, \pi(s))$ .



- Given  $s$  and  $a$ , the immediate reward  $r$  and the next state  $s'$  has prob  $p(s', r | s, a)$ .  
So,


$$q_\pi(s, a) =$$






- Given  $s$  and  $a$ , the immediate reward  $r$  and the next state  $s'$  has prob  $p(s', r|s, a)$ .  
So,


$$q_\pi(s, a) = \sum_{r, s'} p(s', r|s, a)(r + \gamma v_\pi(s')).$$



$$v_\pi(s) = \sum_a \pi(a|s) q_\pi(s, a)$$



$$\begin{aligned} v_\pi(s) &= \sum_a \pi(a|s) q_\pi(s, a) \\ &= \sum_a \pi(a|s) \sum_{r, s'} p(s', r|s, a) [r + \gamma v_\pi(s')]. \end{aligned}$$




$$q_\pi(s, a) = \sum_{r, s'} p(s', r | s, a) \left[ r + \gamma \sum_{a'} \pi(a' | s') q_\pi(s', a') \right]$$

# Example

**Discount:**  $\gamma = 0.9$ .


**Policy:**  $\pi(a|s) = 0.5$  for all  $a$  and  $s$ .



$$v_{\pi}(s) = \sum_a \pi(a|s) q_{\pi}(s, a), \quad q_{\pi}(s, a) = \sum_{r, s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

**Discount:**  $\gamma = 0.9$ .

**Policy:**  $\pi(a|s) = 0.5$  for all  $a$  and  $s$ .



$$v_{\pi}(s) = \sum_a \pi(a|s) q_{\pi}(s, a), \quad q_{\pi}(s, a) = \sum_{r, s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

$$4.78 = \underbrace{0.5}_{\pi(\text{facebook}|s)} \times \underbrace{\gamma[0.5 \times 3.00 + 0.5 \times 4.78]}_{q_{\pi}(s, \text{facebook})} + \underbrace{0.5}_{\pi(\text{study}|s)} \times \underbrace{[-1 + \gamma \times 7.84]}_{q_{\pi}(s, \text{study})}$$

$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .

$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .
- One equation for each  $s \in \mathcal{S}$ .



$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .
- One equation for each  $s \in \mathcal{S}$ .
- A unique solution, that can be expressed analytically.

$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .
- One equation for each  $s \in \mathcal{S}$ .
- A unique solution, that can be expressed analytically.
- If  $\mathcal{S}$  is large, more efficient to use iterative solutions (Lecture 3).

$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .
- One equation for each  $s \in \mathcal{S}$ .
- A unique solution, that can be expressed analytically.
- If  $\mathcal{S}$  is large, more efficient to use iterative solutions (Lecture 3).
- If  $p(s', r|s, a)$  is not known, we have to learn  $v_{\pi}(s)$  from experience (Lecture 4).

$$v_{\pi}(s) = \sum_a \pi(a|s) \sum_{r,s'} p(s', r|s, a) [r + \gamma v_{\pi}(s')].$$

- A system of linear equations in  $v_{\pi}(s)$ .
- One equation for each  $s \in \mathcal{S}$ .
- A unique solution, that can be expressed analytically.
- If  $\mathcal{S}$  is large, more efficient to use iterative solutions (Lecture 3).
- If  $p(s', r|s, a)$  is not known, we have to learn  $v_{\pi}(s)$  from experience (Lecture 4).
- If  $\mathcal{S}$  is infinite, we can't compute the value for each state individually, and instead have find some function  $\hat{v}(s, \mathbf{w}) \approx v_{\pi}(s)$ . (Second part of course)

## Optimal Value Functions

---


- Optimal state-value function:

$$v_*(s) = \max_{\pi} v_{\pi}(s), \quad \text{for all } s \in \mathcal{S}.$$


- Optimal action-value function:

$$q_*(s, a) = \max_{\pi} q_{\pi}(s, a), \quad \text{for all } s \in \mathcal{S} \text{ and } a \in \mathcal{A}.$$

The optimal  $v_*(s)$  should be the maximum of  $q_*(s, a)$ .




$$v_*(s) = \max_a q_*(s, a).$$




$$q_*(s, a) = \sum_{r, s'} p(s', r | s, a) (r + \gamma v_*(s')).$$




# The Bellman equation for $v_*$




$$v_*(s) = \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')]$$



$$\begin{aligned} v_*(s) &= \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')] \\ &= \max_a \mathbb{E}[R_{t+1} + \gamma v_*(S_{t+1}) | S_t = s, A_t = a] \end{aligned}$$



$$q_*(s, a) = \sum_{r, s'} p(s', r | s, a) \left[ r + \gamma \max_{a'} q_*(s', a') \right]$$



$$\begin{aligned} q_*(s, a) &= \sum_{r, s'} p(s', r | s, a) \left[ r + \gamma \max_{a'} q_*(s', a') \right] \\ &= \mathbb{E}[R_{t+1} + \gamma \max_{a'} q_*(S_{t+1}, a') | S_t = s, A_t = a] \end{aligned}$$

$$v_*(s) = \max_a \sum_{r,s'} p(s', r | s, a) [r + \gamma v_*(s')]$$

- A system of *non*-linear equations.

$$v_*(s) = \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')]$$

- A system of *non*-linear equations.
- One equation for each  $s$ .

$$v_*(s) = \max_a \sum_{r,s'} p(s', r | s, a) [r + \gamma v_*(s')]$$

- A system of *non*-linear equations.
- One equation for each  $s$ .
- In general no closed-form solution!

$$v_*(s) = \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')]$$

- A system of *non*-linear equations.
- One equation for each  $s$ .
- In general no closed-form solution!
- But there are iterative solution methods (Lecture 3).



## Optimal Policy

---

**Partial ordering over policies:**

$$\pi \geq \pi' \text{ if } v_{\pi}(s) \geq v_{\pi'}(s), \text{ for all } s.$$

## Partial ordering over policies:

$$\pi \geq \pi' \text{ if } v_{\pi}(s) \geq v_{\pi'}(s), \text{ for all } s.$$

### Theorem

- There exists (at least one) optimal policy  $\pi_*$  such that  $\pi_* \geq \pi$  for all policies  $\pi$ .

## Partial ordering over policies:

$$\pi \geq \pi' \text{ if } v_{\pi}(s) \geq v_{\pi'}(s), \text{ for all } s.$$

### Theorem


- There exists (at least one) optimal policy  $\pi_*$  such that  $\pi_* \geq \pi$  for all policies  $\pi$ .
- All optimal policies achieve the optimal state-value function  $v_{\pi_*}(s) = v_*(s)$ .

## Partial ordering over policies:

$$\pi \geq \pi' \text{ if } v_{\pi}(s) \geq v_{\pi'}(s), \text{ for all } s.$$

### Theorem

- There exists (at least one) optimal policy  $\pi_*$  such that  $\pi_* \geq \pi$  for all policies  $\pi$ .
- All optimal policies achieve the optimal state-value function  $v_{\pi_*}(s) = v_*(s)$ .
- All optimal policies achieve the optimal action-value function  $q_{\pi_*}(s, a) = q_*(s, a)$ .



What to do in state  $s$ ?

1. Choose an  $a$  that maximize the optimal action-value  $q_*(s, a)$ .
2. Then use an optimal policy from  $s'$ .

- **Control:** Find optimal policy.

- **Control:** Find optimal policy.
- The policy

$$\pi_*(s) = \arg \max_a q_*(s, a)$$

is optimal.



- **Control:** Find optimal policy.
- The policy

$$\pi_*(s) = \arg \max_a q_*(s, a) = \arg \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')]$$

is optimal.


- **Control:** Find optimal policy.
- The policy

$$\pi_*(s) = \arg \max_a q_*(s, a) = \arg \max_a \sum_{r, s'} p(s', r | s, a) [r + \gamma v_*(s')]$$


is optimal.

- **Note:** If we know  $q_*(s, a)$  we don't need the dynamics to find an optimal policy!

## Example: Optimal state-value and action-value




## Example: Optimal policy



**Optimal policy:** Always study!

## Example: Optimal policy



**Optimal policy:** Always study!

...according to this MDP. In real life it may be good to take a break once in a while.

- Markov Decision Processes
- Discounted return
- Value functions
- Bellman equations

- Markov Decision Processes
- Discounted return
- Value functions
- Bellman equations

## Next:

- Find value functions and optimal policy if  $p(s', r|s, a)$  is known. (Lecture 3)
- What if  $p(s', r|s, a)$  is not known? (Lecture 4-5)
- Tinkering Notebook 2: You can do Section 1-5 now.
- Assignment 1: You can look at Problem 1 – Problem 3a.