

ANDROID DEVELOPMENT

Class 4: State & Lists

The Core Loop: Handling Interactivity and Data

Instructor: Mark Joseli


| Today's Goal

Making apps **interactive** and handling dynamic **lists**.

⚡ Understand Recomposition

🏠 Manage State


☰ Build Scrollable Lists



| Theory: Recomposition

Compose functions can execute frequently and in any order.

- > **Recomposition:** The process of re-running composable functions when their **State** changes.
- > Compose is optimistic: it only updates the parts of the UI that actually changed.



State: `mutableStateOf`

To make Compose react to changes, you need **State**.

```
val count = mutableStateOf(0) // Later in UI...  
Text(text = "Count: ${count.value}") Button(onClick  
= { count.value++ })
```

Any Composable reading `count.value` will strictly "subscribe" to it and update automatically.




Observes changes automatically.

Memory: remember

Recomposition destroys and recreates local variables. We need to **remember** the value across updates.

```
var count by remember { mutableStateOf(0) }  
Button(onClick = { count++ }) { Text("Clicks:  
$count") }
```

Without **remember**, the count would reset to 0 every time the screen updates.



| State Hoisting

Moving state up to the caller to make components reusable.



Stateful

A component that holds its own state. Hard to reuse or test.



The Pattern

Pass data **down** (parameters).
Pass events **up** (lambdas).




Stateless

A component that just displays what it's told. Pure and reusable.

| Lists: LazyColumn

Why not just use Column?

- > Column renders **everything** at once. Bad for performance if you have 100+ items.
- > LazyColumn only renders what is currently visible on screen.
- > It is the modern replacement for RecyclerView.




LazyColumn Code

Simple and concise syntax.

```
LazyColumn { items(messages) { message →  
    MessageRow(message) } }
```


We pass a list of data, and define how **one** single row should look. Compose handles the scrolling and recycling.



| Design: **Material 3**

Google's latest design system.


- **Dynamic Color:** UI adapts to the user's wallpaper.
- **Modern Components:** Updated Cards, Buttons, and Navigation bars.
- Implemented via the `MaterialTheme` composable.



Structure: Scaffold

Provides the standard structure for a screen (TopBar, FAB, BottomBar).

```
Scaffold( topBar = { TopAppBar(title = {  
Text("Home") }) } ) { padding → // Screen content  
goes here Box(Modifier.padding(padding)) }
```



Questions?


Let's implement a dynamic list!

Image Sources



<https://cdn.dribbble.com/userupload/6460022/file/original-9a54e848ba3bcf8a80f24b815130d338.png?resize=752x&vertical=center>

Source: dribbble.com



<https://developer.android.com/static/develop/ui/compose/images/lifecycle-newelement-top-all-recompose.png>

Source: developer.android.com



<https://cdn.dribbble.com/userupload/32581025/file/original-3193faaac0052c28c989e5c59f61545e.jpg?resize=400x0>

Source: dribbble.com



<https://cdn.dribbble.com/userupload/5891622/file/original-2feb32f4b93befefb388bd449b9e206e.jpg?resize=752x&vertical=center>

Source: dribbble.com



https://miro.medium.com/v2/resize:fit:1400/0*0TsUyrLKDw94DzVA

Source: medium.com



https://lh3.googleusercontent.com/R6NchWHyVf-clBxfBYoBw7-5iz6ymHQR5DUgW5NzIOZRCArjukJnXOMh5kQZVzEEauU64zRGfzAhXYDeITEGF_4mC-8UIJg44nnOaZFths4=s0

Source: m3.material.io