

# Starling

*Animated renderings of data structures for teaching*

Manual for v0.2.0

## Contents

|                                                            |    |
|------------------------------------------------------------|----|
| 1. Introduction .....                                      | 3  |
| 1.1. Quick start .....                                     | 3  |
| 2. Architecture .....                                      | 5  |
| 2.1. Snapshots, frames, and the renderer .....             | 5  |
| 2.2. Path identity .....                                   | 6  |
| 2.3. Sticky animation accumulation .....                   | 7  |
| 2.4. The cetz integration .....                            | 7  |
| 3. Design decisions .....                                  | 7  |
| 3.1. Why frames, not a wrap callback .....                 | 7  |
| 3.2. Three theme layers, one per concern .....             | 8  |
| 3.3. Frames carry builders, not pre-rendered content ..... | 8  |
| 3.4. State for ergonomics, per-call for perf .....         | 9  |
| 3.5. Two-channel captions .....                            | 9  |
| 3.6. The six-frame rotation .....                          | 10 |
| 3.7. Path-based anchors and the cetz tree quirk .....      | 10 |
| 4. BST animations tour .....                               | 11 |
| 4.1. Static display .....                                  | 11 |
| 4.2. Search .....                                          | 11 |
| 4.3. Insert .....                                          | 12 |
| 4.4. Delete .....                                          | 14 |
| 4.5. Rotate .....                                          | 16 |
| 4.6. Traversals .....                                      | 19 |
| 5. RBT animations tour .....                               | 22 |
| 5.1. Static display .....                                  | 23 |
| 5.2. Insert .....                                          | 23 |
| 5.3. Delete .....                                          | 26 |
| 5.4. Theming the red/black palette .....                   | 29 |
| 6. AVL animations tour .....                               | 30 |
| 6.1. Static display .....                                  | 30 |
| 6.2. Insert .....                                          | 31 |
| 6.3. Delete .....                                          | 34 |
| 6.4. Rotate .....                                          | 38 |
| 6.5. Fix-up .....                                          | 38 |
| 6.6. Traversals .....                                      | 39 |
| 7. B24 animations tour .....                               | 39 |
| 7.1. Static display .....                                  | 39 |

|       |                                                            |    |
|-------|------------------------------------------------------------|----|
| 7.2.  | Search .....                                               | 40 |
| 7.3.  | Insert .....                                               | 41 |
| 7.4.  | Delete .....                                               | 44 |
| 7.5.  | Traversals .....                                           | 46 |
| 8.    | Graph animations tour .....                                | 47 |
| 8.1.  | Construction and layout .....                              | 47 |
| 8.2.  | Static display .....                                       | 47 |
| 8.3.  | Prim's minimum spanning tree .....                         | 47 |
| 8.4.  | Kruskal's minimum spanning tree .....                      | 49 |
| 8.5.  | Dijkstra's shortest paths .....                            | 52 |
| 8.6.  | Traversals .....                                           | 54 |
| 8.7.  | Optional auto-layout with graphviz .....                   | 54 |
| 9.    | Theming .....                                              | 55 |
| 9.1.  | Setting a theme for the whole document .....               | 55 |
| 9.2.  | Per-call overrides .....                                   | 55 |
| 9.3.  | Performance: state-based theming costs a layout pass ..... | 55 |
| 10.   | Touying composition examples .....                         | 56 |
| 10.1. | Captions in a sidebar .....                                | 56 |
| 10.2. | Driving layout from step metadata .....                    | 57 |
| 11.   | Composing with cetz annotations .....                      | 57 |
| 12.   | The Op command stream .....                                | 58 |
| 12.1. | Custom shapes and edge anchors .....                       | 59 |
| 13.   | API reference .....                                        | 60 |
| 13.1. | Render helpers .....                                       | 60 |
| 13.2. | Animation core .....                                       | 63 |
| 13.3. | Tree backend .....                                         | 69 |
| 13.4. | Graph .....                                                | 73 |
| 13.5. | Graph renderer .....                                       | 74 |
| 13.6. | Graph auto-layout .....                                    | 78 |

# 1. Introduction

Starling renders animated data structures in Typst, built on top of cetz, typsy, and (optionally) touying. The package is designed for a programming course: it ships a binary search tree today and is structured to grow to heaps, hash tables, and graphs without rewriting the animation kernel.

Every animation in starling is built from the same primitive — an ordered array of Frame records. Each Frame carries a rendered cetz canvas, an optional textual caption, and free-form step metadata. The package supplies a few helpers to collapse the array into a final image, a vertical stack, or an array of subslide figures, but you are free to ignore them and lay frames out however your document needs.


## 1.1. Quick start

```
#import "@preview/starling:0.2.0" as starling
#import starling: bst




#let t = bst(4, 1, 7, 3, 6)
```


The first argument becomes the root; the rest are inserted in order. For custom node labels, pass a (value, label) 2-tuple in place of a bare value — e.g. `bst((4, [FOUR]), 1, (7, [SEVEN]))`. The lower-level constructor `(BST.new)(value:, label:, left:, right:)` and the `(t.insert-many)(..vals)` method are still available for finer control.

A static render of the tree, taking the final frame from `(t.display)()`:



A full search animation, stacked vertically with per-step captions:





## 2. Architecture

Starling is layered into three source files, each with a single responsibility:

| File                 | Role                                                                                                                                                                                           |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| src/anim-core.typ    | The structure-agnostic animation core — defines Snapshot, Frame, the Renderer (with a pluggable draw backend), make-renderer, Op, and apply-ops. Knows nothing about any particular structure. |
| src/tree-anim.typ    | The tree backend on the core — draw-tree, the cetz-tree builders, PathId, path-anchor, and the tree-bound make-renderer wrapper. Re-exports the core.                                          |
| src/bst.typ          | The BST class — implements pure operations (insert, delete, rotate) and the *-display methods that build animations using the kernel.                                                          |
| src/graph-draw.typ   | The graph renderer on the core — draw-graph, edge-key, node-anchor, and the graph-bound make-graph-renderer wrapper. The graph analog of tree-anim.typ; knows drawing, not algorithms.         |
| src/graph.typ        | The Graph class — data plus the MST / Dijkstra / BFS / DFS *-display algorithms. Split from its renderer, like bst.typ is from draw-tree.                                                      |
| src/graph-layout.typ | Optional graphviz auto-layout (auto-layout) via diagraph-layout. The only file importing that dependency, and nothing on the lib.typ path imports it — so it stays optional.                   |
| src/lib.typ          | The public surface — re-exports everything users need, plus the render helpers (last, stacked, figures, canvases-only).                                                                        |

This split lets us add a new data structure (e.g. a heap) by writing just a new file at the bst.typ layer; the kernel does not need to change. Conversely, a power user who wants to assemble custom animations can talk to the kernel directly without touching the BST class at all.

### 2.1. Snapshots, frames, and the renderer

Four types do most of the work. Their roles are intentionally distinct:

| Type         | Role                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Snapshot     | A <i>sparse style overlay</i> for one moment in time — which nodes are filled what colour, which edges are dashed or hidden, which notes are attached to which nodes. Built up by chaining <code>style-node</code> / <code>style-edge</code> / <code>note-node</code> calls. Pure data; no theme awareness, no content.                                                                                                                                                                                         |
| TreeRenderer | A tree plus an ordered list of snapshots plus optional caption / step-metadata for each snapshot. The thing you build up while describing an animation.                                                                                                                                                                                                                                                                                                                                                         |
| Frame        | The <i>output</i> record: ( <code>render</code> , <code>caption</code> , <code>step</code> , <code>alt</code> ). <code>render</code> is a builder function ( <code>op-theme</code> , <code>render-theme</code> ) -> content — not pre-baked content — so callers can resolve theme state at layout time and reuse the same animation across documents with different themes. <code>TreeRenderer.render</code> produces an array of these, one per snapshot. This is what <code>*-display</code> methods return. |
| Theme dict   | One of three layers, in merge order: <code>render-theme</code> (structural defaults like node fill, edge stroke, note colour), <code>op-theme</code> (operation strokes/fills shared across data structures, like <code>search-stroke</code> , <code>success-fill</code> , <code>traversal-palette</code> ), and an optional per-DS theme (e.g. <code>rbt-theme</code> 's red/black palette). Frames are theme-agnostic until a render helper feeds resolved themes into each frame's render builder.           |

The data flow, end to end:

```

Snapshot array → TreeRenderer.render
→ Array(Frame) (builders, theme-agnostic)
→ helper resolves theme state once
→ helper calls each (f.render)(op, rt)
→ document content

```

The shape matters: snapshots and frames are both pure data until the final step. That makes them inspectable, slicable, and composable — you can pull a frame out, look at its `step` metadata, swap its caption, or thread it into a custom layout without rendering. The theming-aware materialisation is concentrated at the helper boundary.

## 2.2. Path identity

Every node is identified by its position in the tree, encoded as a string of "L" and "R" characters from the root. The root is "", the right child of the root is "R", the left child of "R" is "RL", and so on. Edges are identified by the path of their *child* node — each child has exactly one parent, so this is unambiguous.

Path identity is the linchpin that keeps node and edge styling independent of the tree's value or layout. It also means a node-highlighting animation built for one tree can be reused on a tree of the same shape with different values just by passing a different `tree` to `make-renderer`.

The only places that interpret path characters are `PathId` (the refined string type), `_build-cetz-tree` (which walks `.left` and `.right`), and the BST's own `by-value` / `path-to` / `resolve` methods. Everywhere else treats paths as opaque keys, which leaves room to generalise — n-ary trees would use slash-separated child indices like "0/1/2" or arrays of ints, and only those four places need to change.

## 2.3. Sticky animation accumulation

`make-renderer(tree, sticky: true)` is the common case: each new frame pushed via `r.push-frame()` starts from the previous frame’s snapshot. That means a sequence like

```
#let r = starling.make-renderer(t, sticky: true)
#let r = (r.push-with-node)("", stroke: blue + 2pt) // frame 1
#let r = (r.push-with-node)("L", stroke: blue + 2pt) // frame 2
#let r = (r.push-with-node)("LR", stroke: blue + 2pt) // frame 3
```

produces three frames where each highlights one more node than the last — frame 3 has all three highlights, not just LR. This matches the natural mental model for teaching (“we visited these nodes in order”). Set `sticky: false` if you want each frame to start fresh.

Captions and step metadata do *not* sticky-accumulate; each frame’s caption is whatever was last set on that frame, with no carry-over.

## 2.4. The cetz integration

The animation kernel renders each snapshot via `draw-tree`, which emits `cetz` draw commands using `cetz.tree.tree(...)` for layout. The key choice here is *not* to wrap `draw-tree`’s output in `cetz.canvas` inside the kernel — that wrap happens one layer up, in `_render-canvas`. The two functions are split so a power user can write their own `cetz.canvas` block, call `draw-tree` inside it, and add their own `cetz` annotations alongside the tree (see Section 11).

Anchors for individual nodes are exposed by `path-anchor`, which translates an L/R path string into the `cetz` anchor name produced by `draw-tree`. The fact that this needs a translation function at all is a quirk worth flagging — see Section 3.7.

## 3. Design decisions

This section explains the major calls that shape the API. None of them are obvious from reading the code, but each was a conscious choice and the reasoning is load-bearing for anyone considering a refactor.

### 3.1. Why frames, not a wrap callback

The original (v0.1) API let users configure `starling.configure(wrap: alternatives)` to bake `touying`’s `alternatives` into the `BST` class via closure capture. Each `*-display` method internally called `wrap(...figs)` on the array of figures it generated.

That approach was rigid in two ways. First, the rendering decision was made *inside* the animation method, so the same animation could not appear as a static figure in handouts and as a subslide sequence in slides — you’d configure differently per context. Second, and worse, the animation was always one opaque blob: there was no way to weave the caption “ $6 > 4$ ” alongside other slide content while keeping the visual animation synchronised, because everything lived inside a single `alternatives` mark.

The current API solves both: `*-display` returns the raw frame array, and the helpers (`last`, `stacked`, `figures`) collapse it however the caller wants. Wanting to lay captions in a sidebar while the animation plays? Pull them out yourself:

```
#let frames = (t.search-display)(6)
#grid(columns: 2,
```

```
alternatives(..starling.figures(frames, caption: false)),
alternatives(..frames.map(f => f.caption)),
)
```

A historical note worth preserving: closure-captured wrap was itself chosen over a state-based approach (`std.state`, `typsy`'s `safe-state`) because `touying`'s `alternatives` is a layout-time “mark” that `touying` rejects inside context `{ ... }` blocks. With frames as plain data, that constraint no longer applies to the animation API — and state did become viable later for the theming layer (see *State for ergonomics, per-call for perf* below).

### 3.2. Three theme layers, one per concern

Theming is split into three dicts that each own a different concern:

- **Render theme** (`default-render-theme`, in `anim-core.typ`) holds structural defaults — node fill, node stroke, node text fill, edge stroke, note fill. Anything any data structure would need to render a tree at all.
- **Op theme** (`default-op-theme`, in `op-theme.typ`) holds operation- semantic strokes/fills/palettes that apply to *any* data structure with those operations — `search-stroke`, `attention-stroke`, `success-stroke`, `settled-stroke`, `success-fill`, `danger-stroke`, `reset-stroke`, `traversal-palette`. BST search and a hypothetical hash-table search share the same `search-stroke` from this layer.
- **Per-DS theme** (e.g. `default-rbt-theme`, in `rbt.typ`) holds styling intrinsic to one data structure — the red/black palette for RBTs is the canonical example. BST itself has no per-DS theme, because BST nodes have no intrinsic differentiation.

The split lets each layer own its own concerns. A new data structure (heap, trie, B-tree) brings its own per-DS theme dict if needed and reuses the render theme and op theme as-is. If operation strokes lived in a BST theme, every new data structure would either duplicate them or grow a coupling to BST.

The render theme also has a clear “lowest in the chain” role: `draw-tree` falls back to it when neither a snapshot override nor a `make-renderer(default-node-style:, default-edge-style:)` argument specifies a property. So the merge order, lowest precedence first, is: `default-render-theme` → user render-theme override → op-theme / per-DS-theme overlays applied per snapshot → renderer defaults → per-snapshot per-path overrides. Each layer adds more specificity.

Strokes throughout the op theme are full stroke dictionaries (`(paint:, thickness:, dash:)`), not bare colours. That lets users change any aspect of a stroke (dash pattern, cap, width) without us adding more theme keys for each possibility.

### 3.3. Frames carry builders, not pre-rendered content

`Frame.render` is a function (`op-theme, render-theme`) -> content, not a piece of pre-baked content. This is so render helpers (`last`, `stacked`, `figures`) can resolve theme state *once per call* and feed those resolved themes into every frame's builder, rather than each frame independently resolving theme inside its own context block.

The frame-as-builder shape also has a non-perf benefit: an `Array(Frame)` is now a portable, theme-agnostic description of an animation. The same frames can render against different themes in different contexts without re-running the `*-display` method. That's a cleaner separation than the older (`canvas, caption, step`) shape, where `canvas` baked in whatever theme was active at construction time.



A typsy quirk worth noting: typsy auto-injects `self` into any function-typed field on a class. To keep `(frame.render)(op, rt)` from getting a spurious third argument, the actual closure is stored as `_builder: (fn: ...)` — a singleton dict around the function — and exposed through a `render` method that dereferences it. Users only see `(frame.render)(op, rt)`; the dict wrap is private.

RBT and any future per-DS theme are read inside the frame’s builder itself, not by the `lib.typ` helpers. The helpers only resolve the two universal layers — `op-theme` and `render-theme` — and pass them in; per-DS themes are state-read on demand. That keeps the helper signature stable as more data structures land.

### 3.4. State for ergonomics, per-call for perf

Theme overrides come in two flavours:

| Form                                                                                                  | Behaviour                                                                                                                                                                                                                          |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>set-op-theme(...)</code> / <code>set-render-theme(...)</code> / <code>set-rbt-theme(...)</code> | State-based. One declaration at the top of the document propagates through every subsequent <code>*-display</code> call. Ergonomic and intent-matching, but participates in Typst’s state-convergence machinery — see Section 9.3. |
| <code>(t.search-display)(v, theme: ...)</code>                                                        | Per-call. Overrides the theme for one call; ignores state for that call. Verbose if you have many calls, but skips the state-cost path entirely. Run at the no-state baseline.                                                     |

Both paths exist because there’s no single answer. State is right for a document that uses one theme throughout — write `set-op-theme(my-palette)` once, forget about it. Per-call is right when compile speed dominates and the user is happy threading a `let palette = (...) value` through their calls. The library does not pick a winner.

The cost being structural to Typst — not something starling can optimise away — meant choosing whether to expose state at all was a real call. Skipping state would have removed the perf footgun but also removed the ergonomic win. Exposing both, with the cost documented up-front, lets users decide.

### 3.5. Two-channel captions

For `search-display` and `insert-display`, the comparison string (“6 > 4”) appears in *two* places:

- **Inline**, as a small note drawn beside the highlighted node in the `cetz` canvas. This labels which comparison happened at which node spatially.
- **Caption**, as a textual track on the Frame record. This is what `stacked` and `figures` render below the canvas, and what callers pulling captions out for custom layouts read.

The redundancy is deliberate. The inline note is part of the visual: when looking at a single frame, you should be able to see at a glance what the algorithm just did. The caption is a parallel *textual* track for layouts that want narration apart from the animation.

This is why `last(frames)` defaults to `caption: false` — the inline note already labels the node, so adding a caption block below the static figure would be redundant. `stacked` and `figures` default to `caption: true` because animated rendering invites the textual narrative.

### 3.6. The six-frame rotation

`rotate-display` walks through rotation as six discrete frames: `init`, `pivots`, `break`, `restructure`, `connect`, `settle`. The sequence is calibrated for teaching: each frame answers exactly one question.

| step.kind   | Question answered                               |
|-------------|-------------------------------------------------|
| init        | What's the starting tree?                       |
| pivots      | Which two nodes are rotating?                   |
| break       | Which edges are about to disappear?             |
| restructure | What does the new shape look like, edges aside? |
| connect     | Where do the new edges go?                      |
| settle      | What does the final, clean tree look like?      |

An earlier draft had a “dashed red” intermediate between `pivots` and `break` (edges going dashed before disappearing). That was dropped because the orange pivot highlight already cues the eye to those edges — the extra frame added length without information.

The `restructure` frame is the load-bearing one: it shows the new tree shape with the rotated edges still hidden, so the student can see the new positions form *before* the edges connect. Without it, the rotation would collapse into one cut from “broken” to “rotated + highlighted edges”, which is too much information at once.

### 3.7. Path-based anchors and the `cetz` tree quirk

`cetz.tree` numbers its nodes internally as `0`, `0-0`, `0-1`, `0-0-1`, ... — sibling indices joined by hyphens, with the root being `0`. Starling configures `cetz-tree`'s `group-name-prefix` to `"node-"`, so the resulting anchor names look like `node-0-0-1`. The whole tree also sits inside an outer named group (`"tree"` by default), so the fully qualified anchor for path `"LR"` is `tree.node-0-0-1`.

Two things made me reach for path-anchor rather than letting users type that out:

1. The user thinks in `"LR"`, not `"0-0-1"`. The translation is mechanical (`L` → `0`, `R` → `1`, prepend the root `0`) but it's error-prone to do by hand.
2. The naming scheme is a `cetz-tree` implementation detail. Wrapping it in `path-anchor(path, tree-name:, prefix:)` lets us swap to a different naming scheme later (e.g. if we drop `cetz-tree` for a custom layout) without churn at every annotation call site.

Phantom siblings (used to off-centre lone children — see `_build-cetz-tree`) also get `cetz-tree-internal` anchor names like `node-0-0-0`, but they are hidden at draw time and you generally should not annotate them.

## 4. BST animations tour


The BST class provides five \*-display methods. Each returns Array(Frame); the examples below pass the result to starling.stacked to render every frame vertically with its caption.

We'll use the same sample tree throughout this section, seeded via the bst(..vals) factory (first arg = root, rest are inserted):

```
#let t = bst(4, 1, 7, 3, 6, 8)
```


### 4.1. Static display


(t.display)() returns a one-element frame array — the unmodified tree, with no step metadata.



### 4.2. Search




(t.search-display)(v) walks the search path, highlighting each node visited and labelling it with the comparison made. step.kind is "init" for the initial frame and "compare" for each step; step.found records whether the value was reached.






### 4.3. Insert

`(t.insert-display)(v)` walks the search path as for `search-display`, then transitions to the after-tree with the new node highlighted via `success-stroke / success-fill`. `step.kind` is "init", "compare" (per search step), and finally "inserted".








#### 4.4. Delete

`(t.delete-display)(v)` has three internal cases — leaf, one-child, and two-children — and dispatches on the target's children. `step.kind` ranges over "init", "highlight", "break", "descend", "transfer", and "settle" depending on case.


The two-children deletion is the most complex: it highlights the target, descends into the left subtree to find the in-order predecessor, annotates the value transfer, then jumps to the after-tree with the new root of the affected subtree highlighted via `success-stroke`.




Delete 4




Find predecessor



Find predecessor



Transfer 3





Done


## 4.5. Rotate

`(t.rotate-display)(c)` rotates around node `c` — any node in the tree with a parent, not just a direct child of the root. The direction (left/right) is inferred from `c`'s position in the BST. The six-frame sequence is described in Section 3.6.







Rotate around 1




Break edges



Restructure tree




Reconnect edges









## 4.6. Traversals

`(t.in-order-display)()`, `(t.pre-order-display)()`, `(t.post-order-display)()`, and `(t.level-order-display)()` animate the four standard traversals. Each returns one frame per visit (plus the initial frame): the visited node is filled with the next color in a perceptually-uniform palette (magma by default) and tagged with a numbered badge marking its visit order, and the caption accumulates the running output sequence. `step.kind` is "init" for the initial frame and "visit" thereafter, with `step.value` and `step.index` (1-indexed) recording each visit. Switch palettes via the theme system (see Theming) — either doc-wide with `set-op-theme((traversal-palette: color.map.viridis))` or per-call with `(t.in-order-display)(theme: (traversal-palette: ...))`.


Pure-data variants `(t.in-order)()`, `(t.pre-order)()`, `(t.post-order)()`, and `(t.level-order)()` return the visit sequence as an array of path strings without producing any animation, in case you want to drive a custom layout.







The final frame of each traversal carries the algorithm's full color signature. Laying all four out side-by-side gives a fast visual comparison — especially useful as a recall cue in review material where students already understand the algorithms and the gradient pattern reads as “oh right, post-order goes leaves-cool to root-warm”:



## 5. RBT animations tour

The RBT class ships three `*-display` methods today: `display`, `insert-display`, and `delete-display`. Each returns `Array(Frame)` in the same shape as the BST methods, so the render helpers (`last`, `stacked`, `figures`) and the caption / step / alt conventions carry over unchanged. The `rbt-theme` palette (red and black fill, stroke, and text-fill) is layered on top of the render theme so every frame's nodes wear their semantic colors automatically; operation-specific highlights from the `op-theme` (search-stroke on descent, attention-stroke on fix-up pivots, settled / success strokes on resolution) compose on top.


The sample tree throughout this section is seeded via the `rbt(..vals)` factory — first arg becomes the (black) root, the rest are inserted in order so the CLRS fix-ups produce a clean balanced shape with a mix of red and black nodes:

```
#let t = rbt(8, 4, 12, 2, 6, 10, 14, 1)
```

For finer control, the lower-level `(RBT.new) (value:, label:, red:, left:, right:)` constructor plus `(t.insert-many) (..vals)` method are still available — the root takes a `red:` argument because a single-node tree also carries a colour (it must be black after every public operation).

## 5.1. Static display



`(t.display)()` returns a one-element frame array — the unmodified tree, with every node coloured by its red field from the active rbt-theme palette.



## 5.2. Insert


`(t.insert-display)(v)` traces the CLRS insertion algorithm: a BST descent records each visited node, the new value splices in as a red leaf, then a fix-up loop walks back up the tree applying Case 1 (uncle red — recolour parent and uncle black, grandparent red, continue at the grandparent), Case 2 (zigzag — rotate around the parent to straighten the red-red pair), and Case 3 (straight line — rotate around the grandparent and swap its colour with the new subtree root). The root is blackened at the end if it ended up red. `step.kind` ranges over "init", "descend", "insert", "check", "recolor", "rotate-zigzag", "rotate-recolor", and "blacken-root".

Inserting 0 walks down to the red leaf 1, splices a red 0 beneath it, then resolves the red-red pair via a straight-line Case 3 (rotate around the grandparent 2, swap its colour with the new subtree root 1):




Search for 0






Insert 0 as red leaf



Red-red violation





Rotate and color swap


### 5.3. Delete

`(t.delete-display)(v)` traces a BST search for the target, the in-order predecessor walk if the target has two children, the value transfer, the structural excise, and the four-case rebalancing loop. `step.kind` covers "init", "descend" (a single frame highlighting the full search path; `pass search: true` for one "compare" frame per step instead), "not-found", "mark-target", "find-predecessor", "transfer", "excise", "paint-black-promoted", "paint-black-db", and the fix-up cases. Cases 1, 3, and 4 each emit two frames — a rotation-only intermediate ("case-1-rotate", "case-3-rotate", "case-4-rotate") followed by the recolor ("case-1", "case-3", "case-4") — so the structural pivot lands separately from the color swap. Case 2 is a pure recolor and emits a single "case-2" frame.


Excising a black node leaves the subtree one black short of the rest of the tree. The animation marks that imbalance with a small filled circle at the child end of the affected edge — the textbook convention. The circle stays in place across each fix-up step that doesn't resolve the missing black; it disappears once a Case 4 rotation drains it or a red ancestor absorbs it. Deleting the black leaf 6 takes the Case 4 branch directly (sibling 2 is black, far nephew 1 is red):




Search for 6




Delete 6



Remove node



Rotate parent



Recolor

## 5.4. Theming the red/black palette

The `rbt-theme` palette lives in its own state, separate from the render theme and op theme, with `default-rbt-theme` as the seed and `set-rbt-theme` / a per-call theme: argument as the two override paths. Recognised keys are `red-fill`, `red-stroke`, `red-text-fill`, `black-fill`, `black-stroke`, and `black-text-fill`; unknown keys panic so typos surface immediately.

Set the palette document-wide via `set-rbt-theme` (state-based, participates in the layout-pass cost — see Section 9.3):

```
#import "@preview/starling:0.2.0": RBT, set-rbt-theme

#set-rbt-theme((
  red-fill: orange,
  red-stroke: orange.darken(20%),
  black-fill: navy,
```

```
    black-stroke: navy,  
  ))
```

Or per-call to skip state and run at the no-state baseline:

```
(t.display)(theme: (red-fill: red.darken(20%)))
```

## 6. AVL animations tour

The AVL class is a height-balanced BST. Each node carries an extra height field; after every public operation the height is up-to-date and  $|h(\text{left}) - h(\text{right})|$  (the **balance factor**) is at most 1. Imbalances are repaired with single or double rotations, dispatched on four cases (LL, RR, LR, RL) — the same ones every textbook walks through.

AVL ships the standard suite of `*-display` methods (`display`, `search-display`, `insert-display`, `delete-display`, `rotate-display`, `fixup-display`, and the four `*-order-display` traversals), all returning `Array(Frame)` so the render helpers and `caption / step / alt` conventions carry across unchanged. AVL has no per-DS theme — animation strokes come from the `op-theme`, structural defaults from the `render theme`.


The sample tree throughout this section is seeded via the `avl(..vals)` factory — first arg becomes the root, the rest are inserted in order so the AVL rebalancing produces a clean balanced shape:

```
#let t = avl(5, 3, 7, 2, 4, 6, 8, 1, 9)
```

For finer control, the lower-level `(AVL.new)(value:, label:, height:, left:, right:)` constructor plus `(t.insert-many)(..vals)` method are still available — the root takes a `height:` argument because a single-node tree already has height 1.

### 6.1. Static display


`(t.display)()` returns a one-element frame array — the unmodified tree. Pass `factors: true` to tag every node with its signed balance factor (e.g. "+1", "0", "-1"), drawn just west of the node so it doesn't compete with the label or the operation note slot. The tag layer is reused by every `*-display` method as a base layer (off by default; opt in per call).




## 6.2. Insert


`(t.insert-display)(v)` traces the AVL insertion algorithm. A BST descent records each visited node, the new leaf appears with height 1, then the climb back to the root recomputes each ancestor's height in turn. On the first ancestor whose balance factor reaches  $\pm 2$ , the animation labels the imbalance case (LL/LR/RR/RL), applies a child rotation if the case is a zigzag (LR or RL), and finishes with the single rotation at the imbalanced node. After a single insertion the subtree's height returns to its pre-insert value, so the climb stops there. `step.kind` ranges over "init", "descend", "insert", "recompute", "check", "rotate-zigzag", and "rotate-finish".

Inserting 0 into the sample tree triggers an LL fix-up at node 2 (after the climb sees node 1's height grow). The fix-up is a single right rotation:






Search for 0




Insert 0 as new leaf







Recompute height



Recompute height



Imbalance: case LL



Rotate (case LL)



The zigzag cases (LR/RL) emit an extra rotate-zigzag frame between check and rotate-finish for the child rotation that straightens the configuration before the final rotation at the imbalanced node.

### 6.3. Delete


`(t.delete-display) (v)` traces a BST search for the target, the in-order predecessor walk if the target has two children, the value transfer, the structural excise, and then a climb that recomputes heights and rotates at every imbalanced ancestor. Unlike insert, a single deletion can trigger several rotations on the way up

— the loop runs to the root. `step.kind` covers "init", "descend" (single frame; pass search: true for one "compare" per step instead), "not-found", "mark-target", "find-predecessor", "transfer", "excise", and the same "recompute" / "check" / "rotate-zigzag" / "rotate-finish" events insert emits.


Deleting 3 from the sample tree takes the two-child branch (predecessor transfer from 2) and stays balanced — the climb recomputes heights without triggering any rotation:




Search for 3




Delete 3




Find predecessor




Transfer 2



Remove node



Recompute height



Recompute height

## 6.4. Rotate

`(t.rotate-display)(c)` is the same six-frame structural rotation animation BST exposes, with heights refreshed in the after-tree. AVL rebalancing in `insert` / `delete` does **not** go through this method — the case-dispatch rotations are applied directly so the animation can narrate the recompute-then-rotate logic.

## 6.5. Fix-up

`(t.fixup-display)(violation-path)` runs the AVL fix-up climb from a hand-constructed (possibly invalid) tree. The tree is **not** validated: this is intended for teaching configurations that can't arise from a single insert or delete — for example, multiple imbalances on one spine where the inner rotation propagates the imbalance up. The climb walks every proper prefix of `violation-path` deepest-first, emitting the same recompute / check / rotate-zigzag / rotate-finish events that `insert` and `delete` use.

## 6.6. Traversals

`(t.in-order-display)()`, `(t.pre-order-display)()`, `(t.post-order-display)()`, and `(t.level-order-display)()` work exactly like their BST counterparts — one frame per visit, gradient fill from the op-theme's traversal-palette, running output sequence in the caption. Pass `factors: true` on any traversal to layer the balance-factor tags under the per-visit highlights.

## 7. B24 animations tour

The B24 class is a 2-3-4 tree (a B-tree of order 4) — every internal node holds 1, 2, or 3 keys (so 2, 3, or 4 children) and every leaf sits at the same depth. The node renderer for this data structure is the subdivided rectangle shape "btree-node", which scales its width with the number of keys; per-key compartments are individually addressable via the "`<path>#<i>`" path syntax and the `key-styles` slot on `NodeStyle`.

B24 exposes the standard suite of `*-display` methods (`display`, `search-display`, `insert-display`, `delete-display`, and the four `*-order-display` traversals). Insert and delete accept a `strategy` argument that switches between two textbook algorithms:

- **Top-down** (the default): preventive — split any 3-key node on the way down for insert; refill any 1-key node on the way down for delete. Single-pass recursion.
- **Bottom-up**: reactive — walk to the leaf first, then propagate splits or merges back up through the descent path.

Both produce valid 2-3-4 trees containing the same keys but they can produce structurally different **shapes** — bottom-up promotes a key from the **post-overflow** 4-key state (so the freshly inserted key may itself be promoted), while top-down promotes the middle of the **pre-insert** 3-key state. There is no per-DS theme — animation strokes come from the op-theme; structural defaults from the render theme.


The sample tree throughout this section is seeded via the `b24(..vals)` factory:

```
#let t = b24(10, 5, 15, 1, 7, 12, 20, 25, 30, 17, 19)
```

For finer control, the lower-level `(B24.new)(keys:, labels:, children:)` constructor lets you hand-build a tree with any compartment count at every depth — useful for fixtures that demonstrate a specific fix-up case.


### 7.1. Static display

`(t.display)()` returns a one-frame array — the unmodified tree. Compartment widths scale with key count, and edges fan out from the gap anchors (`gap-0` through `gap-k`) on the parent's south face.




## 7.2. Search

(t.search-display)(v) highlights one key compartment per comparison. The descent path stays visible as the search progresses (sticky search strokes); the inline note at each visited node carries the comparison text. Misses end at the leaf without panicking – the final frame reports that the value isn't in the tree.












### 7.3. Insert


`(t.insert-display)(v, strategy: ..)` traces the full insertion algorithm. Top-down splits trigger a `td-pre-split-attention` frame that outlines a full node about to be split, then a `split-done` frame showing the promoted key with its two new child edges. The final settled frame highlights the inserted compartment.







The bottom-up variant runs the descent first, then animates the leaf insertion plus any cascading splits:






## 7.4. Delete


`(t.delete-display)(v, strategy: ..)` traces the deletion algorithm. Top-down's preventive `td-pre-fix-attention` frame outlines a 1-key descent target before the fix; subsequent `td-borrow-left` / `td-borrow-right` / `td-merge` frames carry out the rotation or merge. Internal-key deletions visit a `td-target` highlight, swap with the predecessor (`td-pred-swap`), then continue the descent to remove the predecessor's old value from its leaf.




Merge




15 > 10



15 = 15




Target found



## 7.5. Traversals

The four traversal animations sample the op-theme's traversal-palette across the per-compartment visit order — each visited compartment gets a fill from the gradient and the caption accumulates the output sequence. In-order on a 2-3-4 tree threads keys with their flanking subtrees (child[0], key[0], child[1], key[1], ..., child[k]); pre- and post-order group all of a node's keys at the node-visit point.



## 8. Graph animations tour

The Graph class is the first non-tree structure in starling: an undirected-or-directed weighted graph for teaching minimum spanning trees (Prim and Kruskal), Dijkstra's shortest paths, and breadth- and depth-first traversals. It rides the same Frame / op-theme / render-theme stack as the trees, so every render helper, theming knob, and touying composition works unchanged. There is no per-DS theme — animation strokes come from the op-theme, structural defaults from the render theme.

Unlike trees, graphs have no root and no path-from-root, so node identity is a plain string id and edges are keyed by edge-key(u, v, directed:) (sorted "u--v" when undirected, "u->v" when directed). The renderer (graph-draw.typ, the draw-graph backend) is split from the Graph class (graph.typ, data plus algorithms) exactly as draw-tree is split from the tree classes — both inject their backend into the shared Renderer in anim-core.typ.

### 8.1. Construction and layout


Layout is decoupled from rendering: the Graph carries node positions (in cetz units) and the renderer simply draws nodes there. The graph(...) factory takes placed nodes and weighted edges:

```
#let g = graph(  
  (("A", 0, 0), ("B", 3, 0.4), ("C", 1.5, 2.4), ("D", 4.5, 2.2)),  
  edges: (("A", "B", 7), ("B", "C", 2), ("A", "C", 4),  
          ("C", "D", 5), ("B", "D", 1)),  
)
```

Hand-placement is the first-class path — small teaching graphs read best when you control the layout. For larger graphs, the optional auto-layout helper (below) computes positions with graphviz.


### 8.2. Static display

(g.display)() returns a one-frame array. Edge weights are drawn at each edge midpoint; a directed graph gets arrowheads.




### 8.3. Prim's minimum spanning tree


(g.mst-prim-display)(start) grows the tree from start. Each selection shows the frontier (crossing edges in the search stroke) with the lightest edge picked out in the attention stroke, then commits it to the tree (success stroke) and settles the newly reached node. The caption tracks the running tree weight.




Start at A




Min crossing edge: A-C (4)



Add A-C tree weight 4




Min crossing edge: B-C (2)




Add B-C tree weight 6






Min crossing edge: B-D (1)




Add B-D tree weight 7




MST weight 7

#### 8.4. Kruskal's minimum spanning tree


`(g.mst-kruskal-display)()` considers edges in weight order, adding each unless it would join two nodes already in the same component (a cycle, drawn in the danger stroke). The union-find forest is shown by **node color**: same color means same set, and colors merge as the components do — no extra dependency, and robust to any layout.




Sort edges by weight




Consider B-D (1)




Add B-D weight 1




Consider B-C (2)




Add B-C weight 3




Consider A-C (4)




Add A-C weight 7




Consider C-D (5)




Reject C-D (cycle)



Consider A-B (7)




Reject A-B (cycle)




MST weight 7

## 8.5. Dijkstra's shortest paths


(g.dijkstra-display)(source, target: ..) carries each node's tentative distance in its note slot ( $\infty$  until reached). Each round finalizes the nearest unvisited node (attention stroke, then settled), relaxes its outgoing edges (search stroke, updating distances), and grows the shortest-path tree in the success stroke. With a target the search stops early and the path is highlighted. It works on directed graphs:








Initialize:  $S = 0$




Visit S (0)




Relax from S






Relax from T



Shortest path to T: 3

## 8.6. Traversals

(g.bfs-display)(start) and (g.dfs-display)(start) sample the op-theme's traversal-palette across the visit order — each visited node gets a fill from the gradient and a 1-indexed badge, and the caption accumulates the visit sequence (the same pattern as the tree \*-order-display methods). The final frame wears the full visit signature:



## 8.7. Optional auto-layout with graphviz

For graphs too large to place by hand, auto-layout (in the separate graph-layout.typ module) computes positions with graphviz via the diagraph-layout package — a WASM build, so no external binary is needed. It is an **optional** dependency: nothing on the import starling path imports it, so projects that only hand-place graphs never pull it in. Import it explicitly and feed the result to any display via the positions: argument:

```
#import "@preview/starling:0.3.0/src/graph-layout.typ": auto-layout

// Position-less graph — bare ids, no coordinates.
#let g = graph(("A", "B", "C"), edges: (("A", "B", 7), ("B", "C", 2)))
#last((g.mst-prim-display)("A", positions: auto-layout(g)))
```

## 9. Theming

Starling exposes three theme layers so document authors can match starling's palette to their own document style:

- **Render theme** (default-render-theme) — the structural defaults the renderer falls back on for the unstyled tree: node-fill, node-stroke, node-text-fill, edge-stroke, note-fill.
- **Op theme** (default-op-theme) — the operation-semantic colors and strokes that any data structure's `*-display` methods use to communicate operation state: search-stroke, attention-stroke, success-stroke, settled-stroke, success-fill, danger-stroke, reset-stroke, traversal-palette. Shared across data structures — BST search, RBT search, and a future heap delete all read the same search-stroke. Strokes are full stroke dicts (`(paint:, thickness:, dash:)`) so any aspect — color, width, dash — is overridable without adding more keys.
- **Per-DS theme** — styling intrinsic to one data structure. RBT has default-rbt-theme with red-fill, red-stroke, red-text-fill, black-fill, black-stroke, black-text-fill for the red/black palette. BST has no per-DS theme of its own because BST nodes carry no intrinsic styling.

### 9.1. Setting a theme for the whole document

Call any combination of `set-render-theme`, `set-op-theme`, and the per-DS setters (e.g. `set-rbt-theme`) once near the top of your document. Each override is state-based and scoped by Typst's normal layout flow, so it propagates to every subsequent `*-display` call.

```
#import "@preview/starling:0.1.0": BST, set-op-theme, set-render-theme

#set-op-theme((
  search-stroke: (paint: teal, thickness: 2.5pt),
  success-stroke: (paint: olive, thickness: 2.5pt),
  settled-stroke: (paint: olive, thickness: 3.5pt),
  success-fill: olive.lighten(75%),
))
#set-render-theme((node-fill: yellow.lighten(85%)))
```

Pass a partial dictionary — only the keys you list are changed. Unknown keys panic so typos surface immediately rather than silently falling back to defaults.

### 9.2. Per-call overrides

For one-off variations, every `*-display` method accepts `theme:` and `render-theme:` arguments. A partial dict is merged into the defaults and used in place of the state value for that call only.

```
(t.search-display)(6, theme: (search-stroke: (paint: olive, thickness: 2pt)))
```

### 9.3. Performance: state-based theming costs a layout pass

Typst's state machinery is what makes `set-op-theme` / `set-render-theme` work: a `state.update` later in the document can affect renders earlier in document order, so Typst evaluates the document, propagates state, and re-evaluates anything that observed it. In practice that means **using either state setter roughly doubles the compile time of the state-observed portion of the document** — a small fixed cost on top of each tree, plus a full extra layout pass through everything that placed a starling render helper or rendered a frame's render builder against that state.

Concretely, a 50-tree synthetic benchmark goes from 1.85s to 3.1s when `set-op-theme` is added. The cost scales with document size, not with the number of state reads (one read or a thousand is the same), because the price is “Typst does a second layout pass”, not “the read is slow”.

This is a structural property of Typst’s state model, not something starling can work around without giving up state. If compile speed matters more than the ergonomic win, hoist your theme dict into a plain `let` and pass it to each `*-display` call via the `per-call theme: argument` — that path skips state entirely and runs at the no-state baseline:

```
#let palette = (
  search-stroke: (paint: teal, thickness: 2.5pt),
  success-stroke: (paint: olive, thickness: 2.5pt),
  // ...
)

#starling.stacked((t.search-display)(6, theme: palette))
#starling.stacked((t.insert-display)(5, theme: palette))
// ...
```

This is the usual perf/ergonomics tradeoff: `set-op-theme` is one declaration at the top of the document and “just works”; `per-call theme:` is more typing but avoids the extra pass.

## 10. Touying composition examples

Starling is layout-agnostic. In a touying deck, the simplest use splats figures into alternatives:

```
#import "@preview/touying:0.7.3": *
#import "@preview/starling:0.2.0" as starling
#import starling: BST

== Searching
#alternatives(..starling.figures((t.search-display)(6)))
```

Each frame becomes a subslide; touying handles the rest.

### 10.1. Captions in a sidebar

When the visual animation should sit alongside synchronised text elsewhere on the slide, pull the captions out separately:

```
== Searching for 6
#let frames = (t.search-display)(6)
#grid(columns: 2, column-gutter: 2em,
  alternatives(..starling.figures(frames, caption: false)),
  alternatives(..frames.map(f => f.caption)),
)
```

Both `alternatives` calls produce the same number of subslides, so they step in lockstep.



## 10.2. Driving layout from step metadata

`frame.step` is free-form per-method metadata. For example, a slide that wants to colour-code its narration by step kind:

```
#let kind-colors = (compare: blue, inserted: green)

#let captioned-frames = frames.map(f => figure(context {
  let op = starling._op-theme-state.get()
  let rt = starling._render-theme-state.get()
  let color = kind-colors.at(f.step.kind, default: black)
  stack(dir: ttb, spacing: 0.5em,
    (f.render)(op, rt), text(fill: color, f.caption))
}))

#alternatives(..captioned-frames)
```


`frame.render` is a builder `(op, rt) => content` rather than pre-baked content, so themes resolve at layout time. The `context` block above reads the active themes and feeds them in; if you don't need state-driven theming, you can call `(f.render)(starling.default-op-theme, starling.default-render-theme)` without the wrapper.

## 11. Composing with cetz annotations

For callouts or overlays that need to track specific nodes, drop down to the `cetz` layer. `draw-tree(tree, snapshot, ...)` emits the tree's `cetz` drawables without wrapping them in `cetz.canvas`, so you can compose them with your own draw commands in a shared canvas. `path-anchor(path)` translates an L/R path string to the `cetz` anchor name of the corresponding node.

```
#import "@preview/cetz:0.5.2"

#cetz.canvas({
  starling.draw-tree(t, starling.blank-snapshot())
  import cetz.draw: *
  circle(starling.path-anchor("LR"), radius: 0.85, stroke: red + 2pt)
})
```





The same trick combines with frame canvases: each frame's canvas is itself a `cetz.canvas` block, so for static “annotate the final frame” use you can either render once via `draw-tree` (as above) or extract the `cetz` block from a frame and add to it externally.

## 12. The Op command stream

For animations that don't fit the BST's built-in methods — say, a custom hash-table probe sequence or a graph traversal — drop down to the `Op` command stream. Build a sequence of declarative ops and fold them into a renderer with `apply-ops`:

```
#let r = starling.make-renderer(t, sticky: true)
#let r = (r.with-caption)([start at root])
#let r = starling.apply-ops(r, (
  (starling.Op.Highlight.new)(path: "", color: blue),
  (starling.Op.Annotate.new)(path: "", text: [1 < 4]),
  (starling.Op.Commit.new)(
    alt: "Comparing the target 1 against the root 4.",
  ),
),
)
#let r = (r.with-caption)([descend left])
#let r = starling.apply-ops(r, (
  (starling.Op.ClearNotes.new)(),
  (starling.Op.Highlight.new)(path: "L", color: blue),
  (starling.Op.StyleEdge.new)(path: "L", style: (stroke: blue + 2pt)),
  (starling.Op.StyleNode.new)(path: "L", style: (fill: green.lighten(70%))),
  (starling.Op.Annotate.new)(path: "L", text: [1 = 1]),
  (starling.Op.Alt.new)(
    text: "Descended into the left subtree; 1 matches the left child.",
  ),
),
)
#starling.stacked((r.render)())
```





`Op.Commit` closes the current frame, attaches the supplied `alt` text to it, and opens a fresh blank frame. The `alt` argument is required so every frame the command stream produces carries accessible text. The trailing in-progress frame is kept implicitly — no final `Op.Commit` is needed — but use `Op.Alt(text)` (or `r.with-alt(...)` on the returned renderer) to give that last frame its `alt` text too.

`Op.Caption` does *not* exist; captions and step metadata are renderer-level, set via `r.with-caption(...)` / `r.with-step(...)` directly between `Op` batches. The split keeps each `Op`'s responsibility narrow (modifying the current snapshot) and matches how the `*-display` methods are written internally.

## 12.1. Custom shapes and edge anchors

Two node-style and edge-style keys let you swap the default circular node for a triangle or rectangle and steer where the incoming or outgoing edge connects:

- `shape` (node style) accepts "circle" (default), "triangle" (apex up), or "rectangle". The triangle and rectangle share a 1.4×1.2 bounding box; the circle keeps its 1.2×1.2 footprint.
- `parent-anchor` / `child-anchor` (edge style) accept a cetz anchor name like "north" or "south" and override the edge endpoint on the parent or child side respectively. The default for both stays the empirical fractional-distance trick that looks clean between two circles.

The canonical use case is using a triangle to stand in for an entire subtree — a common pattern when only the top-level shape matters and the details would clutter the slide. Because the triangle's apex sits at the north anchor of its bounding box, an incoming edge with `child-anchor: "north"` lands cleanly on the tip:


```

#let t = (starling.BST.new)(value: 5, label: auto, left: none, right: none)
#let t = (t.insert-many)(2, 8, 1, 3)

#let ops = (
  (starling.Op.StyleNode.new)(path: "L", style: (shape: "triangle", fill:
aqua.lighten(60%))),
  (starling.Op.StyleEdge.new)(path: "L", style: (child-anchor: "north")),
  (starling.Op.StyleNode.new)(path: "LL", style: (hide: true)),
  (starling.Op.StyleNode.new)(path: "LR", style: (hide: true)),
  (starling.Op.StyleEdge.new)(path: "LL", style: (hide: true)),
  (starling.Op.StyleEdge.new)(path: "LR", style: (hide: true)),

```

```
(starling.Op.Alt.new)(text: "Left subtree summarised as a triangle."),
)
#let r = starling.apply-ops(starling.make-renderer(t, sticky: true), ops)
#starling.last((r.render)())
```



Shape and anchor are deliberately independent — the library doesn't auto-set `child-anchor: "north"` when you switch a node to a triangle, because there are legitimate uses for the default endpoint behavior even on non-circular shapes (e.g. a labelled rectangle whose edges you want pulled toward its center rather than flush against its top). When you want flush meeting points, set the anchors yourself.

## 13. API reference

The remainder of this manual is an auto-generated reference, produced by the `tidy` package from doc-comments in the source.

### 13.1. Render helpers

- `canvases-only()`
- `figures()`
- `last()`
- `stacked()`

#### 13.1.1. canvases-only

Drop captions and step metadata, returning just the array of canvases. Useful when you want to lay out captions yourself — e.g. alongside other slide content in a custom touying layout.

Like `figures()`, this returns one piece of content per frame and therefore can't amortize theme state reads — each canvas resolves state independently. If you're calling this on hot paths under a state-set theme, prefer per-call theme arguments on the `*-display` method.

##### 13.1.1.1. Parameters

```
canvases-only(frames: array) -> array
```

##### 13.1.1.1.1. frames array

The frame array returned by any `*-display` method.

### 13.1.2. figures

Build an array of figure content, one per frame, suitable for splatting into `touying's alternatives(...)` so each frame becomes its own subslide. Starling itself does not depend on `touying` — the result is just an array of standard Typst figures.

Unlike `last()` / `stacked()`, this helper can't collapse theme state reads to one — each figure is an independent piece of content laid out separately (`touying` splits them into subslides), so each figure's body resolves theme state in its own context block. In many-tree documents that rely on `set-op-theme` / `set-render-theme`, prefer per-call `theme:` arguments on the `*-display` method to skip state altogether when you're using figures.

#### 13.1.2.1. Parameters

```
figures(  
  frames: array,  
  caption: bool,  
  alt: auto str,  
  caption-spacing: length  
) -> array
```

##### 13.1.2.1.1. frames array

The frame array returned by any `*-display` method.

##### 13.1.2.1.2. caption bool

Whether to stack each frame's caption below its canvas inside the figure body.

Default: `true`

##### 13.1.2.1.3. alt auto or str

Alt-text override applied to every frame. `auto` uses each frame's `alt` field, falling back to the caption (if it's a plain string) and then to a generic "Animation frame N" placeholder.

Default: `auto`

##### 13.1.2.1.4. caption-spacing length

Spacing between canvas and caption when `caption: true`.

Default: `0.5em`

### 13.1.3. last

Final frame as a single piece of content. Useful for static renderings in print or for “just show me the end state” usage.

The inline node annotations (drawn next to nodes in the cetz canvas) already label what the final step did, so the textual caption is suppressed by default. Pass `caption: true` to stack the caption below the canvas.

The returned content is wrapped in an alt-tagged figure for accessibility. The alt text comes from the frame's `alt` field; pass an explicit string to `alt` to override.

#### 13.1.3.1. Parameters

```
last(  
  frames: array,  
  caption: bool,  
  spacing: length,  
  alt: auto str  
) -> content
```

##### 13.1.3.1.1. frames array

The frame array returned by any `*-display` method.

##### 13.1.3.1.2. caption bool

Whether to render the step's caption below the canvas.

Default: `false`

##### 13.1.3.1.3. spacing length

Vertical spacing between canvas and caption when `caption: true`.

Default: `0.5em`

##### 13.1.3.1.4. alt auto or str

Alt-text override. `auto` uses the frame's `alt` field.

Default: `auto`

#### 13.1.4. stacked

All frames stacked vertically as one block of content. Useful for handouts that want to show the full animation in a single figure. Captions are on by default since the stack is read as a sequence — the caption text annotates which step each tree corresponds to.

Each frame is wrapped individually in an alt-tagged figure so screen-reader users hear the per-step narration. Pass a string to `alt` to set the same override on every frame.

#### 13.1.4.1. Parameters

```
stacked(  
  frames: array,  
  caption: bool,  
  spacing: length,  
  caption-spacing: length,  
  alt: auto str  
) -> content
```

##### 13.1.4.1.1. frames array

The frame array returned by any `*-display` method.

##### 13.1.4.1.2. caption bool

Whether to include each frame's caption below its canvas.

Default: `true`

##### 13.1.4.1.3. spacing length

Vertical spacing between frames.

Default: `1em`

##### 13.1.4.1.4. caption-spacing length

Spacing between each canvas and its caption.

Default: `0.5em`

##### 13.1.4.1.5. alt auto or str

Alt-text override applied to every frame. `auto` uses each frame's `alt` field.

Default: `auto`

### 13.2. Animation core

- `apply-ops()`
- `blank-snapshot()`
- `concat-frames()`
- `make-renderer()`
- `set-render-theme()`

#### Variables

- `NodeStyle`
- `EdgeStyle`

- default-render-theme
- RenderTheme
- Snapshot
- Frame
- Renderer
- Op

### 13.2.1. apply-ops

Fold a sequence of Op values into a renderer, returning the updated renderer. The trailing in-progress frame is kept — no explicit Op.Commit is needed after the last batch of edits, but attach alt text to that trailing frame via Op.Alt (or `r.with-alt(...)` on the returned renderer) so it has accessible text like the committed frames do.

#### 13.2.1.1. Parameters

```
apply-ops(
  renderer: Renderer ,
  ops: array
) -> Renderer
```

##### 13.2.1.1.1. renderer    Renderer

The renderer to apply ops to.

##### 13.2.1.1.2. ops    array

Sequence of Op values to fold left-to-right.

### 13.2.2. blank-snapshot

Build a fresh Snapshot with no node or edge style overrides. Useful when you want to render a structure once with a draw backend and no per-frame state.

#### 13.2.2.1. Parameters

```
blank-snapshot() -> Snapshot
```

### 13.2.3. concat-frames

Stitch frame arrays from multiple renderers (or pre-rendered arrays) into one flat Array(Frame). Use this when an animation spans a structure-shape change (rotation, deletion, insertion) and one renderer can't hold all the frames — one renderer per shape, joined at the boundary.

Accepts a mix of Renderer instances and already-rendered arrays; the former are render-ed in place.

#### 13.2.3.1. Parameters

```
concat-frames(..parts) -> array
```



#### 13.2.3.1.1. ..parts

Variadic mix of renderers and frame arrays.

#### 13.2.4. make-renderer

Build a Renderer seeded with one blank initial frame, bound to a draw backend.

draw is the structure-specific backend wrapped in a singleton dict (fn: ..) — see the Renderer section comment. Backend-binding wrappers live in each backend module (make-renderer in tree-anim.typ, make-graph-renderer in graph-draw.typ).

With sticky: true (the default), each new frame pushed via r.push-frame() starts from the previous frame's style snapshot — so highlights accumulate over the course of an animation. Set sticky: false to start each frame from a clean slate.

With theme: auto (the default), each rendered canvas reads the active render theme from state at layout time, so a set-render-theme(..) earlier in the document propagates. Pass an explicit dictionary to bake a theme in and skip the state lookup.

##### 13.2.4.1. Parameters

```
make-renderer(  
  structure: any,  
  draw: dictionary,  
  default-node-style: dictionary,  
  default-edge-style: dictionary,  
  sticky: bool,  
  theme: auto dictionary  
) -> Renderer
```

##### 13.2.4.1.1. structure any

The structure to render — interpreted only by the draw backend.

##### 13.2.4.1.2. draw dictionary

Draw backend wrapped in a singleton dict (fn: ..).

##### 13.2.4.1.3. default-node-style dictionary

Default node-style overrides applied before per-snapshot overrides.

Default: (:)

#### 13.2.4.1.4. **default-edge-style** `dictionary`

Default edge-style overrides applied before per-snapshot overrides.

Default: `( : )`

#### 13.2.4.1.5. **sticky** `bool`

When `true`, new frames inherit the previous frame's style. When `false`, each new frame starts blank.

Default: `true`

#### 13.2.4.1.6. **theme** `auto` or `dictionary`

Render-theme override for this renderer. `auto` reads the active render-theme from state at layout time. A dict is merged into `default-render-theme` once and baked in.

Default: `auto`

### 13.2.5. **set-render-theme**

Override one or more render-theme keys for the rest of the document (state-based, scoped by Typst's normal layout flow). Pass a partial dictionary — only the keys you list are changed; the rest stay at their current values. Unknown keys panic.

#### 13.2.5.1. **Parameters**

`set-render-theme`(`theme`)

### 13.2.6. **NodeStyle**

Typsy refinement: a dictionary of node-style overrides. Recognised keys are `fill`, `stroke`, `text-fill`, `note`, `note-fill`, `hide`, `shape`, `tag`, `label`, `materialize`, and `key-styles`. `shape` accepts the string `"circle"` (default), `"triangle"` (apex up; useful as a subtree-summary marker), `"rectangle"`, or `"btree-node"` (B24 subdivided rectangle; reads the node's keys array). The triangle and rectangle share a  $1.4 \times 1.2$  bounding box; the circle keeps its  $1.2 \times 1.2$  footprint; the `btree-node` width scales as  $1.2 \times \text{keys.len}()$ , height stays 1.2. Named cetz anchors on the node's group (`north`, `south`, `east`, `west`) follow each shape's bounding box; `btree-node` additionally exposes `key-<i>` anchors at each compartment center and `gap-<i>` anchors at each child-edge attachment point on the south face. `tag` is a small piece of content drawn just outside the west of the node — useful for compact per-node annotations that don't compete with the label or the operation note slot (e.g. the RBT black-height bits enabled by `display(bits: true)`). `label` replaces the node's rendered label (otherwise derived from the structure node's `label` field, or `str(value)` when that's `auto`). For `"btree-node"`, the node has multiple compartments — per-key labels come from the node's `labels` array (entry `auto` falls back to `str(keys.at(i))`); per-compartment styling comes from

`key-styles`, an array of dicts (one per compartment) with `fill/stroke/text-fill` overrides. Use `(:)` in a slot to leave a compartment unstyled. `key-styles` merges index-wise across sticky frames so highlighting compartment 0 in one frame and compartment 1 in the next keeps both annotations. `materialize: true` draws an otherwise-phantom slot as a real node — useful for one-off pedagogical animations that need to expose a nil child (e.g. rendering  $\emptyset$  at a just-deleted leaf's position). Phantoms only exist at paths the tree either naturally generates as layout-balance siblings or where an edge style sets `force-show: true` materializing without one of those has no node to attach to.

### 13.2.7. EdgeStyle

Typsy refinement: a dictionary of edge-style overrides. Recognised keys are `stroke`, `note`, `note-fill`, `tag`, `mark`, `hide`, `parent-anchor`, `child-anchor`, and `force-show`. The two `*-anchor` keys accept a `cetz` anchor name (e.g. "north") and override the default fractional-distance endpoint on the parent or child side respectively; useful for connecting edges to non-circular shapes (e.g. `child-anchor:`

"north" to land on a triangle's apex). `force-show: true` renders an edge even when one endpoint is a phantom — used by the RBT delete animation to draw a stub edge into a now-nil position when marking double-black. `tag` is a small persistent annotation drawn near the edge midpoint in the render theme's `edge-tag-fill` color — the edge counterpart to a node's `tag`, distinct from the gold operation-level `note` slot. Used by AVL `display(heights: true)` to label each edge with the height of the subtree it points to, and by graphs to label each edge with its weight.

### 13.2.8. default-render-theme

Default render theme. The structural defaults the renderer falls back on when neither a snapshot nor `default-node-style/ default-edge-style` specifies otherwise.

### 13.2.9. RenderTheme

Typsy refinement: a dictionary whose keys are a subset of the render-theme keys (`node-fill`, `node-stroke`, `node-text-fill`, `edge-stroke`, `note-fill`, `edge-tag-fill`).

### 13.2.10. Snapshot

Typsy class representing one sparse style overlay — the per-node and per-edge style overrides for a single frame. Build one via `blank-snapshot()` and chain its `style-node/ style-edge/ note-node/ note-edge/ clear-notes` methods. Snapshots are rarely constructed directly — they're managed by `make-renderer()` and the data structures' `*-display` methods.

### 13.2.11. Frame

Typsy class representing one frame in an animation. Fields and methods:

- `render(op-theme, render-theme)` — method that, given resolved theme dicts, produces the cetz canvas for this frame. Theming-aware deferral lives here: by carrying a builder rather than pre-baked content, the `lib.typ` helpers (`last`, `stacked`, `figures`) can resolve theme state once per call instead of once per frame, which is meaningfully faster in many-structure documents. Per-data-structure themes (e.g. the RBT palette) are read inside each frame’s builder rather than passed in — the helpers only carry the two universal layers.
- `caption` — optional textual track for the step (possibly none).
- `step` — optional free-form per-method metadata (possibly none).
- `alt` — optional accessible text describing the frame (possibly none). Carried verbatim into the `alt:` argument on the Typst figure wrapping the canvas. The first frame of each operation includes the full structure (via the `describe` method) so screen-reader users have a baseline; subsequent frames describe only the per-step change.

Direct rendering pattern for custom layouts:

```
context {  
  let op = _op-theme-state.get()  
  let rt = _render-theme-state.get()  
  ... (frame.render)(op, rt) ...  
}
```

Or simply pass the frame array to one of the `lib.typ` helpers, which handle the state wrap for you.

The internal `_builder` field carries the actual rendering closure wrapped in a singleton dict so typsy’s auto-self-injection doesn’t fire on it; treat it as private and call `render` instead.

### 13.2.12. Renderer

Typsy class accumulating an animation. Holds the structure, a draw backend, parallel arrays of snapshots / captions / steps / alts (one entry per frame), and default node/edge styles. Methods include `push-frame()`, `patch(fn)`, `push-with-node(path, ..style)`, `push-with-edge(path, ..style)`, `push-note-node(path, txt)`, `push-note-edge(path, txt)`, `with-caption(c)`, `with-step(s)`, `with-alt(a)`, and `render()`. Build one via `make-renderer()`.

### 13.2.13. Op

Typsy enumeration describing a declarative command stream for building animations. Variants:

- `Op.Highlight(path, color)` — set a node’s stroke to `color + 2pt`.
- `Op.Annotate(path, text)` — attach an inline note to a node (drawn in-canvas).
- `Op.StyleNode(path, style)` — arbitrary node-style overrides.

- `Op.StyleEdge(path, style)` — arbitrary edge-style overrides.
- `Op.Commit(alt)` — finalise the current frame, attach `alt` text to it, and open a fresh blank frame. `alt` is required so every frame the command stream produces carries accessible text.
- `Op.Alt(text)` — set `alt` text on the in-progress frame without committing. Primary use is the trailing frame, which has no following `Op.Commit` to carry its `alt`; can also be used to set `alt` earlier in a frame's lifecycle if convenient.
- `Op.ClearNotes()` — drop all notes from the current frame's snapshot.

Captions and step metadata are renderer-level rather than snapshot-level: set them between `Op` batches via `r.with-caption(...)` / `r.with-step(...)`, not through an `Op`. Fold a sequence of `Ops` into a renderer with `apply-ops()`.

### 13.3. Tree backend

- `draw-tree()`
- `make-renderer()`
- `path-anchor()`

#### Variables

- `PathId`

#### 13.3.1. draw-tree

Emit the `cetz` draw commands for one styled snapshot of `tree`, *without* wrapping them in a `cetz.canvas`. Caller is responsible for the canvas wrap. Use this when you want to add your own `cetz` annotations alongside the tree — for example, callouts anchored at specific nodes.

The whole tree is wrapped in a named `cetz` group (name, default `"tree"`); each non-phantom node has an inner-name of `<node-prefix><cetz-tree-name>` where the `cetz-tree` name is `"0"` for the root, `"0-0"` for L (or child 0), `"0-1"` for R (or child 1), and so on. Fully qualified anchor names therefore look like `"tree.node-0-0-1"` — use `path-anchor()` to compute them from a path string.

Tree-shape dispatch: if `tree` exposes a `children` field, the `n`-ary builder is used (no phantom-sibling layout, each child path-segment is a digit indexing into `children`). Otherwise, the binary `.left` / `.right` builder runs.

#### 13.3.1.1. Parameters

```
draw-tree(
  tree: dictionary,
  snapshot: Snapshot,
  default-node-style: dictionary,
  default-edge-style: dictionary,
  render-theme: dictionary,
  name: str,
  node-prefix: str,
  grow: float,
  spread: float
) -> content
```

#### 13.3.1.1.1. **tree** dictionary

The tree to render. Two accepted shapes:

- Binary: any value with `value`, `label`, `left`, and `right` fields (e.g. a BST instance). `label` of `auto` falls back to `str(value)` any other value (string, image, content) is rendered as the node's drawn label.
- N-ary: any value with `keys` (array of key values), optional `labels` (parallel array of label overrides), and `children` (array of child subtrees; empty for leaves). Used with `shape: "btree-node"` in the default `node-style` to render the canonical subdivided rectangle.

#### 13.3.1.1.2. **snapshot** Snapshot

Style overlay for this snapshot. Use `blank-snapshot()` (from the animation core) for an unstyled tree.

#### 13.3.1.1.3. **default-node-style** dictionary

Default node-style overrides applied before per-node overrides.

Default: `(:)`

#### 13.3.1.1.4. **default-edge-style** dictionary

Default edge-style overrides applied before per-edge overrides.

Default: `(:)`

#### 13.3.1.1.5. **render-theme** dictionary

Structural defaults — the lowest layer of the style chain. Defaults to `default-render-theme` pass an already-merged dict (e.g. read from `set-render-theme`'s state inside a context block) to apply user overrides.

Default: `default-render-theme`

#### 13.3.1.1.6. **name** str

Outer group name for the whole tree. Must match the `tree-name` argument to `path-anchor()` for anchors to resolve.

Default: `"tree"`

#### 13.3.1.1.7. node-prefix `str`

Prefix attached to each node's cetz-tree internal name. Must match the prefix argument to `path-anchor()`.

Default: `"node- "`

#### 13.3.1.1.8. grow `float`

Depth-direction layout factor passed to cetz-tree. Values below 1 shorten edges between levels; values above 1 stretch them. Node sizes are unaffected.

Default: `1`

#### 13.3.1.1.9. spread `float`

Sibling-direction layout factor passed to cetz-tree. Values below 1 pull siblings together; values above 1 push them apart. Node sizes are unaffected.

Default: `1`

### 13.3.2. make-renderer

Build a tree Renderer seeded with one blank initial frame, bound to the `draw-tree()` backend. Thin wrapper over the generic `make-renderer` in `anim-core.typ` that injects the tree draw backend, preserving the historical `make-renderer(tree, ..)` signature.

#### 13.3.2.1. Parameters

```
make-renderer(  
  tree: dictionary,  
  default-node-style: dictionary,  
  default-edge-style: dictionary,  
  sticky: bool,  
  theme: auto dictionary  
) -> Renderer
```

##### 13.3.2.1.1. tree `dictionary`

The tree to render — any value with `value`, `label`, `left`, and `right` fields (binary) or `keys` / `children` (n-ary). See `draw-tree()`.

#### 13.3.2.1.2. **default-node-style** dictionary

Default node-style overrides applied before per-snapshot overrides.

Default: ( : )

#### 13.3.2.1.3. **default-edge-style** dictionary

Default edge-style overrides applied before per-snapshot overrides.

Default: ( : )

#### 13.3.2.1.4. **sticky** bool

When true, new frames inherit the previous frame's style. When false, each new frame starts blank.

Default: true

#### 13.3.2.1.5. **theme** auto or dictionary

Render-theme override for this renderer. auto reads the active render-theme from state at layout time. A dict is merged into default-render-theme once and baked in.

Default: auto

### 13.3.3. **path-anchor**

Translates a starling path-id to the fully-qualified cetz anchor name produced by `draw-tree()`. Path "" maps to the root anchor; binary paths use "L" / "R" (mapping to child indices 0 and 1); n-ary paths use digit characters "0" to "9" that pass through verbatim.

An optional "#<int>" suffix on the path (n-ary only) resolves to a per-compartment sub-anchor key-<int> on the btree-node — e.g. `path-anchor("01#1")` returns the anchor of the middle key compartment of the leftmost grandchild.

The `tree-name` and `prefix` arguments must match the name and node-prefix passed to `draw-tree`.

#### 13.3.3.1. **Parameters**

```
path-anchor(  
  path: str,  
  tree-name: str,  
  prefix: str  
) -> str
```



#### 13.3.3.1.1. path str

Path-id string identifying a node (optionally followed by "#<int>" for a btree-node compartment).

#### 13.3.3.1.2. tree-name str

Outer-group name; must match draw-tree's name.

Default: "tree"

#### 13.3.3.1.3. prefix str

Per-node prefix; must match draw-tree's node-prefix.

Default: "node- "

### 13.3.4. PathId

Typsy refinement: a path-id string. Binary trees use "L" / "R" characters (empty string = root, "L" = the root's left child, "LR" = the root's left child's right child, and so on). N-ary trees use digit characters "0" to "9" with each digit indexing into the parent's children array. An optional "#<int>" suffix addresses an internal key compartment of an n-ary node — used by path-anchor(), e.g. "01#1" is the middle-key compartment of the leftmost grandchild. The binary and n-ary alphabets are not mixed within a single path.

## 13.4. Graph

- graph()

### 13.4.1. graph

Factory: build a Graph from a positional list of nodes plus a named list of edges. Each node is one of:

- a bare id string (no position — supply positions later, e.g. via auto-layout in graph-layout.typ, or pass positions: to a \*-display method),
- an (id, x, y) tuple (label defaults to the id), or
- an (id, x, y, label) tuple.

Each edge is an (u, v) tuple (weight defaults to 1) or (u, v, weight). Positions are in cetz units.

```
// hand-placed
let g = graph(
  (("A", 0, 0), ("B", 3, 1), ("C", 1.5, 2.4)),
  edges: (("A", "B", 7), ("B", "C", 2), ("A", "C", 4)),
)
// position-less (lay out later)
let h = graph(("A", "B", "C"), edges: (("A", "B", 7),))
```

#### 13.4.1.1. Parameters

```
graph(  
  nodes: array ,  
  edges: array ,  
  directed: bool  
) -> Graph
```

##### 13.4.1.1.1. nodes array

Positional array of nodes — a bare id, an (id, x, y) tuple, or an (id, x, y, label) tuple.

##### 13.4.1.1.2. edges array

Edges — array of (u, v) or (u, v, weight).

Default: ()

##### 13.4.1.1.3. directed bool

Whether the graph is directed (arrowheads + ordered edge keys).

Default: **false**

### 13.5. Graph renderer

- draw-graph()
- edge-key()
- make-graph-renderer()
- node-anchor()

#### Variables

- GraphNodeId

#### 13.5.1. draw-graph

Emit the cetz draw commands for one styled snapshot of a positioned graph, *without* wrapping them in a `cetz.canvas`. The caller wraps the canvas — use this to add your own cetz annotations alongside the graph — see `node-anchor()`.

Edges are drawn first (straight lines between node centers) and the filled node glyphs on top, so the line ends are cleanly occluded by the nodes. Each edge's intrinsic weight/label is drawn at its midpoint in the render theme's `edge-tag-fill` a snapshot edge tag overrides that text, and a snapshot note (gold) draws an operation annotation on the edge. Directed graphs get arrowheads unless an edge sets its own mark.

### 13.5.1.1. Parameters

```
draw-graph(  
  pg: dictionary,  
  snapshot: Snapshot,  
  default-node-style: dictionary,  
  default-edge-style: dictionary,  
  render-theme: dictionary,  
  node-prefix: str  
) -> content
```

#### 13.5.1.1.1. pg dictionary

The positioned graph — see the module header for its shape.

#### 13.5.1.1.2. snapshot Snapshot

Style overlay for this snapshot. Use `blank-snapshot()` (from the animation core) for an unstyled graph.

#### 13.5.1.1.3. default-node-style dictionary

Default node-style overrides applied before per-node overrides.

Default: `(:)`

#### 13.5.1.1.4. default-edge-style dictionary

Default edge-style overrides applied before per-edge overrides.

Default: `(:)`

#### 13.5.1.1.5. render-theme dictionary

Structural defaults — the lowest layer of the style chain.

Default: `default-render-theme`

#### 13.5.1.1.6. node-prefix str

Per-node cetz element-name prefix. Must match the `prefix` argument to `node-anchor()`.

Default: `"node- "`

### 13.5.2. edge-key

Canonical snapshot key for the edge between u and v. Directed graphs key edges by "u->v" (order significant); undirected graphs sort the endpoints into "u - v" so the same edge has one key regardless of which endpoint is named first.

#### 13.5.2.1. Parameters

```
edge-key(  
  u: str,  
  v: str,  
  directed: bool  
) -> str
```

##### 13.5.2.1.1. u str

First endpoint id.

##### 13.5.2.1.2. v str

Second endpoint id.

##### 13.5.2.1.3. directed bool

Whether the graph is directed.

Default: false

### 13.5.3. make-graph-renderer

Build a graph Renderer seeded with one blank initial frame, bound to the draw-graph() backend. Thin wrapper over the generic make-renderer in anim-core.typ that injects the graph draw backend.

#### 13.5.3.1. Parameters

```
make-graph-renderer(  
  pg: dictionary,  
  default-node-style: dictionary,  
  default-edge-style: dictionary,  
  sticky: bool,  
  theme: auto dictionary  
) -> Renderer
```

##### 13.5.3.1.1. pg dictionary

The positioned graph to render.

#### 13.5.3.1.2. **default-node-style** dictionary

Default node-style overrides applied before per-snapshot overrides.

Default: ( : )

#### 13.5.3.1.3. **default-edge-style** dictionary

Default edge-style overrides applied before per-snapshot overrides.

Default: ( : )

#### 13.5.3.1.4. **sticky** bool

When true, new frames inherit the previous frame's style.

Default: true

#### 13.5.3.1.5. **theme** auto or dictionary

Render-theme override; auto reads state at layout time.

Default: auto

### 13.5.4. **node-anchor**

The fully-qualified cetz anchor name for the node id drawn by draw-graph(). Use it to attach your own callouts to a node when you call draw-graph inside your own cetz.canvas. The prefix must match the node-prefix passed to draw-graph. Sub-anchors follow (e.g. node-anchor("A") + ".north").

#### 13.5.4.1. **Parameters**

```
node-anchor(  
  id: str,  
  prefix: str  
) -> str
```

##### 13.5.4.1.1. **id** str

Node id.

##### 13.5.4.1.2. **prefix** str

Per-node name prefix; must match draw-graph's node-prefix.

Default: "node- "

### 13.5.5. GraphNodeId

Typsy refinement: a graph node id. Any string.

## 13.6. Graph auto-layout

- `auto-layout()`

### 13.6.1. auto-layout

Compute node positions for `g` with graphviz and return a `(id: (x, y))` map in cetz units, suitable for the `positions`: argument of any `Graph *-display` method (or `Graph.positioned`).

`diagraph-layout` returns node centers in points (y-up, matching cetz); each coordinate is divided by `unit` to convert to cetz units. The default 36pt ( $\frac{1}{2}$  inch) gives spacing that suits the renderer's radius-0.6 nodes; lower it to spread the graph out, raise it to pack it tighter. Edge spline points from graphviz are ignored — starling draws straight edges.

#### 13.6.1.1. Parameters

```
auto-layout(  
    g: Graph,  
    engine: str,  
    unit: length  
) -> dictionary
```

##### 13.6.1.1.1. `g` `Graph`

The Graph to lay out. Its positions (if any) are ignored; only nodes, edges, and directedness are used.

##### 13.6.1.1.2. `engine` `str`

graphviz layout engine — "dot" (layered, the default), "neato", "fdp", "sfdp", "circo", or "twopi".

Default: "dot"

##### 13.6.1.1.3. `unit` `length`

Points per cetz unit used to scale graphviz's output.

Default: 36pt