12-12-2023 12:06:19 DATE: REV.

ISSUED FOR REFERENCE

DESCRIPTION

2121-FO40P11-3 SPEC 1C17 E 139532015 F5 G6 B7 N 113388072 ALLIGNMENT BOLTS SUPPLIED BY VALVE VENDOR STEM EAST 2121-FO40P11-1-E 139526203

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A13/4XS> (L-6679) I132785 11.2 M FITTINGS 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREQD I1651298 <90FA300LBK3/4>(L-178) COUPLING ASME B16.11 3000# A105N SWE SWE - R01FNC441101 NREQD I1651676 <FCPA300LBK3/4> (L-180) 45 ELBOW ASME B16.11 3000# A105N SWE SWE - R32FNC441101 NREQD I1651294 <45FA300LBK3/4> (L-184) FLANGES SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS 15378342 <SWFA300R153/4XS> (L-295) GASKETS SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL CARBON STEEL SS 304 3/4 163508895 ASME B16.5 G03GDP1IS12 < N/A > (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437245 <SB2R51G1/231/2> - 2 NUTS PER BOLT - 90 mm Length

REMARKS FOR MECHANICAL SUBCONTRACTOR:  1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.  2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.  3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT  4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-0000603.  5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.  6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.  7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.  8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603).								ISSUED FOR REFERENCE
9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.  SUPPORTS LEGEND: Denotes Parts list no support — A = resting support G = Guide F = AXIAL STOP B = ANCHOR M = SPRING S = TIFFLON PAD WHERE WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								Signature for construction is shown on Iso list of relevant CWA
						STRESS CALC. N°		TITLE
01	ISSUED FOR REFERENCE	15-DEC-23	M YADAV	P VAZE	G PAGANONI	P & ID		ISOMETRIC DRAWING

P.VAZE

CHECK BY

08-MAY-23

DATE

M.YADAV

DRW. BY

G.PAGANONI

APPR. BY

APPR. CLIENT

19-A-19-000-1-01-00001 sheet 45

19-L-19-000-2-00-86196 sheet 2

19-L-19-000-2-00-80602

CS PAINTING SCHEME (3) n is shown PIPING CLASS WELDING CLASS (4) PED CATEGORY

LINE

3/4"-FO-40P11-1C17

PIPE MATERIAL

HEAT TREATMENT (PWHT) CONTRACTOR:

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102.

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

CONTRACTOR DRAWING NUMBER:

4274-XH-DL-2121FO40P11-2 1C17 LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS FOR PROJECT - ALBA PROJECT

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

PROJECT:

4001008

01

REPSQL Art 4.3 INSULATION CODE / THK. (mm) DRAWING NUMBER 19-000-2-02-00001 sheet 2121FO40P11-2 ANNEX SPEC.