

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) FITTINGS STRAIGHT TEE ASME B16.9 A234-WPB BE SMLS C31DC04V01 S-XS I128999 <TEBA200F312161216> (L-7940) WN FLANGE ASME B16.5 300# A105N RFFE BE 125 - 250 AARH F01CFC44BV05 S-XS I4217849 PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A11XS > (L-6679) I132793 0.5 M PLUG ROUND HEAD ASME B16.11 - A105N MTE NREQD - R42FQC44W001 NREQD 110088245 GASKETS SPIRAL WOUND GASKET ASME B16.20 300# RFTBE 304/GRAFOIL CARBON STEEL SS 304 1 163508951 ASME B16.5 G03GFP1IS12 < N/A > (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 I53437418 <SB2R51G5/831/4> - 2 NUTS PER BOLT - 80 mm Length NIPPLED BALL VALVE ASME B16.34 600# A105N PE PE 4130 STEEL + Cr Carbide 164665976 B7/2H FB FLOATING BALL LE SCH1-XS SCH2-XS NIPPLE LENGTH 100mm V36JHC44ZZDH NREOD < N/A > (N/A)NIPPLED BALL VALVE ASME B16.34 600# A105N PE FTE 4130 STEEL + Cr Carbide 164947576 B7/2H FB FLOATING BALL LE SCH1-XS SCH2-XS NIPPLE LENGTH 100mm V36JHC44Z2DH NREOD < N/A > (N/A)NSTRUMENTS INSTRUMENT COMPONENT 19-KV-4041E 1

1) L1 2) A 3) F0 4) F0 5) G 6) C: 7) IN	REMARKS FOR MECHANICAL SUBCONTRACTOR:  1) LINES 1.1.12" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.  2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.  3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT  4) FOR EXTRA PIPE LENGTH REFER TO 42/4-LZ-PC-00000603.  5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.  6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.  7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.							
8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603).  9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.  SUPPORTS LEGEND:    DENOTES PARTS LIST NO   PIPE     A = RESTING SUPPORT   G = GUIDE   F = AXIAL STOP   B = ANCHOR   M = SPRING   S = TEPLON PAD   WHERE   WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								Si
							STRESS CALC. N° - P & ID 19-A-19-000-1-01-00001 sheet 49	I
00	ISSUED FOR REFERENCE	23-JUN-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N° 19-L-19-000-2-00-80602	
REV	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT N° 19-L-19-000-2-00-86197 sheet 7	

Signature for construction is shown on Iso list of relevant CWA ISOMETRIC DRAWING

LINE

1"-VA-40U09-1E18

**ISSUED FOR** 

REFERENCE

PIPING CLASS

PIPE MATERIAL

HEAT TREATMENT (PWHT)

CS

PAINTING SCHEME (3) CONTRACTOR:

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

CONTRACTOR DRAWING NUMBER:

4274-XH-DL-2121VA40U09-1 1E18 WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

4001008

00

PROJECT:

Art 4.3 REPSQL INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 19-000-2-02-00001 sheet 2121VA40U09-1