STREAM REV. NO.: 9

STREAM NO.:4404

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

PROVIDE BIRDSCREEN OPEN END CUT TO 45DEG 3 EL +28644\ N 113389622 ORIENT EAST SEE ISO 2121-VA40U08-1 EL +27114 SEE ISO 2121-VA40U10-1 F8 SPEC 1C2 E 139537122 EL +26383

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A106-B BE SMLS T01AC03V02 S-STD < PIPA010B13STD > (L-7806) I117921 FITTINGS REDUCING SOCKOLET MSS-SP-97 3000# A105N BE SWE - R13DNC44V101 NREQD I1651368 <SOKA300LB01511> (L-343) I128599 (L-7955) PIPE SUPPORTS STAKES SUPPORTS ST02 HEA120 721 U BOLT (FOR GUIDE)-P02D 721 STOP HORIZ VERT FOR NOT INS. PIPING-N1F1 PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A13/4XS > (L-6679) I132785 1.0 M FLANGES SW FLANGE ASME B16.5 300# A105N RFFE SWE 125 - 250 AARH F02CFC44B105 S-XS 19762190 <SWFA300R353/4XS> (L-375)

71.67.11	2) ALL 3) FOR 4) FOR 5) GUS 6) CRC 7) IN C 8) ACT	1) LINES 1.1/2 AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. 2) ALL DIMENSION AND PROPER CONSTRUCTION. 3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT. 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-000000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274+LZ-PC-00000003). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00900/2 4274-NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.							
	SUPPORTS LEGEND: DENOTES PARTS LIST NO PIPE — A=RESTING SUPPORT G=GUIDE F=AUAL STOP B=ANCHOR M=SPRING S=THEON PAD WHERE WHERE WHEN UNIT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								<u>'</u>
; [STRESS CALC. Nº	Т
:								-	
i								P & ID 19-A-19-000-1-01-00001 sheet 49	
	00	ISSUED FOR CONSTRUCTION	14-JUL-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N° 19-L-19-000-2-00-80602	
	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT N° 19-L-19-000-2-00-86197 sheet 7	

CONSTRUCTION Signature for construction is shown on Iso list of relevant CWA

APPROVED FOR

CS

HEAT TREATMENT (PWHT)

PAINTING SCHEME (3)

INSULATION CODE / THK. (mm)

ISOMETRIC DRAWING LINE

3"-VA-40U10-1C2

PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

ANNEX

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

19-000-2-02-00001 sheet 2121VA40U10-2

CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: 4001008 PIPING CLASS 4274-XH-DL-2121VA40U10-2 WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX

DRAWING NUMBER

AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT Art 4.3 REPSQL

REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00

FILENAME: 19-000-2-02-00001 sheet 2121VA40U10-2.dwg