REV.

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

DESCRIPTION

2)

ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT

2X1/2"NPD 20MM OFFSET F2 G6 B7 SEE ISO 2121-DC40L14-1 SPEC 7E28 E 139534754 N 113388151 EL +2006 2X1"NPD SEE ISO 2121-DC40L10-SPEC 6G69 E 139534653 N 113388416

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY (IN) STATUS FITTINGS ECCENTRIC SWAGE MSS SP-95 - A403-WP304/304L DG BE PE SMLS SCH1-80S SCH2-80S 2X1/2 I2506802 R22FQL2FVZ05 <ESWB04DGR14041004> (L-ESW22) WN FLANGE ASME B16.5 600# A182-F316/316L DUAL GR RFFE BE 125 - 250 AARH I3707122 PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-80S < PIPB04DA21/280S > 12257955 0.1 M FITTINGS 90 ELBOW ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R31FNL2A1103 I2258115 NREOD <90FB450LBK1/2> (L-90F05) COUPLING ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R01FNL2A1101 I2258103 NREOD < FCPB450LBK 1/2 > (L-FCP08) GASKETS SPIRAL WOUND GASKET ASME B16.20 600# RFTBE 304/GRAFOIL SS 304 SS 304 ASME I1169028 B16.5 G03GHP1IS04 < N/A > (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437270 <SB2R51G5/841/4> - 2 NUTS PER BOLT - 110 mm Length

4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. (7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603 A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. DENOTES PARTS LIST NO PIPE SUPPORT — SUPPORTS LEGEND: TRESS CALC. Nº 19-A-19-000-1-01-00001 sheet 42 ISSUED FOR CONSTRUCTION 19-MAY-23 U.CHAVAN P.VAZE G.PAGANONI 19-L-19-000-2-00-80602

CHECK BY

APPR. BY

APPROVED FOR CONSTRUCTION

Signature for construction is shown on Iso list of relevant CWA

ISOMETRIC DRAWING LINE

2"-DC-40L14-7E28 (ET)

PIPE LAYOUT No

19-L-19-000-2-00-86196 sheet 1

APPR. CLIENT

PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

ANNEX

304, dual grade

HEAT TREATMENT (PWHT)

INSULATION CODE / THK. (mm)

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: NR PIPING CLASS 4001008 4274-XH-DL-2121DC40L14-2

DRAWING NUMBER

7E28 WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT REPSQL

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00

19-000-2-02-00001 sheet 2121DC40L14-2