STREAM NO.:200

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

29-05-2023 12:54:06

SEE ISO 2121-IA68W20-1 SPEC B-13 E 139535970 SCREWED END N 113391580 EL +3490 2 1X1"NPD \ EL +3463 E 139535970 FUSIBLE GLASS BULB N 113391580 -SEE ISO 2121-IA68W20-3 E 139535412 EL +2244

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A53-B GALV MTE SMLS T01AC11W02 S-XS < PIPG010C11XS > (N/A) I145594 FITTINGS TEE ASME B16.11 3000# A105 GALV FTE FTE - R11FNC022201 NREQD <TETG300KBK1> I214944 (L-8911) CONCENTRIC SWAGE MSS SP-95 - A105 GALV MTE MTE SMLS SCH1-XS SCH2-XS R21FQC02WW01 < CSWG010DR12161016 > (L-CSW28) 90 ELBOW ASME B16.11 3000# A105 GALV FTE FTE - R31FNC022203 NREQD I214920 <90TG300KBK1>(L-8907) I45867360 UNION ASME B16.11 3000# A105 GALV FTE FTE - R43FNC022201 NREOD <N/A> (N/A) COUPLING ASME B16.11 3000# A105 GALV FTE FTE - R01FNC022201 NREQD I214897 <FCPG300KBK1>(L-8910) COUPLING ASME B16.11 3000# A105 GALV FTE FTE - R01FNC022201 NREQD I214895 <FCPG300KBK1/2>(L-8910)

12.34.00	3) FOR 4) FOR 5) GUS 6) CRO 7) IN C 8) ACT	2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION. 3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF. TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-0007-06-00902/ 4274-NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.							
SUPPORTS LEGEND: DENOTES PARTS LIST NO PIPE — A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=THELON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.									
0-6								STRESS CALC. Nº	Т
1 a								P & ID 19-A-19-000-1-01-00001 sheet 124	
2	00	ISSUED FOR REFERENCE	26-MAY-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N° 19-L-19-000-2-00-80602	
	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT № 19-L-19-000-2-00-86197 sheet 1	

REFERENCE Signature for construction is shown on Iso list of relevant CWA

ISSUED FOR

ISOMETRIC DRAWING LINE 1"-IA-68W20-B-13

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

ANNEX

PIPE MATERIAL

CS, Galvanized

HEAT TREATMENT (PWHT)

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

19-000-2-02-00001 sheet 2121IA68W20-2

PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: 4001008 PIPING CLASS 4274-XH-DL-2121IA68W20-2

DRAWING NUMBER

WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT REPSQL Art 4.3 INSULATION CODE / THK. (mm)

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00