2121-IA91F62-7 SPEC 6C4 E 139521470 \2X3/4"NPD F2 G3 B4 E 139521004 N 113400734 v EL +5012 TO 19-KV-4102P2

BILL OF MATERIAL HOLD N.S. COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-40S < PIPB04DA23/440S > I2257938 (L-PIP111) SW FLANGE ASME B16.5 150# A182-F304/304L DUAL GR RFFE SWE 125 - 250 AARH 12260362 SASKETS SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL SS 304 SS 304 ASME I1654481 B16.5 G03GDP1IS04 <N/A> (N/A) BOLTS STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B8M CL2/A194-8MA INCH SIZE I63801410 I01OB1601 <SB2R58G1/221/2> - 2 NUTS PER BOLT - 65 mm Length VALVES / IN-LINE ITEMS GATE VALVE API 602 800# A182-F316/316L DUAL GR SWE SWE 12-316&HF API 602 13404186 A193-B8M CL2/8MA BB-OS&Y SOW API 602 HW V01GIL1M114N NREQD < G63 4L-AL021>

27									
STRE		RKS FOR MECHANICAL SUBCONTRACTOR:	·	·				<u> </u>	
S		1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.							
		2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.							
		3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT							
	4) FOR	4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.							1
7		5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.							1
9:2		6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.							
33		7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.							1
$\tilde{\infty}$		8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603).							
0	9) WHI	9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.							∫Si
23		TIDENOTES PAPTS I ISTNO PIPE — A=RESTING SUPPORT G=GLIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD							
202	SUPPORTS LEGEND: DENOTES PARTS LIST NO SUPPORT — A=RESING SUPPORT G=GUDE F=AXIAL SIOP B=ANCHOR M=SPRING S=TEPLON PAD WHERE A WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								
12								STRESS CALC. Nº	TITI
								-	
DATE: 09.								D 0 ID	- I
	01	ISSUED FOR REFERENCE	08-DEC-23	M.YADAV	P.VAZE	G.PAGANONI		P&ID	I
								19-A-19-000-1-01-00001 sheet 106	1
Ϋ́		MOLIER FOR REPERFYOR	20 777 22			a n. a		LINE LIST Nº	
EXTR. D	00	ISSUED FOR REFERENCE	28-JUL-23	M.YADAV	P.VAZE	G.PAGANONI		19-L-19-000-2-00-80602	
								PIPE LAYOUT N°	1
X	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT		
Ш,	v.	Discini IION	D.T.E	DR. W. BT	CILLUI DI	D1	I III CEILINI	19-L-19-000-2-00-86197 sheet 2	

Signature for construction is shown on Iso list of relevant CWA

ISSUED FOR

REFERENCE

PIPE MATERIAL

PIPING CLASS

WELDING CLASS (4)

INSULATION CODE / THK. (mm)

PED CATEGORY

304, dual grade

HEAT TREATMENT (PWHT)

ISOMETRIC DRAWING LINE

3/4"-IA-91FAA-6C4

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

ANNEX

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: NR

> 4274-XH-DL-2121IA91FAA-1 6C4 LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS FOR PROJECT - ALBA PROJECT REPSQL Art 4.3

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

4001008

DRAWING NUMBER 01 19-000-2-02-00001 sheet 2121IA91FAA-1