REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

DESCRIPTION

6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED


ISSUED FOR REFERENCE

2)

ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT

(7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.



A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE[A] WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.

P.VAZE

CHECK BY

G.PAGANON

APPR. BY

01-SEP-23

U.CHAVAN

TRESS CALC. No

PIPE LAYOUT No

APPR. CLIENT

19-L-19-000-2-00-80602

19-L-19-000-2-00-86196 sheet 1

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY (IN) STATUS PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A11/2XS > (L-6679) I132777 FITTINGS CONCENTRIC SWAGE MSS SP-95 - A105N PE PE SMLS SCH1-XS SCH2-XS R21FQC44ZZ01 3/4X1/2 I63782564 <CSWA010AR11161016> (L-7890) COUPLING ASME B16.11 3000# A105N SWE SWE - R01FNC441101 NREQD I1651676 <FCPA300LBK3/4> (L-180) TEE ASME B16.11 3000# A105N SWE SWE - R11FNC441101 NREQD <TESA300LBK1/2> 11651299 1/2X1/2 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREOD I1651295 <90FA300LBK1/2>(L-178) PLUG ROUND HEAD ASME B16.11 - A105N MTE NREQD - R42FQC44W001 NREQD 110088243 <PLUA300CK1/2> (L-77) COUPLING ASME B16.11 3000# A105N SWE SWE - R01FNC441101 NREQD 11651675 <FCPA300LBK1/2> (L-180) SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS I5378341 SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL CARBON STEEL SS 304 1/2 I63508894 ASME B16.5 G03GDP1IS12 < N/A > (N/A) BOLTS 10 STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437179 <SB2R51G1/221/2> - 2 NUTS PER BOLT - 60 mm Length VALVES / IN-LINE ITEMS 1 BALL VALVE API 608 150# A216-WCB REFE 316/R-PTFE, GF B7/2H 125 - 250 AARH 1/2 110013685 2PSB-FULL BORE FLOATING BALL OHW ASME B16.5 V04JDC29BZZG NREQD <N/A> (N/A) BALL VALVE ASME B16.34 800# A105N SWE FTE 316/R-PTFE, GF 3PSB-RED BORE 167130076 FLOATING BALL OHW FIRE SAFE :API 607 & ANTISTATIC DEVICES "A60T series" TEAL V04JIC44126IG NREQD <N/A> (N/A) PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 CS 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: PIPING CLASS 4001008 4274-XH-DL-2121VG40R02-1 1C17 WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS REPSOL POLYMEROS/ PED CATEGORY FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX Art 4.3 REPSQL INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 00 19-000-2-02-00001 sheet 2121VG40R02-1

ISSUED FOR

REFERENCE

Signature for construction is shown

FILENAME: 19-000-2-02-00001 sheet 2121VG40R02-1.dwg