REV. CAUSE ID:

REV.

ISSUED FOR CONSTRUCTION

DESCRIPTION

2X1/2"NPD 20MM OFFSET~ FLAT SIDE D SEE ISO 2121-DC40L13-1 /N 113386251 EL +2006 F2 G6 B7 SEE ISO 2121-DC40L16-1 SPEC 6G69 E 139534653 N 113386516

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE STATUS (IN) FITTINGS ECCENTRIC SWAGE MSS SP-95 - A403-WP304/304L DG BE PE SMLS SCH1-80S SCH2-80S 2X1/2 I2506802 R22FQL2FVZ05 <ESWB04DGR14041004> (L-ESW22) WN FLANGE ASME B16.5 600# A182-F316/316L DUAL GR RFFE BE 125 - 250 AARH I3707122 PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-80S < PIPB04DA21/280S > 12257955 0.1 M FITTINGS I2258115 NREOD <90FB450LBK1/2> (L-90F05) COUPLING ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R01FNL2A1101 I2258103 NREQD <FCPB450LBK1/2> (L-FCP08) SASKETS SPIRAL WOUND GASKET ASME B16.20 600# RFTBE 304/GRAFOIL SS 304 SS 304 ASME I1169028 B16.5 G03GHP1IS04 < N/A > (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437270 <SB2R51G5/841/4> - 2 NUTS PER BOLT - 110 mm Length

REMARKS FOR MECHANICAL SUBCONTRACTOR:
1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.
2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.
3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL 🗶 , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT
4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.
6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.
7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.
8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF. TO 4274-LZ-PC-00000603).
9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.
SUPPORTS LEGEND: DENOTES PARTS LIST NO PIPE — A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.

19-MAY-23

U.CHAVAN

P.VAZE

CHECK BY

G.PAGANONI

APPR. BY

Signature for construction is shown on Iso list of relevant CWA

2"-DC-40L13-7E28 (ET)

LINE

19-A-19-000-1-01-00001 sheet 42

19-L-19-000-2-00-86196 sheet 1

19-L-19-000-2-00-80602

PIPE LAYOUT Nº

APPROVED FOR

CONSTRUCTION

PIPING CLASS ISOMETRIC DRAWING PED CATEGORY INSULATION CODE / THK. (mm)

PIPE MATERIAL

304, dual grade

HEAT TREATMENT (PWHT)

PAINTING SCHEME (3) CONTRACTOR: NR 7E28 WELDING CLASS (4)

ANNEX

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" CONTRACTOR DRAWING NUMBER: PROJECT:

4274-XH-DL-2121DC40L13-2 LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS

FOR PROJECT - ALBA PROJECT REPSQL

DRAWING NUMBER

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX 00

4001008

19-000-2-02-00001 sheet 2121DC40L13-2