
REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.



BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-40S < PIPB04DA2140S > I2257939 19.4 M (L-PIP111). REDUCING TEE ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE 1X3/4 12258205 R12FNL2A1101 NREQD < RTEB450LBK13/4> (L-RTE18) 90 ELBOW ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R31FNL2A1103 12258117 NREQD <90FB450LBK1> (L-90F05). COUPLING ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R01FNL2A1101 I2258105 NREOD <FCPB450LBK1> (L-FCP08) NIPPLE - - A312-TP304/304L DUAL GR PE MTE SMLS LENGTH 100mm R03AQL2CZW04 I2258068 S-80S <NTOB04DE2110424> (L-NTO09) CAP ASME B16.11 3000# A182-F304/304L DUAL GR FTE NREQD - R41FNL2A2001 I2259129 NREQD <CATB450KBK3/4> (L-CAT04) LANGES SW FLANGE ASME B16.5 150# A182-F304/304L DUAL GR RFFE SWE 125 - 250 AARH I2260363 F02CDL2AB105 S-40S <SWFB450R15140S> (L-SWF30). SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL SS 304 SS 304 ASME 11654482 B16.5 G03GDP1IS04 <N/A> (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B8M CL2/A194-8MA INCH SIZE I63801410 I01OB1601 <SB2R58G1/221/2> - 2 NUTS PER BOLT - 65 mm Length

ATE: 24-06-2	4) FOR 5) GUS 6) CRO 7) IN O 8) ACT	3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ★, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274-NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.							
	SUPPORTS LEGEND: DENOTES PARTSLIST NO PIPE — A=RESTING SUPPORT G=GUDE F=AXIALSTOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. STRESS CALC. N°							STRUCTURE.	Si
	00	ISSUED FOR REFERENCE	23-JUN-23	U.CHAVAN	P.VAZE	G.PAGANONI		P & ID 19-A-19-000-1-01-00001 sheet 106 LINE LIST N° 19-I19-000-2-00-80602	I
EXTR.	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	ADDD CLIENT	PIPE LAYOUT N° 19-L-19-000-2-00-86192 sheet 1	

Signature for construction is shown on Iso list of relevant CWA

ISSUED FOR

REFERENCE

ISOMETRIC DRAWING LINE

1"-IA-91F39-6C4

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

CONTRACTOR:

ANNEX

PIPE MATERIAL

304, dual grade

HEAT TREATMENT (PWHT)

PAINTING SCHEME (3)

INSULATION CODE / THK. (mm)

PIPING CLASS

NR

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

CONTRACTOR DRAWING NUMBER:

4274-XH-DL-2121IA91F39-1 WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT Art 4.3 REPSQL

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

4001008

PROJECT:

DRAWING NUMBER 00 19-000-2-02-00001 sheet 2121IA91F39-1