REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

F3 G4 B5 F3 G4 B5 2121-LPN40N06-2 N 113381700 EL +3024 3/4X1/2"NPD CONN TO 19-PK-4003/DC ARM/N5' 0.5/in/RFFE/150 E 139536206 N 113382059

BILL OF MATERIAL HOLD STATUS COMPONENT DESCRIPTION ITEM CODE QTY (IN) PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A11/2XS> (L-6679) I132777 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREQD I1651295 <90FA300LBK1/2>(L-178) FLANGES SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS 15378341 <SWFA300R151/2XS> (L-295) SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL CARBON STEEL SS 304 1/2 163508894 ASME B16.5 G03GDP1IS12 <N/A> (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437179 <SB2R51G1/221/2> - 2 NUTS PER BOLT - 60 mm Length VALVES / IN-LINE ITEMS BALL VALVE API 608 150# A216-WCB RFFE 316/R-PTFE, GF B7/2H 125 - 250 AARH I10013685 2PSB-FULL BORE FLOATING BALL OHW ASME B16.5 V04JDC29BZZG NREQD <N/A> (N/A)

9	2) ALI 3) FOR 4) FOR	1) LINES 1.1/2 AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. 2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION. 3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.								
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274-NN-DW-00000002 AND ASSEMBLY N								FEA005 AND FE019.	Sig	
7-2023	SUPPORTS LEGEND: DENOTES PARTSLIST NO SUPPORT — A=RESTING SUPPORT G=GUIDE F=AXIALSTOP B=ANCHOR M=SPRING S=TEFLONPAD WHERE WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								TITI	
07-0′								-	TITL	
VTE:								P & ID 19-A-19-000-1-01-00001 sheet 44	10	
D	00	ISSUED FOR REFERENCE	07-JUL-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST № 19-L-19-000-2-00-80602		
EXTR.	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT N° 19-L-19-000-2-00-86196 sheet 1		

REFERENCE Signature for construction is shown on Iso list of relevant CWA

ISSUED FOR

PIPE MATERIAL

HEAT TREATMENT (PWHT)

INSULATION CODE / THK. (mm)

CS

ISOMETRIC DRAWING LINE

1/2"-LPN-40N25-1C17

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

19-000-2-02-00001 sheet 2121LPN40N25-1

PAINTING SCHEME (3)

DRAWING NUMBER

CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: 4001008 PIPING CLASS 4274-XH-DL-2121LPN40N25-1 1C17

WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT REPSQL Art 4.3

ANNEX

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00