REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

3/4"NPD SEE ISO 2121-IW91N26-1 SPEC B-1 E 139532746 -N 113388025 EL +15372 2 -3/4X3/4"NPD E 139532922 ~ EL +13721 E 139532826 N 113388025

BILL OF MATERIAL HOLD STATUS COMPONENT DESCRIPTION ITEM CODE QTY (IN) PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A13/4XS> (L-6679) I132785 FITTINGS TEE ASME B16.11 3000# A105N SWE SWE - R11FNC441101 NREQD <TESA300LBK3/4> I1651300 45 ELBOW ASME B16.11 3000# A105N SWE SWE - R32FNC441101 NREQD I1651294 <45FA300LBK3/4> (L-184) NIPPLE - - A106-B PE MTE SMLS LENGTH 100mm R03AQC03ZW04 S-XS I2221184 <NTOA010E1111624> (L-7888) CAP ASME B16.11 3000# A105N FTE NREQD - R41FNC442001 NREQD <CATA300KBK3/4> 3/4 11651686 SPECIALTY COMPONENT SP-04-291N0-08 1 VALVES / IN-LINE ITEMS GLOBE VALVE API 602 800# A105N SWE SWE 5-HARDFACED API 602 B7/2H BB-OS&Y I11426472 API 602 HW V02GIC441162 NREQD < A63 4L-296> (L-296) GATE VALVE API 602 800# A105N SWE SWE 5-HARDFACED API 602 B7/2H BB-OS&Y SOW 3/4 I11426464 API 602 HW V01GIC441111 NREQD < G63\_4L-6566> (L-6566)

:48:22	2) ALI 3) FOR 4) FOR 5) GUS 6) CRO 7) IN O	1) LINES 1.1/2 AND SWALLER STALL BE SUPPOKTED IN FIELD IN FOIL OF HERWISE INDICATED. 2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES INSI. 1.1/2 AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION. 3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.							
8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/4274-NN-DW-00000002 AND ASSEMBLY NO FEA005.  SUPPORTS LEGEND:  DENOTES PARTS LIST NO PIPE — A-RESTING SUPPORT G-GUDE F-AXIAL STOP B-ANCHOR M-SPRING S-TIFLON PAD WHERE WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCT								FLON PAD	S
01-06		_						STRESS CALC. Nº	TIT
ATE: 0								P & ID 19-A-19-000-1-01-00001 sheet 111	J
Õ	00	ISSUED FOR REFERENCE	02-JUN-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N° 19-L-19-000-2-00-80602	
EXTR.	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT N° 19-L-19-000-2-00-86196 sheet 4	

REFERENCE Signature for construction is shown on Iso list of relevant CWA

LINE

3/4"-IW-91N26-B-1

**ISSUED FOR** 

PIPING CLASS WELDING CLASS (4) ISOMETRIC DRAWING PED CATEGORY INSULATION CODE / THK. (mm)

PIPE MATERIAL

HEAT TREATMENT (PWHT)

CS

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST.

CONTRACTOR:

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

CONTRACTOR DRAWING NUMBER:

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" PAINTING SCHEME (3)

4001008 4274-XH-DL-2121IW91N26-2 LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS

CLIENT / COMPLEX REPSOL POLYMEROS/ FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX

PROJECT:

REPSQL Art 4.3 DRAWING NUMBER ANNEX 00 19-000-2-02-00001 sheet 2121IW91N26-2