STREAM REV. NO.: 9 STREAM NO.:4204

REV. CAUSE ID:

DATE:

REV.

2121-LPN40P08-1 E 139529663 N 113384964 EL +11943 1.1/2X3/4"NPD 11MM OFFSET FLAT SIDE D F4 G5 B6 G5 B6 CONN TO 19-D-4045/F 0.75/in/RFFE/15 E 139530390 STEM SOUTH N 113386831

COUPLING ASME B16.11 3000# A105N SWE SWE - R01FNC441101 NREQD I1651676 <FCPA300LBK3/4> (L-180) FLANGES SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS I5378342 <SWFA300R153/4XS> (L-295) SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL CARBON STEEL SS 304 3/4 163508895 ASME B16.5 G03GDP1IS12 < N/A > (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 I53437190 <SB2R51G1/221/2> - 2 NUTS PER BOLT - 65 mm Length VALVES / IN-LINE ITEMS BALL VALVE API 608 150# A216-WCB RFFE 316/R-PTFE, GF B7/2H 125 - 250 AARH I10013686 2PSB-FULL BORE FLOATING BALL OHW ASME B16.5 V04JDC29BZZG NREQD <N/A> (N/A) PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 CS 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: PIPING CLASS 4001008 4274-XH-DL-2121LPN40P08-2 1C17 LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS REPSOL POLYMEROS/ FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX Art 4.3 REPSQL INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 00 19-000-2-02-00001 sheet 2121LPN40P08-2

BILL OF MATERIAL

COMPONENT DESCRIPTION

<90FA300LBK3/4> (L-178)

FITTINGS

PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A13/4XS > (L-6679)

90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREQD

NS

(IN)

ITEM CODE

I132785

I1651298

HOLD

STATUS

QTY

Signature for construction is shown on Iso list of relevant CWA
TITLE
ISOMETRIC DRAWING

ISSUED FOR

REFERENCE

WELDING CLASS (4) PED CATEGORY

FILENAME: 19-000-2-02-00001 sheet 2121LPN40P08-2.dwg

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. 2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT

4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.

6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.
7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603'

9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.

I DENOTES PARTS LIST NO PIPE SUPPORT — A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. SUPPORTS LEGEND:

19-A-19-000-1-01-00001 sheet 45 ISSUED FOR REFERENCE 23-JUN-2023 M.YADAV P.VAZE G.PAGANONI 19-L-19-000-2-00-80602 PIPE LAYOUT Nº APPR. CLIENT DESCRIPTION CHECK BY APPR. BY

LINE 3/4"-LPN-40P08-1C17

TRESS CALC. No

19-L-19-000-2-00-86196 sheet 3