01-09-

FITTINGS TEE ASME B16.11 3000# A105N SWE SWE - R11FNC441101 NREQD <TESA300LBK11/2> 1.1/2X1.1/2 I1651302 REDUCING TEE ASME B16.11 3000# A105N SWE SWE - R12FNC441101 NREQD <RTEA300KBK11/21> (L-RTE15) COUPLING ASME B16.11 3000# A105N SWE SWE - R01FNC441101 NREQD 11651679 1.1/2 <FCPA300LBK11/2>(L-180) 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREOD 11651297 1.1/2 LANGES SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS 1.1/2 15378345 <SWFA300R1511/2XS>(L-295) BLIND FLANGE ASME B16.5 150# A105N RFFE NREQD 125 - 250 AARH F10CDC44B005 I1652359 SEE ISO 2121-LS91A0T-1 <BLFA300R1511/2> (L-140) GASKETS SPEC B-5 E 139529939 SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 316/GRAP CARBON STEEL SS 316 I1256083 ASME B16.5 G03GDP1IA01 <SPWO400R111/2> (L-1527) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I01OB0301 153437201 4 EL +3124 <SB2R51G1/223/4> - 2 NUTS PER BOLT - 70 mm Length N 113366172 2121-LS91A79-1 SPEC B-5 SEE ISO 2121-LS91A80-1 E 139519674 N 113366685 SPEC B-5 E 139530272 E 139530272 /N 113365307 N 113366172 N 113365475 SEE ISO 2121-LS91A78-2 3 1.1/2X1"NPD SPEC B-5 E 139530272 N 113365475 SEE ISO 7111-LS91A78-1 SPEC B-5 E 139513150 N 113366685 EL +3124 1.1/2"NPD REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. **ISSUED FOR** 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 2)

ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT CS 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 REFERENCE 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002 HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. (7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603 Signature for construction is shown A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE[A] WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. PIPING CLASS 4001008 4274-XH-DL-2121LS91A78-1 SUPPORTS LEGEND: on Iso list of relevant CWA TRESS CALC. Nº WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS ISOMETRIC DRAWING REPSOL POLYMEROS/ PED CATEGORY 19-A-19-000-1-01-00001 sheet 117 FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX LINE Art 4.3 REPSQL ISSUED FOR REFERENCE 01-SEP-23 U.CHAVAN P.VAZE G.PAGANONI 19-L-19-000-2-00-80602 INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 00 PIPE LAYOUT No 1-1/2"-LS-91A78-B-5 (HA) 19-000-2-02-00001 sheet 2121LS91A78-1 REV. DESCRIPTION APPR. CLIENT CHECK BY APPR. BY 19-L-19-000-2-00-86192 sheet 1

BILL OF MATERIAL

COMPONENT DESCRIPTION

PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A111/2XS > (L-6679)

N.S.

(IN)

1.1/2

ITEM CODE

I132809

HOLD

STATUS

QTY

18.2 M