STREAM NO.:4036

REV.

DESCRIPTION

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY (IN) STATUS PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-80S <PIPB04DA21/280S> I2257955 (L-PIP110) JACK SCREWS TO BE SUPPLIED BY MECHANICAL CONTRACTOR.
THE DRILLING AND THREADING FOR JACK SCREW SHALL BE DONE BY MECHANICAL CONTRACTOR ACCORDING TO PE-L-0100.13 "JACK SCREW". 45 LR ELBOW ASME B16.9 A403-WP304/304L DG BE SMLS C02DL2FV01 S-80S I2376173 LANGES WN FLANGE ASME B16.5 600# A182-F316/316L DUAL GR RFFE BE 125 - 250 AARH I2254580 F01CHL1MBV05 S-80S <> () GASKETS SPIRAL WOUND GASKET ASME B16.20 600# RFTBE 304/GRAFOIL SS 304 SS 304 ASME I1169016 B16.5 G03GHP1IS04 < N/A > (N/A) BOLTS SPEC 7E28 STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437223 N 113395737 <SB2R51G1/231/4> - 2 NUTS PER BOLT - 80 mm Length F3 G4 B6 EL +18272 STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437245 <SB2R51G1/231/2> - 2 NUTS PER BOLT - 90 mm Length NIPPLED BALL VALVE BS EN ISO 17292 800# A182-F316/316L DUAL GR PE PE 164005281 316/PEEK A193-B8M CL2/8MA 3PSB-FULL BORE FLOATING BALL OHW SCH1-80S SCH2-80S LENGTH 75mm V36FIL1MZZAO NREOD <B61 2L-AL293> (L-AL293) $\overline{}$ 7 STEM HOR -135.0 DEG VOR 60.0 DEG-SP-33-240C2-01/TEAL INLET E 139529673 REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. **ISSUED FOR** 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 2)

ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 304, dual grade 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 REFERENCE 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. () CROSSING BETWEEN WEEDS ON THE ELING STALE NOT BE ADMITTED.

7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. PAINTING SCHEME (3) CONTRACTOR DRAWING NUMBER: CONTRACTOR: PROJECT: 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603 NR 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019. Signature for construction is shown I DENOTES PARTS LIST NO PIPE SUPPORT — A=RESTING SUPPORT G=GUIDE F=AYAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE Δ WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. PIPING CLASS 4001008 4274-XH-DL-2121TEA40C01-5 on Iso list of relevant CWA SUPPORTS LEGEND: 7E28 TRESS CALC. Nº WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS ISOMETRIC DRAWING REPSOL POLYMEROS/ PED CATEGORY 19-A-19-000-1-01-00001 sheet 32 FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX REPSQL LINE Art 4.3 ISSUED FOR REFERENCE 21-JUL-23 U.CHAVAN P.VAZE G.PAGANONI 19-L-19-000-2-00-80602 INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 00 PIPE LAYOUT Nº 19-000-2-02-00001 sheet 2121TEA40C01-5 1/2"-TEA-40C01-7E28

APPR. CLIENT

19-L-19-000-2-00-86197 sheet 5

CHECK BY

APPR. BY