REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

6 STEM HOR -118.3 DEG VOR -77.0 DEG MITRE 3.8° 6 STEM HOR -112.8 DEG VOR -69.3 DEG SEE ISO 2121-VG40E01-2 SPEC 2E63 E 139524027 CONN TO N 113390237 19-D-4040/J EL +22104 l/in/RFFE/300 E 139524338 EL +22270

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY (IN) STATUS PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-40S < PIPB04DA2140S > I2257939 (L-PIP111) 90 ELBOW ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R31FNL2A1103 I2258117 LANGES SW FLANGE ASME B16.5 300# A182-F316/316L DUAL GR RFFE SWE 125 - 250 AARH I2500941 F02CFL1MB105 S-40S <SWFB34DR35140S> (L-SWF37) SPIRAL WOUND GASKET ASME B16.20 300# RFTBE 304/PTFE SS 304 SS 304 ASME I219568 B16.5 G03GFP1IG04 < N/A > (N/A) BOLTS STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A320-L7/A194-7 INCH SIZE I010B5301 155705037 <SB2R55G5/831/4> - 2 NUTS PER BOLT - 80 mm Length ALVES / IN-LINE ITEMS BALL VALVE ASME B16.34 300# A351-CF8M RFFE 316/R-PTFE, GF A193-B8M CL2/8MA 164815734 125 - 250 AARH 2PSB-FULL BORE FLOATING BALL OHW ASME B16.5 V04JFL08B05C NREOD < N/A > (N/A)INSTRUMENTS INSTRUMENT COMPONENT 19-KV-4040M 1

2)

ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. () CROSSING BETWEEN WEEDS ON THE ELING STALE NOT BE ADMITTED.

7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603 A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. DENOTES PARTS LIST NO PIPE SUPPORT — SUPPORTS LEGEND: TRESS CALC. Nº 19-A-19-000-1-01-00001 sheet 48 ISSUED FOR REFERENCE 14-JUL-23 U.CHAVAN P.VAZE G.PAGANONI 19-L-19-000-2-00-80602 PIPE LAYOUT Nº REV. DESCRIPTION APPR. CLIENT CHECK BY APPR. BY

REFERENCE Signature for construction is shown on Iso list of relevant CWA

**ISSUED FOR** 

ISOMETRIC DRAWING LINE

1"-VG-40E07-2E63

19-L-19-000-2-00-86197 sheet 6

NR PIPING CLASS 2E63 WELDING CLASS (4)

ANNEX

PIPE MATERIAL

CS, low temperature

INSULATION CODE / THK. (mm)

HEAT TREATMENT (PWHT)

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT:

DRAWING NUMBER

4274-XH-DL-2121VG40E07-1

LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT Art 4.3 REPSQL

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00

4001008

19-000-2-02-00001 sheet 2121VG40E07-1

FILENAME: 19-000-2-02-00001 sheet 2121VG40E07-1.dwg