HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) GASKETS SPIRAL WOUND GASKET ASME B16.20 300# RFTBE 316/GRAP LTCS SS 316 ASME B16.5 I46364709 G03GFP1IAG8 < N/A> (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A320-L7/A194-7 INCH SIZE I010B5301 155705085 <SB2R55G3/441/2> - 2 NUTS PER BOLT - 115 mm Length ALVES / IN-LINE ITEMS GLOBE VALVE BS 1873 300# A352-LCC RFFE 16-HARDFACED BS 1873 L7/7 125 - 250 I64156253 AARH BB-OS&Y BS 1873 HW ASME B16.5 V02BFC82B0BE NREQD < A44L-7865> (L-786. INSUL: CG - THK 50 mr CLASS: C-42 INSUL: CG - THK 65 mm SEE ISO SPEC 1E21 SEE ISO N 113398679 G1 B2 EL +5817 2121-VRG52A10-1 SPEC C-42 REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. APPROVED FOR 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT CS, low temperature 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 CONSTRUCTION 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.
7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603 PROJECT: Signature for construction is shown I DENOTES PARTS LIST NO PIPE SUPPORT — A=RESTING SUPPORT G=GUIDE F=AYAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE  $\Delta$  WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE. PIPING CLASS 4001008 4274-XH-DL-2121VRG52A39-1 on Iso list of relevant CWA SUPPORTS LEGEND: C-42 TRESS CALC. Nº WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS ISOMETRIC DRAWING REPSOL POLYMEROS/ ISSUED FOR CONSTRUCTION M.YADAV P.VAZE G.PAGANONI 18-AUG-23 PED CATEGORY 19-A-19-000-1-01-00001 sheet 53 FOR PROJECT - ALBA PROJECT SINES INDUSTRIAL COMPLEX LINE REPSQL ISSUED FOR CONSTRUCTION 27-JAN-23 M.YADAV P.VAZE G.PAGANONI 19-L-19-000-2-00-80602 INSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 01 PIPE LAYOUT Nº 4"-VRG-52A39-C-42 (CG) 19-000-2-02-00001 sheet 2121VRG52A39-1 REV. DESCRIPTION CHECK BY APPR. CLIENT APPR. BY 19-L-19-000-2-00-86197 sheet 2

BILL OF MATERIAL