SEE ISO 2121-N91M67-2 SPEC 1C13 E 139521400 N 113393675 ALLIGNMENT BOLTS SUPPLIED BY VALVE VENDOR E 139520787 N 113393675 EL +27584 SPEC 1C13 E 139522487 N 113393675

BILL OF MATERIAL HOLD STATUS COMPONENT DESCRIPTION ITEM CODE QTY (IN) PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A13/4XS> (L-6679) I132785 FITTINGS TEE ASME B16.11 3000# A105N SWE SWE - R11FNC441101 NREQD <TESA300LBK3/4> 3/4X3/4 I1651300 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREQD 11651298 <90FA300LBK3/4> (L-178) NIPPLE - - A106-B PE MTE SMLS LENGTH 100mm R03AQC03ZW04 S-XS 12221184 <NTOA010E1111624> (L-7888) CAP ASME B16.11 3000# A105N FTE NREQD - R41FNC442001 NREQD <CATA300KBK3/4> 3/4 11651686 LANGES SW FLANGE ASME B16.5 150# A105N RFFE SWE 125 - 250 AARH F02CDC44B105 S-XS 15378342 <SWFA300R153/4XS> (L-295) ASKETS SPIRAL WOUND GASKET ASME B16.20 150# RFFE 304/PTFE CARBON STEEL SS 304 ASME 3/4 I2230475 B16.5 G03GDB1IG12 < SPAO505R1EA3/4> (L-SPA04) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437245 <SB2R51G1/231/2> - 2 NUTS PER BOLT - 90 mm Length ALVES / IN-LINE ITEMS DISC CHECK WFR VALVE ASME B16.34 150# A216-WCB RFTBE 316/R-PTFE, GF 125 -I10016147 250 AARH SL VERTICAL&HORIZONTAL CRACK. PRESS. 1/2 PSI ASME B16.5 V40JDC29P01 NREQD < N/A> (N/A)

07:00:18	4) FOR 5) GUS 6) CRO 7) IN O 8) ACT	3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002. 6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN. 8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF. TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/4274-NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.							
SUPPORTS LEGEND: DENOTES PARTS LIST NO PIPE — A=RESTING SUPPORT G=GLIDE F=AXIAL STOP B=ANCHOR M=SPRING S=WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STE								FLONPAD STRUCTURE. STRESS CALC. Nº	TIT
0								P & ID	l j
ë l								19-A-19-000-1-01-00001 sheet 110	1
DΑ	00	ISSUED FOR REFERENCE	02-JUN-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N° 19-L-19-000-2-00-80602	
XTR.	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR. CLIENT	PIPE LAYOUT N° 19-L -19-000-2-00-86197 sheet 7	

3/4X3/4"NPD

Signature for construction is shown on Iso list of relevant CWA

LINE

3/4"-N-91M67-1C13

**ISSUED FOR** 

REFERENCE

WELDING CLASS (4) ISOMETRIC DRAWING PED CATEGORY INSULATION CODE / THK. (mm)

PIPE MATERIAL

HEAT TREATMENT (PWHT)

PAINTING SCHEME (3)

Art 4.3

CS

CONTRACTOR:

ANNEX

NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

CONTRACTOR DRAWING NUMBER: PROJECT:

PIPING CLASS 4001008 4274-XH-DL-2121N91M67-1 LOW LINEAL DENSITY POLYETHILENE (PEL)

AND POLYPROPYLENE (PP) PLANTS FOR PROJECT - ALBA PROJECT REPSQL

DRAWING NUMBER

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

00

FILENAME: 19-000-2-02-00001 sheet 2121N91M67-1.dwg

2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

19-000-2-02-00001 sheet 2121N91M67-1