REV. CAUSE ID:

STREAM REV. NO.: 7

STREAM NO.:4001 REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED. SUPPORTS LEGEND: DATE: REV.

2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT

9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.

13-MAR-23

U.CHAVAN

DRW. BY

A=RESTING SUPPORT G=GUIDE F=AYAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE Δ WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.

P.VAZE

CHECK BY

G.PAGANONI

APPR. BY

TRESS CALC. No

PIPE LAYOUT Nº

APPR. CLIENT

19-A-19-000-1-01-00001 sheet 29

19-L-19-000-2-00-86196 sheet 3

19-L-19-000-2-00-80602

4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.

I DENOTES PARTS LIST NO PIPE SUPPORT —

DESCRIPTION

ISSUED FOR REFERENCE

6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.
7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.

8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603)

SEE ISO 2121-ET40B15-2~ N 113383500 EL +12100 ALLIGNMENT BOLTS SUPPLIED BY VALVE VENDOR SEE ISO 2121-ET40A07-4 SPEC 1E21 E 139526647 N 113383650 FI.+9070 STEM NORTH

PIPE - A106-B PE SMLS T01AC03Z02 S-XS < PIPA010A11XS > (L-6679) I132793 FITTINGS 90 ELBOW ASME B16.11 3000# A105N SWE SWE - R31FNC441103 NREQD I1651296 <90FA300LBK1> (L-178) FLANGES SW FLANGE ASME B16.5 300# A105N RFFE SWE 125 - 250 AARH F02CFC44B105 S-XS I4217823 <SWFA300R351XS>(L-375) SPIRAL WOUND GASKET ASME B16.20 300# RFTBE 304/GRAFOIL CARBON STEEL SS 304 1 163508951 ASME B16.5 G03GFP1IS12 < N/A> (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B7/A194-2H INCH SIZE I010B0301 153437269 <SB2R51G5/841/4> - 2 NUTS PER BOLT - 105 mm Length ALVES / IN-LINE ITEMS DISC CHECK WFR VALVE ASME B16.34 300# A216-WCB RFTBE 316/R-PTFE, GF 125 -I10208505 250 AARH SL VERTICAL&HORIZONTAL CRACK. PRESS. 1/2 PSI ASME B16.5 V40JFC29P01 NREQD <N/A> (N/A) PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 CS 3. WELDING ACCORDING TO 45-L-45-000-2-00-80021 HEAT TREATMENT (PWHT) 5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE" PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: 4001008 4274-XH-DL-2121ET40B15-1 1E21 VELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) CLIENT / COMPLEX AND POLYPROPYLENE (PP) PLANTS REPSOL POLYMEROS/ ED CATEGORY FOR PROJECT - ALBA PROJECT Art 4.3 REPSQL NSULATION CODE / THK. (mm) DRAWING NUMBER ANNEX 00 19-000-2-02-00001 sheet 2121ET40B15-1 N

BILL OF MATERIAL

COMPONENT DESCRIPTION

HOLD

STATUS

QTY

ITEM CODE

(IN)

Signature for construction is shown on Iso list of relevant CWA	PIF
TITLE	WI
ISOMETRIC DRAWING	
	PE
LINE	
	INS
1"-ET-40B15-1E21	
	ISOMETRIC DRAWING LINE

ISSUED FOR

REFERENCE

IPING CLASS

SINES INDUSTRIAL COMPLEX

FILENAME: 19-000-2-02-00001 sheet 2121ET40B15-1.dwg