REV. CAUSE ID:

STREAM REV. NO.: 9

STREAM NO.:3250

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

E 139520949 CONN TO 19-IAM-011/INLET 1/in/RFFF/150 E 139520949 N 113364656 SEE ISO 2121-IA91F34-1 SPEC 6C4

N 113367035

BILL OF MATERIAL HOLD COMPONENT DESCRIPTION ITEM CODE QTY STATUS (IN) PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-40S < PIPB04DA2140S > 12257939 (L-PIP111) REDUCING TEE ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE -1X3/4 12258205 R12FNL2A1101 NREQD < RTEB450LBK13/4> (L-RTE18) 90 ELBOW ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R31FNL2A1103 12258117 NREQD <90FB450LBK1> (L-90F05) NIPPLE - - A312-TP304/304L DUAL GR PE MTE SMLS LENGTH 100mm R03AQL2CZW04 I2258068 S-80S < NTOB04DE2110424> (L-NTO09) CAP ASME B16.11 3000# A182-F304/304L DUAL GR FTE NREQD - R41FNL2A2001 I2259129 NREOD <CATB450KBK3/4> (L-CAT04) FLANGES SW FLANGE ASME B16.5 150# A182-F304/304L DUAL GR RFFE SWE 125 - 250 AARH 12260363 F02CDL2AB105 S-40S <SWFB450R15140S> (L-SWF30) SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL SS 304 SS 304 ASME 11654482 B16.5 G03GDP1IS04 <N/A> (N/A) STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B8M CL2/A194-8MA INCH SIZE I63801410 I01OB1601 <SB2R58G1/221/2> - 2 NUTS PER BOLT - 65 mm Length VALVES / IN-LINE ITEMS GATE VALVE API 602 800# A182-F316/316L DUAL GR SWE SWE 12-316&HF API 602 I3404187 A193-B8M CL2/8MA BB-OS&Y SOW API 602 HW V01GIL1M114N NREQD <G61L-AL021>

	2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION. 3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗ , ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT 4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00006603. 5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.								
7									
Σ. 	6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED. 7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.								
-2023 07::	8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603). 9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274-NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.								Si
	SUPPORTS LEGEND: DENOTES PARTS LIST NO PIPE A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.								
<u>;</u>								STRESS CALC. Nº	TITI
4								-	J ∓,
ži								P & ID 19-A-19-000-1-01-00001 sheet 106	
Ā	00	ISSUED FOR REFERENCE	28-JUL-23	U.CHAVAN	P.VAZE	G.PAGANONI		LINE LIST N°	
~	00	ISSUED FOR REFERENCE	26-JCE-23	O.CHAVAN	1.VAZE	G.I AGAINONI		19-L-19-000-2-00-80602	4
Ξ	REV.	DESCRIPTION	DATE	DRW. BY	CHECK BY	APPR. BY	APPR CLIENT	PIPE LAYOUT Nº 10-I -10-000-2-00-86102 sheet 2	
-3	ICL V.	DESCRI HOW	DATE	DICW. DI	CILCRE	ATTR. DI	ATTIC CEILINI	110 I 10 000 2 00 86102 chast 2	1

Signature for construction is shown on Iso list of relevant CWA

**ISSUED FOR** 

REFERENCE

ISOMETRIC DRAWING LINE

1"-IA-91FBE-6C4

PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102 304, dual grade

ANNEX

HEAT TREATMENT (PWHT)

INSULATION CODE / THK. (mm)

PIPING CLASS

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: NR

4274-XH-DL-2121IA91FBE-1

WELDING CLASS (4) LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS PED CATEGORY FOR PROJECT - ALBA PROJECT REPSQL Art 4.3

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

4001008

DRAWING NUMBER 00 19-000-2-02-00001 sheet 2121IA91FBE-1

FILENAME: 19-000-2-02-00001 sheet 2121IA91FBE-1.dwg

