23

REV.

SUPPORTS LEGEND:

ISSUED FOR REFERENCE

ISSUED FOR REFERENCE

REMARKS FOR MECHANICAL SUBCONTRACTOR:

1) LINES 1.1/2" AND SMALLER SHALL BE SUPPORTED IN FIELD IF NOT OTHERWISE INDICATED.

DESCRIPTION

2) ALL DIMENSION AND PROPER CONFIGURATION FOR LINES NPS 1.1/2" AND SMALLER SHALL BE CHECKED IN FIELD BEFORE CONSTRUCTION.

3) FOR THE COMPONENTS MARKED AS FIELD WELDED WITH THIS SYMBOL ✗, ONE WELD FOR ADJUSTMENT OF IN LINE COMPONENT MUST BE LEFT

9) WHERE EARTHING BONDING IS REQUIRED, MECHANICAL SUBCONTRACTOR TO PERFORM IT BASED ON DOC. 45-P-000-7-06-00902/ 4274 -NN-DW-00000002 AND ASSEMBLY NO FEA005 AND FE019.

08-DEC-23

28-JUL-23

M.YADAV

M.YADAV

DRW. BY

A=RESTING SUPPORT G=GUIDE F=AXIAL STOP B=ANCHOR M=SPRING S=TEFLON PAD WHERE A WITHOUT NUMBERING IS INDICATED, THIS MEANS THAT THERE IS A REST DIRECTLY ON STEEL STRUCTURE.

P.VAZE

P.VAZE

CHECK BY

G.PAGANONI

G.PAGANONI

APPR. BY

TRESS CALC. Nº

PIPE LAYOUT No

APPR. CLIENT

19-A-19-000-1-01-00001 sheet 106

19-L-19-000-2-00-86197 sheet 6


19-L-19-000-2-00-80602

4) FOR EXTRA PIPE LENGTH REFER TO 4274-LZ-PC-00000603.
5) GUSSETING TO BE IMPLEMENTED BY MECHANICAL SUBCONTRACTOR AS PER 45-L-45-000-2-00-80004 / 4274-XH-SG-00000002.

DENOTES PARTS LIST NO PIPE SUPPORT —

6) CROSSING BETWEEN WELDS ON PIPELINE SHALL NOT BE ADMITTED.
7) IN CASE OF DISCREPANCIES BETWEEN DATA SHOWN ON ISO AND IN LINE LIST (AS APPLICABLE, DATA SHOWN IN LINE LIST GOVERN.

8) ACTUAL CUT LENGTH OF PIPE AND FIELD WELDS SHALL BE DEFINED BY MECHANICAL SUBCONTRACTOR (REF.TO 4274-LZ-PC-00000603'



BILL OF MATERIAL NS HOLD. COMPONENT DESCRIPTION ITEM CODE QTY (IN) STATUS PIPE - A312-TP304/304L DUAL GR PE SMLS T01AL2CZ02 S-40S < PIPB04DA23/440S> I2257938 (L-PIP111) 90 ELBOW ASME B16.11 3000# A182-F304/304L DUAL GR SWE SWE - R31FNL2A1103 I2258116 NREQD <90FB450LBK3/4> (L-90F05) SPECIALTY COMPONENT 19-FX-4104 FLANGES SW FLANGE ASME B16.5 150# A182-F304/304L DUAL GR RFFE SWE 125 - 250 AARH I2260362 F02CDL2AB105 S-40S <SWFB450R153/440S> (L-SWF30) SPIRAL WOUND GASKET ASME B16.20 150# RFTBE 304/GRAFOIL SS 304 SS 304 ASME 11654481 B16.5 G03GDP1IS04 < N/A > (N/A) BOLTS STUD BOLTS&NUTS ASME B18.31.2/ B18.2.2 A193-B8M CL2/A194-8MA INCH SIZE I63801410 I01OB1601 <SB2R58G1/221/2> - 2 NUTS PER BOLT - 65 mm Length VALVES / IN-LINE ITEMS GATE VALVE API 602 800# A182-F316/316L DUAL GR SWE SWE 12-316&HF API 602 I3404186 A193-B8M CL2/8MA BB-OS&Y SOW API 602 HW V01GIL1M114N NREQD < G63 4L-AL021>

Signature for construction is shown on Iso list of relevant CWA
TTLE
ISOMETRIC DRAWING
LINE
3/4"-IA-91F0V-6C4

ISSUED FOR

REFERENCE

PIPE MATERIAL NOTES: 1. FOR TECHNICAL DETAILS SEE LINE LIST. 304, dual grade

ANNEX

HEAT TREATMENT (PWHT)

6C4

PIPING CLASS

WELDING CLASS (4)

INSULATION CODE / THK. (mm)

PED CATEGORY

2. FOR VENT, DRAIN OR INSTRUMENT CONNECTION DETAILS SEE 45-L-45-000-2-00-80102

4274-XH-DL-2121IA91F0V-1

3. WELDING ACCORDING TO 45-L-45-000-2-00-80021

5. CODE SHOWN IN BOM BETWEEN "<" & ">" DENOTES REPSOL UNICODE. "<N/A>" MEANS UNICODE IS "NOT AVAILABLE"

N PAINTING SCHEME (3) CONTRACTOR: CONTRACTOR DRAWING NUMBER: PROJECT: NR

> LOW LINEAL DENSITY POLYETHILENE (PEL) AND POLYPROPYLENE (PP) PLANTS FOR PROJECT - ALBA PROJECT Art 4.3 REPSQL

CLIENT / COMPLEX REPSOL POLYMEROS/ SINES INDUSTRIAL COMPLEX

4001008

DRAWING NUMBER 01 19-000-2-02-00001 sheet 2121IA91F0V-1