



University of sigmas

Oiowe chady

Adam Biel, Mateusz Jurach, Karol Żeleźnik

2024-02-24

Data structures (1)

wavelet.cpp

Opis: Wavelet Tree, operacje w $O(\log ALPH)$

84cff0, 59 lines

```
struct wavelet_tree {
    const static int ALPH = (1<<18)-1;
    struct Node {
        int low, high, mid;
        vector<int> v;
        Node *left, *right;

        Node() {
            low = 0, high = ALPH;
            left = right = nullptr;
            mid = (low+high)/2;
        }

        Node (const vector<int> &x, const vector<int> &t, int a =
            0, int b = ALPH): low(a), high(b), v(x) {
            mid = ((1l)low+high)/2;
            if(ssize(x) && low != high) {
                vector<int> div[2];
                for(auto e : v) div[t[e]<=mid].eb(e);
                if(ssize(div[1])) left = new Node(div[1], t, low, mid);
                else left = nullptr;
                if(ssize(div[0])) right = new Node(div[0], t, mid+1,
                    high);
                else right = nullptr;
            }
            else {
                left = right = nullptr;
            }
        }
    };

    Node *root;
    wavelet_tree(const vector<int> &b) {
        vector<int> idx;
        REP(i, ssize(b)) idx.eb(i);
        root = new Node(idx, b);
    };

    int cnt(Node *v, int l, int r) {
        if(v == nullptr) return 0;
        return int(upper_bound(all(v->v), r)-lower_bound(all(v->v),
            l));
    }

    int rank(int l, int r, int k, Node *v) {
        if(v->low == v->high) return v->low;
        if(cnt(v->left, l, r) >= k) return rank(l, r, k, v->left);
        else return rank(l, r, k-cnt(v->left, l, r), v->right);
    }

    int rank(int l, int r, int k) {
        return rank(l, r, k, root);
    }

    void clear(Node *v) {
        if(v->left != nullptr) clear(v->left);
        if(v->right != nullptr) clear(v->right);
        delete v;
    }

    ~wavelet_tree() {
        clear(root);
    }
};
```