

Rajalakshmi Engineering College

Name: RAGHAVAN M.K
Email: 240701408@rajalakshmi.edu.in
Roll no: 240701408
Phone: 7397247776
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 1_PAH_modified

Attempt : 1
Total Mark : 5
Marks Obtained : 3

Section 1 : Coding

1. Problem Statement

Imagine you are managing the backend of an e-commerce platform. Customers place orders at different times, and the orders are stored in two separate linked lists. The first list holds the orders from morning, and the second list holds the orders from the evening.

Your task is to merge the two lists so that the final list holds all orders in sequence from the morning list followed by the evening orders, in the same order

Input Format

The first line contains an integer n , representing the number of orders in the morning list.

The second line contains n space-separated integers representing the morning orders.

The third line contains an integer m , representing the number of orders in the evening list.

The fourth line contains m space-separated integers representing the evening orders.

Output Format

The output should be a single line containing space-separated integers representing the merged order list, with morning orders followed by evening orders.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
101 102 103
2
104 105
Output: 101 102 103 104 105

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct node{
    int data;
    struct node* next;
};
struct node* createnode(int data)
{
    struct node* newnode = (struct node*)malloc(sizeof(struct node));
    newnode->data = data;
    newnode->next = NULL;
    return newnode;
}
struct node* createlinkedlist(int count)
```

```

{
    if(count==0) return NULL;
    int val;
    scanf("%d",&val);
    struct node* head = createnode(val);
    struct node* current = head;
    for(int i=1; i<count; i++)
    {
        scanf("%d",&val);
        current->next = createnode(val);
        current = current->next;
    }
    return head;
}
void printlist(struct node* head)
{
    while(head!=NULL)
    {
        printf("%d ", head->data);
        head = head->next;
    }
}
int main()
{
    int n,m;
    scanf("%d", &n);
    struct node* morning = createlinkedlist(n);
    scanf("%d",&m);
    struct node* evening = createlinkedlist(m);
    if(morning == NULL)
    {
        printlist(evening);
        return 0;
    }
    struct node* temp = morning;
    while(temp->next!=NULL)
    {
        temp = temp->next;
    }
    temp->next = evening;
    printlist(morning);
    return 0;
}

```

}

Status : Correct

Marks : 1/1

2. Problem Statement

Write a program to manage a singly linked list. The program should allow users to perform various operations on the linked list, such as inserting elements at the beginning or end, deleting elements from the beginning or end, inserting before or after a specific value, and deleting elements before or after a specific value. After each operation, the updated linked list should be displayed.

Input Format

The first line contains an integer choice, representing the operation to perform:

- For choice 1 to create the linked list. The next lines contain space-separated integers, with -1 indicating the end of input.
- For choice 2 to display the linked list.
- For choice 3 to insert a node at the beginning. The next line contains an integer data representing the value to insert.
- For choice 4 to insert a node at the end. The next line contains an integer data representing the value to insert.
- For choice 5 to insert a node before a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 6 to insert a node after a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 7 to delete a node from the beginning.
- For choice 8 to delete a node from the end.
- For choice 9 to delete a node before a specific value. The next line contains an integer value representing the node before which deletion occurs.
- For choice 10 to delete a node after a specific value. The next line contains an integer value representing the node after which deletion occurs.
- For choice 11 to exit the program.

Output Format

For choice 1, print "LINKED LIST CREATED".

For choice 2, print the linked list as space-separated integers on a single line. If the list is empty, print "The list is empty".

For choice 3, 4, 5, and 6, print the updated linked list with a message indicating the insertion operation.

For choice 7, 8, 9, and 10, print the updated linked list with a message indicating the deletion operation.

For any operation that is not possible print an appropriate error message such as "Value not found in the list".

For choice 11 terminate the program.

For any invalid option, print "Invalid option! Please try again".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

5

3

7

-1

2

11

Output: LINKED LIST CREATED

5 3 7

Answer

-

Status : Skipped

Marks : 0/1

3. Problem Statement

John is working on evaluating polynomials for his math project. He needs to compute the value of a polynomial at a specific point using a singly linked list representation.

Help John by writing a program that takes a polynomial and a value of x as input, and then outputs the computed value of the polynomial.

Example

Input:

2

13

12

11

1

Output:

36

Explanation:

The degree of the polynomial is 2.

Calculate the value of x^2 : $13 * 12 = 13$.

Calculate the value of x^1 : $12 * 11 = 12$.

Calculate the value of x^0 : $11 * 10 = 11$.

Add the values of x^2 , x^1 and x^0 together: $13 + 12 + 11 = 36$.

Input Format

The first line of input consists of the degree of the polynomial.

The second line consists of the coefficient x^2 .

The third line consists of the coefficient of x^1 .

The fourth line consists of the coefficient x^0 .

The fifth line consists of the value of x , at which the polynomial should be evaluated.

Output Format

The output is the integer value obtained by evaluating the polynomial at the given value of x.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2

13

12

11

1

Output: 36

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
typedef struct node{
    int coeff;
    struct node* next;
}node;
node* createnode(int coeff)
{
    node* newnode = (node*)malloc(sizeof(node));
    newnode->coeff = coeff;
    newnode->next = NULL;
    return newnode;
}
void insertend(node** head, int coeff)
{
    node* newnode = createnode(coeff);
    if(*head ==NULL)
    {
        *head = newnode;
    }
    else
    {
```

```

        node* temp = *head;
        while(temp->next!=NULL)
            temp = temp->next;
        temp->next = newnode;
    }
}

int evaluatePoly(node* head, int degree, int x)
{
    int result = 0;
    int power = degree;
    node* temp = head;
    while(temp!=NULL)
    {
        int term = temp ->coeff;
        int x_pow = 1;
        for(int i=0; i<power; i++)
            x_pow *= x;
        result += term * x_pow;
        power--;
        temp = temp->next;
    }
    return result;
}

int main()
{
    int degree, x;
    scanf("%d", &degree);
    node* head = NULL;
    for(int i=0; i<=degree; i++)
    {
        int coeff;
        scanf("%d",&coeff);
        insertend(&head, coeff);
    }
    scanf("%d",&x);
    int result = evaluatePoly(head, degree, x);
    printf("%d", result);

    node* temp;
    while(head!=NULL)
    {
        temp = head;

```



```
    head = head->next;
    free(temp);
}
return 0;
}
```

Status : Correct

Marks : 1/1

4. Problem Statement

Bharath is very good at numbers. As he is piled up with many works, he decides to develop programs for a few concepts to simplify his work. As a first step, he tries to arrange even and odd numbers using a linked list. He stores his values in a singly-linked list.

Now he has to write a program such that all the even numbers appear before the odd numbers. Finally, the list is printed in such a way that all even numbers come before odd numbers. Additionally, the even numbers should be in reverse order, while the odd numbers should maintain their original order.

Example

Input:

6

3 1 0 4 30 12

Output:

12 30 4 0 3 1

Explanation:

Even elements: 0 4 30 12

Reversed Even elements: 12 30 4 0

Odd elements: 3 1

So the final list becomes: 12 30 4 0 3 1

Input Format

The first line consists of an integer n representing the size of the linked list.

The second line consists of n integers representing the elements separated by space.

Output Format

The output prints the rearranged list separated by a space.

The list is printed in such a way that all even numbers come before odd numbers and the even numbers should be in reverse order, while the odd numbers should maintain their original order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6

3 1 0 4 30 12

Output: 12 30 4 0 3 1

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
typedef struct node{
    int data;
    struct node* next;
}node;
node* createnode(int value)
{
    node* newnode = (node*)malloc(sizeof(node));
    newnode->data = value;
    newnode->next = NULL;
    return newnode;
}
void insertatbegin(node** head, int value)
{
    node* newnode = createnode(value);
```

```

    newnode->next = *head;
    *head = newnode;
}
void insertatend(node** head, int value)
{
    node* newnode = createnode(value);
    if(*head == NULL)
    {
        *head = newnode;
    }
    else
    {
        node* temp = *head;
        while(temp->next!=NULL)
            temp = temp->next;
        temp->next = newnode;
    }
}
void printlist(node* head)
{
    while(head!=NULL)
    {
        printf("%d", head->data);
        if(head->next!=NULL)
            printf(" ");
        head = head->next;
    }
}
int main()
{
    int n, value;
    scanf("%d", &n);
    node* evenhead = NULL;
    node* oddhead = NULL;
    for(int i=0; i<n; i++)
    {
        scanf("%d", &value);
        if(value %2 ==0)
            insertatbegin(&evenhead, value);
        else
            insertatend(&oddhead, value);
    }
}

```

```

node* temp = evenhead;
if(temp ==NULL)
{
    printlist(oddhead);
}
else
{
    while(temp->next!=NULL)
        temp = temp->next;
    temp->next = oddhead;
    printlist(evenhead);
}
return 0;
}

```

Status : Correct

Marks : 1/1

5. Problem Statement

Emily is developing a program to manage a singly linked list. The program should allow users to perform various operations on the linked list, such as inserting elements at the beginning or end, deleting elements from the beginning or end, inserting before or after a specific value, and deleting elements before or after a specific value. After each operation, the updated linked list should be displayed.

Your task is to help Emily in implementing the same.

Input Format

The first line contains an integer choice, representing the operation to perform:

- For choice 1 to create the linked list. The next lines contain space-separated integers, with -1 indicating the end of input.
- For choice 2 to display the linked list.
- For choice 3 to insert a node at the beginning. The next line contains an integer data representing the value to insert.
- For choice 4 to insert a node at the end. The next line contains an integer data representing the value to insert.
- For choice 5 to insert a node before a specific value. The next line contains two integers: value (existing node value) and data (value to insert).

- For choice 6 to insert a node after a specific value. The next line contains two integers: value (existing node value) and data (value to insert).
- For choice 7 to delete a node from the beginning.
- For choice 8 to delete a node from the end.
- For choice 9 to delete a node before a specific value. The next line contains an integer value representing the node before which deletion occurs.
- For choice 10 to delete a node after a specific value. The next line contains an integer value representing the node after which deletion occurs.
- For choice 11 to exit the program.

Output Format

For choice 1, print "LINKED LIST CREATED".

For choice 2, print the linked list as space-separated integers on a single line. If the list is empty, print "The list is empty".

For choice 3, 4, 5, and 6, print the updated linked list with a message indicating the insertion operation.

For choice 7, 8, 9, and 10, print the updated linked list with a message indicating the deletion operation.

For any operation that is not possible print an appropriate error message such as "Value not found in the list".

For choice 11 terminate the program.

For any invalid option, print "Invalid option! Please try again".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

5

3

7

-1

2

11

Output: LINKED LIST CREATED
5 3 7

Answer

-

Status : Skipped

Marks : 0/1