Submit Query v1

SSE event reference

POST **/v1/sessions/{sessionId}/query** (public) or **/v1/client/sessions/{sessionId}/query** (client), with **responseMode: "stream"**. The response is **text/event-stream; charset=utf-8**. Events describe query progress, reasoning, agent activity and answer generation; optional events depend on the execution path.

Wire format and shared fields

Each frame has an SSE **event:** name and a **data:** payload, followed by a blank line. The SSE name selects the channel; JSON **eventType** selects the subtype. Structured query events carry **sessionId**, **messageId**, **eventIndex** and **status** (usually processing). Event indexes may have gaps; heartbeats and terminal markers have no index.

```
event: message
data: {"sessionId":"...","messageId":"...","eventIndex":3,
data:  "eventType":"fulfillment","status":"processing","answer":"Hello"}
```

Event names and payloads

message / statusLog - Progress in currentStatusLog: statusType, statusMessage, time; optional stepQuery, queryPlan, retrievedAgents, executedAgents, suggestedPlugins or answer. Includes summarize_history.initialized / completed as statusType values.

message / fulfillment - Answer text chunks in answer; append them in arrival order. A fulfillment_completed status log can carry the complete answer in currentStatusLog.answer.

message / metricsLog - Usage and timing metrics in publicMetrics.

message / clarification_request - Planning is waiting for input. Render clarificationRequest.queries[] (query and suggested options); keep the stream open while submitting answers.

thinking / planning_thinking - Planning reasoning chunks in thinking.delta.

thinking / step_thinking - Step reasoning chunks in thinking.delta.

thinking / fulfillment_thinking - Answer-generation reasoning chunks in thinking.delta.

thinking / planning_output - Planning output chunks in output.delta (mapped from planning_answer).

thinking / step_output - Step output chunks in output.delta (mapped from plugin_answer). Internal plugin_thinking maps to step_thinking.

agent / ondemand_agent.* - Agent envelope adds agent (id, name) and subtype-specific data. Agent events currently have status: processing; agent completion does not end the query.

heartbeat / (none) - Keep-alive every 3 seconds: sessionId, messageId, time. No eventType; do not treat it as answer content.

Agent subtypes (all prefixed ondemand_agent.)

Lifecycle: before_init, no_init, initiated, progress, thinking, completed, stopped, error, token_usage. **Execution:** tool_call, tool_result, tool_details, terminal, skills_used, todo, subagent_status. **Outputs:** code_generation_init, code_generated, file_written, artifact_ready, preview_ready, sandbox_created. **Interaction/UI:** require_creds, awaiting_input, awaiting_browser_action, novnc_ready, novnc_ended, graphs_ready, graphs_ended, filler_start, filler_end.

Common data shapes: content for text; name/inputParams for tool calls and output/error for results; language/title/delta/final for generated code. Credential requests provide pluginId, service and fields. novnc_ended, graphs_ended and filler toggles omit data. unknown is reserved and is not currently emitted.

Completion, pauses and client handling

A **message** frame with literal **[DONE]** ends the query successfully. Literal **[ERROR]:** followed by JSON ends it with failure or cancellation. Check these strings before JSON parsing. A disconnect alone does not prove completion. Listen to all four event names and tolerate unknown subtypes.

For clarification, POST {userResponse: [{question, answer}]} to **/v1/client/sessions/{sessionId}/messages/{messageId}/plan-clarification**. For require_creds, POST pluginId plus fields: [{key, value}] (or cancelled: true) to the client **.../messages/{messageId}/tool-credentials** route. Keep the original stream open; agent events and intermediate status logs are not terminal signals.

Source: internal/logic/chatmessage/submitstream.go; contract/worker.go; internal/queue/consumer/handler/fulfillment/common.go; chatmessage/route.go.