

Leveraging Large Language Models for Autoformalizing Theorems: A Case Study

Michail Karatarakis

Radboud University Nijmegen, The Netherlands

Motivation

LLMs like Mistral show promise in automating tasks in formal theorem proving, yet they encounter challenges such as inaccuracies and handling complex proofs. In our investigation, we employ Mistral for autoformalization in mathematics using the Lean 4 theorem prover [3] and its math library, `mathlib` [1]. We focus on autoformalizing the following two theorems in transcendental number theory.

Theorem 01 (Lemma 8.1 [2]) *Let $0 < M < N$, and a_{jk} be rational integers satisfying $|a_{jk}| \leq A$ where $1 \leq A$, $1 \leq j \leq M$ and $1 \leq k \leq N$. Then there exists a set of rational integers x_1, \dots, x_N , not all zero, satisfying $a_{j1}x_1 + \dots + a_{jN}x_N = 0$ and $|x_k| \leq (NA)^{\frac{M}{N-M}}$.*

Theorem 02 (Lemma 8.2 [2]) *Let $0 < p < q$, and a_{kl} be rational integers satisfying $|a_{kl}| \leq A$ where $A \geq 1$, $1 \leq k \leq p$ and $1 \leq l \leq q$. Then there exists a set of rational integers ξ_1, \dots, ξ_q , not all zero, satisfying $a_{k1}\xi_1 + \dots + a_{kq}\xi_q = 0$ and $|\xi_l| < c_1(1 + (c_1qA)^{\frac{p}{q-p}})$.*

Our aim is to generate formal proof sketches as the primary output. We preprocess text to extract relevant mathematical statements in \LaTeX from the source text [2] and utilize prompt engineering for auto-formalization by initially excluding proofs. We provide a centralized prompt repository¹ to ensure consistency and a list of our observations from our experiments. For more details and the complete informal mathematical text and generated code, the reader should consult Appendix 1.

- **Ensure precision and clarity** Ensuring proper text preprocessing is equally significant as the act of prompting. For instance, within the first Lemma 01, the source text contains the following: "... $-B_j$ represents the sum of the negative coefficients of y_j ..." and Mistral presented the following approach (despite the incorrect Lean syntax)

```
1 let B : Fin M → ℤ
2 | j => ∑ k, if a j k < 0 then -a j k else 0
```

Various methods exist for transcribing these definitions into Lean. One strategy that we found promising is changing the informal text based on the formal definition that we choose. For example, after changing the aforementioned informal text to "We define B_j as the sum of the $-\min(0, a_{jk})$ for all a_{jk} .", Mistral change its response to the following :

```
1 let B : Fin M → ℕ
2 | j => ∑ k : Fin N, -min 0 (a j k)
```

Thus, it proves beneficial to review the existing content in `mathlib` (comprising developed APIs and prerequisites) to facilitate more informed decision-making and provide an example of the correct syntax. Such a review will inevitably influence the preprocessing phase as well.

- **Adhere to Lean4 syntax and conventions** Mistral's training data, constrained to Lean 3 syntax until January 2022, shapes its approach to syntax. Addressing this requires encompassing modifications to notation, replacement of outdated imports, and provision of examples demonstrating the correct syntax.

For example, in the proof of Theorem 01, Mistral employed conventional mathematical notation, such as $\#$ for the cardinality of sets, which diverges from Lean's syntax.

```
1 -- Prove that the number of sets of x_k is (H + 1)^N
2 have hXCount : # { x : Fin N → ℤ | ∀ k, 0 ≤ x k ∧ x k ≤ H } = (H + 1) ^ N :=
  sorry
```

¹ <https://github.com/mkaratarakis/autoformalization-LLMs>

In most cases, Mistral encountered difficulties in introducing certain notions such as the sum B_j and many attempts led to the introduction of syntax that was invalid in both Lean 3 and Lean 4.

```
1 let B : Fin M → ℤ
2 B j := ∑ k, -min 0 (a j k)
```

To fix such issues, we prompted using examples :

Here is an example of the correct syntax for "let" statements:

```
1 let y : Fin M → ℤ
2 | j => ∑ k : Fin N, a j k * x k
```

should change to

```
1 let y : Fin M → ℤ := fun j => ∑ k : Fin N, a j k * x k.
```

Do the same for "C" and "B".

Finally, after managing to get the proof sketches of both theorems at a reasonable state, we were unable to ensure that the LLM adhered to Lean4 syntax despite our continuous efforts to prompt. In some cases Mistral would refuse to replace the `begin` with `by` and to eliminate the `end` commands. In other cases, it would agree to make this modification but refuse to remove the commas at the end of the sub-proof statements.

- **Handling Type Mismatch Errors** Type mismatch errors, commonly encountered in theorem proving, indicate disparities between expected and actual types. For instance, Mistral might define B_j as:

```
1 def B : Fin M → ℕ := fun j => ∑ k : Fin N, -min 0 (a j k)
```

and the type of B had to be updated to $\text{Fin } M \rightarrow \mathbb{Z}$ to match the type of a.

- **Addressing Autonomy Challenges** The challenge lies in the LLM autonomously generating its prerequisite definitions and theorems. Thus, it's crucial to provide contextual information or by explicitly including relevant mathematical definitions and theorems.

1. **Definitions** Establishing definitions is widely recognized as one of the most challenging aspects of formalization endeavors. For instance, Theorem 01, is about rational integers. A one-shot attempt generated the following definition of a rational integer

```
1 abbrev RationalInteger := Int
```

despite Mistral's understanding that a rational integer is simply an integer.

The real issues arise when the system is prompted to formalize definitions that it hasn't seen before. For example, Let K be an algebraic number field of degree h , and let α be an algebraic integer in K . We shall denote by $|\bar{\alpha}|$ the maximum of the modulus of the conjugates $\alpha^{(i)}$ with $(1 \leq i \leq h)$ of α , that is $|\bar{\alpha}| = \max_{1 \leq i \leq h} |\alpha^{(i)}|$.

We want to assist Mistral in formulating the definition of the *house* of an algebraic integer. Following the initial prompt, the expected response follows a familiar pattern, with Mistral attempting independently and selectively to delineate the prerequisites:

```
1 -- Define the conjugates of an algebraic integer
2 def conjugates (α : K) : List K :=
3   -- insert definition here
4 -- Define the house of an algebraic integer
5 def house (α : K) : ℝ :=
6   (conjugates α).map (fun x => abs x).max'
```

The customary approach to tackle these challenges involves supplying the LLM with definitions sourced from existing libraries such as `mathlib`, or ones provided by the user.

2. **Proofs** Dealing with proofs poses challenges due to Lean's syntax and the LLM's tendency to prove things autonomously. Common issues include selectively proving sub-proofs, using arbitrary identifiers, mixing Lean 3 and Lean 4 syntax, and utilizing theorems from Lean's 3 `mathlib`. Thus, it's important to review the informal proof steps, break down complex informal proofs into manageable components and supply the LLM with the relevant theorems from `mathlib`, or ones provided by the user.

References

1. mathlib Community.: The Lean mathematical library. In: Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020). pp. 367–381 (2020)
2. Hua, L.K.: Introduction to number theory. Springer Science & Business Media (2012)
3. de Moura, L., Kong, S., Avigad, J., van Doorn, F., von Raumer, J.: The Lean Theorem Prover (System Description). In: Felty, A.P., Middeldorp, A. (eds.) Automated Deduction - CADE-25. pp. 378–388. Springer International Publishing, Cham (2015)

1 Appendix

We showcase the prerequisite definitions, informal statements and proofs for two lemmata (p. 489-490, [2]), alongside the proof sketches obtained through our Mistral experiments.

Theorem 11 (Lemma 8.1 ([2])) *Let $0 < M < N$, and a_{jk} be rational integers satisfying $|a_{jk}| \leq A$ where $1 \leq A$, $1 \leq j \leq M$ and $1 \leq k \leq N$. Then there exists a set of rational integers x_1, \dots, x_N , not all zero, satisfying $a_{j1}x_1 + \dots + a_{jN}x_N = 0$, $1 \leq j \leq M$ and $|x_k| \leq (NA)^{\frac{M}{N-M}}$, $1 \leq k \leq N$.*

Proof. Let $H = (NA)^{\frac{M}{N-M}}$. Then $NA < (H + 1)^{\frac{N-M}{M}}$.

Hence $(NAH) + 1 \leq NA(H + 1)$ and $NA(H + 1) < (H + 1)^{\frac{N}{M}}$
Define

$$y_j = a_{j1}x_1 + \dots + a_{jN}x_N, \quad 1 \leq j \leq M. \quad (1)$$

We define B_j as the sum of the $-\min(0, a_{jk})$ for all a_{jk} .

Similarly, we define C_j as the sum of the $\max(0, a_{jk})$ for all a_{jk} .

For any set of integers (x_1, \dots, x_N) satisfying

$$0 \leq x_k \leq H, \quad 1 \leq k \leq N. \quad (2)$$

we have that $-B_jH \leq y_j \leq C_jH$, and $B_j + C_j \leq NA$.

The number of sets of (x_1, \dots, x_N) satisfying

$$0 \leq x_k \leq H, \quad 1 \leq k \leq N \quad (3)$$

is $(H + 1)^N$, and the corresponding number of set of sets (y_1, \dots, y_M) is at most $(NAH + 1)^M$.

It follows from the fact

$$(NAH) + 1 \leq NA(H + 1) < (H + 1)^{\frac{N}{M}} \quad (4)$$

and the pigeonhole principle that there must be two sets (x'_1, \dots, x'_N) and (x''_1, \dots, x''_N) which correspond to the same set (y_1, \dots, y_M) .

Let $x_k = x'_k - x''_k$, $(1 \leq k \leq N)$ so that (x_1, \dots, x_N) is now the required set satisfying

$$a_{j1}x_1 + \dots + a_{jN}x_N = 0, \quad 1 \leq j \leq M \quad (5)$$

and

$$|x_k| \leq (NA)^{\frac{M}{N-M}}, \quad 1 \leq k \leq N. \quad (6)$$

After several prompts, the system successfully produced the correct syntax and came up with the statement and a proof sketch of the lemma. Through further iterations, we achieved a stage where the auto-formalization of both the primary statement and its sub-proof statements became reasonably accurate.

```

1 theorem lemma81 (M N : ℕ) (hMN : 0 < M ∧ M < N) (A : ℝ) (hA : 1 ≤ A)
2   (a : Matrix (Fin M) (Fin N) ℤ) (ha : ∀ j k, |a j k| ≤ A) :
3   ∃ x : Fin N → ℤ, (∃ k, x k ≠ 0) ∧ ∀ j, ∑ k, a j k * x k = 0
4   ∧ ∀ k, |x k| ≤ (N * A)^(M / (N - M)) := by
5   -- Define H
6   let H := (N * A) ^ (M / (N - M))
7
8   -- Define X as the set of all sets of x_k satisfying 0 ≤ x_k ≤ H
9   let X : Set (Fin N → ℤ) := { x | ∀ k, 0 ≤ x k ∧ x k ≤ H }
10

```

```

11  -- Define Y as the set of all corresponding sets of y_j
12  let Y : Set (Fin M → ℤ) := { y | ∃ x ∈ X, ∀ j, y j = ∑ k, a j k * x k }
13
14  -- Prove that NA < (H+1)^(N-M)/M
15  have hNA : N * A < (H + 1) ^ ((N - M) / M) := by sorry
16
17  -- Prove that (NAH) + 1 ≤ NA(H + 1)
18  have hNAH : (N * A * H) + 1 ≤ N * A * (H + 1) := by sorry
19
20  -- Prove that NA(H + 1) < (H + 1)^(N/M)
21  have hNAH' : N * A * (H + 1) < (H + 1) ^ (N / M) := by sorry
22
23  -- Define y_j for a given x
24  let y (x : Fin N → ℤ) : Fin M → ℤ := fun j => ∑ k : Fin N, a j k * x k
25
26  -- Define B_j and C_j
27  let B : Fin M → ℤ := fun j => ∑ k : Fin N, -min 0 (a j k)
28
29  let C : Fin M → ℤ := fun j => ∑ k : Fin N, max 0 (a j k)
30
31  -- Prove that for any set of integers x_k satisfying 0 ≤ x_k ≤ H,
32  -- -B_j * H ≤ y_j ≤ C_j * H and B_j + C_j ≤ N * A
33  have hYBound : ∀ (x : Fin N → ℤ), (∀ k, 0 ≤ x k ∧ x k ≤ H) →
34    ∀ j, -B j * H ≤ y x j ∧ y x j ≤ C j * H ∧ B j + C j ≤ N * A := by sorry
35
36  -- Prove that X and Y have finite cardinalities
37  haveI : Fintype X := by sorry
38
39  haveI : Fintype Y := by sorry
40
41  -- Prove that the number of sets of x_k is (H + 1)^N
42  have hXCount : Finset.card X.toFinset = (H + 1) ^ N := by sorry
43
44  -- Prove that the number of corresponding sets of y_j is at most (NAH + 1)^M
45  have hYCount : Finset.card Y.toFinset ≤ (N * A * H + 1) ^ M := by sorry
46
47  -- Prove that the cardinality of X is larger than the cardinality of Y
48  have hCardXY : Finset.card X.toFinset > Finset.card Y.toFinset := by sorry
49
50  -- Apply the pigeonhole principle to find two sets of x_k that correspond to the
   same set of y_j
51  have hPigeonhole : ∃ (x' x'' : Fin N → ℤ) ( _ : x' ∈ X ) ( _ : x'' ∈ X ), ∀ j, y x' j = y
   x'' j := by sorry
52
53  -- Extract the two sets of x_k that correspond to the same set of y_j
54  rcases hPigeonhole with ⟨x', x'', hx', hx''⟩
55
56  -- Define x_k as the difference between the two sets of x_k
57  let x : Fin N → ℤ := fun k => x' k - x'' k
58
59  -- Prove that x_k satisfies the required conditions
60  have hX : (∃ k, x k ≠ 0)
61    ∧ ∀ (j : Fin M), ∑ k : Fin N, a j k * x k = 0
62    ∧ ∀ (k : Fin N), |x k| ≤ (↑N * A) ^ (M / (N - M)) := sorry
63
64  -- Complete the proof by existential introduction
65  exact ⟨x, hX⟩

```

Example 2

Let K be an algebraic number field of degree h , and let β_1, \dots, β_h be an integer basis, so that every integer in K has the unique representation $a_1\beta_1 + \dots + a_h\beta_h$ where a_1, \dots, a_h are rational integers. We

shall denote by $|\overline{\alpha}|$ the maximum of the modulus of the conjugates $\alpha^{(i)}$ with $(1 \leq i \leq h)$ of α , that is

$$|\overline{\alpha}| = \max_{1 \leq i \leq h} |\alpha^{(i)}|.$$

The subsequent step is to assist Mistral in formulating the definition of the *house* of an algebraic integer. Following the initial prompt, the expected response follows a familiar pattern, with Mistral attempting independently to delineate the prerequisites but without achieving success.

```

1 -- Define the conjugates of an algebraic integer
2 def conjugates (α : K) : List K :=
3   -- insert definition here
4
5 -- Define the house of an algebraic integer
6 def house (α : K) : ℝ :=
7   (conjugates α).map (fun x => abs x).max'

```

Additionally, Mistral encounters difficulty in completing specific definitions, such as `conjugates`. The customary approach in such cases involves furnishing the LLM with foundational definitions that it cannot generate autonomously but are already available in `mathlib`. A few more prompts eventually led the LLM to propose the following definition:

```

1
2 -- Define the house of an algebraic integer
3 def house (α : K) : ℝ :=
4   let embeddings := NumberField.Embeddings.range_eval_eq_rootSet_minpoly α
5   (embeddings.map (fun x => abs x)).max'

```

Subsequently, efforts were directed towards rectifying this definition, and subsequent prompts were formulated accordingly and a partial formalization was successfully attained.

```

1 variable {K : Type*} [Field K] [NumberField K]
2
3 instance : Algebra ℚ K := sorry
4
5 -- Define a theorem stating that the set of absolute values of the conjugates of an
   algebraic integer is nonempty
6 theorem nonempty_conjugates_abs (α : K) :
7   (Set.toFinset (Set.image Complex.abs (Polynomial.rootSet (minpoly ℚ α) ℂ
8     ))) .Nonempty := sorry
9
10 -- Define the house of an algebraic integer
11 noncomputable def house (α : K) : ℝ :=
12   Finset.max' (Set.toFinset (Set.image Complex.abs (Polynomial.rootSet (minpoly ℚ α) ℂ
13     )))
14   (nonempty_conjugates_abs α)

```

The next theorem we aim to address is as follows:

Theorem 12 (Lemma 8.2 [2]) *Let $0 < p < q$, and a_{kl} be rational integers satisfying $|\overline{a_{kl}}| \leq A$ where $A \geq 1$, $1 \leq k \leq p$ and $1 \leq l \leq q$. Then there exists a set of rational integers ξ_1, \dots, ξ_q , not all zero, satisfying*

$$a_{k1}\xi_1 + \dots + a_{kq}\xi_q = 0, \quad 1 \leq k \leq p, \quad 1 \leq l \leq q. \quad (7)$$

and

$$|\overline{\xi_l}| < c_1(1 + (c_1 q A)^{\frac{p}{q-p}}) \quad (8)$$

Proof. Let

$$\xi_l = x_{l1}\beta_1 + \dots + x_{lh}\beta_h, \quad (1 \leq l \leq q) \quad (9)$$

where x_{1l}, \dots, x_{lh} are rational integers.

Let $a_{kl}\beta_r = a_{klr1}\beta_1 + \dots + a_{klrh}\beta_h$

where $a_{klr1}, \dots, a_{klrh}$ are also rational integers. For $1 \leq k \leq p$, we have, from $a_{k1}\xi_1 + \dots + a_{kq}\xi_q = 0$, $1 \leq k \leq p$, $1 \leq l \leq q$, that

$$0 = \sum_{l=1}^q a_{kl} \xi_l \quad (10)$$

$$= \sum_{n=1}^q a_{kl} \sum_{r=1}^h x_{lr} \beta_r \quad (11)$$

$$= \sum_{n=1}^h \sum_{l=1}^q x_{lr} \sum_{r=1}^h a_{aklru} \beta_u \quad (12)$$

$$= \sum_{u=1}^h \left(\sum_{r=1}^h \sum_{l=1}^q a_{aklru} x_{lr} \right) \beta_u \quad (13)$$

Since β_1, \dots, β_h are linearly independent we have the hp number of equations

$$\sum_{r=1}^h \sum_{l=1}^q a_{aklru} x_{lr}, \quad 1 \leq u \leq h, \quad 1 \leq k \leq p \quad (14)$$

with hq number of unknowns.

From $a_{kl}\beta_r = a_{klr1}\beta_1 + \dots + a_{klrh}\beta_h$, and our remark preceeding Lemma 8.1 we see that

$$|a_{aklru}| \leq c \max_{1 \leq i \leq h} \beta^{(i)} A \quad (15)$$

$$\leq c_2 A. \quad (16)$$

It now follows from Lemma 8.1 that the system (8) has a non trivial set of solutions in rational integers satisfying

$$|x_{lr}| \leq 1 + (hqc_2 A)^{\frac{p}{(p-q)}}, \quad 1 \leq l \leq q \text{ and } 1 \leq r \leq h. \quad (17)$$

Therefore

$$\begin{aligned} |\xi_l| &\leq |x_{l1}| |\beta_1| + \dots + |x_{lh}| |\beta_h| \\ &\leq c_2 h (1 + (hqc_2 A)^{\frac{p}{(q-p)}}). \end{aligned} \quad (18)$$

Taking $c_1 = c_2 h$ the lemma is proved.

After some prompting we managed to get the statement of the theorem almost correct but when prompted to remove commas by specifying all the **have** statements, the system consistently responded in the same manner – the system flagged the length of the message as excessive and advised shortening it for handling. Subsequently, it became impossible to proceed with that particular chat session. Nevertheless, following a new chat session and several prompts, we succeeded in obtaining a reasonable proof sketch of the lemma.

```

1 variable {K : Type*} [Field K] [NumberField K] (b : Basis
  (Module.Free.ChooseBasisIndex ℤ (NumberField.ringOfIntegers K)) ℚ K)
2
3 instance : Algebra ℚ K := sorry
4
5 -- Define a theorem stating that the set of absolute values of the
6 --conjugates of an algebraic integer is nonempty
7 theorem nonempty_conjugates_abs (α : K) :
8 (Set.toFinset (Set.image Complex.abs (Polynomial.rootSet (minpoly ℚ α) ℂ))).Nonempty
  := sorry
9
10 -- Define the house of an algebraic integer
11 noncomputable def house (α : K) : ℝ :=
12 Finset.max' (Set.toFinset (Set.image Complex.abs (Polynomial.rootSet (minpoly ℚ α) ℂ)
  )))

```

```

13 (nonempty_conjugates_abs  $\alpha$ )
14
15 abbrev coeffs ( $\alpha : K$ ) : Fin (finrank  $\mathbb{Q} K$ )  $\rightarrow \mathbb{Z} := \text{sorry}$ 
16
17 -- Formalize the statement of the remark
18 theorem remark ( $\alpha : K$ ) :
19  $\forall (i : \text{Fin} (\text{finrank } \mathbb{Q} K)), |\text{coeffs } \alpha i| \leq c * \text{house } \alpha := \text{sorry}$ 
20
21 abbrev  $c_2 : \mathbb{Z} := \text{sorry}$ 
22
23 variable (b : Basis (Module.Free.ChooseBasisIndex  $\mathbb{Z}$  (NumberField.ringOfIntegers K))  $\mathbb{Q} K$ )
24
25 variable ( $\sigma : K \rightarrow^+ \mathbb{C}$ )
26
27 theorem lemma82 (p q :  $\mathbb{N}$ ) (hpq :  $0 < p \wedge p < q$ ) (A :  $\mathbb{R}$ ) (hA :  $1 \leq A$ )
28 (a : Matrix (Fin p) (Fin q) ( $\mathcal{O} K$ )) (h_bound :  $\forall k l, \text{house } ((\text{algebraMap } (\mathcal{O} K) K) (a k l)) \leq A$ ) :
29  $\exists \xi : \text{Fin } q \rightarrow \mathbb{Z}, \xi \neq 0 \wedge \forall k, (\sum l, a k l * \xi l = 0) \wedge \forall l, \text{Complex.abs } (\sigma (\xi l)) < c_2 * (1 + (c_2 * q * A ^ (p / (h - p)))) ^ (1 / (q - p)) :=$ 
30 by
31 -- Define the matrix  $a'$  by mapping each entry of  $a$  to its absolute value
32 have  $a' : \text{Matrix} (\text{Fin } p) (\text{Fin } q) \mathbb{Z} := \text{sorry}$ 
33
34 -- Define the hypothesis  $ha'$  by applying the house function to each entry of  $a$ 
35 have  $ha' : \forall j k, |a' j k| \leq A := \text{sorry}$ 
36
37 -- Apply Lemma 8.1 to get a non-trivial set of solutions to the system of equations
38 obtain  $\langle x', hx', hx\_bound \rangle := \text{lemma81 } p q hpq A hA a' ha'$ 
39
40 -- Define  $\xi$  in terms of the coefficients  $x'$ 
41 have  $\xi : \text{Fin } q \rightarrow K := \text{fun } i \Rightarrow \sum j, x' i * b j$ 
42
43 -- Expand the equation  $a * \xi = 0$  and rearrange to get a system of  $hp$  equations with  $hq$  unknowns
44 have eq1 :  $\forall k, \sum l, a k l * \xi l = 0 := \text{sorry}$ 
45
46 -- Bound the complex absolute values of the  $\xi$ 's using the triangle inequality and the bound on the  $x$ 's
47 have bound2 :  $\forall l, \text{Complex.abs } (\sigma (\xi l)) < c_2 * (1 + (c_2 * q * A ^ (p / (h - p)))) ^ (1 / (q - p)) := \text{sorry}$ 
48
49 -- Set  $c_1 = c_2$  and finish the proof
50 sorry

```

Despite our continuous efforts to prompt, we were unable to ensure that the LLM adhered to Lean4 syntax. In some cases Mistral would refuse to replace the `begin` with `by` and to eliminate the `end` commands. In other cases, it would agree to make this modification but refuse to remove the commas at the end of the sub-proof statements.

2 Conclusion

During our investigation, establishing necessary concepts and prerequisite theorems posed challenges, requiring guidance and adjustments to conform to established conventions within the `Lean4` and `mathlib` frameworks. To streamline the auto-formalization of mathematics in Lean4, we suggest the following strategies:

1. Provide clear and unambiguous mathematical statements and employ standard mathematical notation to facilitate better understanding and accurate Lean4 code generation.
2. Utilize Lean4 syntax and conventions to ensure adherence to best practices and enhance code readability.

3. Include relevant mathematical definitions and theorems to provide context and improve the accuracy of Lean4 code.
4. Present examples of the mathematical concepts to be formalized to facilitate understanding and improve code accuracy.
5. Simplify complex proofs into smaller, manageable components to enhance comprehension and promote accurate code generation.
6. Evaluate the generated Lean4 code, provide feedback, and iterate as necessary to enhance comprehension and accuracy in subsequent iterations.