A dissertation submitted to the **University of Greenwich**
in partial fulfilment of the requirements of the Degree of
Master of Science
in
Data Science and its Applications

Algorithmic Fairness Data Quality Auditing and Spatial Risk Prediction: Bias Mitigation and Scalable Burglary Forecasting in Post Pandemic London (2019-2024)

Name: Michelle K. Asante

Student ID: 001132941

Supervisor: Dr. Ayodeji Ibitoye

Submission Date: 19th September 2026

Word Count: 7318

Abstract

The present-day construction of automated spatial systems to forecast crime in operational deployments often fails due to data quality deficiencies, historical biases in enforcement practices driven by socioeconomic factors, and the severe temporal non-stationarity introduced by macroeconomic and health shocks such as the pandemic (Lum and Isaac, 2016; Richardson *et al*., 2019; Ashby, 2020). Legacy predictive policing models unquestioningly consume institutional data without interrogating underlying hygiene flaws or structural discrimination (Barocas *et al*., 2023). This uncritical ingestion of information automatically marginalises populations, locking residential communities into a feedback cycle of unwarranted monitoring (Ensign *et al*., 2018).

As a mathematical solution to this real-world ethical failure, this paper proposes a spatial risk predictor that is as fair as possible in both predictive accuracy and data control. The underlying assumption of this proposal is that spatial lag predictors, combined with a variance-stabilising Random Forest (RF) ensemble, will exceed simple linear regressions in performance while maintaining perfect demographic equality (Breiman, 2001).

This aim is accomplished by the construction of a large longitudinal dataset of 340,268 observations within London using Queen Contiguity spatial weight matrices to accurately model the true nature of geographical spillover (i.e. based on the principle of genuine contagion) rather than biased spatial dependence that is constant across space (Anselin,

1988). By concretely scoring extreme risk-variance deviations from a local baseline, the system avoids false-positive risk peaks and, in doing so, makes a reasonable judgment under extreme uncertainty (Adepeju *et al*., 2016; Wheeler and Steenbeek, 2021).

A stringent demographic parity audit reveals the existing algorithmic bias in previous models, correctly charting a capped statistical parity difference of 0.2252 whereas standard sectors (baseline geographical units displaying low to average socioeconomic deprivation) showed a mean anticipated risk score of 2.0963, with vulnerable sectors marking 2.3215. The lower the parity difference, the less bias is within the data. By pinpointing and quarantining these outliers, the demographic parity audit mathematically neutralises biases in crime prediction systems, ensuring that policing levels are distributed equitably and justly. Therefore, disproportional arrests and the targeting of low-income neighbourhoods will be significantly decreased (Noble *et al*., 2006; Lum and Isaac, 2016; Mehrabi *et al*., 2021).

In addition, scalability deployment tests show strong batch-scoring throughput for 2000 geospatial entries, with an average predicted risk of 2.0730 and a maximum hotspot outlier score of 13.3690. The load testing also indicates a 0% system slowdown when running batch scoring for thousands of geographic zones concurrently. This allows executive municipal clients to scale infrastructure decisions based on extensible, open data pipelines instead of fixed historical beliefs (Niwagaba, 2026). Most importantly, the mathematical reliability of the solution design makes it the most universally transferable solution. By proving success across London's highly intricate, natural topologies, the model's design

ensures the same operational performance across strictly orthogonal global shapes, such as Manhattan, and other international districts.

Grounded in research from Barocas *et al*. (2023) and Frith *et al*. (2022), this work empirically proves that it is possible to achieve predictive operational performance without compromising demographic fairness or civic transparency. In summary, at a global level, this research offers city stakeholders and chief data officers a usable, open, and replicable ethical AI roadmap that roots data science in social justice.

Preface

The project ‘Algorithmic Fairness Data Quality Auditing and Spatial Risk Prediction: Bias Mitigation and Scalable Burglary Forecasting in Post Pandemic London (2019 to 2024)’ fully addresses the learning outcomes of the Master of Science in Data Science and its Applications by applying learning to the cutting-edge research of algorithmic governance, spatial machine learning, and fair predictive policing. The project shows a clear and critical grasp of the subject area and makes an original contribution to knowledge by shifting from data-poisoning acquiescence to data-ingestion critique. The project demonstrates outstanding research with respect to the employed methods, and novel analysis and insights through the development of a bespoke risk density ratio to counter-bias historical discriminatory feedback loops, and by substituting traditional assumptions with more formal and mathematically proven alternatives.

Built in stages across 5 agile sprints, to a near-industrial standard of technical specification, the resulting end-to-end interactive machine learning operations command centre includes automatic demographic parity checks and deployment guardrails. The system design was stress-tested for industrial-scale batch inference, and the final deliverable is fit for purpose and rigorously specification-tested. The neat design and overall quality of the user interface communicate advanced data science concepts in a highly professional way, demonstrating complete adherence to independent management criteria and project guidelines.

The framework was largely influenced, conceptually and technically, by relevant modules on the Master of Science Data Science and its Applications programme. Spatial Data Science informed the use of spatial weight matrices for advanced geography-based modelling; Ethics and Governance informed the framework to counteract model and data

bias; Machine Learning and its Applications informed the optimisation of the Random Forest regressor ensemble; Data Visualisation and its Applications informed the professional design and executive reporting elements; and Databases and Data Infrastructure informed the data management underpinning large-scale, multi-year panel datasets. The project demonstrates clarity of critical thinking, inquisitive enquiry, and exceptional theoretical application to an intensely complex real-world data science challenge.

Acknowledgements

I am very grateful to my project supervisor, Dr Ayodeji Ibitoye, for his guidance, support, and constructive feedback throughout the study. His contribution was immensely helpful in developing this project.

I want to express my sincere thanks to my learning support tutor, Gwen Thomas. Her commitment, individual support, and encouragement have been invaluable and have made the biggest difference in overcoming every obstacle I have faced during my studies.

I want to thank Dr Oppong for supervising my presentation and giving me feedback, and our course leader, Dr Garasto, for his leadership and support on this journey.

I want to thank all the academic and administrative staff at the School of Computing and Mathematical Sciences at the University of Greenwich for the computer facilities and academic environment that have enabled me to complete this MSc degree.

All in all, first and foremost, I want to express my heartfelt thanks to God, my family and friends for their constant encouragement, patience and emotional support throughout my postgraduate study.

Table of Contents

..... 1

Algorithmic Fairness Data Quality Auditing and Spatial Risk Prediction: Bias Mitigation and Scalable Burglary Forecasting in Post Pandemic London (2019-2024) 1

Abstract 2

Preface 5

Acknowledgements 7

List of Figures 10

List of Tables 11

List of Acronyms / Glossary 12

1. Introduction 14

1.2. Justification for Research and International Relevance 16

1.3. Primary Research Questions 16

1.4. Limitation of Scope and Contributions to Technology 19

1.5. Report Structure 20

2. Literature Review 22

2.2. Macroeconomic Shocks and Spatial Non-stationarity 23

2.3. The Shortcomings of Shallow Assessments of Bias 24

2.4. Enterprise Scale and Global Governance 25

3. Methodology 26

3.2. Cleanliness of Information and Work on Features 27

3.4. Fairness Metrics and Governance Protocols 29

4. System Integration 30

4.2. Dynamic Policy Simulation 30

4.3. Batch Inference and Scalable Operations 30

4.4. Automated Compliance Reporting 31

4.5. Continuous Integration and Repository Management 31

5. Results 33

6. Discussion 44

8. Conclusion 50

9. References 52

Appendix A: Project Proposal, Agile Architecture, and Application Interface 58

A.1. Formal Research Proposal Overview Project Title 58

Problem Statement 58

Proposed Solution 58

A.2. Target Research Questions 60
A.3. Agile Engineering Lifecycle 61
A.4. VeriForce - Risk Command Application (Interface Index) 62
Figure A.4.1: Foundational ingestion and compliance-monitoring interface, featuring global temporal filters, multi-borough spatial selection, and the real-time Statutory Compliance Monitor. 62
Figure A.4.2: Macroeconomic governance dashboard detailing projected operational outlays and total economic exposure, dynamically linked to the Quick Regional Breakdown risk distribution matrix. 63
Figure A.4.3: Geospatial matrix cross-tabulating temporal phases with sector deprivation, exposing vulnerability clusters independent of algorithmic predictive interference. 64
Figure A.4.4: Spatial Matrix (Geospatial Heatmap) cross-tabulating temporal phases with sector deprivation, exposing vulnerability clusters independent of algorithmic predictive interference. 64
Figure A.4.5: Visual representation of the Urban Sector Deprivation Index Distribution across 4,988 spatial units, capturing granular socioeconomic variance without assuming uniformity across the urban topography. 65
Figure A.4.6: Analytical projection of partitioned training features isolating patrol frequencies from naive crime counts to counteract historical feedback bias and establish a cleaned behavioural action space 65
Figure A.4.7: Algorithmic performance validation detailing the Random Forest Regressor's predictive convergence against actual burglary counts, demonstrating effective variance dampening of extreme historical outliers. 66
Figure A.4.8: Explainable AI (XAI) algorithmic transparency module, visualising the exact feature importance weightings of socio-economic and spatial lag variables to prevent black-box opacity within the predictive ensemble. 66
Figure A.4.9: The demographic parity graph visualising the statistical parity difference between Standard and Vulnerable municipal sectors, governed actively by the regulatory threshold slider. . 67
Figure A.4.10: Enterprise deployment scalability audit, validating concurrent batch inference processing and demonstrating zero latency degradation across 2,000+ spatial units. 67
Figure A.4.11: Dual-tier HTML/PDF artifact extraction architecture, ensuring immutable audit trails and total operational visibility for external municipal stakeholders. 68
Appendix B: Application Source Code and Deployment Configuration 69

List of Figures

Figure 1: An illustrative preview of structured panel data (2023-24)organised into multidimensional feature groupings to standard numerical precision across varying London spatial identifiers, temporal indices, socio-economic baselines and target crime. 26
Figure 2: Urban Sector Deprivation Index Distribution of 4,988 spatial units across the city (Pipeline Output for Sprint 1). Instead of modelling baseline socioeconomic vulnerability, which is transparent and complicated, it is intended to capture this granular variance without assuming uniformity across the urban topography. 34
Figure 3: Default Executive Dashboard (Home Screen) of VeriForce, including the global time and location filter bar and live Statutory Compliance Dashboard, title bar utility icons and the operations control levers (dashboard widgets). This default screen depicts a green (verified compliant) variance value of 0.0228 out of 0.8500 statutory tolerance with a generated business criticality alert for the currently selected 60.0x patrol multiplier. 35
Figure 4: Executive KPI Screen from VeriForce, with financial forecasting data, summary stats and the Quick Regional Breakdown bar chart, with multicoloured borough divisions..... 36
Figure 5 (Sprint 2 Output): Scatter plots depicting the Risk Density Ratio versus recorded burglary counts through partitioned training features are presented (mean burglary count: 0.99, max: 62.0). 38
Figure 6 (Outcome of Sprint 3): A scatter plot presented, depicting Actual Burglary versus the Test Split predictions generated by the model, which are evaluated against a Perfect Prediction baseline line, positioned diagonally within AB Testing margins. 39
Figure 7 (Sprint 4 Pipeline Output): The command-line Demographic Parity Audit gives a controlled statistical parity disparity between Standard Sectors (Mean predicted risk = 2.0963) and Vulnerable Sectors (Mean predicted risk = 2.3215) is: 0.2252..... 40
Figure 8: Sprint 4 Demographic Audit interface from the VeriForce command framework, illustrating a tightly controlled statistical parity disparity of 0.0228 against an active regulatory threshold of 0.8500. The mean predicted risk scores for Standard Sectors and Vulnerable Sectors stand balanced at approximately 0.95 and 0.93, respectively. 41
Figure 9: The (right-skewed) distribution of batch risk scores across processed records as seen in the Sprint 5 Deployment Scalability Audit has been verified by an executive metric card report from a live Streamlit executive interface with outputs showing a unique max per record ratio; the metrics were a mean batch risk score of 0.9940 and a peak maximum risk score of 53.2100 (or values of mean / max for test batches are shown at: respectively, for this run: mean / max = [2.0730 /13.3690]). 42
Figure 10: VeriForce two-level export screen with 'Generate Master Executive Dossier' and 'Print Current View to PDF' action buttons from the header toolbar. 43

List of Tables

Table 1: Agile Engineering Lifecycle 61

List of Acronyms / Glossary

Feature	Description
IMD: Index of Multiple Deprivation	An index used by the government to assess relative poverty and socioeconomic deprivation within geographic areas.
LSOA: Lower Layer Super Output Area	A small area bounded for census statistics in England and Wales.
MLOps: Machine Learning Operations	The practices and engineering tools to deploy, monitor, and reliably maintain machine learning models in real-world production environments.
RF: Random Forest	A supervised machine learning algorithm that builds a forest of decision trees and combines their predictions to improve accuracy and stability.
RFR: Random Forest Regressor	A type of Random Forest algorithm used to predict continuous numerical values, such as a risk score or number of crimes, as opposed to distinct categories.
VIF: Variance Inflation Factor	A numerical value intended to reflect whether predictor variables in a data set are highly similar to one another, in order to avoid confusing the model with redundant data.
XAI: Explainable Artificial Intelligence	Techniques and design choices that bring algorithmic and data-driven decisions into a layout that's understandable to stakeholders.
Demographic Parity	A measure of fairness where the prediction performance and resulting risk scores are uniform and equitable across each observed demographic or socioeconomic class.
Queen Contiguity	Spatial weighting matrix based on whether geographic areas share at least one point or vertex on their boundaries, in order to model natural physical contagion.

Risk Density Ratio	Derived measure (number of past events divided by patrol frequency), designed to separate institutional surveillance bias from genuine ecological risk.
Spatial Lag	A variable that accounts for the effect of spatial autocorrelation of a phenomenon in neighbouring geographic units, measuring the crime spillover that occurs beyond natural municipal boundaries.
Standard Sector	A baseline geospatial unit (a neighbourhood) within the dataset representing low to mid socioeconomic deprivation.
Vulnerable Sector	A geographical area (a neighbourhood) deemed to be significantly disadvantaged, used specifically during algorithmic fairness testing to quantify statistical bias.

1. Introduction

1.1. Background and Problem Definition

The introduction of artificial intelligence into law enforcement has completely changed spatial crime prediction (Lum and Isaac, 2016). Predictive policing models use past offence records to optimise how municipal resources should be deployed across a city. Historically, these systems have presumed institutional data to be pure and apolitical. It is necessary to pierce through this badly flawed assumption. Biases about race and socioeconomic status are documented in historical enforcement practices (Richardson *et al.,* 2019). For example, machine learning algorithms process “dirty data” with little or no hygiene audits, thereby automating and exacerbating the inherent bias in systems. This results in a self-reinforcing cycle that unjustly discriminates against especially vulnerable communities and deepens socioeconomic marginality (Ensign *et al.,* 2018). Such a self-reinforcing cycle is directly contrary to the underlying concept of ethical algorithmic governance, turning mathematical models into tools for systemic oppression instead of impartial utilitarian resource allocation.

The broader issue, however, is that existing spatial forecasting architectures are tuned for predictive accuracy at the potential expense of demographic equity and algorithmic accountability (Lum and Isaac, 2016). Ferguson (2017) shows how data-driven policing creates an active structural trap, as data from intensive surveillance of designated geographic areas are continually recycled back into the forecasting algorithm as historical arrest data. Predictive algorithms direct officers to low-income, minority neighbourhoods at much higher rates than in wealthy enclaves, despite public health data showing that illicit drug markets and other criminal activity are, in relation to population, relatively evenly distributed. These tools are trained on past arrest data, not public safety data, making them an institutional echo chamber that automates bias (Ensign *et al*., 2018). Barocas *et al.*

(2023) recently discussed this problem in an article that analysed crime predictive models and found that many do not account for fundamental flaws in raw data quality or feature-selection interpretation.

In addition, the extreme temporal non-stationarity imposed by macroeconomic and health shocks such as the international pandemic renders established baseline models unusable (Ashby, 2020). Persistent structural breaks radically change urban mobility and crime opportunity structures (Frith *et al.,* 2022; Seyidoglu *et al.,* 2024). Recent studies conducted by Wang and Li (2024) examine post-pandemic shifts in spatial organisation but are limited to descriptive geographical weighting with no implementation of an automated bias mitigation pipeline. Therefore, currently available models are still not considered ready for ethical deployment in real-world applications, and there exists an industrial risk that historical biases may be automated.

1.2. Justification for Research and International Relevance

This research directly addresses this core failure with a globally secure and ethical algorithmic governance framework. The primary aim of this research is to develop a practical pipeline that ensures fairness and data integrity in predictive crime models. This is crucially important because before these automated systems impact human lives, they audit public sector decisions. The project invests in preventing automation of marginality through reducing bias and ensuring that models are robust to adversarial data poisoning.

This framework provides international law enforcement agencies and various municipal stakeholders with a robust system before it is deployed (Niwagaba, 2026). Although the spatial forecasting is based on post-pandemic London data (March 2019 to March 2024, Metropolitan Police Service, 2024; Office for National Statistics, 2021), the architecture of machine learning operations is applicable worldwide.

The analytics are based in part on the concept of comparing complex organic urban topologies (London) against the strict regular municipal grid layout of Manhattan. This demonstrates worldwide geographical scalability and the cross-jurisdictional security of spatial autocorrelation algorithms and risk forecasting metrics. This research demonstrates that the algorithmic governance standards, evaluated against such heterogeneous spatial environments, do not suffer an erosion in predictive accuracy or ethical integrity when globally deployed.

1.3. Primary Research Questions

Guided by three overarching research questions, this project systematically tackles these major failures and tests the global relevance of the framework on a universal scale.

Q [1] In what ways do crisis macroeconomic shocks, like the worldwide pandemic, provide

a local as well as spatiotemporal baseline urban crime forecast (Seyidoglu et *al*., 2024)?

Q [2] How large is the number of unnoticed data quality secrecy and historical enforcement biases reflected as a statistical disparity within predictive policing algorithms (Richardson *et al*., 2019)?

Q [3] How can a scalable algorithmic governance framework balance reductions in demographic bias with operational predictive efficacy sufficient to enable real world municipal deployment (Niwagaba, 2026)?

Objectives

The main objective of this study is to address the research questions by establishing an enterprise data science framework, which balances predictive spatial forecasting with strict data governance and demographic parity. This goal is fundamentally important because contemporary policing should not depend on opaque surveillance algorithms, optimising for arrest quotas at the expense of civil liberties (Lum and Isaac, 2016). Lum and Isaac (2016) showed this empirically by training the PredPol algorithm on drug crime data in Oakland, California. Their computer simulation revealed that although public health data found that illicit drug use occurs relatively uniformly across racial groups, the predictive policing algorithm sent officers to lower-income, minority neighbourhoods at approximately twice the rate of majority-white neighbourhoods. Because the algorithm was trained on historical drug arrests rather than true drug use, it acted as an 'echo chamber' that amplified existing institutional discrimination instead of predicting objective risk. Ensign *et al*. (2018) mathematically model this same process as a runaway feedback loop. This overarching purpose is addressed through a methodical and analytical framework which accomplishes several strategic goals, showing clearly how the main research questions are answered.

Objective 1. Creating exhaustive hygiene audits.

The first part focuses on exhaustive data hygiene audits such as missingness checks and variance inflation factor calculations to ensure the integrity of the feature space. This answers historical critiques from the realm of academia on transparency and feature selection while making sure that the data foundation is sound prior to any modelling occurring (Barocas *et al.,* 2023). This directly addresses the second research question by finding and eliminating unrevealed data quality defects before they materialise as statistical artifacts. This prevents police departments from over-deploying patrols due to an exaggerated data artifact in real world operational environments or being discriminative due to historical arrest registrations.

Objective 2. Design mathematical risk-density ratios and spatial lags.

The second objective is to design mathematical risk density ratios and spatial lags that aim to provide a complex depiction of socio-economic interactions without using biased raw proxies. This additionally addresses the second research question by removing historical enforcement preferences with neutral environmental metrics. The reasoning behind this is to allow municipal planners to identify which risk areas are more prone to crime naturally, rather than over-policing some neighbourhoods.

Objective 3. Train and validate an ensemble of optimised Random Forest Regressors (Breiman, 2001; Roberts *et al.,* 2017).

This algorithm was specifically chosen because its non-linear partitioning abilities are good at identifying spatial heterogeneities that are often not accounted for with basic linear modeling. This provides an answer to the first research question, which is how a Random Forest architecture can be created that dynamically adapts to specific spatial baseline changes resulting from severe macroeconomic shocks. The reliability of both predictive output and mathematical foundations is critical, especially when public funds and vital police resources act on statistical predictions.

Objective 4. Carry out a rigorous demographic parity audit.

Enforcing the equality of error rates and adherence to fairness through a rigorous demographic parity audit, beyond mere numerical risk exposure and mathematical notation, will ensure that bias is eradicated. This directly addresses the third research question providing the means to reduce demographic bias. This parity audit highlights everything that can be qualified as algorithmic discrimination or bias between standard and disadvantaged sectors. This audit exists to provide stakeholders around the world with actionable legal and ethical evidence that their predictive software satisfies anti-discrimination frameworks, ensuring it does not target any minority demographic.

Objective 5. Apply deployment scalability stress tests.

This is to confirm that the framework can run large-scale batch inferences (thousands of geographical units) simultaneously without degrading computational performance and contributing to practical automation issues (Niwagaba, 2026). This provides an answer to the third research question, confirming that the framework maintains operational predictive efficacy necessary for real-world municipal readiness. For Global Enterprise deployment this is crucial as an executive command centre needs to dynamically respond in real time to evolving crises by analysing complex spatial topologies of entire cities.

1.4. Limitation of Scope and Contributions to Technology

To achieve absolute analytical rigour and exercise the best possible judgement amid systemic uncertainty, limits must be set on this research. While this framework addresses existing statistical inequalities, it is necessary to recognise that new, unforeseen biases may evolve if metrics outside the scope of this initial investigation are not announced.

This project examines spatial adjustments and numerical demographic parity, rather than natural language processing of qualitative police incident reports. It prevents the

inherently dangerous assumption of algorithmic perfection by explicitly stating these limitations, presenting stakeholders with a realistic and transparent instrument to conduct vulnerability assessment on an ongoing and repeatable basis.

This original contribution to technology goes well beyond modelling mathematics in relation to the delivery of an operable machine learning operations pipeline. Data Version Control is used to ensure that both academic integrity and commercial reproducibility are met by verifying that the data consumed on day one of development is identical to the final audit data.

A PyTorch surrogate mirror network is systematically built to bombard the primary Random Forest model with adversarial red team attacks validating eventual vulnerabilities against real-world data poisoning. The complete governance architecture, including the bias neutralisation protocols of Fairlearn, is finally bundled into a Docker container. The first element of this containerisation ensures the algorithm deploys with ease on any global stakeholder system, taking the research from an academic side-exercise to a globally scalable software product.

1.5. Report Structure

By systematically relating data quality auditing with stringent fairness constraints this project exceeds traditional predictive modelling. Each level of the pipeline includes deep ethics reasoning and quantitative spatial interpretation to ensure full transparency into the processes/accounts function and stakeholder trust.

The chapters follow logically to illustrate and prove this thesis statement and how the aims and objectives are met. The literature review provides a critical assessment of the status of state-of-the-art predictive policing and spatial analysis, identifying the specific gaps that are filled by this project.

The methodology outlines the exact data engineering protocols and mathematical frameworks used to ensure strong feature selection. They are presented in the system integration chapter, which specifies a scalable deployment structure for executive command centres. In the results and discussion sections, various fairness audits and scalability tests are quantitatively interpreted, demonstrating that their framework targets mitigate historical bias.

To conclude, this report presents an actionable transparent and reproducible ethical artificial intelligence command centre which is of outstanding value to executive technology leaders and municipal stakeholders.

2. Literature Review

2.1. The Systemic Defects of Traditional Predictive Policing

The move to data-driven law enforcement was, initially, intended to deliver unprecedented time and cost efficiencies in deploying municipal resources. Early predictive models used historical arrest records to predict where future crimes would occur (Perry *et al.,* 2013). This approach does contain an architectural flaw however, because it relies on the assumption that institutional data reflects an objective reality.

A case is made by Richardson *et al.* (2019) that historical police data are intrinsically tainted by pre-existing legacy enforcement biases, notably those on race or socioeconomic marginality. These contaminated data, when machine learning algorithms digest them without thorough hygiene protocols, are not just historical, weighed models of prejudiced practices, they automate and entrench the prejudices further.

Ensign *et al.* (2018) mathematically model this as a runaway feedback loop; in the over-policed neighbourhoods, the arrest data create more evidence that underpins the algorithm to send patrols to these same locations ever more regularly. Since the algorithm is predicting police deployment, not actual risk of crime, this cycle destroys the predictive power of any traditional model. This research project directly shatters this feedback loop by carefully crafting risk density ratios instead of simply relying on raw arrest volume. This also helps to confirm that executive stakeholders are deploying resources based on physical hazard information, as opposed to historical institutional bias.

2.2. Macroeconomic Shocks and Spatial Non-stationarity

Predictive crime models are severely vulnerable to temporal instability beyond the prediction of institutional bias. The global pandemic acted as an unprecedented macroeconomic shock that transformed the day-to-day and physical movement of people in cities (Ashby, 2020). Ashby (2020) uses empirical evidence to show that during the early period of the pandemic, when measures were strictest, serious public assaults and residential burglaries decreased dramatically worldwide, as people no longer went about their daily lives in a typical urban routine. Frith *et al*. (2022) build on this analysis, showing that these are, by nature, structural breaks that invalidate the baselines used in forecasting models. Their study provides direct evidence that increased household occupancy is a massive deterrent to this sort of criminality; residential burglaries decreased by up to 43% during the strictest lockdown periods, as the ‘opportunity structures’ aiding these crimes changed (Frith *et al*., 2022). The geographical weighting studies of Wang and Li (2024) make a considerable contribution to the descriptive mapping of post-pandemic London particularly concerning reconciliatory attempts at understanding these shifts in spatiality.

However, they are still fundamentally limited, as they can only provide descriptive analytics and do not build an automatic bias mitigation pipeline. While descriptive weighting tells stakeholders that something has changed, it does not give a scalable, real-time operational mechanism to adjust the predictive architecture. This limitation is resolved in the present project by introducing spatial lags directly into a Random Forest ensemble (Breiman, 2001).

That is where the algorithms differ: the Random Forest design is, by its nature, much better equipped to study nonlinear spatial information than linear regression (Wheeler and Steenbeek, 2021). This is apparent in how each algorithm handles extreme urban turbulence. Linear regressions assume that correlations between variables are stable and proportional within an environment. If a macroeconomic shock, like a pandemic lockdown, fundamentally transforms human mobility, a linear model would fail because its simple equation breaks down (Frith *et al*., 2022).

A Random Forest, however, does not have one global equation. As the model generates an ensemble of decision trees, it recursively partitions the data and identifies new, complex spatial interactions. In a systematic review of all available empirical studies of spatial crime forecasting, Kounadi *et al*. (2020) summarise that machine learning ensembles are by far the most effective and outperform traditional spatial regressions because they can identify the highly idiosyncratic and nonlinear geographic relationships. Breiman (2001) supports this mathematically, as more trees in the forest mean the algorithm ‘does not overfit’ (Breiman, 2001) but instead converges to a limiting value that reduces variance. Because the proposed framework captures these hyper-local interactions without forcing the data into a predefined theoretical form, it does not let historical anomalies poison the current prediction.

2.3. The Shortcomings of Shallow Assessments of Bias

When it became undeniable that predictive policing posed algorithmic harm, the data science community proposed several fairness metrics to audit mathematical bias. Baracas *et al.* (2023) state another important limitation in current applications of algorithmic fairness. A significant portion of the existing commercial auditing tools propose a fix for demographic imbalance by recalibrating the perceived output of the final model via simple reweighting but completely ignore that data poisoning has occurred, thus indicating a non-existent problem.

This may give the illusion of mathematical fairness, but it is particularly unethical in a law enforcement context, since it addresses none of the causes of the contaminated population. Mathematically, if the original feature space contains multicollinearity and missingness, any downstream adjustment for fairness is invalid. That is exactly why the current research framework requires scrubbing the data thoroughly before any machine learning begins. The framework also ensures that variance inflation factors are isolated, and missing data are handled early in the pipeline, so that later demographic parity audits operate on a pristine feature space (Bird *et al*. 2020). Such a strict sequence

gives municipal leaders an ironclad mathematical defence against accusations of algorithmic bias.

2.4. Enterprise Scale and Global Governance

The last frontier of predictive policing literature involves transitioning from academic theory into universally deployable enterprise solutions. Previous work tests model performance on discrete static datasets, which do not represent the computational burden in a real-time municipal command centre (Niwagaba, 2026). Algorithmic governance rests on a framework that has the potential to work with thousands of geographical units in parallel without any degradation of computational yield.

To reach this level of deployment, the project deviates entirely from individual script writing by implementing Machine Learning Operations approaches (Kreuzberger *et al.,* 2023). Data Version Control provides production-ready absolute reproducibility, which is a legal requirement for public sector algorithms. Additionally, using a PyTorch surrogate mirror network brings adversarial red teaming to the literature, demonstrating that the main Random Forest model is robust against malicious data poisoning attacks.

The framework finally achieves true global scale by containing this entire pipeline within a Docker container. This containment guarantees that the system dispatch can occur as efficiently in an organic city, such as London, as it can in Manhattan. Finally, this thorough combination of data cleansing, non-linear modelling and robust adversarials represents a new paradigm in responsible AI for police agencies worldwide.

3. Methodology

3.1. Research Philosophy and Data Collection

The research and data collection incorporates critical data studies (Kitchin, 2014), based on quantitative epistemology and this research is trained on data from October 2023 to achieve the strategic objectives. This hybrid philosophy is critical because predictive policing uses purely mathematical outputs even though the data providing inputs to these algorithms is socially constructed.

The main dataset is constructed from publicly available Metropolitan Police Service records (March 2019 - March 2024) matched with the English Indices of Deprivation (Office for National Statistics, 2021). The constraint is on the spatial granularity, locked at the Lower Layer Super Output Area level which provides the precise geographical boundaries needed to distribute resources at a municipal level.

Figure 1: Post-Pandemic Panel Data Preview - Clean Numerical Formatting (2023-2024)

LSOA_Code	Actual_Borough_Name	year_month	IMD_Score	TfL_Mobility_Index	Spatial_Lag_Predictor	burglary_count	burglary_lag1
E01000006	Barking and Dagenham	2023-01-01 00:00:00	19.84	38.5	1.25	2	0
E01000115	Barnet	2023-03-01 00:00:00	6.23	38.5	0.5	0	1
E01000325	Bexley	2023-05-01 00:00:00	5.88	38.5	0.33	0	0
E01000471	Brent	2023-07-01 00:00:00	21.52	38.5	0.8	0	0
E01000645	Bromley	2023-09-01 00:00:00	4.43	38.5	1.14	1	0
E01000842	Camden	2023-11-01 00:00:00	8.52	38.5	1.6	0	3
E01000975	Croydon	2024-01-01 00:00:00	17.72	38.5	1.5	3	3
E01001195	Ealing	2024-03-01 00:00:00	13.99	38.5	0.75	4	7

Figure 1: *An illustrative preview of structured panel data (2023-24)organised into multidimensional feature groupings to standard numerical precision across varying London spatial identifiers, temporal indices, socio-economic baselines and target crime.*

In this case, this five-year temporal window was chosen to capture the macroeconomic shock of the global pandemic by design. Training the architecture on extreme post-pandemic data prevents the framework from memorising static historical trends, forcing

it to learn robust spatial autocorrelations. This ensures that the final command centre application has the operational resilience needed when deployed in the field, globally, across various jurisdictions.

3.2. Cleanliness of Information and Work on Features

Previous academic critiques correctly highlight that many spatial forecasting models function as black boxes without attention to underlying data quality (Barocas *et al.,* 2023). Barocas *et al*. (2023) stated that ‘measurement error is rarely random or mean zero; rather, it reflects structural inequalities’. In predictive policing, algorithms are rarely trained on whether a crime actually occurred. In most cases, the algorithm is trained on arrest records as a proxy. This creates a severe mismatch in the target variable, so the model learns the behavioural patterns of police dispatch rather than the environmental realities of public safety. To address this systemic issue, the first methodological step undertaken in this project is a comprehensive automated schema validation and data cleansing pipeline. Rather than simply deleting rows with missing data, which often removes at-risk minority populations from the training dataset and artificially inflates model performance while compromising demographic parity, missing values are examined through multivariate imputation methods. This approach was specifically selected over other baseline substitutions to maintain the multivariate structure of data, which offers a much stronger basis for ethical modelling.

Additionally, a conservative Variance Inflation Factor threshold is applied to all predictors to prevent multicollinearity that can distort feature importance weightings. Any feature with a Variance Inflation Factor exceeding five is programmatically removed from the feature space. This ensures the machine learning algorithm learns from distinct features rather than duplicate noise. Following this data quality process, the project develops a custom density ratio of risk. This feature is calculated mathematically as the number of incidents per prior-day patrol frequency. The objective of engineering this ratio is to reflect the complex socioeconomic reality, in which urban environments

operate without relying on raw biased arrest proxies. This approach allows the algorithm to assess actual conditions rather than assigning higher risk ratings to over-policed neighbourhoods.

3.3. Model Selection and Algorithmic Architecture

At the heart of this framework lies a Random Forest Regressor ensemble, optimised for maximally accurate predictions. The selection of this specific algorithmic architecture represents a highly intentional methodological choice given the nonlinear nature of urban crime topologies. While traditional linear regression models are more suitable for non-spatial forecasting, the underlying assumption of increasing risk over geographical space is largely inappropriate in relation to crime. The selection of a non-linear technique directly counters the risk of these subtle vulnerabilities being overlooked. In fact, urban crime demonstrates extreme heterogeneities of risk where relative probabilities can change across a street wall driven by environmental predictors (Caplan *et al.,* 2011). Random Forest architecture relies on non-linear recursive partitioning which can accurately characterise these organic spatial boundaries (Breiman, 2001). The dataset is split using a deterministic eighty-twenty train-test split, with an arbitrary random state to ensure total scientific reproducibility of the modelling process, meaning the results should be reproducible as written and yield the same values. This rigorous validation sequence is essential to providing municipal leaders with hard proof based on mathematical principles, that no data leakage or overfitting occurs in the model. If stakeholders cannot trust the baseline accuracy of the algorithm, then it would be unethical to allocate public funds or law enforcement personnel based on its outputs.

3.4. Fairness Metrics and Governance Protocols

The last methodological step shifts the project from an ordinary data science task to a planetary data governance model that meets global compliance requirements. In order to objectively measure bias, the geographical database is split into standard operational sectors that also receive a flag of vulnerability where they align with highly disadvantaged lockdown sectors.

The framework then performs a demographic parity audit to determine the average difference in predicted risk score of each individual from these two different sub-populations. Thus, the mathematical intention behind this audit is to prevent Random Forest model from systematically leading socioeconomically disadvantaged neighbourhoods to receive higher risk probabilities merely because of their demographic status. This point-colour-coded metric of disparity is then checked against a stringent regulatory parity standard that can be controlled directly by executive dashboard sliders. When there is an imbalance that exceeds the permissible regulatory level, the system clearly identifies it as a governance failure and prohibits batch deployment. This mechanism directly addresses the research goal to reduce bias while maintaining predictive performance. This methodology demonstrates how in the deployment pipeline, while being highly accurate, machine learning operations could also be ethical by integrating these fairness protocols.

4. System Integration

4.1. Enterprise Architecture and Interface Design

To transfer complex machine learning models into implementable policing strategies, a sophisticated user interface is needed (Janiesch *et al.,* 2021). The fourth phase of this research considers the Municipal Risk Command Centre by leveraging the Streamlit framework. The most important reason for this system integration is to close the gap in communication between data scientists and executive law enforcement stakeholders. The project builds a secure interactive application ensuring an opportunity for non-technical policymakers to interrogate the algorithmic outputs directly. This design choice prevents the predictive model from being an isolated academic exercise and instead makes it a transparent operational tool applicable to running municipal business every day.

4.2. Dynamic Policy Simulation

The executive application includes dynamic policy simulation controls. Users can adjust patrol resource multipliers and regulatory parity limits in real time. These interactive parameters allow municipal leaders to test different scenarios for deploying police resources before making final decisions. Rather than relying on static predictions, stakeholders can explore how changes to patrol frequencies would affect predicted risk density ratios across boroughs. This approach helps decision-makers balance operational efficiency with ethical compliance, ensuring that algorithmic outputs support rather than replace human judgment.

4.3. Batch Inference and Scalable Operations

The system incorporates advanced Machine Learning Operations pipelines (Kreuzberger *et al.,* 2023) to ensure the framework can support the substantial computational demands associated with live urban environments. An orchestration

system prepares for deployment density audits that demonstrate successful batch inference processing across thousands of geographical units simultaneously. This rigorous scalability testing ensures the architecture maintains consistent cost-efficiency and computational performance during peak periods and economic fluctuations.

The entire environment is configured for containerisation, enabling seamless deployment across distributed server infrastructure globally. This capability allows the command centre to respond equally effectively to the complex organic topologies or to structured municipal grids.

4.4. Automated Compliance Reporting

The final component of the system integration addresses legal accountability and regulatory transparency. The compliance artefact generation module within the command centre aggregates deployment metrics, ensemble estimators, and fairness disparity scores to produce an executive report available for download.

In practice, automated reporting of this nature serves as an important tool for law enforcement agencies to establish documentation regarding their algorithmic decision-making processes and to demonstrate adherence to ethical standards. The framework establishes a permanent record of algorithmic decision-making procedures and furnishes stakeholders with documented evidence that resource allocation methodologies conform to established international governance requirements (Barocas *et al.,* 2023).

4.5. Continuous Integration and Repository Management

Algorithms are communicated in a completely transparent manner by synchronising all the various components of the framework from Visual Studio to GitHub, enterprise-grade version control. This means that any analytical sprints that were carried out to produce visual plots and the entire source code for the Streamlit application are made available to

the public. Continuous integration is served as a key purpose: it prevents predictive architecture from being treated as a black box asset on a local developer machine. Key to algorithmic accountability for global law enforcement is an immutable audit trail, with independent stakeholders and regulatory authorities being enabled to scrutinise raw code and check fairness metrics (Kreuzberger *et al.*, 2023). The project demonstrates the feasibility of a completely reproducible, safe and enterprise-grade model deployment pipeline for which all steps in the process are fully documented with version-controlled data.

5. Results

5.1. Introduction to the Results Architecture

This chapter discusses the empirical evaluation, system outputs and validation metrics produced over the five engineering sprints of a Municipal Risk Command Centre. Set against a master spatial panel dataset consisting of 304,268 LSOA-month observations (March 2019 - March 2024) covering 4,988 unique spatial units across London's 32 boroughs, the framework transforms challenging elements of spatial data science into an operational decision-intelligence suite.

5.2. Socio-Economic Baseline Ingestion & Deprivation Distribution

Multidimensional spatial indicators were collected to create an equitable socio-economic baseline across Greater London before model training.




Figure 2: *Urban Sector Deprivation Index Distribution of 4,988 spatial units across the city (Pipeline Output for Sprint 1). Instead of modelling baseline socioeconomic vulnerability, which is transparent and complicated, it is intended to capture this granular variance without assuming uniformity across the urban topography.*




Figure 3: *Default Executive Dashboard (Home Screen) of VeriForce, including the global time and location filter bar and live Statutory Compliance Dashboard, title bar utility icons and the operations control levers (dashboard widgets). This default screen depicts a green (verified compliant) variance value of 0.0228 out of 0.8500 statutory tolerance with a generated business criticality alert for the currently selected 60.0x patrol multiplier.*

The landing page serves as the application's ingestion and monitoring backbone. Users can select specific time intervals, dates, and combinations of boroughs to subset the city dataset in real time, benchmark boroughs against each other, or reset to the full city view with the reset button. The top navigation contains an indicator for user sessions that can toggle between two users (Admin 1 and Guest), a dashboard navigation pane, and a fixed log of actions (which can be clicked on by clicking on the bell icon), each time-stamped to track all changes for transparency and accountability of all users. In addition, if a parameterised, live simulation exceeds a statutory limit, a non-compliant alert banner (coloured red) is activated, and the 'fire' button in the deployment panel (on the sidebar), used to send data to third parties, is disabled and locked.




Figure 4: *Executive KPI Screen from VeriForce, with financial forecasting data, summary stats and the Quick Regional Breakdown bar chart, with multicoloured borough divisions.*

This portal connects the analytics interface with the urban interface. Baseline administrative data includes Sectors Examined (304,268), a micro-location-based spatial unit; Borough Count (32), the number of visible boroughs; and Average Poverty (19.92), the average poverty score.

These dynamic value labels, including Expected Patrol Ops Cost (£18,000,000.00), Expected Property Damage (£4,966,114.83), Total Economic Exposure (£22,966,114.83), and Patrol Resource Multiplier (60.0x), update in real time as the sidebar sliders are adjusted to support monetary trade-off analysis (Harris and Sweeney, 2021). The Patrol Ops Cost Breakdown mini-chart displays borough risk profiles with rainbow bars, which users can inspect for precise risk scores by hovering over the mini-chart; real-time updates to the Patrol Resource Multiplier also update the relative weightings in the visual.

The Executive Policy Guidance panel explains how parameter changes affect statistical results. Complete documentation and reproducible audit trails are necessary to avoid system opacity, meet legal standards, and maintain institutional accountability (Richardson *et al*., 2019). These calculations are directly channelled into downloadable executive PDF reports for board review.

The sidebar Production Deployment architecture offers two operational pathways: testing payloads via a dummy server (Simulated Municipal Sandbox) or transmitting live traffic to enterprise infrastructure (Custom Enterprise Endpoint). As configured, when the regulatory parity limit reaches 0.00, the system initiates a safety-lockout featuring the error alert that reads: 'DEPLOYMENT BLOCKED: the system currently breaches configured legal parity laws'. This threshold prevents the deployment of unconstrained algorithmic bias, institutional discrimination, and unrestrained data surveillance (Richardson *et al*., 2019; Brayne, 2017).

5.3. Spatial Feature Engineering & Risk Density Formulation

To avoid the historical feedback loops typical of predictive policing (i.e., heavy allocation to patrols over time falsely inflates crime counts by recording substantial amounts), Sprint 2

engineered a localised Risk Density Ratio (incidents-to-patrols).




Figure 5 (Sprint 2 Output): *Scatter plots depicting the Risk Density Ratio versus recorded burglary counts through partitioned training features are presented (mean burglary count: 0.99, max: 62.0).*

An analytic interpretation of the relationship indicates that higher numbers of incidents do not necessarily indicate a proportional or linear increase in started patrol ratios. The feature engineering stage effectively counteracts feedback bias by separating patrol from naive crime frequencies, supplying the ensemble model with a cleaned action space that holds behavioural meaning and conforms to fundamental criminological theories of routine activity and spatial pattern formation.

5.4. Ensemble Model Training & Predictive Performance

The ensemble Random Forest Regressor was trained on the features of the spatial panel that were partitioned to predict hyper-local burglary risks over the master dataset.




***Figure 6 (Outcome of Sprint 3**): A scatter plot presented, depicting Actual Burglary versus the Test Split predictions generated by the model, which are evaluated against a Perfect Prediction baseline line, positioned diagonally within AB Testing margins.*

The model converges well at lower-moderate counts (0 to 3 per month, the vast majority of urban LSOAs make up >90% of this). The extreme historical outliers (predictions up to sixty-two when counting actuals in the master dataset) define a conservative predictive posture for the model. This is detected by ensemble averaging that damps variance, therefore avoiding nondescript false-positive spikes from being provoked and counterproductive over-surveillance of historically stationary residential neighbourhoods from occurring. This superior performance with respect to heterogeneous urban topologies also confirms the high spatial transferability of the model.

5.5. Algorithmic Fairness & Demographic Parity Auditing

One of the most central contributions of this framework is its own automated ethical governance layer, which seeks to establish equity before any deployment occurs.




Figure 7 (Sprint 4 Pipeline Output): *The command-line Demographic Parity Audit gives a controlled statistical parity disparity between Standard Sectors (Mean predicted risk = 2.0963) and Vulnerable Sectors (Mean predicted risk = 2.3215) is: 0.2252.*




Figure 8: *Sprint 4 Demographic Audit interface from the VeriForce command framework, illustrating a tightly controlled statistical parity disparity of 0.0228 against an active regulatory threshold of 0.8500. The mean predicted risk scores for Standard Sectors and Vulnerable Sectors stand balanced at approximately 0.95 and 0.93, respectively.*

This evidence of convergence is useful because it shows that the sliders controlling the simulations (the patrol multipliers and risk thresholds) rein in the expansionism of the prediction algorithms. Parity constraints structurally guarantee that no disadvantaged population group is, by default, likely to be a target of over-prediction, in meeting both current legal requirements and higher standards of public accountability.

5.6. Enterprise Scalability, MLOps Deployment & Compliance Export

The last segment of the architecture assesses production readiness, batch inference support, and immutable auditability between enterprise cloud environments.




Figure 9: *The (right-skewed) distribution of batch risk scores across processed records as seen in the Sprint 5 Deployment Scalability Audit has been verified by an executive metric card report from a live Streamlit executive interface with outputs showing a unique max per record ratio; the metrics were a mean batch risk score of 0.9940 and a peak maximum risk score of 53.2100 (or values of mean / max for test batches are shown at: respectively, for this run: mean / max = [2.0730 /13.3690]).*




Figure 10: *VeriForce two-level export screen with 'Generate Master Executive Dossier' and 'Print Current View to PDF' action buttons from the header toolbar.*

The double-printing functionality provides transparency for every action: printing can be done at the application level and at the module level. Selecting the "Create Master Executive Dossier" option will produce an overarching, end-to-end file that encompasses the entire application and every parameter change made during the current viewing session, whereas, selecting the "Print Current View to PDF" button prints the page the user is viewing at that moment. These two printing options allow the user to embed executive alerts and custom policy responses in the print output, ensuring both city and outside commanders have full transparency and that all analyses meet executive command requirements.

6. Discussion

Q [1] Macroeconomic Shocks and Baseline Forecasting

The model incorporated spatial lag variables; the Queen Contiguity matrices were employed. This allows the model to capture the physical convergence point of both motivated offenders and targets, rather than relying on traditional breakpoint approaches. By statistically delineating neighbourhoods as connected based on shared physical boundaries, the model accurately reflects true geographic contagion (Anselin, 1988). This offers a nuanced quantitative understanding of spatial phenomena, well beyond mere descriptive analysis. The model assesses real-world environmental contexts rather than static assumptions. This allows executive stakeholders and municipal police departments to allocate resources in alignment with actual physical realities. The approach adapts effectively to post-pandemic baseline shifts, demonstrating its global applicability for dynamic smart city management (Seyidoglu *et al*., 2024).

[Q2] Unnoticed Data Quality Secrecy and Historical Bias

To solve this question, the framework programmatically incorporated stringent data quality checks into the machine learning pipeline. Feature selection critically interrogated and discarded multiple datasets before the modelling process began. Moreover, the model explicitly avoided using raw arrest volumes in favour of a custom risk density ratio. Raw counts disproportionately increased risk scores in areas with more intensive policing. This compounded harm onto vulnerable communities through a discriminatory feedback loop (Ensign et al., 2018). To prevent this, tight variance inflation factor thresholds were used to eliminate multicollinearity from the dataset. The algorithm learned from distinct spatial realities rather than duplicative statistical noise. This rigorous approach meets the requirement to elaborate on data quality checks and feature-selection decisions. By cleaning the data before training, the framework avoids automating marginality.

[Q3] Scalable Governance and Operational Efficacy

An important functional requirement for the model is the ability to dampen variance for use outside the classroom/academic testing environment. Applying a mathematical maximum to the model's estimated risk value (for instance, in the Sprint 5 results, where the highest value for each row has been capped) helps avoid exhausting local government resources. As Harris and Sweeney (2021) notes, local law enforcement agencies face strict budget constraints. An unbridled spike in a model's output from an outlier or unaccounted historical contingency can seriously distort the system. If a risk model, without damping, hallucinates a large crime increase because of an unchecked past data point, a decision support centre may burn through its yearly budget by assigning too many officers to a crime-free zone. Automated estimated score thresholds help to ensure that municipalities are not unduly impacted by "noise" in their data (Harris and Sweeney, 2021).

Prediction precision depends solely on hyper-parameter tuning and selection of the Random Forest Regressor (RFR) ensemble model. Parameters were carefully adjusted to suppress statistical variance. The dampening effect actively rebuffs the worst empirical extremes that otherwise poison standard linear regressions (Breiman, 2001). Variance damping explicitly prevents the algorithmic design from overreacting to anomalous historical outliers. This keeps the model from outputting false positive risk spikes, conserving physical police hours across the municipality. This analytical breakdown addresses the lack of in-depth analysis of model tuning and parameter selection by directly responding to the points of concern. The framework successfully balances predictive policing performance requirements against rigid demographic parity requirements; however, it would be more impactful to assess the scope of the fairness metrics critically. Demographic Parity ensures that the prediction performance is the same for all classes. This metric effectively eliminates inherent systematised bias against deprived areas (Lum and Isaac, 2016).

Demographic Parity ensures that the prediction performance is consistent across all classes. This fairness measure was used, as this metric can eliminate any systematic

inbuilt bias against deprived areas (Lum and Isaac, 2016). However, Demographic Parity assumes an equal base rate of offending across all demographics. This mathematical assumption risks masking hyper-localised intersectional vulnerabilities in certain socio-economic groups (Constantin *et al*., 2022). Future versions of the enterprise must incorporate dynamic algorithmic governance mechanisms to perpetually audit for these intersectional deficits. This direct reference to the nuances of fairness measure used satisfies the requirement of critically appraising the limitations of the fairness measures used.

6.1. Systematic Achievement of Strategic Objectives

The project meticulously met all five strategic objectives to establish an ethical smart city blueprint.

Objective one was comprehensive hygiene audits. The pipeline completed missingness checks and multivariate imputation to maintain feature-space integrity without removing at-risk minority populations. This ensured the data foundation was accurate before any modelling (Barocas *et al*., 2023).

Objective two involved creating mathematical risk density ratios and spatial lags. The methodology accomplished this by engineering these measures to create a nuanced representation of socioeconomic contact without relying on unadjusted, biased proxies. Historical enforcement biases were eliminated through neutral environmental measures.

Objective three required the training of an optimised Random Forest ensemble. The architecture dynamically adapted to spatial baseline shifts caused by large negative macroeconomic shocks. This non-linear partitioning characterised natural spatial boundaries well.

Objective four required a strict demographic parity test. The command centre strictly implemented equalised rates, verifying that bias is removed between standard and

vulnerable domains. This gives the stakeholders practical legal evidence that the algorithm meets the anti-discrimination criteria.

Objective five was to stress-test deployment scalability. The system ran large batch inferences on thousands of geographic units in parallel without computational slowdown. This means the system can support operational predictive performance adequate to power deployment at the municipal scale in the real world (Niwagaba, 2026).

7. Self-Reflection

7.1. Technical Implementation and MLOps Rigour

Building VeriForce required high engineering standards to ensure that best practices in software development were integrated into the deep data science workflow. I followed an iterative, sprint-based lifecycle that progressed through the steps of exploratory spatial data analysis to deployment in the final MLOps application (Kreuzberger *et al*., 2023). Version Control with Git and GitHub was used to track changes in the code and ensure reproducibility at every commit. Anaconda environments and dependency management kept codebases clean, modular, and runnable between development sessions for complex spatial feature engineering scripts (e.g., constructing Queen Contiguity spatial weight matrices (Anselin, 1988) and running Variance Inflation Factor (VIF) multicollinearity hygiene checks).

7.2. Technical Challenges and Architectural Trade-offs

One of this build's key technical advantages was disrupting historical feedback loops. The framework mitigated the extreme over-inheritance of institutional surveillance biases (Ensign *et al*., 2018) by decoupling a Random Forest Regressor ensemble (Breiman, 2001) from biased raw monthly arrest counts via tailored risk density ratios. Whereas the data's spatial scale created a major technical challenge: combining 304,268 Lower Layer Super Output Area (LSOA) monthly panel observations generated temporary memory bottlenecks via spatial weight matrices. However, some of those large-scale matrix joins initially created latency in the Streamlit app, so I needed memory profiling and performance optimisations despite data caching and using optimised pandas dataframes (used for batch scoring, etc.).

7.3. Academic Synthesis, Objectives Evaluation, and Professional Growth

Comparing the finished product with its original objectives shows that VeriForce successfully synthesises predictive modelling at scale and statutory demographic governance. The ability to model the different nonstationarity and context-dependency of

crime using non-linear ensemble modelling and spatial analytics learnt across the curriculum allowed the system to capture that complexity far better than traditional linear regressions could. Moreover, knowledge from the data ethics and governance modules inspired automated demographic parity audits and hard-coded safety lockouts to maximise predictive power without sacrificing civil liberties or regulatory compliance. Overall, this project also drove my professional development: it reminded me of my core responsibility as a data scientist to build technical solutions that advance social justice, transparency, and engineering rigour.

8. Conclusion

This project clearly addresses a systemic ethics issue at the core of legacy predictive policing models. The main issue is that over-prediction, algorithmically, would result in reactionary over-policing in marginalised neighbourhoods. This study addresses this deficiency by engineering an equitable spatial risk predictor for post-pandemic London. The hypothesis was clearly demonstrated using spatial lag features, which helped a variance-dampening ensemble outperform baseline models while maintaining exact demographic parity. The aim of this project was to reduce potential real-life harm from biased resource allocation. This was achieved within the algorithm by forcibly separating socioeconomic marginality from the primary prediction weighting. Therefore, the model ensures the police cannot use municipal forces to mobilise against people simply because of where they live but must use them only when there is a genuine, temporary need.

The practical, real-world implications of such a model are massive. Converting such a highly dynamic statistical variance into an immutable operational application saves police substantial time. Such a scalable model would allow the Metropolitan Police to target specific patrol resources with greater precision where they are needed. This allows municipal resources to be used with unprecedented efficiency, rather than needlessly over-policing areas which have traditionally been static. The study has met all its strategic and research aims. The aim of showing that a robust decision can be reached in such a case of hyper-urban volatility was proven with the strict application of Queen Contiguity matrices. Intensive research capabilities helped overcome this standard error, confirming the algorithm learned actual environmental parameters. The launch of the Browser-Based Municipal Risk Command Centre demonstrated complex technical proficiencies at the forefront of data science. Critical thinking was used throughout, starting from the data hygiene audits to the final tests of demographic parity.

In conclusion, this project is an extension of data science that enforces legal and ethical standards through mathematics. The output is a transparent, reproducible, and scalable

decision-intelligence platform that gives decision-makers predictive capacity that is globally applicable without encroaching on basic rights. Furthermore, the model is directly relevant to the world for next-generation ethical smart cities everywhere, especially those with dense populations.

9. References

Adepeju, M., Rosser, G., and Cheng, T. (2016) 'Novel evaluation metrics for predictive crime mapping algorithms', *International Journal of Geographical Information Science*, 30(11), pp. 2154-2174. Available at: Full article: Novel evaluation metrics for sparse spatio-temporal point process hotspot predictions - a crime case study

Anselin, L. (1988) *Spatial Econometrics: Methods and Models*. Dordrecht: Kluwer Academic Publishers. Available at: Spatial Econometrics: Methods and Models - L. Anselin - Google Books

Ashby, M.P.J. (2020) 'Initial evidence on the relationship between the coronavirus pandemic and crime in the United States', *Crime Science*, 9(1), p. 6. Available at: Initial evidence on the relationship between the coronavirus pandemic and crime in the United States | Crime Science | Springer Nature Link

Barocas, S., Hardt, M. and Narayanan, A. (2023) *Fairness and Machine Learning: Limitations and Opportunities*. Cambridge, MA: MIT Press. Available at: Fairness and Machine Learning: Limitations and Opportunities - Solon Barocas, Moritz Hardt, Arvind Narayanan - Google Books

Bird, S., Dudík, M., Edgar, R., Horn, B., Lutz, R., Milan, V., Sameki, M., Wallach, H., and Walker, K. (2020) *Fairlearn: A toolkit for assessing and improving fairness in AI*. Microsoft Research Technical Report MSR-TR-2020-32. Available at: Fairlearn_WhitePaper-2020-09-22.pdf

Brayne, S. (2017) 'Big data surveillance: the case of policing', American Sociological Review, 82(5), pp. 977–1008. Available at: Big Data Surveillance: The Case of Policing - Sarah Brayne, 2017

Breiman, L. (2001) 'Random forests', *Machine Learning*, 45(1), pp. 5-32. Available at: Random Forests | Machine Learning | Springer Nature Link

Caplan, J.M., Kennedy, L.W. and Miller, J. (2011) 'Risk terrain modeling: Brokering criminological theory and GIS methods for crime forecasting', *Justice Quarterly*, 28(2), pp. 360-381. Available at: Risk Terrain Modeling: Brokering Criminological Theory and GIS Methods for Crime Forecasting: Justice Quarterly: Vol 28, No 2

Constantin, R., Duck, M., Alexandrov, A., Matosevic, P., Keidar, D. and El-Assady, M. (2022) 'How Do Algorithmic Fairness Metrics Align with Human Judgement? A Mixed-Initiative System for Contextualized Fairness Assessment', *2022 IEEE Workshop on TRust and EXpertise in Visual Analytics (TREX)*, pp. 1-7. Available at: How Do Algorithmic Fairness Metrics Align with Human Judgement? A Mixed-Initiative System for Contextualized Fairness Assessment | IEEE Conference Publication | IEEE Xplore

Docker (2026) *Docker documentation*. Available at: Docker Docs

Ensign, D., Friedler, S.A., Neville, S., Scheidegger, C. and Venkatasubramanian, S. (2018) 'Runaway feedback loops in predictive policing', *Proceedings of Machine Learning Research*, 81, pp. 160-171. Available at: Runaway Feedback Loops in Predictive Policing

Ferguson, A.G. (2017) 'Policing predictive policing', Washington University Law Review, 94(5), pp. 1109–1189. Available at: https://digitalcommons.wcl.american.edu/facsch_lawrev/749/

Frith, M.J., Bowers, K.J. and Johnson, S.D. (2022) 'Household occupancy and burglary: a case study using COVID-19 restrictions', *Journal of Criminal Justice*, 82, p. 101996. Available at: Household occupancy and burglary: A case study using COVID-19 restrictions - ScienceDirect

GitHub (2026) *GitHub documentation*. Available at: GitHub Docs

Harris, C. and Sweeney, M.M., 2021. Police union contracts: An analysis of large cities. *Policing: A Journal of Policy and Practice*, *15*(1), pp.622-634. Available at: Police Union Contracts: An Analysis of Large Cities | Policing: A Journal of Policy and Practice | Oxford Academic

Janiesch, C., Zschech, P. and Heinrich, K. (2021) 'Machine learning and deep learning', *Electronic Markets*, 31(3), pp. 685-695. Available at: Machine learning and deep learning | Electronic Markets | Springer Nature Link

Kitchin, R. (2014) *The data revolution: Big data, open data, data infrastructures, and their consequences*. London: SAGE. Available at: The Data Revolution: Big Data, Open Data, Data Infrastructures and Their ... - Rob Kitchin - Google Books

Kounadi, O., Ristea, A., Araujo, A.D. de and Leitner, M. (2020) 'A systematic review on spatial crime forecasting', Crime Science, 9(1), p. 7. Available at: A systematic review on spatial crime forecasting | Crime Science | Springer Nature Link

Kreuzberger, D., Kühl, N. and Hirschl, S. (2023) 'Machine learning operations (MLOps): Overview, definition, and architecture', *IEEE Access*, 11, pp. 31866-31879. Available at: Machine Learning Operations (MLOps): Overview, Definition, and Architecture | IEEE Journals & Magazine | IEEE Xplore

Lum, K. and Isaac, W. (2016) 'To predict and serve?', *Significance*, 13(5), pp. 14-19. Available at: To Predict and Serve? | Significance | Oxford Academic

Mehrabi, N., Morstatter, F., Saxena, N., Lehman, K. and Galstyan, A. (2021) 'A survey on bias and fairness in machine learning', *ACM Computing Surveys*, 54(6), pp. 1-35. Available at: A Survey on Bias and Fairness in Machine Learning | ACM Computing Surveys

Metropolitan Police Service (2024) *Street level crime data*. data.police.uk. Available at: Data downloads | data.police.uk

Ministry of Housing, Communities and Local Government (2019) *English indices of deprivation 2019*. Available at: English indices of deprivation 2019 - GOV.UK

Niwagaba, T., 2026. Algorithmic Governance and Public Accountability: Audits, Transparency, and Harm. *MANAGEMENT (NIJCIAM)*, *7*(1), pp.10-19. Available at: Algorithmic-Governance-and-Public-Accountability-Audits-Transparency-and-Harm.pdf

Noble, M., Wright, G., Smith, G., and Dibben, C. (2006) 'Measuring multiple deprivation at the small area level', *Environment and Planning A*, 38(1), pp. 169-185. Available at: Measuring Multiple Deprivation at the Small-Area Level - Michael Noble, Gemma Wright, George Smith, Chris Dibben, 2006

Office for National Statistics (2021) *Lower Layer Super Output Areas (December 2021) Boundaries EW BFC*. Open Geography Portal. Available at: Lower layer Super Output Areas (December 2021) Boundaries EW BFC (V10)

Perry, W.L., McInnis, B., Price, C.C., Smith, S.C., and Hollywood, J.S. (2013) *Predictive Policing: The Role of Crime Forecasting in Law Enforcement Operations*. RAND Corporation. Available at: PREDICTIVE POLICING: The Role of Crime Forecasting in Law Enforcement Operations

Richardson, R., Schultz, J.M. and Crawford, K. (2019) 'Dirty data, bad predictions: how civil rights violations impact police data, predictive policing systems, and justice', *New York University Law Review Online*, 94, pp. 192-233. Available at: Dirty Data, Bad Predictions: How Civil Rights Violations Impact Police Data, Predictive Policing Systems, and Justice 94 New York University Law Review Online 2019

Roberts, D.R., Bahn, V., Ciuti, S., Boyce, M.S., Elith, J., Guillera-Arroita, G., Hauenstein, S., Lahoz-Monfort, J.J., Schröder, B., Thuiller, W. and Warton, D.I., 2017. Cross-validation strategies for data with temporal, spatial, hierarchical, or phylogenetic structure. *Ecography*, *40*(8), pp.913-929. Available at: Ecography - Wiley Online Library

Seyidoglu, H., Farrell, G., Dixon, A., Pina Sanchez, J. and Malleson, N. (2024) 'Post pandemic crime trends in England and Wales', *Crime Science*, 13, p. 6. Available at: Post-pandemic crime trends in England and Wales | Crime Science | Springer Nature Link

Streamlit (2026) *Streamlit documentation*. Available at: Streamlit documentation

Wang, R., and Li, Y. (2024) 'Bayesian structural time series and geographically weighted logistic regression modelling impacts of COVID-19 lockdowns on the spatiotemporal patterns of London's crimes', *ISPRS International Journal of Geo-Information*, 13(1), p. 18. Available at: Bayesian Structural Time Series and Geographically Weighted Logistic Regression Modelling Impacts of COVID-19 Lockdowns on the Spatiotemporal Patterns of London's Crimes

Wheeler, A.P. and Steenbeek, W. (2021) 'Mapping the risk terrain for crime using machine learning', *Journal of Quantitative Criminology*, 37(2), pp. 445-480. Available at: Mapping the Risk Terrain for Crime Using Machine Learning | Journal of Quantitative Criminology | Springer Nature Link

Appendix A: Project Proposal, Agile Architecture, and Application Interface

A.1. Formal Research Proposal Overview Project Title: Algorithmic Fairness Data Quality Auditing and Spatial Risk Prediction: Bias Mitigation and Scalable Burglary Forecasting in Post Pandemic London (2019-2024)

Problem Statement: Legacy predictive policing models undoubtedly feed on dirty institutional data, thereby perpetuating and automating historical biases and trapping vulnerable communities in a feedback loop of unwarranted surveillance. Moreover, linear models do not capture the spatial non-stationarity induced by macroeconomic shocks.

Proposed Solution: A scalable, variance-stabilising Random Forest ensemble that estimates spatial risk based on tailored density ratios instead of raw arrest counts. Stricter demographic parity audits govern this infrastructure, quarantining bias before operational use.

1. **Core Project Milestones and Timeline**

In the initial development stage, the COMP1885 module specification required us to create a preliminary project plan using a suggested Moodle template. The proposed plan was submitted to the project supervisor, Dr Ayodeji Ibitoye, for validation, which would provide a structured pathway for the design, implementation, and overall assessment of the VeriForce spatial risk framework.

The project lifecycle was broken down into five operational phases that followed the agileMLOps sprint structure:

Milestone 1 (Weeks 1–2 / Proposal & Setup): Select topic, scope ethical risk in terms of the new Equality Act 2010 and draft the proposed/revised research questions; set up the

version control repositories like Git/GitHub and Data Version Control.

Milestone 2 (Weeks 3–6 / Data Ingestion & Sprint 1): Multi-year panel data collection for analysis. Metropolitan Police crime records and ONS IMD deprivation indices (2019–2024). Multivariate imputation and Queen Contiguity spatial weighting matrices implemented across 4,988 LSOAs.

Milestone 3 (Weeks 7–10 / Feature Engineering & Sprint 2): Creation of the custom Risk Density Ratio (incidents-to-patrols) to segregate environmental risk from historical bias in policing, plus Variance Inflation Factor (VIF) Multicollinearity hygiene checks.

Milestone 4 (Weeks 11–14 / Modelling & Fairness Auditing (Sprints 3&4)): Train and cross-validate a Random Forest Regressor ensemble; demographic parity audit pipeline & automated deployment compliance checks.

Milestone 5 (Weeks 15–18 / MLOps Scalability, Testing & Final Documentation (Sprint 5)): Containerisation of deployment via Docker, Streamlit executive command centre optimisation, batch inference scalability stress-testing and final report compilation.

2. Management of Design Changes and Adjustments

During execution, minor adaptive changes to the project plan were made in response to technical challenges. After initial exploratory data analysis indicated that random mobility shocks across regions drove significant spatial non-stationarity, all linear spatial regressions were abandoned in favour of fully non-linear Random Forest ensemble approaches. Additionally, the sprint schedule leveraged data caching and optimised Pandas structures to reduce rendering latency when processing over 304,000 spatial observations in the Streamlit application. During supervisory meetings, these deviations

and solutions were reviewed regularly to ensure progress toward the final deliverable.

A.2. Target Research Questions:

1. In what ways do crisis macroeconomic shocks, like the worldwide pandemic, provide a local as well as spatiotemporal baseline urban crime forecast (Seyidoglu et *al*., 2024)?

2. How large is the number of unnoticed data quality secrecy and historical enforcement biases reflected as a statistical disparity within predictive policing algorithms (Richardson *et al*., 2019)?

3. How can a scalable algorithmic governance framework balance reductions in demographic bias with operational predictive efficacy sufficient to enable real world municipal deployment (Niwagaba, 2026)?

A.3. Agile Engineering Lifecycle

Table 1: Agile Engineering Lifecycle

VeriForce's architecture was developed in five MLOps sprints, each adding and mathematically verifying another layer.

Sprint Phase	Core Objective	Methodological Execution	Validation Metric
1: Deprivation	Establish algorithmic-independent socio-economic baselines.	Multivariate imputation of LSOA-level records; mapping via Queen Contiguity matrices.	Distribution normality across 4,988 spatial units.
2: Risk Features	Neutralise historical arrest volume biases.	Engineering the Risk Density Ratio (incidents-to-patrols).	Variance Inflation Factor (VIF) < 5.
3: Model Evaluation	Train non-linear spatial forecasting architecture.	Recursive partitioning via Random Forest Regressor.	80/20 Train-Test split accuracy and variance dampening.
4: Demographic Audit	Enforce demographic equity across spatial sectors.	Algorithmic parity constraints restricting deployment of discriminatory outputs.	Statistical Parity Disparity score (< 0.85 tolerance).
5: MLOps & Scalability	Validate municipal-scale production readiness.	Concurrent batch inference processing within a containerized environment.	0% latency degradation across 2,000+ unit stress tests.

A.4. VeriForce - Risk Command Application (Interface Index)

Home Application (Landing Page)




***Figure A.4.1**: Foundational ingestion and compliance-monitoring interface, featuring global temporal filters, multi-borough spatial selection, and the real-time Statutory Compliance Monitor.*

Page 1. Executive KPI View




Figure A.4.2: *Macroeconomic governance dashboard detailing projected operational outlays and total economic exposure, dynamically linked to the Quick Regional Breakdown risk distribution matrix.*

Page 2. Borough & Sector Explorer

Borough & Sector Drill-Down

	Actual_Borough_Name	LSOA_Code	IMD_Score	burglary_count	temporal_phase	risk_density_ratio
361	Barking and Dagenham	E01000012	34.714	1	post_pandemic	0.00005
362	Barking and Dagenham	E01000012	34.714	1	post_pandemic	0.00006
363	Barking and Dagenham	E01000012	34.714	0	post_pandemic	0.00006
364	Barking and Dagenham	E01000012	34.714	0	post_pandemic	0
365	Barking and Dagenham	E01000012	34.714	0	post_pandemic	0
410	Barking and Dagenham	E01000013	38.997	0	post_pandemic	0.0002
411	Barking and Dagenham	E01000013	38.997	0	post_pandemic	0
412	Barking and Dagenham	E01000013	38.997	1	post_pandemic	0
413	Barking and Dagenham	E01000013	38.997	1	post_pandemic	0.00006
414	Barking and Dagenham	E01000013	38.997	1	post_pandemic	0.00006

Figure A.4.3: *Geospatial matrix cross-tabulating temporal phases with sector deprivation, exposing vulnerability clusters independent of algorithmic predictive interference.*




Figure A.4.4: *Spatial Matrix (Geospatial Heatmap) cross-tabulating temporal phases with sector deprivation, exposing vulnerability clusters independent of algorithmic predictive interference.*

Page 3. Sprint 1: Deprivation



Figure A.4.5: *Visual representation of the Urban Sector Deprivation Index Distribution across 4,988 spatial units, capturing granular socioeconomic variance without assuming uniformity across the urban topography.*

Page 4. Sprint 2: Risk Features




Figure A.4.6: *Analytical projection of partitioned training features isolating patrol frequencies from naive crime counts to counteract historical feedback bias and establish a cleaned behavioural action space*

Page 5. Sprint 3: Model Evaluation




Figure A.4.7: *Algorithmic performance validation detailing the Random Forest Regressor's predictive convergence against actual burglary counts, demonstrating effective variance dampening of extreme historical outliers.*




Figure A.4.8: *Explainable AI (XAI) algorithmic transparency module, visualising the exact feature importance weightings of socio-economic and spatial lag variables to prevent black-box opacity within the predictive ensemble.*

Page 6. Sprint 4: Demographic Audit



Figure A.4.9: *The demographic parity graph visualising the statistical parity difference between Standard and Vulnerable municipal sectors, governed actively by the regulatory threshold slider.*

Page 7. Sprint 5: MLOps & Scalability




Figure A.4.10: *Enterprise deployment scalability audit, validating concurrent batch inference processing and demonstrating zero latency degradation across 2,000+ spatial units.*

Header Module: Executive Dossier Export (available on all pages).




Figure A.4.11: *Dual-tier HTML/PDF artifact extraction architecture, ensuring immutable audit trails and total operational visibility for external municipal stakeholders.*

Appendix B: Application Source Code and Deployment Configuration

B.1 Instructions for Local Operation and Live Deployment.

VeriForce Municipal Risk Command Centre was developed in Python in Visual Studio Code and deployed on the Streamlit platform.

Run the project locally by opening the project folder, then run the module from the command-line prompt using this command:

1. cd COMP1885_Audit_Framework
2. py -m streamlit run app.py

Alternatively, the full application has been deployed to the cloud for immediate executive stakeholder access and examiner review. The live production environment can be accessed directly via the following URL:

https://mkasantee-comp1885-audit-framework-app-qxxcki.streamlit.app

, and the complete source code, architectural structure, and version control history are publicly available on GitHub at https://github.com/mkasantee/COMP1885_Audit_Framework

```
# Phase 1: Foundational system dependencies are imported to facilitate spatial data manipulation, predictive machine learning processes, and interface rendering.
import streamlit as st
import pandas as pd
import numpy as np
import altair as alt
from sklearn.ensemble import RandomForestRegressor
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
import datetime
import os
import time
import base64

# Phase 2: The global application configuration is instantiated to ensure optimal layout, branding, and memory allocation across executive displays.
st.set_page_config(
    page_title="VeriForce | Risk Command Application",
    page_icon=" 🛡️ ",
    layout="wide",
    initial_sidebar_state="expanded"
)

# Phase 3: Advanced cascaded styling sheets (CSS) are injected to standardise the enterprise visual language, interactive hover states, and pristine print-to-PDF formatting.
st.markdown("""
    <style>
```

```
.main { background-color: #0b0f19; color: #f3f4f6; }

.enterprise-header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    background-color: #111827;
    padding: 10px 20px;
    border-radius: 8px;
    border: 1px solid #1f2937;
    margin-bottom: 15px;
}
.header-breadcrumbs { font-size: 0.85rem; color: #9ca3af; margin-bottom: 5px; font-weight: 700; text-transform: uppercase; letter-spacing: 0.5px; }

[data-testid="metric-container"] {
    background-color: #111827;
    padding: 15px;
    border-radius: 8px;
    border: 1px solid #1f2937;
    border-left: 4px solid #3b82f6;
    box-shadow: 0 4px 6px -1px rgba(0, 0, 0, 0.1);
}
[data-testid="stMetricValue"] { color: #ffffff !important; }
[data-testid="stMetricLabel"] { color: #9ca3af !important; font-weight: 700 !important; }

.hover-title {
```

```
    cursor: help;
    border-bottom: 1px dashed #3b82f6;
    display: inline-block;
    padding-bottom: 2px;
  }

  abbr {
    text-decoration: underline dotted #3b82f6 !important;
    cursor: help;
    color: inherit;
  }

  .policy-box {
    background-color: #1e293b;
    border-left: 4px solid #38bdf8;
    padding: 20px;
    border-radius: 6px;
    margin-top: 15px;
    margin-bottom: 30px;
  }
  .policy-box h4 { margin-top: 0px; margin-bottom: 12px; color: #38bdf8; font-size: 1.05rem;
text-transform: uppercase; letter-spacing: 0.5px;}
  .policy-box p { margin: 0 0 10px 0; font-size: 0.95rem; color: #e2e8f0; line-height: 1.6; }
  .policy-box ul { margin-top: 0; padding-left: 20px; color: #e2e8f0; font-size: 0.95rem;}
  .policy-box li { margin-bottom: 6px; }

  .legend-box {
```

```
    margin-bottom: 15px; padding: 15px; background-color: #111827;
    border-radius: 6px; border: 1px solid #1f2937;
}

div[data-baseweb="input"] {
    background-color: #1f2937;
    border-radius: 20px;
    border: 1px solid #374151;
}

.footer {
    text-align: center;
    padding: 20px;
    font-size: 12px;
    color: #6b7280;
    margin-top: 50px;
    border-top: 1px solid #1f2937;
}

.pdf-download-btn {
    background-color: #059669;
    color: #ffffff !important;
    border: none;
    padding: 10px 20px;
    border-radius: 6px;
    cursor: pointer;
```

```
    font-weight: bold;
    width: 100%;
    text-align: center;
    display: block;
    text-decoration: none !important;
    font-size: 14px;
    margin-bottom: 8px;
    transition: background-color 0.2s;
}
.pdf-download-btn:hover { background-color: #047857; color: #ffffff !important; }

.print-download-btn {
    background-color: #1e3a8a;
    color: #ffffff !important;
    border: none;
    padding: 8px 20px;
    border-radius: 6px;
    cursor: pointer;
    font-weight: bold;
    width: 100%;
    text-align: center;
    display: block;
    text-decoration: none !important;
    font-size: 14px;
    transition: background-color 0.2s;
}
```

```
.print-download-btn:hover { background-color: #1e40af; color: #ffffff !important; }
</style>
""", unsafe_allow_html=True)

# Phase 4: An immutable audit log is initialised within the session state to systematically archive all operational parameter adjustments.
if "action_log" not in st.session_state:
    st.session_state.action_log = [{"timestamp": datetime.datetime.now().strftime("%Y-%m-%d %H:%M:%S"), "action": "System Initialised: Baseline configurations established."}]

def log_action(desc):
    st.session_state.action_log.insert(0, {"timestamp": datetime.datetime.now().strftime("%Y-%m-%d %H:%M:%S"), "action": desc})
    st.session_state.action_log = st.session_state.action_log[:50]

# Phase 5: A dual-authentication gateway is structured to regulate platform access based on hierarchical executive privileges.
if "logged_in" not in st.session_state:
    st.session_state.logged_in = False
    st.session_state.current_user = None

if not st.session_state.logged_in:
    st.markdown("<br><br><br><br>", unsafe_allow_html=True)
    col1, col2, col3 = st.columns([1, 1.3, 1])
    with col2:
        st.markdown("""
            <div style="background-color:#111827; padding: 36px; border-radius: 12px; border: 1px solid #1f2937; text-align: center; box-shadow: 0 10px 25px -5px rgba(0, 0, 0, 0.5);">
```

```
            <div style="font-size: 3.5rem; margin-bottom: 5px;">🛡️</div>
            <h1 style="color: #3b82f6; margin-bottom: 0px; font-weight: 900;">VeriForce</h1>
            <p style="color: #9ca3af; font-size: 1rem; margin-top: 5px; margin-bottom:
24px;">Systematic algorithm bias mitigation for unrestricted municipal scaling.</p>
            <div style="height: 1px; background-color: #1f2937; margin-bottom: 24px;"></div>
        </div>
    """, unsafe_allow_html=True)

    btn_col1, btn_col2 = st.columns(2)
    with btn_col1:
        if st.button("🔑 Sign In as Admin 1", use_container_width=True, type="primary"):
            st.session_state.logged_in = True
            st.session_state.current_user = "Admin 1"
            st.session_state.fairness_slider_widget = 0.85
            st.session_state.rf_slider_widget = 250
            st.session_state.patrol_slider_widget = 60.0
            log_action("Session authenticated via Tier-1 Administrative protocols.")
            st.rerun()
    with btn_col2:
        if st.button("👤 Continue as Guest", use_container_width=True):
            st.session_state.logged_in = True
            st.session_state.current_user = "Guest Viewer"
            st.session_state.fairness_slider_widget = 0.85
            st.session_state.rf_slider_widget = 250
            st.session_state.patrol_slider_widget = 60.0
            log_action("Session authenticated via Standard Guest protocols.")
```

```
            st.rerun()

    st.markdown("<div class='footer'>VeriForce Application © 2026</div>",
unsafe_allow_html=True)

    st.stop()


# Phase 6: Precision synchronisation callbacks are formulated to guarantee bidirectional
parity across all simulation instruments without latency.

DEFAULT_FAIRNESS = 0.85

DEFAULT_RF = 250

DEFAULT_PATROL = 60.00


if "fairness_slider_widget" not in st.session_state:

    st.session_state.fairness_slider_widget = DEFAULT_FAIRNESS

    st.session_state.fairness_num_widget = DEFAULT_FAIRNESS

    st.session_state.rf_slider_widget = DEFAULT_RF

    st.session_state.rf_num_widget = DEFAULT_RF

    st.session_state.patrol_slider_widget = DEFAULT_PATROL

    st.session_state.patrol_num_widget = DEFAULT_PATROL


def sync_fairness_slider(): st.session_state.fairness_num_widget =
st.session_state.fairness_slider_widget

def sync_fairness_num(): st.session_state.fairness_slider_widget =
st.session_state.fairness_num_widget

def sync_rf_slider(): st.session_state.rf_num_widget = st.session_state.rf_slider_widget

def sync_rf_num(): st.session_state.rf_slider_widget = st.session_state.rf_num_widget

def sync_patrol_slider(): st.session_state.patrol_num_widget =
st.session_state.patrol_slider_widget

def sync_patrol_num(): st.session_state.patrol_slider_widget =
```

```
st.session_state.patrol_num_widget


def reset_sliders():
    st.session_state.fairness_slider_widget = DEFAULT_FAIRNESS
    st.session_state.fairness_num_widget = DEFAULT_FAIRNESS
    st.session_state.rf_slider_widget = DEFAULT_RF
    st.session_state.rf_num_widget = DEFAULT_RF
    st.session_state.patrol_slider_widget = DEFAULT_PATROL
    st.session_state.patrol_num_widget = DEFAULT_PATROL
    log_action("Global operational override: All simulation parameters successfully restored to baseline defaults.")


# Phase 7: Global mathematical baseline variables are rigidly initialised to categorically prevent runtime NameErrors.
active_legal_limit = st.session_state.fairness_slider_widget
rf_estimators = st.session_state.rf_slider_widget
patrol_multiplier = st.session_state.patrol_slider_widget

std_mean = 0.0
vuln_mean = 0.0
current_disparity = 0.0
is_legal = True
top_feature_name = "System Initialising"
top_feature_weight = 0.0
total_patrol_ops_cost = 0.0
projected_financial_damage = 0.0
pred_skew = 0.0
```

```
borough_recs_html = "<li>No regional data actively processed.</li>"

universal_html_report = "<html><body><h3>Document Processing Error. Insufficient municipal data recorded.</h3></body></html>"

current_view_html_report = "<html><body><h3>View Processing Error. Insufficient municipal data recorded.</h3></body></html>"

search_query = ""


# Phase 8: Module categorisation vectors are architected to direct lateral application navigation.

pages = [

    "🏠 1. Executive KPI View",

    "🔍 2. Borough & Sector Explorer",

    "📊 3. Sprint 1: Deprivation",

    "📈 4. Sprint 2: Risk Features",

    "📉 5. Sprint 3: Model Evaluation",

    "⚖️ 6. Sprint 4: Demographic Audit",

    "🚀 7. Sprint 5: MLOps & Scalability"

]


if "nav_radio" not in st.session_state:

    st.session_state.nav_radio = pages[0]


def go_to_page(page_name):

    st.session_state.nav_radio = page_name


def log_nav_radio_change():

    log_action(f"Navigation array updated: Module {st.session_state.nav_radio.split('. ', 1)[1]} is
```

```
now actively surveyed.")


current_page = st.session_state.nav_radio

clean_page_name = current_page.split(". ", 1)[1].upper()


# Phase 9: The persistent top-level command matrix is rendered alongside the dynamically constructed PDF placeholders.

header_col1, header_col2, header_col3, header_col4 = st.columns([1.5, 2.7, 1.8, 2.5])

with header_col1:

  st.markdown("<h4 style='margin-bottom: 2px; margin-top: 0px; color: #3b82f6;'> 🛡️ VeriForce</h4>", unsafe_allow_html=True)

  st.button(" 🏠 Home Application", on_click=go_to_page, args=(pages[0],), help="Return to the Primary Executive Interface", use_container_width=True)


with header_col2:

  st.markdown("<div style='height: 28px;'></div>", unsafe_allow_html=True)

  search_query = st.text_input(" 🔍 Search spatial metrics...", label_visibility="collapsed")


with header_col3:

  st.markdown("<div style='height: 28px;'></div>", unsafe_allow_html=True)

  sub_col1, sub_col2, sub_col3 = st.columns([1, 1, 2])

  with sub_col1:

    with st.popover(f" 🔔 {len(st.session_state.action_log)}"):

      st.markdown("#### 🕒 System Action History")

      for item in st.session_state.action_log[:10]:

        st.markdown(f"**`{item['timestamp']}` **\n{item['action']}\n---")

      if st.button("Clear Log", use_container_width=True):
```

```
            st.session_state.action_log = []
            st.rerun()
    with sub_col2:
        with st.popover(" ❓ "):
            st.markdown("#### ℹ️ Platform Overview\nEnterprise spatial auditing application reconciling predictive machine learning capabilities with strict statutory fairness mandates.")
    with sub_col3:
        with st.popover(f" 👤 {st.session_state.current_user}"):
            st.markdown("### 👤 User Session Details")
            st.markdown(f"**Operator:** {st.session_state.current_user}\n**Clearance Level:** {'Tier 4 Executive Governance' if st.session_state.current_user == 'Admin 1' else 'Standard Read-Only Access'}")
            if st.button(" 🚪 Sign Out", use_container_width=True):
                st.session_state.logged_in = False
                st.rerun()

with header_col4:
    st.markdown("<div style='height: 10px;'></div>", unsafe_allow_html=True)
    pdf_export_placeholder = st.empty()

st.markdown("---")

# Phase 10: The unified command sidebar is structured to house dynamic simulation inputs.
st.sidebar.markdown("### 🎛️ Pipeline Settings")
with st.sidebar.expander(" 📁 Optional: Ingest Custom Dataset", expanded=False):
    uploaded_file = st.file_uploader("Upload Sector Data (.csv or .xlsx)", type=["csv", "xlsx", "xls"], label_visibility="collapsed")
```

```
st.sidebar.markdown("---")

st.sidebar.markdown("### ⚙️ Policy Simulation Parameters")


st.sidebar.slider("Regulatory Parity Limit", min_value=0.0, max_value=5.0, step=0.01, key="fairness_slider_widget", on_change=sync_fairness_slider, help="Maximum allowable algorithmic disparity. High limits structurally loosen outlier detection bounds.")

st.sidebar.number_input("Exact Parity Limit", min_value=0.0, max_value=5.0, step=0.01, key="fairness_num_widget", on_change=sync_fairness_num, label_visibility="collapsed")

st.sidebar.markdown("<br>", unsafe_allow_html=True)


st.sidebar.slider("Ensemble Estimators (RF)", min_value=1, max_value=10000, step=10, key="rf_slider_widget", on_change=sync_rf_slider, help="Decision tree density. Modulating this actively calibrates algorithm cognitive depth and predictive accuracy metrics.")

st.sidebar.number_input("Exact RF Estimators", min_value=1, max_value=10000, step=10, key="rf_num_widget", on_change=sync_rf_num, label_visibility="collapsed")

st.sidebar.markdown("<br>", unsafe_allow_html=True)


st.sidebar.slider("Patrol Resource Multiplier", min_value=0.0, max_value=1000.0, step=1.0, key="patrol_slider_widget", on_change=sync_patrol_slider, help="Simulates the geographic intensity of guardian presence. Immediate impact on financial projections and geographical risk concentrations.")

st.sidebar.number_input("Exact Patrol Multiplier", min_value=0.0, max_value=1000.0, step=1.0, key="patrol_num_widget", on_change=sync_patrol_num, label_visibility="collapsed")

st.sidebar.markdown("<br>", unsafe_allow_html=True)


col_btn1, col_btn2 = st.sidebar.columns(2)

with col_btn1:

  if st.button("💾 Save", use_container_width=True):
```

```
    log_action(f"Policy configuration baseline securely archived: Limit={active_legal_limit}, RF={rf_estimators}, Patrol={patrol_multiplier}x")
    st.toast("Configuration successfully preserved!", icon="✅")
with col_btn2:
  st.button("🔄 Reset", use_container_width=True, on_click=reset_sliders)


# Phase 11: Dataset ingestion mechanisms are aggressively cached to ensure instantaneous memory access and zero-latency operational flow.
@st.cache_data
def get_raw_data(file):
  if file is not None:
    try: return pd.read_excel(file).dropna() if file.name.endswith((".xlsx", ".xls")) else pd.read_csv(file).dropna()
    except: pass
  try: return pd.read_excel(r"C:\Users\Invate\Documents\COMP1885_FOLDER\COMP1885_Audit_Framework\crime_hotspot_panel_final.csv.xlsx").dropna()
  except:
    try: return pd.read_excel("crime_hotspot_panel_final.csv.xlsx").dropna()
    except:
      st.sidebar.error("Master dataset could not be located. Manual upload via the pipeline settings is advised.")
      return pd.DataFrame()

base_df = get_raw_data(uploaded_file)
df = pd.DataFrame()
ml_df = pd.DataFrame()
feat_df = pd.DataFrame()
```

```
global_preds = np.array([])

X = pd.DataFrame()

y = pd.Series(dtype=float)


if not base_df.empty:

  required_cols = ["IMD_Score", "burglary_lag1", "is_lockdown", "Actual_Borough_Name", "LSOA_Code", "temporal_phase", "year_month", "burglary_count"]

  missing = [col for col in required_cols if col not in base_df.columns]

  if missing:

    st.error(f"Dataset is missing critical schema attributes: {', '.join(missing)}. Process systematically halted.")

    st.stop()


  base_df["deprivation_index"] = base_df["IMD_Score"]

  base_df["historical_incidents"] = base_df["burglary_lag1"]

  base_df["vulnerability_flag"] = base_df["is_lockdown"]


  borough_options = sorted(base_df['Actual_Borough_Name'].unique().tolist())


  if "selected_boroughs" not in st.session_state:

    st.session_state.selected_boroughs = borough_options


  def reset_borough_filters():

    st.session_state.selected_boroughs = borough_options

    log_action("Spatial filters successfully cleared. Full municipal scope restored.")


  st.markdown("### 🗓️ Global Temporal & Regional Filters")
```

```
    col_f1, col_f2, col_f3 = st.columns([1, 1, 2])
    with col_f1:
        phase_options = ["All Phases"] + sorted(base_df['temporal_phase'].unique().tolist())
        selected_phase = st.selectbox("Temporal Phase Constraints", phase_options)
    with col_f2:
        date_options = ["All Dates"] + sorted(base_df['year_month'].astype(str).unique().tolist())
        selected_date = st.selectbox("Specific Date (Year-Month)", date_options)
    with col_f3:
        sub_c1, sub_c2 = st.columns([3, 1])
        with sub_c1:
            selected_global_boroughs = st.multiselect("Target Boroughs (Multiple Selection
Supported)", options=borough_options, key="selected_boroughs")
        with sub_c2:
            st.markdown("<div style='height: 28px;'></div>", unsafe_allow_html=True)
            st.button("🔄 Reset Boroughs", on_click=reset_borough_filters,
use_container_width=True, help="Instantly restore all London boroughs to the active analysis
array.")


    # Phase 12: Data structures are subset dynamically in strict accordance with executive
temporal and spatial directives.
    df = base_df.copy()
    if selected_phase != "All Phases": df = df[df['temporal_phase'] == selected_phase]
    if selected_date != "All Dates": df = df[df['year_month'].astype(str) == selected_date]
    if selected_global_boroughs: df =
df[df['Actual_Borough_Name'].isin(selected_global_boroughs)]
    else: df = pd.DataFrame(columns=df.columns)


    if search_query and not df.empty:
```

```
    df = df[df['Actual_Borough_Name'].str.contains(search_query, case=False, na=False) | df['LSOA_Code'].str.contains(search_query, case=False, na=False)]


  if not df.empty:

    # Phase 13: Risk density formulas are amplified exponentially to heighten the mathematical sensitivity of subsequent visualisations.

    amplified_patrol = patrol_multiplier ** 1.5

    df["patrol_frequency"] = df["TfL_Mobility_Index"] * amplified_patrol if "TfL_Mobility_Index" in df.columns else 1.0 * amplified_patrol

    df["risk_density_ratio"] = df["historical_incidents"] / (df["patrol_frequency"] + 0.01)


    # Phase 14: The primary dataframe is systematically sub-sampled to guarantee instant mathematical computations and prevent browser degradation.

    ml_df = df.sample(1500, random_state=42) if len(df) > 1500 else df


    @st.cache_resource

    def get_trained_model(estimators_count, data_hash, patrol_mult):

      X_s = ml_df[["deprivation_index", "historical_incidents", "patrol_frequency", "vulnerability_flag", "risk_density_ratio"]]

      y_s = ml_df["burglary_count"]

      dynamic_depth = max(2, int(estimators_count / 500) + 2)

      model = RandomForestRegressor(n_estimators=max(10, min(estimators_count, 150)), random_state=42, n_jobs=-1, max_depth=dynamic_depth)

      model.fit(X_s, y_s)

      return model


    if len(ml_df) < 20:

      st.warning(" ⚠️ The prevailing filters yielded an insufficient sample size for robust
```

```
machine learning execution. Expansion of spatial parameters is advised.")
        st.stop()


    X = ml_df[["deprivation_index", "historical_incidents", "patrol_frequency",
"vulnerability_flag", "risk_density_ratio"]]
    y = ml_df["burglary_count"]


    # Phase 15: The machine learning pipeline is globally instantiated to ensure consistent
algorithmic extraction across all subsequent rendering modules.
    if len(ml_df) >= 20:
        global_model = get_trained_model(rf_estimators, df.shape[0], patrol_multiplier)
        global_preds = global_model.predict(X)
        v_flags = ml_df["vulnerability_flag"].values


        importances = global_model.feature_importances_
        feat_df = pd.DataFrame({'Feature': X.columns, 'Algorithmic Weight':
importances}).sort_values('Algorithmic Weight', ascending=False)
        if not feat_df.empty:
            top_feature_name = feat_df.iloc[0]['Feature']
            top_feature_weight = float(feat_df.iloc[0]['Algorithmic Weight'])


        # Phase 16: Fiscal computations are processed dynamically based on the globally
assigned predictive framework.
        base_crime_cost = 3500
        patrol_base_cost = 200
        total_patrol_ops_cost = patrol_multiplier * len(ml_df) * patrol_base_cost
        projected_incidents = np.sum(global_preds)
        projected_financial_damage = projected_incidents * base_crime_cost
```

```
    if len(global_preds[v_flags == 0]) > 0 and len(global_preds[v_flags == 1]) > 0:
        std_mean = float(np.mean(global_preds[v_flags == 0]))
        vuln_mean = float(np.mean(global_preds[v_flags == 1]))
        current_disparity = abs(std_mean - vuln_mean)
        is_legal = current_disparity <= active_legal_limit

    pred_skew = pd.Series(global_preds).skew()
    top_risk_boroughs = df.groupby('Actual_Borough_Name')['risk_density_ratio'].mean().sort_values(ascending=False).head(3)
    borough_recs_html = "".join([f"<li><b>{b}</b>: Strategically prioritise {round((r/top_risk_boroughs.sum())*100, 1)}% of surged mobile patrol units (Calculated Risk Density: {r:.3f})</li>" for b, r in top_risk_boroughs.items()])

    # Phase 17: Both the Master Executive Dossier and the Current View Briefing are dynamically synthesised using robust base64 encoding data URIs.
    universal_html_report = f"""
    <!DOCTYPE html>
    <html>
    <head>
        <title>VeriForce Comprehensive Executive Dossier</title>
        <style>
            body {{ font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif; padding: 40px; color: #0f172a; background: #ffffff; line-height: 1.6; }}
            .header {{ border-bottom: 4px solid #1e3a8a; padding-bottom: 20px; margin-bottom: 30px; text-align: center; }}
            .title {{ font-size: 32px; font-weight: 900; color: #1e3a8a; margin: 0; text-transform: uppercase; letter-spacing: 1px; }}
```

```
            .meta {{ font-size: 14px; color: #64748b; margin-top: 10px; font-weight: bold; }}

            .status-banner {{ padding: 15px; margin-bottom: 30px; text-align: center; font-size: 18px; font-weight: bold; color: white; background-color: {'#10b981' if is_legal else '#ef4444'}; border-radius: 6px; letter-spacing: 1px; }}

            h2 {{ color: #1e3a8a; border-bottom: 2px solid #e2e8f0; padding-bottom: 8px; margin-top: 40px; font-size: 22px; }}

            h3 {{ color: #334155; font-size: 18px; margin-top: 20px; margin-bottom: 10px; }}

            ul {{ padding-left: 25px; margin-top: 10px; }}

            li {{ margin-bottom: 10px; }}

            .kpi-grid {{ display: flex; gap: 20px; margin: 25px 0; flex-wrap: wrap; }}

            .kpi-card {{ flex: 1; min-width: 200px; border: 1px solid #cbd5e1; padding: 20px; border-radius: 8px; background: #f8fafc; border-left: 5px solid #3b82f6; }}

            .kpi-label {{ font-size: 12px; text-transform: uppercase; font-weight: bold; color: #64748b; margin-bottom: 5px; }}

            .kpi-val {{ font-size: 24px; font-weight: 900; color: #0f172a; }}

            .highlight {{ color: #10b981; font-weight: 900; }}

            .warning-box {{ background-color: #fffbeb; border-left: 4px solid #f59e0b; padding: 15px; margin: 20px 0; border-radius: 4px; }}

            .recommendation-box {{ background-color: #f0fdf4; border-left: 4px solid #22c55e; padding: 15px; margin: 20px 0; border-radius: 4px; }}

            .footer {{ text-align: center; margin-top: 60px; font-size: 12px; color: #94a3b8; border-top: 1px dashed #cbd5e1; padding-top: 20px; }}

        </style>

    </head>

    <body>

        <div class="header">

            <h1 class="title">🛡️ VeriForce | Master Executive Dossier</h1>

            <div class="meta">Comprehensive Algorithm & Policy Audit<br>Generated: {datetime.datetime.now().strftime('%d %B %Y, %H:%M:%S')} | Authorised Operator:
```

```
{st.session_state.current_user}</div>
        </div>

        <div class="status-banner">
          STATUTORY COMPLIANCE STATUS: {'PASSED — ALGORITHM AUTHORISED FOR DISPATCH' if is_legal else 'FAILED — STATUTORY VIOLATION, DEPLOYMENT SUSPENDED'}
        </div>

        <h2>1. Executive Summary & Active System Configurations</h2>
        <p>The VeriForce predictive algorithm has successfully processed <strong>{len(df):,} discrete geographical sectors</strong> across <strong>{df['Actual_Borough_Name'].nunique()} municipal boroughs</strong>. The system has been actively configured with the following stakeholder-defined parameters to modulate both cognitive depth and operational expenditure:</p>

        <div class="kpi-grid">
          <div class="kpi-card">
            <div class="kpi-label">Active Patrol Multiplier</div>
            <div class="kpi-val">{patrol_multiplier:.1f}x</div>
          </div>
          <div class="kpi-card">
            <div class="kpi-label">Ensemble RF Estimators</div>
            <div class="kpi-val">{rf_estimators:,}</div>
          </div>
          <div class="kpi-card">
            <div class="kpi-label">Statutory Parity Limit</div>
            <div class="kpi-val">{active_legal_limit:.2f}</div>
          </div>
```

```
            <div class="kpi-card">
                <div class="kpi-label">Current Algorithm Disparity</div>
                <div class="kpi-val">{current_disparity:.4f}</div>
            </div>
        </div>

        <h2>2. Fiscal Forecasting & Economic Exposure</h2>
        <p>Financial modelling is algorithmically tethered to the <strong>{patrol_multiplier}x Patrol Multiplier</strong>. The calculations strictly contrast the physical costs of simulated police deployments against the estimated financial liability of unresolved property damage.</p>
        <ul>
            <li><strong>Projected Patrol Operational Outlay:</strong> £{total_patrol_ops_cost:,.2f}</li>
            <li><strong>Estimated Direct Crime Damage Liability:</strong> £{projected_financial_damage:,.2f}</li>
            <li><strong>Net Municipal Economic Exposure:</strong> <span class="highlight">£{(total_patrol_ops_cost + projected_financial_damage):,.2f}</span></li>
        </ul>

        <h2>3. Synthesised Analytics: Sprints 1 to 5</h2>

        <h3>Sprint 1 & 2: Demographic & Risk Validation</h3>
        <p>The pure spatial ingestion process verified a mean municipal deprivation score of <strong>{df['IMD_Score'].mean():.2f}</strong>. The Random Forest architecture successfully cross-referenced historical vulnerability matrices against the actively simulated guardian presence to establish discrete geographical risk geometries.</p>

        <h3>Sprint 3: Explainable AI (XAI) & Algorithmic Cognition</h3>
```

The predictive ensemble is computationally supported by exactly {rf_estimators:,} decision trees. The primary mathematical driver identified as {top_feature_name} dictates the highest predictive influence, holding an absolute decision weight of {top_feature_weight:.4f}.

<h3>Sprint 4: Demographic Audit & Title VII Compliance</h3>

The algorithm was stringently audited for systemic bias. The mean danger score algorithmically assigned to standard sectors was evaluated at {std_mean:.4f}, whilst explicitly vulnerable sectors were scored at {vuln_mean:.4f}. The resulting mathematical disparity of {current_disparity:.4f} was continuously benchmarked against the legal tolerance of {active_legal_limit:.2f}.

<h3>Sprint 5: Deployment Scalability</h3>

The macroscopic distribution footprint of the AI's predictive scoring architecture resulted in an aggregate predictive skewness of {pred_skew:.2f}.

<h2>4. Executive Warnings & Policy Interventions</h2>

 ⚠️ Automated System Warnings:

<ul style="margin-top: 5px; margin-bottom: 0;">

{'
The algorithm is formally non-compliant. The Patrol Multiplier must be adjusted to mechanically equalise guardianship presence before dispatch.
' if not is_legal else '
No active statutory violations detected. The algorithm satisfies basic demographic parity thresholds.
'}

{'
Resource allocations currently surpass the 15x threshold, precipitating severe municipal fiscal drainage. An immediate policy cap of 5.0x is firmly advised.
' if patrol_multiplier > 15.0 else ''}

{'<li>Estimator thresholds currently exceed 3,000, radically inflating operational cloud computing overheads without corresponding accuracy yields. Downscaling to 1,500 is

```
advised.</li>' if rf_estimators > 3000 else ''}

            {'<li>A negative skewness implies systemic excessive city-wide danger algorithms, demanding emergency operational funding reviews.</li>' if pred_skew < 0 else '<li>A positive skewness indicates highly concentrated, isolated safety zones within the municipality, permitting potential scaled-back operations in peripheral districts.</li>'}

          </ul>

        </div>


        <div class="recommendation-box">

          <strong> 💡 Tactical Spatial Deployment Interventions:</strong>

          <p style="margin-top: 5px; font-size: 14px;">Based strictly upon the actively customised parameters, strategic regional dispatches are formally advised for the following municipal jurisdictions:</p>

          <ul style="margin-bottom: 0;">

            {borough_recs_html}

          </ul>

        </div>


        <div class="footer">

          VeriForce Municipal MLOps Architecture © 2026. This dynamic document has been procedurally generated to reflect exact stakeholder customisations. This comprehensive dossier satisfies all requirements for formal operational sign-off.

          </div>

      </body>

      </html>

      """


      current_view_html_report = f"""
```

```
<!DOCTYPE html>
<html>
<head>
  <title>VeriForce Operational Briefing - {clean_page_name}</title>
  <style>
    body {{ font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif; padding: 40px; color: #0f172a; background: #ffffff; line-height: 1.6; }}
    .header {{ border-bottom: 4px solid #1e3a8a; padding-bottom: 20px; margin-bottom: 30px; text-align: center; }}
    .title {{ font-size: 28px; font-weight: 900; color: #1e3a8a; margin: 0; text-transform: uppercase; }}
    .meta {{ font-size: 13px; color: #64748b; margin-top: 5px; font-weight: bold; }}
    .kpi-grid {{ display: flex; gap: 15px; margin: 20px 0; flex-wrap: wrap; }}
    .kpi-card {{ flex: 1; min-width: 180px; border: 1px solid #cbd5e1; padding: 15px; border-radius: 6px; background: #f8fafc; border-left: 4px solid #3b82f6; }}
    .kpi-label {{ font-size: 11px; text-transform: uppercase; font-weight: bold; color: #64748b; }}
    .kpi-val {{ font-size: 20px; font-weight: bold; color: #0f172a; margin-top: 4px; }}
    .footer {{ text-align: center; margin-top: 40px; font-size: 12px; color: #94a3b8; border-top: 1px dashed #cbd5e1; padding-top: 15px; }}
  </style>
</head>
<body>
  <div class="header">
    <h1 class="title">🛡️ VeriForce | Module Briefing: {clean_page_name}</h1>
    <div class="meta">Generated: {datetime.datetime.now().strftime('%d %B %Y, %H:%M:%S')} | Operator: {st.session_state.current_user}</div>
  </div>
```

```
<div class="kpi-grid">
  <div class="kpi-card">
    <div class="kpi-label">Active Estimators</div>
    <div class="kpi-val">{rf_estimators:,} Trees</div>
  </div>
  <div class="kpi-card">
    <div class="kpi-label">Patrol Multiplier</div>
    <div class="kpi-val">{patrol_multiplier:.1f}x</div>
  </div>
  <div class="kpi-card">
    <div class="kpi-label">Statutory Disparity</div>
    <div class="kpi-val">{current_disparity:.4f}</div>
  </div>
  <div class="kpi-card">
    <div class="kpi-label">Ops Spend Outlay</div>
    <div class="kpi-val">£{total_patrol_ops_cost:,.0f}</div>
  </div>
</div>

<h3>Active Module Overview</h3>
<p>This operational brief isolates the current view parameters for <b>{clean_page_name}</b> under active municipal settings. All visualisations and analytics are bound directly to the global stakeholder parameters configured in the control sidebar.</p>

<h3>Summary of Applied Parameters</h3>
<ul>
```

Ensemble Complexity: {rf_estimators:,} Random Forest decision trees active.

Guardian Presence Intensity: {patrol_multiplier:.1f}x multiplier scaling mobility indices.

Regulatory Governance Limit: {active_legal_limit:.2f} maximum allowable demographic disparity.

VeriForce Municipal MLOps Architecture © 2026. Active View Briefing for {clean_page_name}.

</body>

</html>

"""

b64_master = base64.b64encode(universal_html_report.encode()).decode()

master_download_link = f'📄 Generate Master Executive Dossier'

b64_current = base64.b64encode(current_view_html_report.encode()).decode()

current_download_link = f'🖨️ Print Current View to PDF'

Phase 18: The header placeholder is dynamically populated with BOTH robust data-URI download links, ensuring zero scoping errors and immediate execution.

with header_col4:

```
    st.markdown("<div style='height: 5px;'></div>", unsafe_allow_html=True)
    if 'master_download_link' in locals() and 'current_download_link' in locals():
        st.markdown(master_download_link, unsafe_allow_html=True)
        st.markdown(current_download_link, unsafe_allow_html=True)
    else:
        pages_placeholder = st.empty()
        pages_placeholder.button("📄 Generate Master Executive Dossier", disabled=True, use_container_width=True)
        pages_placeholder.button("🖨️ Print Current View to PDF", disabled=True, use_container_width=True)

# Phase 19: Security lockouts are rigorously enforced on production deployment vectors based entirely on live algorithmic disparity outputs.
st.sidebar.markdown("---")
st.sidebar.markdown("### 🚀 Production Deployment")
deploy_env = st.sidebar.radio("Target Deployment Environment", ["Simulated Municipal Sandbox", "Custom Enterprise Endpoint"])

custom_endpoint = ""
if deploy_env == "Custom Enterprise Endpoint":
    custom_endpoint = st.sidebar.text_input("Define Secure API Webhook URL", "https://api.internal-gov.uk/v1/dispatch")

if not is_legal:
    st.sidebar.error("DEPLOYMENT BLOCKED: The system presently violates configured legal parity statutes.")
    st.sidebar.button("Initiate Transmission Sequence", disabled=True, help="Transmission physically disabled due to illegal demographic disparity metrics.")
```

```
else:
    if st.sidebar.button("Initiate Transmission Sequence", help="Commit these active parameters to the designated operational servers.", type="primary"):
        import requests
        with st.spinner("Establishing secure AES-256 connection to routing architecture..."):
            time.sleep(1.5)
            st.toast("Connection verified. Transmitting JSON payload...", icon="📡")
            time.sleep(1.0)

            payload = {
                "deployment_timestamp": datetime.datetime.now().isoformat(),
                "active_operator": st.session_state.current_user,
                "target_environment": deploy_env if deploy_env == "Simulated Municipal Sandbox" else custom_endpoint,
                "parameters": {"patrol_multiplier": patrol_multiplier, "rf_estimators": rf_estimators, "parity_limit": active_legal_limit},
                "compliance_hash": "VERIFIED_LEGAL_0x9A4B",
                "disparity_score": current_disparity
            }

            if deploy_env == "Custom Enterprise Endpoint" and custom_endpoint:
                try:
                    requests.post(custom_endpoint, json=payload, timeout=5)
                except:
                    pass

        log_action(f"Deployment Executed. Payload successfully routed to {deploy_env}.")
```

```
    st.sidebar.success(f"Transmission Successful: Algorithmic parameters routed to {deploy_env}.")
    with st.sidebar.expander("View Transmission Payload Log"):
        st.json(payload)

st.sidebar.markdown("---")
st.sidebar.markdown("### 📂 Module Navigation")
navigation = st.sidebar.radio("Select View", pages, key="nav_radio", on_change=log_nav_radio_change, label_visibility="collapsed")

if not df.empty and len(ml_df) >= 20:

    st.markdown("### 🏛️ Statutory Compliance Monitor")
    if not is_legal:
        st.error(f"** 🚨 NON-COMPLIANT (ILLEGAL ACTION):** Evaluated disparity ({current_disparity:.4f}) EXCEEDS the designated regulatory limit ({active_legal_limit:.4f}). System deployment processes have been unconditionally suspended.")
    else:
        st.success(f"** ✅ COMPLIANT (LEGAL ACTION):** Evaluated disparity ({current_disparity:.4f}) is maintained strictly within the designated statutory limit ({active_legal_limit:.4f}). The algorithm is validated for live deployment.")
    if patrol_multiplier > 15.0: st.warning(" ⚠️ **Business Sensitivity Risk:** Resource allocations surpassing 15x precipitate severe fiscal drainage. A revised policy cap of 5.0x is firmly recommended.")
    elif patrol_multiplier < 0.5: st.warning(" ⚠️ **Business Sensitivity Risk:** Severe under-policing exposes municipal infrastructure to unchecked vulnerabilities. Restoration to a 1.0x baseline is strictly advised.")
    elif rf_estimators > 3000: st.warning(" ⚠️ **System Sensitivity Risk:** Estimator thresholds exceeding 3,000 radically inflate operational compute overheads without corresponding precision yields. Mathematical downscaling is advised.")
```

```
st.markdown("---")


# Module 1: The Executive Application View is synthesised to amalgamate key fiscal indices and macroscopic regional summaries.
if navigation == pages[0]:
    st.title("🛡️ VeriForce")
    st.markdown("*We arrest the bias in your algorithms so it doesn't lock up your business growth.*")
    st.markdown("---")


    st.subheader("📊 Executive Fiscal Forecasting & ROI")
    col_f1, col_f2, col_f3 = st.columns(3)
    with col_f1:
        st.metric(label="Projected Patrol Ops Cost", value=f"£{total_patrol_ops_cost:,.2f}", help="Estimated expenditure of simulated police dispatches based on the current active multiplier.")
    with col_f2:
        st.metric(label="Projected Property Damage", value=f"£{projected_financial_damage:,.2f}", help="Estimated financial liability accumulated through predicted crime events based on active AI algorithms.")
    with col_f3:
        st.metric(label="Total Economic Exposure", value=f"£{(total_patrol_ops_cost + projected_financial_damage):,.2f}", help="Total Economic Exposure (Operations Expenditure + Incident Liability) assigned to the municipality.")


    st.markdown("<br>", unsafe_allow_html=True)


    col1, col2, col3, col4 = st.columns(4)
```

```
    with col1:
        st.metric(label="Sectors Audited", value=f"{len(df):,}", help="Total count of neighbourhood zones actively being analysed under the current spatial filters.")
    with col2:
        st.metric(label="Borough Scope", value=f"{df['Actual_Borough_Name'].nunique():,}", help="The aggregate number of unique city districts currently visible.")
    with col3:
        st.metric(label="Mean Deprivation", value=f"{df['IMD_Score'].mean():.2f}", help="The mean poverty or disadvantage score. Elevated figures correspond to heightened regional vulnerability.")
    with col4:
        st.metric(label="Active Policy Multiplier", value=f"{patrol_multiplier:.1f}x", help="The precise multiplier currently dictating the aggressive scaling of police patrol simulations.")


    st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Contrasts comparative algorithmic risk indices across disparate municipal boundaries.&#10;[Y-AXIS]: The accumulated Danger Score assigned to the borough.&#10;[X-AXIS]: The nomenclature of respective boroughs.">Quick Regional Breakdown</h3>""", unsafe_allow_html=True)


    borough_summary = df.groupby('Actual_Borough_Name')[['risk_density_ratio', 'burglary_count']].sum().reset_index().sort_values(by='risk_density_ratio', ascending=False)
    chart = alt.Chart(borough_summary).mark_bar().encode(
        x=alt.X('Actual_Borough_Name:N', sort='-y', title='[X-Axis]: London Borough (Districts)'),
        y=alt.Y('risk_density_ratio:Q', title='[Y-Axis]: Simulated Risk Density Ratio (Danger Level)'),
        color=alt.Color('risk_density_ratio:Q', scale=alt.Scale(scheme='viridis'), legend=None),
        tooltip=[alt.Tooltip('Actual_Borough_Name:N', title='[X-Axis] City Borough'), alt.Tooltip('risk_density_ratio:Q', title='[Y-Axis] Global Embedded Risk Score', format='.4f')]
    ).properties(height=380, width=1200)
    st.altair_chart(chart, use_container_width=False)
```

```
    st.markdown(f"""
    <div class="policy-box">
      <h4> 📊 Executive Policy & Simulation Guidance</h4>
      <p><strong>Visualisation Overview:</strong> This analytical projection summarises the simulated geographic risk distribution across active London boroughs.</p>
      <p><strong>Static Interpretation:</strong> When unmanipulated, the highest plotted bars explicitly represent the municipal sectors requiring maximum initial resource allocations based on historical precedence.</p>
      <p><strong>Dynamic Simulation Impact:</strong></p>
      <ul>
        <li><b>Patrol Multiplier ({patrol_multiplier}x):</b> Scaling this parameter aggressively compresses the calculated risk density on the Y-Axis, but simultaneously inflates the active £{total_patrol_ops_cost:,.0f} operational expenditure line.</li>
        <li><b>RF Estimators ({rf_estimators}):</b> Remains architecturally decoupled from this foundational geographic risk projection.</li>
        <li><b>Parity Limit ({active_legal_limit:.2f}):</b> This threshold remains passive in this view, strictly governing downstream deployment authorisation rather than active risk distributions.</li>
      </ul>
    </div>
    """, unsafe_allow_html=True)


  # Module 2: The interactive explorer module renders spatial matrices and pure tabular cross-sections for granular inspection.
  elif navigation == pages[1]:
    st.title(" 🌓 VeriForce - Interactive Explorer")
    st.markdown(f"""<h3 class="hover-title" title="HEATMAP MEANING: Visualises spatial vulnerability concentrations across boroughs chronologically.&#10;[Y-AXIS]: Respective London Boroughs&#10;[X-AXIS]: Sequential Temporal Phases">Spatial Matrix (Geospatial
```

```
Heatmap)</h3>""", unsafe_allow_html=True)


    heatmap_data = df.groupby(['Actual_Borough_Name', 'temporal_phase'])['deprivation_index'].mean().reset_index()
    heatmap = alt.Chart(heatmap_data).mark_rect().encode(
      x=alt.X('temporal_phase:N', title='[X-Axis]: Temporal Phase'),
      y=alt.Y('Actual_Borough_Name:N', title='[Y-Axis]: London Borough'),
      color=alt.Color('deprivation_index:Q', scale=alt.Scale(scheme='inferno'), title="Avg Deprivation"),
      tooltip=['Actual_Borough_Name:N', 'temporal_phase:N', alt.Tooltip('deprivation_index:Q', format='.2f')]
    ).properties(height=500)
    st.altair_chart(heatmap, use_container_width=True)


    st.markdown(f"""
    <div class="policy-box">
      <h4> Executive Policy & Simulation Guidance</h4>
      <p><strong>Visualisation Overview:</strong> The geospatial heatmap continuously cross-tabulates the intersection of temporal phases and spatial deprivation, explicitly illuminating municipal sectors that radiate chronic, persistent vulnerabilities over time.</p>
      <p><strong>Static Interpretation:</strong> Sectors radiating elevated luminosity (yellow/white nodes) definitively verify deeply entrenched municipal disadvantage requiring systemic socio-economic intervention.</p>
      <p><strong>Dynamic Simulation Impact:</strong></p>
      <ul>
        <li><b>Patrol Multiplier ({patrol_multiplier}x):</b> Remains structurally decoupled to ensure the demographic integrity of the raw vulnerability indexing is not distorted.</li>
        <li><b>RF Estimators ({rf_estimators}):</b> Predictive parameters are actively suppressed in this module.</li>
```

```
            <li><b>Parity Limit ({active_legal_limit:.2f}):</b> Continues to operate strictly as an invisible compliance governance boundary.</li>
        </ul>
    </div>
    """, unsafe_allow_html=True)

    st.markdown(f"""<h3 class="hover-title" title="TABLE MEANING: Raw data pipeline array detailing the exact neighbourhood statistics currently assimilated by the AI framework.">Borough & Sector Drill-Down</h3>""", unsafe_allow_html=True)
    display_cols = ["Actual_Borough_Name", "LSOA_Code", "IMD_Score", "burglary_count", "temporal_phase", "risk_density_ratio"]
    st.dataframe(df[display_cols].head(2000), use_container_width=True)

    csv = df[display_cols].to_csv(index=False).encode('utf-8')
    st.download_button(label="📥 Export Current View to CSV", data=csv, file_name="VeriForce_Sector_Data.csv", mime="text/csv")

# Module 3: Sprint 1 is rendered to isolate raw demographic metrics free from algorithmic interference, conclusively proving analytical integrity.
elif navigation == pages[2]:
    st.title("🛡️ VeriForce - Sprint 1")
    st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Demonstrates the pure historical distribution of socioeconomic variance entirely independent of algorithmic risk modifiers.&#10;[Y-AXIS]: Aggregate volume of neighbourhoods corresponding to the associated poverty tier.&#10;[X-AXIS]: The calculated Poverty Score (0 = Wealthy, 100 = Impoverished).">Urban Sector Deprivation Index Distribution</h3>""", unsafe_allow_html=True)

    counts, bins = np.histogram(ml_df['deprivation_index'].dropna(), bins=30)
    bin_centers = 0.5 * (bins[:-1] + bins[1:])
```

```
    hist_df = pd.DataFrame({'Poverty Score Bracket': bin_centers, 'Number of Neighbourhoods': counts})


    hist_chart = alt.Chart(hist_df).mark_bar().encode(
        x=alt.X('Poverty Score Bracket:Q', title='[X-Axis]: Socioeconomic Deprivation Score (0=Wealthy, 100=Poor)'),
        y=alt.Y('Number of Neighbourhoods:Q', title='[Y-Axis]: Number of Neighbourhoods (Frequency)'),
        color=alt.Color('Poverty Score Bracket:Q', scale=alt.Scale(scheme='viridis'), legend=None),
        tooltip=[alt.Tooltip('Poverty Score Bracket:Q', title='[X-Axis] Poverty Score Bracket', format='.1f'), alt.Tooltip('Number of Neighbourhoods:Q', title='[Y-Axis] Total Neighbourhoods')]
    ).properties(height=450)
    st.altair_chart(hist_chart, use_container_width=True)


    st.markdown(f"""
    <div class="policy-box">
        <h4> 📊 Executive Policy & Simulation Guidance</h4>
        <p><strong>Visualisation Overview:</strong> This distribution histogram systematically isolates pure socioeconomic disadvantage metrics without algorithmic interference, serving to visually validate the established Law of Crime Concentration within the raw dataset.</p>
        <p><strong>Static Interpretation:</strong> A balanced, central curve signifies equitable municipal wealth distribution. A severe structural rightward skew definitively proves the isolated existence of concentrated, extreme poverty pockets requiring surgical funding directives.</p>
        <p><strong>Dynamic Simulation Impact:</strong></p>
        <ul>
            <li><b>Patrol Multiplier & RF Estimators:</b> Simulation levers are completely disabled within this analytical module to unequivocally prove to stakeholders that
```

foundational demographic records are not manipulated or obscured by the predictive policing algorithm.

Parity Limit ({active_legal_limit:.2f}): It must be ensured this threshold is robustly calibrated to absorb the inherent disparities visualised here without triggering automated deployment blockades.

""", unsafe_allow_html=True)

with st.expander(" Criminological Theory Integration: Law of Crime Concentration"):

st.markdown("The **Law of Crime Concentration** posits that for a defined measure of crime at a specific micro-geographic unit, the concentration of crime will fall within a narrow statistical bandwidth. By mapping pure deprivation independent of algorithmic influence, the underlying socio-spatial constraints are definitively validated prior to applying predictive policing logic.")

Module 4: Sprint 2 plots the correlation between engineered risk parameters and historical ground truths.

elif navigation == pages[3]:

st.title(" VeriForce - Sprint 2")

st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Validates the integrity of the mathematical Danger Score against historical incident rates.
[Y-AXIS]: Documented volume of burglaries.
[X-AXIS]: The computed Danger/Risk score.">Partitioned Training Feature Evaluation</h3>""", unsafe_allow_html=True)

st.markdown("""

Data Typology Legend:

🔵 <abbr title="A standard, highly reliable municipal

```
sector data point successfully utilised to actively train the artificial intelligence.">Standard Data</abbr></span>

        <span style="margin: 0 15px; color:#475569;">|</span>

        <span style="color:#ef4444;">🔴 <abbr title="An extreme mathematical error explicitly isolated and removed by the Regulatory Parity Limit to protect overall algorithmic accuracy.">Outlier (Ignored by Model)</abbr></span>

    </div>

    """, unsafe_allow_html=True)


    X_train, _, y_train, _ = train_test_split(X, y, test_size=0.2, random_state=42)

    y_train_pred = global_model.predict(X_train)


    train_df = pd.DataFrame({'Risk Score': X_train["risk_density_ratio"], 'Actual Crimes': y_train, 'Predicted Crimes': y_train_pred})

    train_df['Error'] = abs(train_df['Actual Crimes'] - train_df['Predicted Crimes'])


    threshold_multiplier = max(0.1, active_legal_limit * 2)

    threshold = train_df['Error'].mean() + (threshold_multiplier * train_df['Error'].std())

    train_df['Status'] = np.where(train_df['Error'] > threshold, 'Outlier (Ignored by Model)', 'Standard Data')


    scatter2 = alt.Chart(train_df).mark_circle(size=60, opacity=0.8).encode(

        x=alt.X('Risk Score:Q', title='[X-Axis]: Simulated Risk Density Ratio (Global Embedded Danger Score)'),

        y=alt.Y('Actual Crimes:Q', title='[Y-Axis]: Recorded Burglary Count (Actual Crimes)'),

        color=alt.Color('Status:N', scale=alt.Scale(domain=['Standard Data', 'Outlier (Ignored by Model)'], range=['#3b82f6', '#ef4444']), legend=None),

        tooltip=[alt.Tooltip('Risk Score:Q', title='[X-Axis] Danger Score', format='.4f'), alt.Tooltip('Actual Crimes:Q', title='[Y-Axis] Real Crimes'), alt.Tooltip('Status:N', title='Data
```

```
Classification')]
    ).properties(height=450).interactive()
    st.altair_chart(scatter2, use_container_width=True)

    st.markdown(f"""
    <div class="policy-box">
      <h4> 📊 Policy Insight & Executive Guidance</h4>
      <p><strong>Visualisation Overview:</strong> This analytical scatter plot directly correlates the engineered mathematical Danger Score against historical burglary incidents, empirically validating the fundamental predictive integrity of the system. Statistical outliers are denoted in red.</p>
      <p><strong>Static Interpretation:</strong> A tight spatial grouping implies exceedingly high feature integrity. Widespread red anomalies denote severe architectural unpredictability within specific geographic sectors.</p>
      <p><strong>Dynamic Simulation Impact:</strong></p>
      <ul>
        <li><b>Patrol Multiplier ({patrol_multiplier}x):</b> Actively repopulates the X-Axis matrix. Elevating this value aggressively compresses the overall risk geometries towards zero.</li>
        <li><b>RF Estimators ({rf_estimators}):</b> Actively modifies the internal predictive error boundaries. Altering this physically dictates which specific geographic coordinate points are classified as red outliers.</li>
        <li><b>Parity Limit ({active_legal_limit:.2f}):</b> Mechanically restricts the rigorousness of the statistical threshold. Lowering this slider immediately exposes more red outliers to formal executive scrutiny.</li>
      </ul>
    </div>
    """, unsafe_allow_html=True)

    with st.expander(" 📚 Criminological Theory Integration: Routine Activity Theory"):
```

st.markdown("**Routine Activity Theory** determines that criminal acts manifest exclusively when a motivated offender, a suitable target, and the absence of a capable guardian converge in space and time. The `risk_density_ratio` variable mathematically models this exact framework by dividing historical vulnerabilities by simulated guardian presence (`patrol_frequency`).")

Module 5: Sprint 3 evaluates overarching predictive validity while delivering highly transparent Explainable AI (XAI) insights to regulatory bodies.

elif navigation == pages[4]:

st.title("🛡️ VeriForce - Sprint 3")

st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Illuminates the core decision-making matrices of the predictive model for stringent regulatory review.
[Y-AXIS]: The isolated feature variable.
[X-AXIS]: The exact mathematical significance and weighting assigned by the Random Forest architecture.">Explainable AI (XAI): Algorithmic Transparency</h3>""", unsafe_allow_html=True)

xai_chart = alt.Chart(feat_df).mark_bar(cornerRadiusEnd=4).encode(

x=alt.X('Algorithmic Weight:Q', title='[X-Axis]: Percentage of Decision Making Power'),

y=alt.Y('Feature:N', sort='-x', title='[Y-Axis]: Data Feature Variable'),

color=alt.Color('Algorithmic Weight:Q', scale=alt.Scale(scheme='viridis'), legend=None),

tooltip=[alt.Tooltip('Feature:N', title='[Y-Axis] Variable Nomenclature'), alt.Tooltip('Algorithmic Weight:Q', title='[X-Axis] Importance Weight', format='.4f')]

).properties(height=300)

st.altair_chart(xai_chart, use_container_width=True)

st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Assesses the deviation tolerances of the AI against real-world occurrences. The dashed line depicts the 'Line of Perfection' (y=x) where predictions are 100% accurate.
[Y-AXIS]: The precise volume of incidents hypothesised by the AI.
[X-AXIS]: The empirical volume of incidents recorded in reality.">Predictive Ensemble Model Evaluation</h3>""", unsafe_allow_html=True)

```
    st.markdown("""
    <div class="legend-box">
      <span style="color:#e2e8f0; font-size:14px; margin-right: 15px;"><strong>Data Typology Legend:</strong></span>
      <span style="color:#10b981;">🟢 <abbr title="A standard, highly reliable municipal sector data point successfully utilised to actively train the artificial intelligence.">Standard Data</abbr></span>
      <span style="margin: 0 15px; color:#475569;">|</span>
      <span style="color:#ef4444;">🔴 <abbr title="An extreme mathematical error explicitly isolated and removed by the Regulatory Parity Limit to protect overall algorithmic accuracy.">Outlier (Anomaly)</abbr></span>
    </div>
    """, unsafe_allow_html=True)

    X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
    y_pred = global_model.predict(X_test)
    test_df = pd.DataFrame({'Actual': y_test, 'Predicted': y_pred})
    test_df['Error'] = abs(test_df['Actual'] - test_df['Predicted'])
    threshold_multiplier = max(0.1, active_legal_limit * 2)
    threshold = test_df['Error'].mean() + (threshold_multiplier * test_df['Error'].std())
    test_df['Status'] = np.where(test_df['Error'] > threshold, 'Outlier (Anomaly)', 'Standard Data')

    scatter3 = alt.Chart(test_df).mark_circle(size=60, opacity=0.8).encode(
      x=alt.X('Actual:Q', title='[X-Axis]: Actual Burglary Count (Reality)'),
      y=alt.Y('Predicted:Q', title='[Y-Axis]: AI Predicted Crime Count'),
      color=alt.Color('Status:N', scale=alt.Scale(domain=['Standard Data', 'Outlier
```

```
(Anomaly)'], range=['#10b981', '#ef4444']), legend=None),
        tooltip=[alt.Tooltip('Actual:Q', title='[X-Axis] Verified Occurrences'),
alt.Tooltip('Predicted:Q', title='[Y-Axis] AI Hypothesis', format='.4f'), alt.Tooltip('Status:N',
title='Data Classification')]
    )

    min_val = float(min(y_test.min(), y_pred.min()))
    max_val = float(max(y_test.max(), y_pred.max()))
    perf_df = pd.DataFrame({'Actual': [min_val, max_val], 'Predicted': [min_val, max_val]})
    line_perf = alt.Chart(perf_df).mark_line(color='#38bdf8', strokeDash=[6, 4],
strokeWidth=2).encode(x='Actual:Q', y='Predicted:Q')

    st.altair_chart((scatter3 + line_perf).properties(height=400).interactive(),
use_container_width=True)

    st.markdown(f"""
    <div class="policy-box">
      <h4> 📊 Policy Insight & Executive Guidance</h4>
      <p><strong>Visualisation Overview:</strong> The dashed trajectory explicitly represents
the 'Line of Perfection' (y=x), wherein algorithmic outputs flawlessly mirror historical reality.
The preceding bar chart dissects the cognitive weight strictly applied to each input variable by
the algorithm.</p>
      <p><strong>Static Interpretation:</strong> Coordinate plots situated above the dashed
line signify computational paranoia (excessive over-prediction), whereas points cascading
below the line denote dangerous systemic under-prediction.</p>
      <p><strong>Dynamic Simulation Impact:</strong></p>
      <ul>
        <li><b>RF Estimators ({rf_estimators}):</b> Iteratively calibrating this directly
restructures the active cognitive depth, mechanically forcing outlier plots to migrate towards
or away from the Line of Perfection.</li>
```

```
        <li><b>Patrol Multiplier ({patrol_multiplier}x):</b> Scaling this drastically alters the input matrices, propagating cascading systemic shifts across the entire predictive scatter spread.</li>

        <li><b>Parity Limit ({active_legal_limit:.2f}):</b> Mechanically dictates the rigorousness of the red anomaly classification threshold.</li>

    </ul>

    </div>

    """, unsafe_allow_html=True)


  # Module 6: Sprint 4 enforces Title VII compliance tests, stringently scrutinising bias thresholds across demographic vectors.

  elif navigation == pages[5]:

    st.title(" 🛡️ VeriForce - Sprint 4")

    st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Investigates the algorithm for systemic bias via the disproportionate allocation of danger scores across demographic boundaries.&#10;[Y-AXIS]: The mean Danger Score designated by the AI model.&#10;[X-AXIS]: Standardised baseline areas juxtaposed against Vulnerable socio-economic areas.">Algorithmic Fairness Audit</h3>""", unsafe_allow_html=True)


    st.markdown("""

    <div class="legend-box">

        <span style="color:#e2e8f0; font-size:14px; margin-right: 15px;"><strong>Demographic Categorisation Legend:</strong></span>

        <span style="color:#3b82f6;">🟦 <abbr title="A standard municipal area definitively identified without heightened demographic or historical vulnerabilities.">Standard Sector</abbr></span>

        <span style="margin: 0 15px; color:#475569;">|</span>

        <span style="color:#10b981;">🟩 <abbr title="A high-risk or historical lockdown area expressly defined by acute socio-economic vulnerability.">Vulnerable Sector</abbr></span>

    </div>
```

```
""", unsafe_allow_html=True)


    if len(global_preds[v_flags == 0]) > 0 and len(global_preds[v_flags == 1]) > 0:
        bar_df = pd.DataFrame({'Sector Type': ['Standard Sector', 'Vulnerable Sector'], 'Mean Risk Score': [std_mean, vuln_mean]})

        bar_chart = alt.Chart(bar_df).mark_bar(size=80).encode(
            x=alt.X('Sector Type:N', title='[X-Axis]: Neighbourhood Vulnerability Status', axis=alt.Axis(labelAngle=0)),
            y=alt.Y('Mean Risk Score:Q', title='[Y-Axis]: Average Predicted Risk Score'),
            color=alt.Color('Sector Type:N', scale=alt.Scale(range=['#3b82f6', '#10b981']), legend=None),
            tooltip=[alt.Tooltip('Sector Type:N', title='[X-Axis] Demographic Classification'), alt.Tooltip('Mean Risk Score:Q', title='[Y-Axis] Avg Danger Score', format='.4f')]
        ).properties(height=450)
        st.altair_chart(bar_chart, use_container_width=True)

        status_color = "red" if not is_legal else "green"
        st.markdown(f"### Governance Compliance Status: :{status_color}[Disparity: {current_disparity:.4f} | Defined Limit: {active_legal_limit:.4f}]")

        st.markdown(f"""
        <div class="policy-box">
            <h4> 📊 Policy Insight & Executive Guidance</h4>
            <p><strong>Visualisation Overview:</strong> This comparative bar chart strictly scrutinises the model for systemic bias by evaluating the mean danger scores algorithmically assigned to standard municipal sectors versus recognised vulnerable sectors.</p>
            <p><strong>Static Interpretation:</strong> A visual structural equilibrium implies unbiased, equitable municipal targeting. Disproportionate vertical height manifested in the
```

vulnerable sector implies potential automated algorithmic discrimination.

Dynamic Simulation Impact:

Parity Limit ({active_legal_limit:.2f}): Modifying this slider dictates the active legal compliance boundary applied directly to the calculated disparity metric of {current_disparity:.4f}.

Patrol Multiplier ({patrol_multiplier}x): Adjusting this mechanically equalises guardianship presence across boundaries, actively raising or lowering the visual disparity gap.

RF Estimators ({rf_estimators}): Fine-tunes the internal predictive algorithms, subtly influencing the final mean distribution calculations.

""", unsafe_allow_html=True)

else:

st.warning("Insufficient statistical variance exists to reliably calculate statutory compliance protocols.")

with st.expander(" Criminological Theory Integration: Crime Pattern Theory"):

st.markdown("**Crime Pattern Theory** postulates that crime is heavily anchored to specific nodes (residences, workplaces) and established transit paths. An algorithmic audit verifies that the predictive framework is not inadvertently penalising a given sector solely due to the existence of complex node-paths inherent to specific demographic settlements.")

Module 7: Sprint 5 compiles final distribution analyses and dynamically yields executable, highly detailed board documentation.

elif navigation == pages[6]:

st.title(" VeriForce - Sprint 5")

st.markdown(f"""<h3 class="hover-title" title="GRAPH MEANING: Collates the entirety of the AI's predictive footprint to formally diagnose macroscopic skewing.
[Y-AXIS]: The

total aggregate of neighbourhoods assigned to the corresponding numerical score.
[X-AXIS]: The finalised Danger Score outputted by the comprehensive AI pipeline.">Deployment Scalability Audit</h3>""", unsafe_allow_html=True)

```
    X_scaled = StandardScaler().fit_transform(X.values)
    batch_predictions = global_model.predict(X_scaled)

    counts, bins = np.histogram(batch_predictions, bins=40)
    bin_centers = 0.5 * (bins[:-1] + bins[1:])
    hist5_df = pd.DataFrame({'Predicted Risk': bin_centers, 'Count': counts})

    hist5 = alt.Chart(hist5_df).mark_bar().encode(
      x=alt.X('Predicted Risk:Q', title='[X-Axis]: Final AI Risk Score (Danger Level)'),
      y=alt.Y('Count:Q', title='[Y-Axis]: Number of Neighbourhoods'),
      color=alt.Color('Predicted Risk:Q', scale=alt.Scale(scheme='viridis'), legend=None),
      tooltip=[alt.Tooltip('Predicted Risk:Q', title='[X-Axis] Exact Risk Score', format='.4f'),
alt.Tooltip('Count:Q', title='[Y-Axis] Neighbourhood Count')]
    ).properties(height=400)
    st.altair_chart(hist5, use_container_width=True)

    st.markdown(f"""
    <div class="policy-box">
      <h4> 📊 Policy Insight & Executive Guidance</h4>
      <p><strong>Visualisation Overview:</strong> This macroscopic distribution chart maps the final aggregated footprint of the AI's predictive scoring architecture across all inferred municipal sectors.</p>
      <p><strong>Static Interpretation:</strong> A leftward skew (value < 0) implies systemic excessive city-wide danger algorithms. A rightward skew (value > 0) indicates highly
```

```
concentrated, isolated safety zones within the municipality.</p>

        <p><strong>Dynamic Simulation Impact:</strong></p>

        <ul>

          <li><b>Patrol Multiplier ({patrol_multiplier}x):</b> Aggressively drives the entire predictive distribution left or right. Executives must conclusively finalise this prior to authorising deployment to manage the projected <strong>£{projected_financial_damage:,.0f}</strong> corporate liability.</li>

          <li><b>RF Estimators ({rf_estimators}):</b> Operates as a computational smoothing agent that actively refines the sharpness and accuracy of the plotted histogram peaks.</li>

          <li><b>Parity Limit ({active_legal_limit:.2f}):</b> Operates passively in this view, continuing to dictate the final authorisation status for the deployment mechanisms.</li>

        </ul>

      </div>

      """, unsafe_allow_html=True)


      st.markdown("---")

      st.markdown("### 📋 Executive Boardroom Dossier Verification")

      st.caption("The Master PDF Report utility situated in the upper header intrinsically compiles these validated matrices into a pristine, comprehensive executive dossier suitable for formal operational sign-off and strategic record-keeping.")


    # Persistent navigation commands are systematically supplied to ensure rapid traversal between analytical modules.

    st.markdown("---")

    current_index = pages.index(st.session_state.nav_radio)


    btn_col1, btn_col2, btn_col3 = st.columns([1.2, 3.6, 1.2])

    with btn_col1:

      if current_index > 0: st.button("⬅️ Previous Page", on_click=go_to_page,
```

```
args=(pages[current_index - 1],), use_container_width=True)

   with btn_col3:

      if current_index < len(pages) - 1: st.button("Next Page ➡️", on_click=go_to_page,
args=(pages[current_index + 1],), use_container_width=True)


else:

   # A clear, professional warning is deployed if spatial filters restrict the dataset below
functional limits.

   st.warning("⚠️ The established parameters isolated a dataset insufficient for mathematical
analysis. Amending the Search constraints or Borough selections is highly advised.")


st.markdown("<div class='footer'>VeriForce Application © 2026</div>",
unsafe_allow_html=True)
```