Navigation 1

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 2

```
def slide_2(index):
    return index + 1
```

Notes 3

A short paragraph with **bold**, *italic*, and inline code.

Navigation 4

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 5

```
def slide_5(index):
    return index + 1
```

Notes 6

A short paragraph with **bold**, *italic*, and inline code.

Navigation 7

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 8

```
def slide_8(index):
    return index + 1
```

Notes 9

A short paragraph with **bold**, *italic*, and inline code.

Navigation 10

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 11

```
def slide_11(index):
    return index + 1
```

Notes 12

A short paragraph with **bold**, *italic*, and inline code.

Navigation 13

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 14

```
def slide_14(index):
    return index + 1
```

Notes 15

A short paragraph with **bold**, *italic*, and inline code.

Navigation 16

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 17

```
def slide_17(index):
    return index + 1
```

Notes 18

A short paragraph with **bold**, *italic*, and inline code.

Navigation 19

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 20

```
def slide_20(index):
    return index + 1
```

Notes 21

A short paragraph with **bold**, *italic*, and inline code.

Navigation 22

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 23

```
def slide_23(index):
    return index + 1
```

Notes 24

A short paragraph with **bold**, *italic*, and inline code.

Navigation 25

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 26

```
def slide_26(index):
    return index + 1
```

Notes 27

A short paragraph with **bold**, *italic*, and inline code.

Navigation 28

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 29

```
def slide_29(index):
    return index + 1
```

Notes 30

A short paragraph with **bold**, *italic*, and inline code.

Navigation 31

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 32

```
def slide_32(index):
    return index + 1
```

Notes 33

A short paragraph with **bold**, *italic*, and inline code.

Navigation 34

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 35

```
def slide_35(index):
    return index + 1
```

Notes 36

A short paragraph with **bold**, *italic*, and inline code.

Navigation 37

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 38

```
def slide_38(index):
    return index + 1
```

Notes 39

A short paragraph with **bold**, *italic*, and inline code.

Navigation 40

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 41

```
def slide_41(index):
    return index + 1
```

Notes 42

A short paragraph with **bold**, *italic*, and inline code.

Navigation 43

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 44

```
def slide_44(index):
    return index + 1
```

Notes 45

A short paragraph with **bold**, *italic*, and inline code.

Navigation 46

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 47

```
def slide_47(index):
    return index + 1
```

Notes 48

A short paragraph with **bold**, *italic*, and inline code.

Navigation 49

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 50

```
def slide_50(index):
    return index + 1
```

Notes 51

A short paragraph with **bold**, *italic*, and inline code.

Navigation 52

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 53

```
def slide_53(index):
    return index + 1
```

Notes 54

A short paragraph with **bold**, *italic*, and inline code.

Navigation 55

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 56

```
def slide_56(index):
    return index + 1
```

Notes 57

A short paragraph with **bold**, *italic*, and inline code.

Navigation 58

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 59

```
def slide_59(index):
    return index + 1
```

Notes 60

A short paragraph with **bold**, *italic*, and inline code.

Navigation 61

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 62

```
def slide_62(index):
    return index + 1
```

Notes 63

A short paragraph with **bold**, *italic*, and inline code.

Navigation 64

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 65

```
def slide_65(index):
    return index + 1
```

Notes 66

A short paragraph with **bold**, *italic*, and inline code.

Navigation 67

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 68

```
def slide_68(index):
    return index + 1
```

Notes 69

A short paragraph with **bold**, *italic*, and inline code.

Navigation 70

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 71

```
def slide_71(index):
    return index + 1
```

Notes 72

A short paragraph with **bold**, *italic*, and inline code.

Navigation 73

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 74

```
def slide_74(index):
    return index + 1
```

Notes 75

A short paragraph with **bold**, *italic*, and inline code.

Navigation 76

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 77

```
def slide_77(index):
    return index + 1
```

Notes 78

A short paragraph with **bold**, *italic*, and inline code.

Navigation 79

- Measure keyboard response
- Keep the cursor responsive
- Show the selected slide

Code 80

```
def slide_80(index):
    return index + 1
```